

Registry Keys Reference

ZENworks® 11 Support Pack 3

December 2014

Novell.



Legal Notices

Novell, Inc., makes no representations or warranties with respect to the contents or use of this documentation, and specifically disclaims any express or implied warranties of merchantability or fitness for any particular purpose. Further, Novell, Inc., reserves the right to revise this publication and to make changes to its content, at any time, without obligation to notify any person or entity of such revisions or changes.

Further, Novell, Inc., makes no representations or warranties with respect to any software, and specifically disclaims any express or implied warranties of merchantability or fitness for any particular purpose. Further, Novell, Inc., reserves the right to make changes to any and all parts of Novell software, at any time, without any obligation to notify any person or entity of such changes.

Any products or technical information provided under this Agreement may be subject to U.S. export controls and the trade laws of other countries. You agree to comply with all export control regulations and to obtain any required licenses or classification to export, re-export or import deliverables. You agree not to export or re-export to entities on the current U.S. export exclusion lists or to any embargoed or terrorist countries as specified in the U.S. export laws. You agree to not use deliverables for prohibited nuclear, missile, or chemical biological weaponry end uses. See the [Novell International Trade Services Web page \(http://www.novell.com/info/exports/\)](http://www.novell.com/info/exports/) for more information on exporting Novell software. Novell assumes no responsibility for your failure to obtain any necessary export approvals.

Copyright © 2014 Novell, Inc. All rights reserved. No part of this publication may be reproduced, photocopied, stored on a retrieval system, or transmitted without the express written consent of the publisher.

Novell, Inc.
1800 South Novell Place
Provo, UT 84606
U.S.A.
www.novell.com

Online Documentation: To access the latest online documentation for this and other Novell products, see the [Novell Documentation Web page \(http://www.novell.com/documentation/zenworks113\)](http://www.novell.com/documentation/zenworks113).

Novell Trademarks

For Novell trademarks, see [the Novell Trademark and Service Mark list \(http://www.novell.com/company/legal/trademarks/tmlist.html\)](http://www.novell.com/company/legal/trademarks/tmlist.html).

Third-Party Materials

All third-party trademarks are the property of their respective owners.

About This Guide

This *ZENworks 11 SP3 Registry Keys Reference* provides information about the registry keys used to control functionality on ZENworks devices (servers and workstations).

Audience

This guide is intended for ZENworks administrators.

Feedback

We want to hear your comments and suggestions about this manual and the other documentation included with this product. Please use the User Comments feature at the bottom of each page of the online documentation.

Additional Documentation

ZENworks 11 SP3 is supported by other documentation (in both PDF and HTML formats) that you can use to learn about and implement the product. For additional documentation, see the [ZENworks 11 SP3 documentation Web site \(http://www.novell.com/documentation/zenworks113\)](http://www.novell.com/documentation/zenworks113).

Contents

About This Guide	3
1 Registry Keys	7
A Documentation Updates	25

1 Registry Keys

This section provides information about registry keys used to carry out general administrative tasks on ZENworks managed devices.

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
AllowAnonymousAccessToContentRepo	Windows: HKLM\Software\Novell\ZCM Linux: /etc/opt/novell/zenworks/conf/xplatzmd.properties	Allows the user to access the content-repo directory anonymously.	String	True
AllowDLUWithoutNovellClient	Windows XP (32-bit): HKLM\Software\Novell\Nwgina Windows Vista or Windows 7 (32-bit and 64-bit) HKLM\Software\Novell\Authentication	To log a dynamic user with an e-directory account into a workstation using the Dynamic Local User policy. For more information, see “Implementing the Dynamic Local User Policy Without the Novell Client” in the <i>ZENworks 11 SP3 Configuration Policies Reference</i> .	DWORD	1
AllowPassiveModeLoginOnServers	HKLM\Software\Novell\ZCM\ZenLgn	To log in to the ZENworks console and to dynamically create user accounts for Windows 2003, Windows 2008, and Windows 2008 R2 devices. You can also use the DLU policy to create users dynamically. NOTE: Passthrough login is not supported on Windows 2003 64-bit devices.	DWORD	1
AllowZenInfoWithoutAdminPwd	HKLM\Software\Novell\ZCM	When the value of this key is set to True, users other than administrators can also log in to ZENworks. For more information, see “zman(1)” in the <i>ZENworks 11 SP3 Command Line Utilities Reference</i> .	String	True

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
BundleOrderingTimeSlice	HKLM\Software\Novell\ZCM	Allows you to configure the time that the agent waits before reordering the assigned bundles on a Windows managed device. The default value is 5 seconds. For more information, see “Enabling Bundle Ordering” in the <i>ZENworks 11 SP3 Software Distribution Reference</i> .	String	Any value greater than 0, in seconds
BUNDLE_ORDERING_TIME_LAG_SECONDS	/etc/opt/novell/zenworks/conf/xplatcmd.properties	Allows you to configure the amount of time that the agent waits before reordering the assigned bundles on a Linux managed device. The default value is 5 seconds. For more information, see “Enabling Bundle Ordering” in the <i>ZENworks 11 SP3 Software Distribution Reference</i> .	String	Any value greater than 0, in seconds
CancelOnNoResponse	Windows 32-bit HKLM\Software\Novell\ZCM\ActionHandler\CancelOnNoResponse Windows 64-bit HKLM\Software\Wow6432Node\Novell\ZCM\ActionHandler\CancelOnNoResponse	Allows reboot control and prompt control to set the auto continue and auto cancel options. For more information, see “User Cancels Allowed” in the <i>ZENworks 11 SP3 Software Distribution Reference</i> .	DWORD	1
CDPWebCallWaitTimeout	HKLM\Software\Novell\ZCM	To modify the Web Service time out on a Satellite device for Windows, set this registry key value to the desired time you want. For more information, see “Manually Configuring the Web Service Timeout Advanced Content Replication Setting” in the <i>ZENworks 11 SP3 Primary Server and Satellite Reference</i> .	String	Desired time in milliseconds
cleanUpStalePrintersAtPostDesktop	HKLM\SOFTWARE\Novell\ZCM\PrinterPolicy	To remove printers of the previous user session when a new user logs in to the same device. NOTE: The printers of the previous user session will be removed only after the registry key is set and the device is rebooted. This is applicable only for Samba printers.	String	True

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
Default	HKLM\Software\Novell\ZCM\Migration\MSIOptions\	<p>You can use this string to determine how much of the user interface to display during the installation of the migrated MSI application.</p> <p>Displays an appropriate user interface level (as chosen by the Windows Installer)</p> <p>For more information, see “Using the Registry Editor to Configure Additional Options for Migrating MSI Applications” in the <i>ZENworks 11 SP3 Configuration Management Migration Guide</i></p>	String	/qb-
defaultUICulture	HKLM\Software\Novell\ZCM	<p>ZENworks Agent reads this registry key and loads the corresponding language resources.</p> <p>If a language pack is installed on a device and the display language is set to an installed language pack that is not supported by ZENworks, then you can load resources for any of the ZENworks supported languages by setting the defaultUICulture registry key to the appropriate culture value. For example, to load English (United States) set it to en-US, or to load French (France) set it to fr-FR.</p>	String	<p>Specify the Language Locale value.</p> <p>Example for English language (United States): en-US</p>
DefaultRealm	HKLM\Software\Novell\ZCM\ZenLgn\	<p>To reduce the device login time, specify the user source in this registry key.</p> <p>For more information, see “Reducing Device Login Time by Specifying the Default User Source” in the ZENworks 11 SP3 User Source and Authentication Reference.</p>	String	<p>Desired User source</p> <p>The DefaultRealm value is case sensitive since the realm name is case sensitive.</p>

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
Delay	HKLM\Software\Netware\Nal\1.0\NalView	<p>During the user login, NalView.exe runs on the device, resulting in delay in the overall login time. To speed up the login process, set the required value in number of seconds to delay NALVIEW from processing its action.</p> <p>The value configured in the registry key will delay, in seconds, the creation of ZCM bundle icons on Explorer, Start Menu, Quick Launch, System Tray, and Desktop (if configured as part of the bundle assignments).</p>	DWORD	60
Disabled	HKLM\Software\Netware\Nal\1.0\NalView	<p>During the user login, NalView.exe runs on the device, resulting in delay in the overall login time. To speed up the login process, set the registry key value to 1.</p> <p>For more information, see “Troubleshooting User Sources” in the ZENworks 11 SP3 User Source and Authentication Reference.</p>	DWORD	1
disableCachedLogin	HKLM\Software\Novell\ZCM	<p>You can use this key to turn on the Disconnected Mode Login feature on Citrix or terminal servers. By default, this feature is disabled on Citrix or terminal servers and enabled on desktop machines.</p> <p>To improve the login performance, disable the caching of credentials for disconnected mode login on terminal server class machine, by setting the value of this registry key to True.</p>	String	True / False
DisableExplorerRestart	HKLM\Software\Novell\ZCM\GroupPolicy	This registry key ensures that ZENworks Configuration Management does not restart the Windows explorer.	String	True / False
DisablePassiveModeLogin	HKLM\Software\Novell\ZCM\ZenLgn	To disable login to the Management Zone when the user logs in through the Microsoft or Novell client.	DWORD	Any value other than zero
DisablePassiveModeLoginPrompt	HKLM\Software\Novell\ZCM\ZenLgn	To disable the ZENworks login prompt that appears if login through the Microsoft client or Novell client fails. For more information, see “Locate the following key in the registry on the user’s device:” in the ZENworks 11 SP3 User Source and Authentication Reference.	DWORD	Any value other than zero

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
DisableZENCredentialProvider	HKLM\Software\Novell\ZCM\ZenLgn	The ZENworks Credential Provider filters the Windows Password Credential Provider. When you install the ZENworks Agent on the Windows Vista or later versions and Windows 2008 Server or later versions device that has third-party products with Credential Providers installed, multiple user tiles are displayed. For more information, see <i>“Disabling the ZENWorks Credential Provider on a Device”</i> in the ZENworks 11 SP3 User Source and Authentication Reference.	DWORD	1
DomainLogin	HKLM\Software\Novell\ZCM\ZenLgn	This key helps you to identify the login domain of the user. If the value is set to 1, the user is in Microsoft Active Directory.	DWORD	1
DonotFetchUserGroups	HKLM\Software\Novell\ZCM\AgentSettings	To significantly improve the time taken to log in to a managed device, if a Dynamic Local User policy that has no login restrictions configured is assigned to the device. For more information, see <i>“Dynamic Local User Policy”</i> in the <i>ZENworks 11 SP3 Configuration Policies Reference</i> .	String	True
Dontdisplaylastuser name	HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows\CurrentVersion\Policies\System	This key removes any user account names from the Windows logon welcome screen and forces user to enter password and user name when logging in.	DWORD	1
DontUpdateGroupMemberships	Windows 32-bit: HKLM\Software\Novell\Nwgina\DynamicLocalUser Windows 64-bit: HKLM\Software\Wow6432Node\Novell\Nwgina\DynamicLocalUser	To update group memberships of the user on the managed device. For more information, see <i>“Unable to update the group membership of the user on the managed device”</i> in the <i>ZENworks 11 SP3 Configuration Policies Reference</i> .	String	0
eDIRLogin	HKLM\Software\Novell\ZCM\ZenLgn\	This key helps you to identify the login domain of the user. If the value is set to 1, the user is in Novell eDirectory.	DWORD	1

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
EnableBatchRefresh	HKLM\Software\Novell\ZCM\	To refresh the user sessions on a device in batches, set this registry key value to 1. For more information, see “The partial or the general refresh of a terminal server might cause high usage of system resources and take considerable time to refresh the server” in the <i>ZENworks 11 SP3 Adaptive Agent Reference</i> .	String	1
EnableEDirPasswordForFA	Windows 32-bit: HKLM\Software\Novell\Nwgina\DynamicLocalUser Windows 64-bit: HKLM\Software\Wow6432Node\Novell\Nwgina\DynamicLocalUser	To enable a Dynamic Local User in logging in to a device again after logging out of the managed device that is disconnected from the network. For more information, see “Dynamic Local User Policy Troubleshooting” in the <i>ZENworks 11 SP3 Configuration Policies Reference</i> .	DWORD	1
EnableSeamlessLogin	HKLM\Software\Novell\ZCM\ZenLgn\	To enable seamless authentication for a user on a device, set this registry key value to 1. For more information, see “Enabling Seamless Authentication on a Device” in the <i>ZENworks 11 SP3 User Source and Authentication Reference</i> .	DWORD	1
EnableSecretStore	HKLM\Software\Novell\ZCM\ZenLgn\	To log in to a ZENworks server that has a Secret Store configured, set this registry key value to 1. For more information, see “Authenticating in to a ZENworks Server That Has Novell SecretStore Configured” in the <i>ZENworks 11 SP3 User Source and Authentication Reference</i> .	DWORD	1
EnableStatusMessages	HKLM\Software\Novell\Authentication	To disable the login status messages on a device screen, set this registry key value to 0. For more information, see “Disabling the Login Status Messages Display on the Device Screen” in the <i>ZENworks 11 SP3 User Source and Authentication Reference</i> .	DWORD	0

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
EnableTraditionalC asa	HKLM\Software\Novell\ZCM	<p>To enable the older Casa Auth Client component and micasa as secret store, by setting the value of this registry key to True.</p> <p>This registry key is used in the following scenarios:</p> <ul style="list-style-type: none"> ◆ When you do not want to change the existing CASA Auth Client and micasa components to newly added CASA components. ◆ If a user has issues due to the newly added CASA Auth Client component, the user can switch to the older CASA components. <p>IMPORTANT: ZENworks Agent maintains the following secret stores for caching the user credentials:</p> <ul style="list-style-type: none"> ◆ HKLM\Software\Novell\ZCM\EnableTraditionalCasa (Reg_SZ) : A successful log in is required after setting to True and log off or log in again. This will ensure that credentials will be cached in old CASA store and will be used for further cache logins using old CASA store. ◆ HKLM\Software\Novell\ZCM\EnableTraditionalCasa (Reg_SZ) : A successful log in is required after setting to False and log off or log in again. This will ensure that credentials will be cached in newly added CASA store and will be used for further cache logins using old CASA store. 	String	True / False
EnableZENMemory Cache	HKLM\Software\Novell\ZCM	To improve the login performance on Terminal servers, enable the caching of objects in memory.	String	True / False

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
EnableZENMemoryKeyCache	HKLM\Software\Novell\ZCM	This registry key creates a memory cache for storing keys of all the cached entries. You can use this memory cache to look up if a particular entry is cached or not, in a Terminal server multiuser login scenario. If the entry is not cached, then the unnecessary access to the persistent cache can be avoided.	String	True / False
ForceHKLMandNoDPAPI	HKLM\Software\Protocom\SecureLogin	To log into the ZENworks Server, while logging into a Windows Vista device, set this registry key value to 1.	DWORD	1
Full	HKLM\Software\Novell\ZCM\Migration\MSIOptions\	Displays a full user interface (Wizard dialog boxes, progress information, error messages and prompts, and so forth). For more information, see “Using the Registry Editor to Configure Additional Options for Migrating MSI Applications” in the <i>ZENworks 11 SP3 Configuration Management Migration Guide</i> .	String	/qf
HonorActionHandlerSetting	HKEY_LOCAL_MACHINE\SOFTWARE\Novell\ZCM\ActionHandler\	Helps environment variables to get resolved in different bundle action context. For example: If the bundle action is set to run as system user, then all the environment variables in the bundle action data will be resolved in the system context.	String	True
HonorClient32WorkstationOnlyCheckbox	HKLM\Software\Novell\ZCM\ZenLgn	To log in directly into a Windows XP workstation that has both the Novell Client and the ZENworks Agent installed, set this registry key value to 1. For more information, see “Logging Directly in to a Workstation That has Both Novell Client and ZENworks Agent Installed” in the ZENworks 11 SP3 User Source and Authentication Reference.	DWORD	1

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
HonorWorkstationOnlyLogin	HKLM\Software\Novell\ZCM\ HKLM\SOFTWARE\Novell\ZCM\INV_CDF	To log in directly into a Windows 7, Windows 8, or Windows Vista workstation that has both the Novell Client and the ZENworks Agent installed, set this registry key value to 1. For more information, see “Logging Directly in to a Workstation That has Both Novell Client and ZENworks Agent Installed” in the ZENworks 11 SP3 User Source and Authentication Reference. To launch the Collection Data Form (CDF) in the background. By default the CDF will appear in front of an active application. Use this registry key to reverse the default behavior.	DWORD	1
IgnorePrezenworksSecuritySettings(REG_SZ)	HKLM\Software\Novell\ZCM\GroupPolicy	To exclude the local group policy security settings from being backed-up and restored.	String	True
LoadAppdataIntoMemoryOnDemand	HKLM\Software\Novell\ZCM\ All ZENworks applications contain some action data. This is required to process actions such as launch, install, uninstall and so forth. For more information, see “Enabling the Loading of Application Data in to the Device Memory on Demand” in the ZENworks 11 SP3 Software Distribution Reference .	To delay loading of the action data into the memory to a required point and to reduce the memory footprint for devices with low memory. All ZENworks applications contain some action data. This is required to process actions such as launch, install, uninstall and so forth. For more information, see “Enabling the Loading of Application Data in to the Device Memory on Demand” in the ZENworks 11 SP3 Software Distribution Reference .	String	True
LocalAccountTokenFilterPolicy	HKLM\Software\Microsoft\Windows\CurrentVersion\Policies\System\LocalAccountTokenFilterPolicy Windows Vista (32-bit) Windows Server 2008(32-bit) Windows 7 and Windows Server 2008 R2(32-bit)	Allows remote users to log in and not be forced to be guest. For more information see, “Enabling Classic File Sharing” in the ZENworks 11 SP3 Discovery, Deployment, and Retirement Reference .	DWORD	1

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
LogoffCheckSysModules	HKLM\System\CurrentControlSet\Control\Citrix\wfshell\TWI	To completely terminate a session on the Citrix server and ensure that policies are unenforced on the device. For more information, see “Closing a published application or logging out of the shared desktop of a Citrix server fails to terminate the session on the Citrix server” in the ZENworks 11 SP3 Configuration Policies Reference .	String	Change the value from ZCMUMHelper.exe to ZenUserDaemon.exe, ZCMUMHelper.exe
ManualDeviceRefresh	HKLM\Software\Novell\ZCM\	To disable the general refresh for a device session on a Windows device, set this registry key value to Disabled. For more information, see “By default, the general refresh on a Windows device refreshes both the device and user sessions.” in the ZENworks 11 SP3 Adaptive Agent Reference .	String	Enabled/Disabled
MigrateWithParentOptions	HKLM\Software\Novell\ZCM\Migration\MSIOptions\	MSPs are migrated in Silent mode. For more information, see “Using the Registry Editor to Configure Additional Options for Migrating MSI Applications” in the ZENworks 11 SP3 Configuration Management Migration Guide .	String	0
MaxValue	HKLM\Software\Novell\ZCM\ZenLgn\History\ZenCacheLimit	To specify the number of credentials that can be cached on a device at any point of time, use this registry key.	String	Specify a number from 1 to 100
MaxLogFileSize	HKLM\Software\Novell\ZCM\ZenLgn\MaxLogFileSize	To retain the old logs and append the new logs in the zenlgn.log file, specify in Kilo Bytes.	DWORD	1024
MaxLogFileSize	HKLM\Software\Novell\NWGINA\MaxLogFileSize	To retain the old logs and append the new logs in the nwgina.log file, specify in Kilo Bytes.	DWORD	1024
MaxZenPrinterProcessingTimeOut		To set a default value that forces the Printer policy handler to wait for a set amount of time. For more information, see “Printer Policy Troubleshooting” in the ZENworks 11 SP3 Configuration Policies Reference .	String	Specify an appropriate time out value in seconds.

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
MergedCacheRequired	HKLM\Software\Novell\ZCM\GroupPolicy	To enable the merged cache feature, set this registry key to a non-zero value.	String	Any value other than zero
NalShellDelay	HKLM\Software\Novell\ZCM\NAL	Configure delay time in seconds for NalShell in the registry key. Based on the configured time in the registry parameter explorer delays the loading process of Nalshell.	DWORD	Specify any value in seconds other than zero.
PassiveMode	HKLM\Software\Novell\NWGINA	To start Novell SecureLogin seamlessly, set this registry key value to 1. For more information, see “Troubleshooting User Sources” in the ZENworks 11 SP3 User Source and Authentication Reference.	DWORD	1
PERMISSION_MS_G_POSTPONES_REMAINING	HKLM\Software\Novell\ZCM\SystemUpdate	The value of this key determines the number of times the user can postpone an update. For more information, see “Configuring the System Update Behavior of the ZENworks Adaptive Agent” in the <i>ZENworks 11 SP3 System Updates Reference</i> .	String	Specify the number of times you need to postpone the update.
PingRetryCount	HKLM\Software\Novell\ZCM\	Controls the number of retries the ZENworks Adaptive Agent attempts after failing to connect to a ZENworks Server during a device refresh. The default is 1 retry. For more information, see “Troubleshooting the Adaptive Agent” in the <i>ZENworks 11 SP3 Adaptive Agent Reference</i> .	String	Any value. Use 0 to specify no retries.

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
PreferredCollectionRollUpServer	<p>64 bit Windows (Windows Server 2008, Windows Vista, Windows Server 2003, and Windows XP):</p> <p>HKLM\Software\Wow6432Node\Novell\ZCM\Satellite\PreferredCollectionRollUpServer</p> <p>32 and 64 bit Windows (Windows 7 and Windows Server 2008 R2, and later):</p> <p>HKLM\Software\Novell\ZCM\Satellite\PreferredCollectionRollUpServer</p>	To assign a different Primary Server to the satellite to roll up collection items instead of using a parent Primary Server.	String	Multiple URLs delimited by ‘;’
PrintWaitTime	HKLM\Software\Novell\ZCM\PrinterPolicy	<p>To install a Samba or a network printer by using a Printer policy.</p> <p>For more information, see “Printer Policy Troubleshooting” in the <i>ZENworks 11 SP3 Configuration Policies Reference</i>.</p>	String	200
ProceedPatchUninstallSetting	HKLM\SOFTWARE\Novell\ZCM\PatchManagement	<p>Allows you to uninstall a patch bundle.</p> <p>From ZENworks 11.3.1 onwards, the <i>Uninstall application if not used within_days</i> option in the Uninstall Options dialog will not be honored for Patch bundles. Use this registry key to honor this option for Patch bundles.</p>	String	True
Progress	HKLM\Software\Novell\ZCM\Migration\MSIOptions\	<p>Displays simple progress information and error messages/prompts.</p> <p>For more information, see “Using the Registry Editor to Configure Additional Options for Migrating MSI Applications” in the <i>ZENworks 11 SP3 Configuration Management Migration Guide</i>.</p>	String	/qb!

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
read-timeout	Windows: HKLM\Software\Novell\ZCM Linux: /etc/opt/novell/zenworks/conf/xplatcmd.properties	To set the read time out value of an Agent on a device, set this registry key value to 100. For more information, see “Troubleshooting the Adaptive Agent” in the <i>ZENworks 11 SP3 Adaptive Agent Reference</i> .	String	100
ReApplyPolicyatDeviceStartup	HKLM\Software\Novell\ZCM\GroupPolicy	To apply Group policy again at device startup even if there is no change in the group policy. This is useful when group policy has security settings, which are not registry configurable. For example: Deny local login. For more information, see “Windows Group Policy Troubleshooting” in the <i>ZENworks 11 SP3 Configuration Policies Reference</i> .	String	Any value other than null
ReApplyPolicyatUserPredeskTop	HKLM\Software\Novell\ZCM\GroupPolicy	If you have assigned Group Policy settings to a user, they might not always apply on the device. For more information, see “Windows Group Policy Troubleshooting” in the <i>ZENworks 11 SP3 Configuration Policies Reference</i> .	String	Any value other than null
REBOOT_MSG_POSTPONEMENT	HKLM\Software\Novell\ZCM\SystemUpdate	This key specifies the number of times that you can postpone a reboot of an update. For more information, see “Configuring the System Update Behavior of the ZENworks Adaptive Agent” in the <i>ZENworks 11 SP3 System Updates Reference</i> .	String	Specify the number of times to postpone an update.
Reduced	HKLM\Software\Novell\ZCM\Migration\MSIOptions\	Displays a full user interface with wizard dialog boxes suppressed For more information, see “Using the Registry Editor to Configure Additional Options for Migrating MSI Applications” in the <i>ZENworks 11 SP3 Configuration Management Migration Guide</i> .	String	/qr

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
RemoveZenPrintersAtLogout	HKLM\SOFTWARE\Novell\ZCM	To uninstall all installed user assigned printers at logout. You cannot uninstall the user assigned printers at logout, If the value is False. For more information, see “The user-assigned printers are not uninstalled at logout” in the ZENworks 11 SP3 Configuration Policies Reference .	String	False/True
runBookmarksMappedDrive	HKLM\SOFTWARE\Novell\ZCM	To enforce Browser Bookmarks policy on a managed device, which has redirected home directory for saving bookmarks. For more information, see “Bookmark policy fails with a redirected home directory” in the ZENworks 11 SP3 Configuration Policies Reference .	String	True
ScheduleRetries	HKLM\Software\Novell\ZCM\	If a bundle with an assignment schedule fails to execute on a device, an attempt to execute the bundle on the device is made five times, by default. For more information, see “Assigning Existing Bundles to Devices” in the ZENworks 11 SP3 Software Distribution Reference .	String	0
seticonondesktop	HKLM\Software\Novell\ZCM\NAL	Allows you to create the shortcut icons for bundles.	String	1
ShutdownOnTimeout	Windows: HKEY_LOCAL_MACHINE\SOFTWARE\Novell\ZCM\ActionHandler Linux: etc/opt/novell/zenworks/conf/xplatzmd.properties	To cancel the reboot or shutdown action on a device when the value of this registry key is set to <i>No</i> and the user does not act on <i>User Cancel</i> prompt. To reboot a device when the value of ShutdownOnTimeout registry key is set to <i>Yes</i> .	String	Yes/No
Silent	HKLM\Software\Novell\ZCM\Migration\MSIOptions\	Displays no user interface. For more information, see “Using the Registry Editor to Configure Additional Options for Migrating MSI Applications” in the ZENworks 11 SP3 Configuration Management Migration Guide .	String	/qn

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
SkipIPrintClientValidation	HKLM\Software\Novell\ZCM\Migration	To migrate an iPrint policy that does not have the policy setup file associated with it, set the value of this registry key to false. For more information, see “Unable to migrate iPrint policy that does not have the policy setup file associated with it” in the <i>ZENworks 11 SP3 Configuration Management Migration Guide</i> .	String	False /True
SqliteAsyncIOExtension	HKLM\Software\Novell\ZCM\	To improve the response of the cache memory on a managed device, enable the Asynchronous IO feature, by setting the value of this registry key to True.	String	True/False
SqliteCacheSeconds	HKLM\Software\Novell\ZCM\	To allow data to persist in the cache memory, set this registry key value to 10000. This allows the data to be present in the cache memory for 10000 milliseconds.	String	10000
SqliteCacheLimit	HKLM\Software\Novell\ZCM\	To allow a certain number of key-value pairs to persist in the Buffer cache, set this registry value to 500. This allows 500 key-value pairs to persist in the Buffer cache.	String	500
UMUserFullName	HKLM\Software\Novell\ZCM\Usage	For user login name, to change the setting from User ID to Full Name mode, set this registry value to 1. For more information, see “Troubleshooting the Adaptive Agent” in the <i>ZENworks 11 SP3 Adaptive Agent Reference</i> .	String	1 / 0
upload-timeout	Windows: HKLM\Software\Novell\ZCM\ Linux:/etc/opt/novell/zenworks/conf/xplat/md.properties	To set the default upload timeout value of an Agent on a managed device, set this registry key value to 200. For more information, see “Troubleshooting the Adaptive Agent” in the <i>ZENworks 11 SP3 Adaptive Agent Reference</i> .	String	200
UserDaemonRetries	HKEY_LOCAL_MACHINE\SOFTWARE\Novell\ZCM\UserDaemon\UserDaemonRetries	If user is not logged in to the device, then this configuration determines how many times the HKCU bundle system requirement retries to get the user daemon.	DWORD	Specify a number.
ZENCachePersistObjectsAsynchronously	HKLM\Software\Novell\ZCM	To improve the login performance on Terminal servers, enable the asynchronous persistence of objects.	String	True / False

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
ZenNotifyConnectionTimeout	HKEY_LOCAL_MACHINE\SOFTWARE\Novell\ZCM\	To configure the timeout value in seconds for a ZENworks service to update the <i>ZenNotifyIcon Progress</i> window. The ZENworks service calls the <i>ZenNotifyIcon</i> process to update the bundle's progress in the <i>ZenNotifyIcon Progress</i> window, and waits for <i>ZenNotifyIcon</i> to update the bundle's progress and return the call. If the <i>ZenNotifyIcon</i> process does not return the call to the ZENworks service within the timeout period, then the ZENworks service will proceed to the next action in the bundle schedule.	DWORD	Any value greater than zero (in seconds).
ZENThreadPoolMaximum	HKLM\Software\Novell\ZCM\	This registry key defines the maximum thread count in ZENworks thread pool. The default value is 150 on a Terminal server and 50 on other devices.	String	Specify a number.
ZENThreadPoolMinimum	HKLM\Software\Novell\ZCM\	This registry key defines the minimum thread count in ZENworks thread pool. The default minimum thread count is 3. Specify a number greater than the default value.	String	Specify a number.
ZISWINClear	HKLM\Software\Novell\ZCM\	When this string value is set to 1, ZISWIN clears all the Image Safe data and exits without performing any other task. For more information, see <i>Novell ZENworks ISD Service in .ZENworks 11 SP3 Preboot Services and Imaging Reference</i>	String	1
ZISWIN Disabled	HKLM\Software\Novell\ZCM\	When this string value is set to 1, ZISWIN exits without performing any task. For more information, see <i>ZENworks 11 SP3 Preboot Services and Imaging Reference</i> .	String	1
ZISWIN Reset Flag	HKLM\Software\Novell\ZCM\	When this string value is set to 1, ZISWIN sets the <i>Just Imaged</i> flag to <i>FALSE</i> exits without performing any other task. For more information, see the <i>ZENworks 11 SP3 Preboot Services and Imaging Reference</i> .	String	1

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
ZISWIN Do Not Restore Mask	HKLM\Software\Novell\ZCM	<p>You can use this DWORD to specify the Image Safe data component that you do not want ZISWIN to restore to the Windows registry after a successful completion of an image. This value is interpreted as a mask.</p> <p>For more information, see the ZENworks 11 SP3 Preboot Services and Imaging Reference.</p>	DWORD	Desired value of the Image Safe data component.
ZISWIN SYSPrep Restore Mask	HKLM\Software\Novell\ZCM	<p>If you are using the SYSPrep process to mask the Image Safe data components, then use this registry key.</p> <p>For more information, see “ZENworks Imaging Engine Commands” in the ZENworks 11 SP3 Preboot Services and Imaging Reference.</p>	DWORD	Desired value of the Image Safe data component.
ZISWIN Do Not Collect Mask	HKLM\Software\Novell\ZCM	<p>You can use this DWORD to specify the components that you do not want ZISWIN to collect in the Image Safe data.</p> <p>For more information, see “Component Masks” in the ZENworks 11 SP3 Preboot Services and Imaging Reference.</p>	DWORD	Desired value of the Image Safe data component.
ZISWIN Clear Mask	HKLM\Software\Novell\ZCM	<p>You can use this DWORD to specify the components that you want ZISWIN to clear from the Image Safe data.</p> <p>For more information, see “Component Masks” in the ZENworks 11 SP3 Preboot Services and Imaging Reference.</p>	DWORD	Desired value of the Image Safe data component.

A Documentation Updates

This section summarizes the significant changes made to the *Registry Key Reference* since the initial release of ZENworks 11 SP3.

December 2014: System Update (11.3.2) for ZENworks 11 SP3

Location	Change
"defaultUICulture" on page 9	Added this registry key to load the corresponding language resources.
"ShutdownOnTimeout" on page 20	Added this registry key to manage the reboot or shutdown action on a device based on the value specified for the ShutdownOnTimeout registry key.
"ZenNotifyConnectionTimeOut" on page 22	Added this registry key to configure the timeout value in seconds for a ZENworks service to update the <i>ZenNotifyIcon Progress</i> window.

July 2014: System Update (11.3.1) for ZENworks 11 SP3

Location	Change
"NalShellDelay" on page 17	Added this registry key that delays the loading of NalShell. This can be useful on devices whose mapped drives are resolved slowly, resulting in bundle shortcuts not displaying immediately in the Start menu.
"ProceedPatchUninstallSetting" on page 18	Added this registry key in order to continue to enforce the <i>Uninstall application if not used within_days</i> option in the Uninstall Options dialog for Patch bundles. Starting with ZENworks 11.3.1, this option is not applied to Patch bundles unless this registry key is used.
"cleanUpStalePrintersAtPostDesktop" on page 8	Added this registry key to remove the previous user's Samba printers when a new user logs in to the same device. The printers are removed only after the registry key is set and the device is rebooted. This is applicable only for Samba printers.
"HonorActionHandlerSetting" on page 14	Added this registry key that helps environment variables to get resolved in different bundle action contexts. For example, if the bundle action is set to run as system user, then all the environment variables in the bundle action data are resolved in the system context.
