

Novell Access Manager

3.0 SP2

March 21, 2008

EVENT CODES

www.novell.com



Novell®

Legal Notices

Novell, Inc., makes no representations or warranties with respect to the contents or use of this documentation, and specifically disclaims any express or implied warranties of merchantability or fitness for any particular purpose. Further, Novell, Inc., reserves the right to revise this publication and to make changes to its content, at any time, without obligation to notify any person or entity of such revisions or changes.

Further, Novell, Inc., makes no representations or warranties with respect to any software, and specifically disclaims any express or implied warranties of merchantability or fitness for any particular purpose. Further, Novell, Inc., reserves the right to make changes to any and all parts of Novell software, at any time, without any obligation to notify any person or entity of such changes.

Any products or technical information provided under this Agreement may be subject to U.S. export controls and the trade laws of other countries. You agree to comply with all export control regulations and to obtain any required licenses or classification to export, re-export or import deliverables. You agree not to export or re-export to entities on the current U.S. export exclusion lists or to any embargoed or terrorist countries as specified in the U.S. export laws. You agree to not use deliverables for prohibited nuclear, missile, or chemical biological weaponry end uses. See the [Novell International Trade Services Web page \(http://www.novell.com/info/exports/\)](http://www.novell.com/info/exports/) for more information on exporting Novell software. Novell assumes no responsibility for your failure to obtain any necessary export approvals.

Copyright © 2008 Novell, Inc. All rights reserved. No part of this publication may be reproduced, photocopied, stored on a retrieval system, or transmitted without the express written consent of the publisher.

Novell, Inc., has intellectual property rights relating to technology embodied in the product that is described in this document. In particular, and without limitation, these intellectual property rights may include one or more of the U.S. patents listed on the [Novell Legal Patents Web page \(http://www.novell.com/company/legal/patents/\)](http://www.novell.com/company/legal/patents/) and one or more additional patents or pending patent applications in the U.S. and in other countries.

Novell, Inc.
404 Wyman Street, Suite 500
Waltham, MA 02451
U.S.A.
www.novell.com

Online Documentation: To access the latest online documentation for this and other Novell products, see the [Novell Documentation Web page \(http://www.novell.com/documentation\)](http://www.novell.com/documentation).

Novell Trademarks

For Novell trademarks, see [the Novell Trademark and Service Mark list \(http://www.novell.com/company/legal/trademarks/tmlist.html\)](http://www.novell.com/company/legal/trademarks/tmlist.html).

Third-Party Materials

All third-party trademarks are the property of their respective owners.

Contents

About This Guide	7
1 Event Codes	9
1.1 Currently Assigned Event Codes	9
1.1.1 Identity Server (001)	9
1.1.2 Linux Access Gateway (045)	44
1.1.3 SSL VPN (005)	45
1.1.4 J2EE Agents (006)	48
1.1.5 Server Communications (JCC) (007)	53
1.1.6 Policy Engine (008)	74
1.1.7 Administration Console (009)	78
1.1.8 Backup and Restore (010)	117
1.1.9 SOAP Policy Enforcement Point (011)	123
1.1.10 Novell Modular Authentication Class (012)	128

About This Guide

This guide is intended to help you understand and resolve any issues with the event codes that are displayed on error pages or logged in files.

- ♦ [Chapter 1, “Event Codes,” on page 9](#)

Audience

This guide is intended for Access Manager administrators. It is assumed that you have knowledge of evolving Internet protocols, such as:

- ♦ Extensible Markup Language (XML)
- ♦ Simple Object Access Protocol (SOAP)
- ♦ Security Assertion Markup Language (SAML)
- ♦ Public Key Infrastructure (PKI) digital signature concepts and Internet security
- ♦ Secure Socket Layer/Transport Layer Security (SSL/TSL)
- ♦ Hypertext Transfer Protocol (HTTP and HTTPS)
- ♦ Uniform Resource Identifiers (URIs)
- ♦ Domain Name System (DNS)
- ♦ Web Services Description Language (WSDL)

Feedback

We want to hear your comments and suggestions about this manual and the other documentation included with this product. Please use the User Comments feature at the bottom of each page of the online documentation, or go to www.novell.com/documentation/feedback.html and enter your comments there.

Documentation Updates

For the most recent version of the *Access Manager Event Codes Guide*, visit the [Novell Access Manager Documentation Web site \(http://www.novell.com/documentation/novellaccessmanager\)](http://www.novell.com/documentation/novellaccessmanager).

Additional Documentation

- ♦ [Novell Access Manager 3.0 SP2 Administration Guide](#)
- ♦ [Novell Access Manager 3.0 SP2 Setup Guide](#)
- ♦ [Novell Access Manager 3.0 SP2 Installation Guide](#)
- ♦ [Novell Access Manager 3.0 SP2 J2EE Agent Guide](#)

Documentation Conventions

In Novell documentation, a greater-than symbol (>) is used to separate actions within a step and items in a cross-reference path.

A trademark symbol (® , ™ , etc.) denotes a Novell trademark. An asterisk (*) denotes a third-party trademark.

When a single pathname can be written with a backslash for some platforms or a forward slash for other platforms, the pathname is presented with a backslash. Users of platforms that require a forward slash, such as Linux or UNIX, should use forward slashes as required by your software.

Event Codes

Event codes for Access Manager consist of 4 fields that describe the type of code and the module that produced it:

- ◆ Severity (1 digit)
 - ◆ 1 = severe - Describes problems that needs to be resolved in order for the system to run correctly.
 - ◆ 2 = error - Describes that a failure occurred, but the system is operational.
 - ◆ 3 = warn - Describes a situation that may exist that the administrator should be aware of and may need to address. The system is currently running properly
 - ◆ 4 = config - Describes configuration related information.
 - ◆ 5 = info - Describes events that occur.
 - ◆ 6 = debug - Describes execution points within the software.
 - ◆ 9 = internal - Describes an error that is for internal use only. This error code will not be documented in any public documentation.
- ◆ Component issuing the error code (3 digits)
- ◆ Sub-grouping for further classification within a component (2 digits)
- ◆ Event code (three digits)

0	000	00	000
Severity	Component field	Sub-grouping	Event Code

1.1 Currently Assigned Event Codes

- ◆ [Section 1.1.1, “Identity Server \(001\),” on page 9](#)
- ◆ [Section 1.1.2, “Linux Access Gateway \(045\),” on page 44](#)
- ◆ [Section 1.1.3, “SSL VPN \(005\),” on page 45](#)
- ◆ [Section 1.1.4, “J2EE Agents \(006\),” on page 48](#)
- ◆ [Section 1.1.5, “Server Communications \(JCC\) \(007\),” on page 53](#)
- ◆ [Section 1.1.6, “Policy Engine \(008\),” on page 74](#)
- ◆ [Section 1.1.7, “Administration Console \(009\),” on page 78](#)
- ◆ [Section 1.1.8, “Backup and Restore \(010\),” on page 117](#)
- ◆ [Section 1.1.9, “SOAP Policy Enforcement Point \(011\),” on page 123](#)
- ◆ [Section 1.1.10, “Novell Modular Authentication Class \(012\),” on page 128](#)

1.1.1 Identity Server (001)

Component 001

- ◆ Sub group 01: End user events

- ◆ Sub group 02: Web Service Framework (WSF)
- ◆ Sub Group 03: Web Service Consumer (WSC)
- ◆ Sub Group 04: User Authentication

Event Code	Message	Remedy
100100001		Type: SEVERE:NIDP:INITIALIZE:001
100100002		Type: SEVERE:NIDP:INITIALIZE:002
100101001	No binding available or set for profile.	Type: SEVERE:NIDP:USERMSG:001 Cause: An action using Liberty or SAML protocols could not be completed because the server and trusted provider are not compatibly configured to interact to complete the action. Action: Set the desired protocol profiles in the administration tool to match those supported at the trusted provider.
100101043	IDP is unable to load ESP metadata.	Type: SEVERE:NIDP:USERMSG:043 Cause: The IDP cannot connect to the metadata URL for the ESP. The IDP may not be able to resolve the domain name for the ESP or if HTTPS is being used, the IDP may not trust the SSL certificate for the ESP. The ESP may also not be running. Action: Make sure that certificates for ESP are imported and trusted into IDP configuration. Check the metadata URL for the ESP and make sure the metadata can be retrieved from a browser: <code>http://<DNS_name>/nosp/idff/metadata</code> For additional help, see “Troubleshooting 100101043 and 100101044 Liberty Metadata Load Errors” in the <i>Novell Access Manager 3.0 SP2 Administration Guide</i> .
100101044	ESP is unable to load IDP metadata	Type: SEVERE:NIDP:USERMSG:044 Cause: The ESP cannot connect to the metadata URL for the IDP. The ESP may not be able to resolve the domain name for the IDP or if HTTPS is being used, the ESP may not trust the SSL certificate for the IDP. The IDP may also not be running Action: Make sure the IDP is running and that all certificates are imported and trusted. Check the metadata URL for the IDP and make sure the metadata can be retrieved from a browser: <code>http://<DNS_name>/nidp/idff/metadata</code> A common cause is the base URL on the IDP is set incorrectly. For additional help, see “Troubleshooting 100101043 and 100101044 Liberty Metadata Load Errors” in the <i>Novell Access Manager 3.0 SP2 Administration Guide</i> .

Event Code	Message	Remedy
100101045	An error happened while the request was being sent to the correct cluster member for processing.	Type: SEVERE:NIDP:USERMSG:045 Cause: The target cluster member may be unavailable. Action: Ensure that all cluster devices are operating correctly.
100102001	Incomplete web service configuration.	Type: SEVERE:NIDP:WSF:001 Cause: The web service instance type (attribute nidsWsfServiceInstanceType on the nidsWsfService object) is not available in the service definition. Action: Delete the associated web service definition and recreate it.
100102002	Invalid web service configuration.	Type: SEVERE:NIDP:WSF:002 Cause: The web service configuration XML (attribute nidsConfigXML on the nidsWsfService object) has invalid XML. Action: Delete the associated web service definition and recreate it.
100102003	Unable to instantiate the web service provider authority class. This class will be com.novell.nidp.liberty.wsf.config.authority.Ildap.WSFConfigAuthorityLdap.	Type: SEVERE:NIDP:WSF:003 Cause: Some Java error (probably a classpath issue) is causing the main authority class to not instantiate. Action: Review how the Access Manager product was installed and attempt to determine if Java class files are being accessed from an unexpected source.
100102004	Unable to load web services.	Type: SEVERE:NIDP:WSF:004 Cause: This error catches all failures encountered while trying to load all web services. The reason will be different depending on where the error happened. Action: Try to delete and recreate the web services.
100102005	Unable to access Novell Secret Store.	Type: SEVERE:NIDP:WSF:005 Cause: The LDAP connection between the IDP and the User Store must be secure LDAP if Novell Secret Store is to be used as the back end storage for Credential Profile. Action: Go to the associated user store and change the connection type to secure LDAP.
100102006	Unable to create user profile object.	Type: SEVERE:NIDP:WSF:006 Cause: A Liberty User Profile Object did not exist for the current user, so an attempt was made to create one. That attempt failed! Action: Determine if the named container exists and that the administrator user has rights to create objects there.

Event Code	Message	Remedy
100102007	Unable to instantiate password callback class.	Type: SEVERE:NIDP:WSF:007 Cause: Could not find the password callback class in the classpath. Action: Make sure the password callback class to check UsernameToken that decrypts an encrypted message in WSS is in the classpath.
100102008	Unable to convert XML into Document.	Type: SEVERE:NIDP:WSF:008 Cause: This error occurred when converting XML to Document in WSS (Receiver side). It may happen due to incorrect WSC requests. Action: Check the WSC (Sender side) request and resend it.
100102009	Unable to process WSSecurity (WSS) message.	Type:SEVERE:NIDP:WSF:009 Cause: This error occurred when processing WSS headers (Receiver side). It may happen due to incorrect WSS headers in WSC requests. Action: Check the WSS headers in WSC (Sender side) request and resend it.
100102010	No WSS header found	Type: SEVERE:NIDP:WSF:010 Cause: This error occurred when processing WSS headers (Receiver side). It may happen due to no WSS headers in WSC requests. Action: Check the WSS headers in WSC (Sender side) request and resend it.
100102011	No processed WSS header found	Type: SEVERE:NIDP:WSF:011 Cause: This error occurred after processing WSS headers (Receiver side). It may happen due to incorrect or no WSS headers in WSC requests. Action: Check the WSS headers in WSC (Sender side) request and resend it.
100102012	WSS untrusted certificate	Type: SEVERE:NIDP:WSF:012 Cause: This error occurred when validating signature on WSS headers (Receiver side). The certificate used for the signature is not trusted. Action: Check the certificate used to sign the message. The certificate is trusted if either it itself or the certificate of the issuer is installed in the trust store.
100102013		Type: SEVERE:NIDP:WSF:013
100102014		Type: SEVERE:NIDP:WSF:014
100102015		Type: SEVERE:NIDP:WSF:015

Event Code	Message	Remedy
100102016		Type: SEVERE:NIDP:WSF:016
100102017		Type: SEVERE:NIDP:WSF:017
100102018		Type: SEVERE:NIDP:WSF:018
100102019		Type: SEVERE:NIDP:WSF:019
100102020		Type: SEVERE:NIDP:WSF:020
100102021		Type: SEVERE:NIDP:WSF:021
100102022		Type: SEVERE:NIDP:WSF:022
100102023		Type: SEVERE:NIDP:WSF:023
100102024		Type: SEVERE:NIDP:WSF:024
100102025		Type: SEVERE:NIDP:WSF:025
100102026		Type: SEVERE:NIDP:WSF:026
100102027		Type: SEVERE:NIDP:WSF:027
100102028		Type: SEVERE:NIDP:WSF:028
100102029		Type: SEVERE:NIDP:WSF:029
100102030		Type: SEVERE:NIDP:WSF:030
100102031		Type: SEVERE:NIDP:WSF:031
100102032		Type: SEVERE:NIDP:WSF:032
100102033		Type: SEVERE:NIDP:WSF:033
100103001	Web Service Consumer XML Configuration Parse Exception.	Type: SEVERE:NIDP:WSC:001 Cause: The nidsConfigXML attribute on the nidsWsf object has invalid XML. Action: Delete the nidsConfigXML attribute and reconfigure WSC.
100103002		Type: SEVERE:NIDP:WSC:002
100103003		Type: SEVERE:NIDP:WSC:003
100103004		Type: SEVERE:NIDP:WSC:004
100103005		Type: SEVERE:NIDP:WSC:005
100103006		Type: SEVERE:NIDP:WSC:006
100103007		Type: SEVERE:NIDP:WSC:007
100103008		Type: SEVERE:NIDP:WSC:008
100103009		Type: SEVERE:NIDP:WSC:009
100103010		Type: SEVERE:NIDP:WSC:010
100103011		Type: SEVERE:NIDP:WSC:011

Event Code	Message	Remedy
100103012		Type: SEVERE:NIDP:WSC:012
100103013		Type: SEVERE:NIDP:WSC:013
100103014		Type: SEVERE:NIDP:WSC:014
100103015		Type: SEVERE:NIDP:WSC:015
100103016		Type: SEVERE:NIDP:WSC:016
100103017		Type: SEVERE:NIDP:WSC:017
100104105	Could not initialize Kerberos/ GSS	Type: SEVERE:NIDP:USERAUTH:105 Cause: Failure at GSS-API Action: Check the following according the details of the error message: Keytab file - validity, presently only understands DES; Service Principal Name (SPN)
100104107	Kerberos Configuration is not properly initialized	Type: SEVERE:NIDP:USERAUTH:107 Cause: Kerberos Configuration is not properly initialized in the admin user interface Action: Make sure all the required configuration setting are properly specified in admin UI
100104108	SPNEGO/Kerberos method not implemented	Type: SEVERE:NIDP:USERAUTH:108 Cause: SPNEGO/Kerberos NegTokenInit not implemented. Action: NegTokenInit token not implemented as the server side does not need to generate it new. No Action needed.
100105001	An error happened while forwarding a request to a cluster member.	Type: SEVERE:NIDP:APP:001 Cause: An internal error occurred. Action: Evaluate the error and take appropriate action.
100105002	Failed to initialize JNDI connections.	Type: SEVERE:NIDP:APP:002 Cause: NIDP attempts to create JNDI connections to each user store replica during NIDP startup. In this case, NIDP was unable to establish connections with the indicated host. Action: Ensure that the host is available and that the configuration information for the replica is correct.
100105003	Error obtaining SOAP response.	Type: SEVERE:NIDP:APP:003 Cause: A SOAP request was made and a response was expected, but an error happened retrieving the response. Action: Evaluate the indicated reason and take appropriate action.

Event Code	Message	Remedy
100105004	Error in SOAP response format.	<p>Type: SEVERE:NIDP:APP:004</p> <p>Cause: A SOAP request was made and a response was expected, the response was obtained but the format of it was unexpected.</p> <p>Action: Evaluate the indicated reason and take appropriate action.</p>
100105005	Error executing Login Policy Check LDAP Extension for user on user store	<p>Type: SEVERE:NIDP:APP:005</p> <p>Cause: User authenticated using X509. An additional check of the directory's user login policy needs to be made using an LDAP method extension. This check was successfully done using an LDAP extension. However, after the LDAP extension is called, it must be called a second time to update the user account with a success or failure. This second call to the extension failed, so directory user account status may be erroneous.</p> <p>Action: Check with eDirectory documentation for LDAP extension with OID 2.16.840.1.113719.1.39.42.100.25</p>
100105006		Type: SEVERE:NIDP:APP:006
100105007		Type: SEVERE:NIDP:APP:007
100106001		Type: SEVERE:NIDP:IDFF:001
200102001	Invalid access code found for web service specific user interaction query policy.	<p>Type: ERROR:NIDP:WSF:001</p> <p>Cause: The web service definition has a service level user interaction policy that is not ALWAYS or NEVER. Disallowed values are NO and ONCE.</p> <p>Action: Using Access Manager management tools, edit the policy associated with the web service.</p>
200102002	Invalid access code found for web service specific user interaction modify policy.	<p>Type: ERROR:NIDP:WSF:002</p> <p>Cause: The web service definition has a service level user interaction policy that is not ALWAYS or NEVER. Disallowed values are NO and ONCE.</p> <p>Action: Using Access Manager management tools, edit the policy associated with the web service.</p>
200102003	Unrecognized web service.	<p>Type: ERROR:NIDP:WSF:003</p> <p>Cause: The web service definition has a service type specifier (attribute nidsWsfServiceInstanceType on object nidsWsfService) that is not recognized.</p> <p>Action: Using Access Manager management tools, delete the associated web service and recreate it.</p>

Event Code	Message	Remedy
200102004	Error writing user interaction access policy to the data store.	<p>Type: ERROR:NIDP:WSF:004</p> <p>Cause: The IDP received user interaction access policy from the user, but was unable to persist it to the data store.</p> <p>Action: Check the Access Manager Configuration datastore to see if it is available.</p>
200102005	Cannot read or write web service data because zero data locations are specified.	<p>Type: ERROR:NIDP:WSF:005</p> <p>Cause: When an IDP web service is reading or writing data it follows the configured data locations to know where to perform its operations. If the administrator has not set up any data locations then the operation must fail.</p> <p>Action: Add at least one data location the web service.</p>
200102006	Cannot read or write web service data because the first data location is unknown.	<p>Type: ERROR:NIDP:WSF:006</p> <p>Cause: When an IDP web service is reading or writing data it follows the configured data locations to know where to perform its operations.</p> <p>Action: Delete all data locations from the associated web service and add them back into the list.</p>
200102007	Unexpected error writing data to web service.	<p>Type: ERROR:NIDP:WSF:007</p> <p>Cause: Writing to web services is prone to various unexpected errors.</p> <p>Action: Evaluate the reason for the error and take appropriate action.</p>
200102008	Unable to locate the cached NIDPSession object given session id.	<p>Type: ERROR:NIDP:WSF:008</p> <p>Cause: The user session has expired.</p> <p>Action: The user must login again.</p>
200102009	Cached NIDPPrincipal object has zero NIDPSubject objects.	<p>Type: ERROR:NIDP:WSF:009</p> <p>Cause: The user session has expired.</p> <p>Action: The user must login again.</p>
200102010	No web service authority available.	<p>Type: ERROR:NIDP:WSF:010</p> <p>Cause: A web service of the provided type did not initialize correctly.</p> <p>Action: Delete the web service and recreate it.</p>
200102011	No web service available.	<p>Type: ERROR:NIDP:WSF:011</p> <p>Cause: A web service of the provided type does not exist, or is not enabled.</p> <p>Action: Create or enable a web service of this type.</p>

Event Code	Message	Remedy
200102012	Unable to understand the web service request's XML.	<p>Type: ERROR:NIDP:WSF:012</p> <p>Cause: A web service sent a request to the IDP that cannot be parsed or it is missing data such that the request cannot be understood.</p> <p>Action: Notify your system administrator that invalid web service requests are being made to the system.</p>
200102013	Error processing web service query request.	<p>Type: ERROR:NIDP:WSF:013</p> <p>Cause: Processing web service requests may result in a number of unexpected errors.</p> <p>Action: Evaluate the reason given in the error message, and take appropriate action.</p>
200102014	Error processing web service modify request.	<p>Type: ERROR:NIDP:WSF:014</p> <p>Cause: Processing web service requests may result in a number of unexpected errors.</p> <p>Action: Evaluate the reason given in the error message, and take appropriate action.</p>
200102015	Unable to locate the user's local identifier in the resource id.	<p>Type: ERROR:NIDP:WSF:015</p> <p>Cause: The web service resource id, an identifier indicating what user the request is destined for, did not contain the information required to identify the user.</p> <p>Action: Notify your system administrator that invalid web service requests are being made to the system.</p>
200102016	Unable to locate a cached NIDPPrincipal object given the local id.	<p>Type: ERROR:NIDP:WSF:016</p> <p>Cause: The user session has expired.</p> <p>Action: The user must login again.</p>
200102017	Unable to locate a NIDPIdentity object given the local id.	<p>Type: ERROR:NIDP:WSF:017</p> <p>Cause: The user session has expired.</p> <p>Action: The user must login again.</p>
200103001	The indicated web service is not available or it has been disabled! An attempt was made to access this service to operate on the indicated data.	<p>Type: ERROR:NIDP:WSC:001</p> <p>Cause: The Web Service Consumer received a request and one of the data tokens referenced a data item that is not available in any of the services known to the Access Manager.</p> <p>Action: The system has encountered an invalid configuration and should be restarted by the system administrator.</p>

Event Code	Message	Remedy
200103002	Cannot make web service request because there are zero web service resource offerings available.	Type: ERROR:NIDP:WSC:002 Cause: The Web Service Consumer received a request but there were zero service resource offerings provided. So, the web service has no destination service to which a request can be made. Action: The user must login again.
200103003	Unable to locate an identity id from the authentications available in the provided NIDPSession.	Type: ERROR:NIDP:WSC:003 Cause: The user session has expired. Action: The user must login again.
200104001	Could not get client certificate.	Type: ERROR:NIDP:USERAUTH:001 Cause: Could not get user certificate from the client browser Action: Install user X509 certificate on the client browser and try again.
200104003	Could not read configuration	Type: ERROR:NIDP:USERAUTH:003 Cause: Could not read configuration out of file Action: Make sure the X509 config properties file is present.
200104004	User Certificate Authentication Failed	Type: ERROR:NIDP:USERAUTH:004 Cause: User Certificate Authentication Failed due to the reasons in detailed message Action: Take appropriate action as per the reasons in the detailed message
200104005	No matching Principal found.	Type: ERROR:NIDP:USERAUTH:005 Cause: No Principal from X509Certificate found in User store Action: Check the X509Class Method and it's attribute mapping profile as defined using administration tool. Also, make sure the matched user exists in the User store.
200104006	More than one Principal matched.	Type: ERROR:NIDP:USERAUTH:006 Cause: Principal from X509Certificate Multiple users found in User store which matched Principal from X509Certificate based on X509Class attribute mapping profile. Action: Check the X509Class Method and it's attribute mapping profile as defined using administrator tool. Also, check if multiple user exists in the User store(s).
200104008	Error loading Trust store	Type: ERROR:NIDP:USERAUTH:008

Event Code	Message	Remedy
200104009	Client certificate not yet valid.	Type: ERROR:NIDP:USERAUTH:009 Cause: X509 certificate is valid in the future Action: Use a valid certificate
200104010	Client certificate no longer valid.	Type: ERROR:NIDP:USERAUTH:010 Cause: X509 certificate is expired Action: Use a valid certificate
200104011	The Certificate has been revoked.	Type: ERROR:NIDP:USERAUTH:011 Cause: The Certificate has been revoked Action: Use a valid certificate which is not revoked.
200104012	Error Parsing Certificate.	Type: ERROR:NIDP:USERAUTH:012 Cause: Error Parsing Certificate when performing certificate validations Action: Use a valid X509 certificate.
200104017	Error getting CRL/OCSP.	Type: ERROR:NIDP:USERAUTH:017 Cause: Could not get to the CRL/OCSP URL for validations. Action: Make sure the CRL/OCSP URLs are accessible Or disable validations in administration. Additionally, can define a different CRL/OCSP URL in the administration tool which the X509Class can also use for validations.
200104018	Could not verify CRL signature.	Type: ERROR:NIDP:USERAUTH:018 Cause: Could not verify signature on the fetched CRL Action: Make sure the CRL server public key/certificate is in NIDP/ESP trust store.
200104019	Could not find Key for this server.	Type: ERROR:NIDP:USERAUTH:019 Cause: Could not find Key/Cert for NIDP/ESP server towards authenticating to OCSP server Action: Make sure the NIDP/ESP Signing keystore has appropriate Key/Cert in it.
200104020	CRL/OCSP is too old; New version already available.	Type: ERROR:NIDP:USERAUTH:020 Cause: During validations, the fetched CRL Or OCSP is stale. Newer version will be available Action: In case of CRLs, next attempt to fetch CRL should get a fresh CRL after purging the cached one. In case of OCSP, notify the OCSP server administrator.

Event Code	Message	Remedy
200104021	No Issuer Certificate found.	Type: ERROR:NIDP:USERAUTH:021 Cause: Issuer of user certificate not found which is required for OCSP validations Action: Make sure the issuer of user/client certificate is either found in certificate-chain or in NIDP/ESP trust store.
200104022	Error getting OCSP Response.	Type: ERROR:NIDP:USERAUTH:022 Cause: Could not get OCSP Response from the OCSP server Action: Make sure its going to the right OCSP server.
200104023	Error processing OCSP Response.	Type: ERROR:NIDP:USERAUTH:023 Cause: OCSP response could not be processed Action: Make sure its going to the right OCSP server and that it is operating correctly.
200104024	At least one parameter of OCSPProcessor was uninitialized.	Type: ERROR:NIDP:USERAUTH:024 Cause: At least one parameter of OCSPProcessor was uninitialized during OCSP validations Action: Make sure the NIDP/ESP Signing keystore has appropriate Key/Cert in it. Also, that the NIDP/ESP OCSP trust store has the valid public-key/certificate of OCSP server.
200104025	Request was already generated.	Type: ERROR:NIDP:USERAUTH:025 Cause: OCSP request was already generated for certificate(s) Action: Check the client certificate chain.
200104026	OCSP response was already processed	Type: ERROR:NIDP:USERAUTH:026
200104027	Internal error occurred in the OCSP Server.	Type: ERROR:NIDP:USERAUTH:027 Cause: OCSP server responded to the request with an internal error. Action: Contact OCSP server administrator.
200104028	Your request did not fit the RFC 2560 syntax.	Type: ERROR:NIDP:USERAUTH:028 Cause: OCSP server responded to the request with malformed request message. Action: Contact OCSP administrator and check the request.

Event Code	Message	Remedy
200104029	Your request was not signed.	Type: ERROR:NIDP:USERAUTH:029 Cause: Request to OCSP server needs to be signed. Action: Enable signing of OCSP requests in X509Class administration.
200104030	The server was too busy to answer you.	Type: ERROR:NIDP:USERAUTH:030 Cause: OCSP server is too busy to respond to requests. Action: Contact OCSP server administrator.
200104031	The server could not authenticate you.	Type: ERROR:NIDP:USERAUTH:031 Cause: OCSP server could not authenticate Novell Identity server. Action: Make sure Signing of OCSP requests is enabled and NIDP signing keystore has appropriate key in it. Also, make sure the OCSP server trusts Nidp server.
200104032	Unknown OCSPResponse status code.	Type: ERROR:NIDP:USERAUTH:032 Cause: OCSP server responded to the request with unknown status code. Action: Contact OCSP server administrator.
200104033	No valid OCSPResponse obtained.	Type: ERROR:NIDP:USERAUTH:033 Cause: Invalid OCSP response obtained. Action: Check the OCSP server response version and contact administrator.
200104034	Response was generated in the future.	Type: ERROR:NIDP:USERAUTH:034 Cause: OCSP response is not yet valid. Action: Disable OCSP validations Or Contact OCSP server administrator.
200104035	Error verifying responder certificate.	Type: ERROR:NIDP:USERAUTH:035 Cause: This may happen when reading the OCSP trust store during OCSP validations. Action: Make sure OCSP trust store exists on NIDP server.
200104036	Response seems to be signed with untrusted certificate.	Type: ERROR:NIDP:USERAUTH:036 Cause: OCSP server trusted-root certificate not found in OCSP trust store. Action: Import OCSP server trusted root in Nidp's OCSP trust store.

Event Code	Message	Remedy
200104037	The received responder id does not match your responder certificate.	Type: ERROR:NIDP:USERAUTH:037 Cause: The response ID received in OCSP response does not match. Action: Make sure NIDP's OCSP trust store has the right OCSP server public-key certificate.
200104038	Could not verify OCSP server response.	Type: ERROR:NIDP:USERAUTH:038 Cause: OCSP server response is incorrect. Action: Verify the OCSP server URL. Make sure NIDP's OCSP trust store has the right OCSP server public-key certificate.
200104039	No client certificates inside OCSP response.	Type: ERROR:NIDP:USERAUTH:039 Cause: Empty response from OCSP server. Action: Verify the OCSP server URL.
200104040	Number of certificates inside OCSP response does not fit to request.	Type: ERROR:NIDP:USERAUTH:040 Cause: OCSP response does not contain the requested number of certificate status. Action: Verify the OCSP server URL.
200104041	Certificate was revoked in the future.	Type: ERROR:NIDP:USERAUTH:041 Cause: OCSP response not yet valid. Action: Verify the OCSP server URL.
200104042	Received certificate twice or one, that was not requested.	Type: ERROR:NIDP:USERAUTH:042 Cause: OCSP response does not match request. Action: Verify the OCSP server URL.
200104043	Request was not accepted.	Type: ERROR:NIDP:USERAUTH:043 Cause: Could not connect to OCSP server. Action: Verify the OCSP server URL.
200104044	Wrong response type (not application/ocsp-response).	Type: ERROR:NIDP:USERAUTH:044 Cause: Malformed OCSP response. Action: Verify the OCSP server URL.
200104045	No OCSPResponse message.	Type: ERROR:NIDP:USERAUTH:045 Cause: No OCSPResponse message. Action: Verify the OCSP server URL.
200104046	Could not read whole OCSPResponse.	Type: ERROR:NIDP:USERAUTH:046 Cause: Malformed OCSP response. Action: Verify the connection to OCSP server URL.

Event Code	Message	Remedy
200104047	Exception Occurred.	Type: ERROR:NIDP:USERAUTH:047 Cause: Error getting CRL. Action: Verify the connection to CRL server URL.
200104051	Unsupported critical extension OID(s).	Type: ERROR:NIDP:USERAUTH:051 Cause: Some Critical extension OID(s) not understood. Action: Check the certificate for unsupported critical extensions. If needed, add the processing of the critical extension in NIDPCertPathChecker class.
200104053	Error processing CRL Response.	Type: ERROR:NIDP:USERAUTH:053 Cause: Error processing CRL Response. Action: Check X509class config and user/client certificate CRL extension.
200104054	Error processing certificate validations.	Type: ERROR:NIDP:USERAUTH:054 Cause: Error processing CRL/OCSP validations. Action: Check X509class config and user/client certificate CRL extension.
200104055	Protocol not supported or none specified.	Type: ERROR:NIDP:USERAUTH:055 Cause: Transport protocol not supported to fetch CRL. Action: Currently, CRLs can be fetched over http and LDAP protocols. Make sure the X509class config and/or user/client certificate CRL extension does not have any other transport protocol specified.
200104057	Unable to do X509 Certificate based authentication over non SSL (HTTP)	Type: ERROR:NIDP:USERAUTH:057 Cause: URL protocol is HTTP Action: URL protocol needs to be HTTPS
200104100	Error processing Authorization header	Type: ERROR:NIDP:USERAUTH:100 Cause: Could not process HTTP Authorization header Action: Try with correct authorization header with base64 encoded SPNEGO token
200104101	Error processing SPNEGO/Kerberos	Type: ERROR:NIDP:USERAUTH:101 Cause: Error processing SPNEGO/Kerberos. The cause is included in detailed message Action: Take action as per the detailed error message
200104102	No Kerberos Principal found in the token	Type: ERROR:NIDP:USERAUTH:102 Cause: Failure at GSS-API Action: Make sure the Kerberos keytab file is generated correctly by KDC

Event Code	Message	Remedy
200104103	No SPNEGO Token found	Type: ERROR:NIDP:USERAUTH:103 Cause: No SPNEGO Token found in the request Action: Include the SPNEGO token in the request to use this authentication
200104104	GSS Context already established	Type: ERROR:NIDP:USERAUTH:104 Cause: GSS Context already established Action: Close the browser and try again
200104106	Unrecognized SPNEGO Token	Type: ERROR:NIDP:USERAUTH:106 Cause: Unrecognized SPNEGO Token Action: Include the correct SPNEGO token in the request to use this authentication
200104109	Malformed SPNEGO NegTokenInit	Type: ERROR:NIDP:USERAUTH:109 Cause: Malformed token NegTokenInit Action: Try again with correct NegTokenInit token
200104110	Malformed SPNEGO Token field	Type: ERROR:NIDP:USERAUTH:110 Cause: Malformed SPNEGO Token field Action: Try again with correct NegTokenInit token
200104111	Multiple users matched in the user stores	Type: ERROR:NIDP:USERAUTH:111 Cause: Multiple users matched in the user stores Action: Make sure the users are unique in user stores
200104112	No user matched in the user stores	Type: ERROR:NIDP:USERAUTH:112 Cause: No user found in the user stores Action: Make sure the user attribute (as defined in admin UI) is populated in correct format.
300101002	An authenticated subject is required.	Type: WARN:NIDP:USERMSG:002 Cause: An action that can only be performed by an authenticated user was attempted. Action: Provide proper user credentials and retry desired action.
300101003	An authentication principal is required.	Type: WARN:NIDP:USERMSG:003 Cause: An action that can only be performed by an authenticated user was attempted. Action: User must be authenticated to perform operation.

Event Code	Message	Remedy
300101004	Identity does not exist or is not specified.	<p>Type: WARN:NIDP:USERMSG:004</p> <p>Cause: An action was attempted that requires a federated identity to exist.</p> <p>Action: Create a federated link prior to performing the action.</p>
300101005	Invalid or no provider is specified.	<p>Type: WARN:NIDP:USERMSG:005</p> <p>Cause: An action was requested related to a trusted provider that does not exist.</p> <p>Action: Add the desired provider as a trusted entity or check for invalid access to system.</p>
300101006	An authenticated session is required.	<p>Type: WARN:NIDP:USERMSG:006</p> <p>Cause: An action that can only be performed by an authenticated user was attempted.</p> <p>Action: Provide proper user credentials and retry desired action.</p>
300101007	Invalid artifact.	<p>Type: WARN:NIDP:USERMSG:007</p> <p>Cause: An artifact was received from an identity provider that is invalid or has not been used within a reasonable time frame.</p> <p>Action: Make sure that the provider sending the artifact is trusted or check for possible security intrusions.</p>
300101008	No assertion returned in response.	<p>Type: WARN:NIDP:USERMSG:008</p> <p>Cause: Assertions will not be returned in a response whenever authentication at the identity provider fails. The cause for this can include invalid configurations and canceling the authentication process at the identity provider.</p> <p>Action: Make sure that both the identity and service providers are configured correctly to trust each other. Provide proper credentials during the authentication process at the identity provider.</p>
300101009	Invalid issuer.	<p>Type: WARN:NIDP:USERMSG:009</p> <p>Cause: A response was received from a provider that is not trusted.</p> <p>Action: Make sure intended provider is trusted or check for possible intrusions.</p>
300101010	Response does not match request.	<p>Type: WARN:NIDP:USERMSG:010</p> <p>Cause: A response was received for a request that was not issued.</p> <p>Action: Retry action and check for possible intrusion.</p>

Event Code	Message	Remedy
300101011	Assertion is being replayed.	<p>Type: WARN:NIDP:USERMSG:011</p> <p>Cause: An assertion has been received that was already used to authenticate a user at the service provider.</p> <p>Action: This is a security mechanism that if persists may require some investigation to determine who is trying to replay the assertion. Assertions are only good for single use.</p>
300101012	Assertion does not contain an authentication statement.	<p>Type: WARN:NIDP:USERMSG:012</p> <p>Cause: An identity provider has sent an assertion that is not complete.</p> <p>Action: Check with administrator of trusted provider to determine why statement is not being sent.</p>
300101013	Unable to validate the subject of the assertion.	<p>Type: WARN:NIDP:USERMSG:013</p> <p>Cause: A subject may not have been sent in the assertion or was not valid. This check protects from certain assertion attacks.</p> <p>Action: If persistent, check the protocol message sent for a missing subject and then notify administrator of trusted site.</p> <p>For more information, see Federation with External SAML 2.0 Partner Gives 300101013 Error (https://secure-support.novell.com/KanisaPlatform/Publishing/992/3903427_f.SAL_Public.html).</p>
300101014	Assertion not yet valid.	<p>Type: WARN:NIDP:USERMSG:014</p> <p>Cause: An assertion was received that is not valid until sometime in the future.</p> <p>Action: Check server's clock for accuracy. Attempt to validate the clock accuracy of the computer generating the assertion.</p>
300101015	Assertion no longer valid.	<p>Type: WARN:NIDP:USERMSG:015</p> <p>Cause: An assertion was received that had a time validity period that is in the past.</p> <p>Action: Check server's clock for accuracy. Attempt to validate the clock accuracy of the computer generating the assertion. Try to authenticate again.</p>

Event Code	Message	Remedy
300101016	No matching audience.	<p>Type: WARN:NIDP:USERMSG:016</p> <p>Cause: An assertion was received that was not intended for your server.</p> <p>Action: Determine the origin of the assertion and make sure that you want to accept assertions from it.</p> <p>For more information, see Access Manager 300101016 Error - No Matching Audience (https://secure-support.novell.com/KanisaPlatform/Publishing/134/3260366_f.SAL_Public.html)</p>
300101017	Missing or invalid signature on assertion.	<p>Type: WARN:NIDP:USERMSG:017</p> <p>Cause: The identity provider did not sign.</p> <p>Action: Check with provider of assertion to determine why assertion is not signed.</p>
300101018	Missing or invalid signature on request/response.	Type: WARN:NIDP:USERMSG:018
300101020	Digital signature is required.	<p>Type: WARN:NIDP:USERMSG:020</p> <p>Cause: A protocol message was received that was expected to be digitally signed, but was not.</p> <p>Action: It may be necessary to contact the trusted provider administrator to determine why the message is not signed. Make sure authentication request signing settings match those for the trusted provider.</p>
300101021	Signature validation failed.	<p>Type: WARN:NIDP:USERMSG:021</p> <p>Cause: The digital signature of a protocol message could not be verified using the public key obtained in the metadata of a trusted provider.</p> <p>Action: Update the metadata of trusted provider. This should ensure you have the latest signing certificate.</p>
300101022	An undetermined problem in the message format has occurred.	<p>Type: WARN:NIDP:USERMSG:022</p> <p>Cause: An error was detected in the exchange of either a Liberty or SAML protocol message.</p> <p>Action: Turn logging/tracing on to print out the message that is problematic. It may be necessary to contact Novell Technical Services in this case.</p>
300101023	User lookup failed.	<p>Type: WARN:NIDP:USERMSG:023</p> <p>Cause: An attempt to identify a user failed while attempting to complete a federation at the server.</p> <p>Action: Check the configuration for identifying users for the trusted provider and ensure the specified method can resolve to a single user in your directory.</p>

Event Code	Message	Remedy
300101024	Failed to load java class.	Type: WARN:NIDP:USERMSG:024 Cause: A Java class failed to be loaded during program execution. Action: Check the logs to determine the class that is failing to load. Make sure the class being loaded is in the classpath of the JVM.
300101025		Type: WARN:NIDP:USERMSG:025
300101026		Type: WARN:NIDP:USERMSG:026
300101027		Type: WARN:NIDP:USERMSG:027
300101028	SOAP TLS authorization failed.	Type: WARN:NIDP:USERMSG:028 Cause: SSL mutual authentication is being used to authenticate a SOAP back channel session and the credentials cannot be validated. Action: Make sure certificates for back channel communications are trusted on each end. For more information, see Access Manager 300101028 - SOAP TLS Authorization Failed (https://secure-support.novell.com/KanisaPlatform/Publishing/441/3813149_f.SAL_Public.html)
300101029		Type: WARN:NIDP:USERMSG:029
300101030	SOAP fault.	Type: WARN:NIDP:USERMSG:030 Cause: An error was detected in the transmission of protocols using SOAP. Action: Turn tracing on and look for any obvious causes for the problem.
300101031	Received an identity that does not resolve to the current logged in user.	Type: WARN:NIDP:USERMSG:031 Cause: This is caused when a user is logged in with one identity and then attempts to authenticate as the identity of another user. For a given session, all authentications must resolve to the same user. Action: Log out of the current user and log in again as the desired user.
300101032	Assertion is expired.	Type: WARN:NIDP:USERMSG:032 Cause: The use of the assertion to authenticate the server did not occur within the time limits specified by the assertion. Action: Try and re-authenticate. Determine if there are any network latencies that may cause the assertion not to arrive in a timely fashion. Look for misuse of the assertion.

Event Code	Message	Remedy
300101033	IDP return authentication failure.	<p>Type: WARN:NIDP:USERMSG:033</p> <p>Cause: An IDP's attempt to authenticate the server was unsuccessful. This particular authentication came from the IDP's intersite transfer service and was not requested by the server.</p> <p>Action: Check at the IDP for a reason why the authentication was a failure. It may just be necessary to attempt authentication again.</p>
300101034	No target is defined.	<p>Type: WARN:NIDP:USERMSG:034</p> <p>Cause: A request was made of the server's intersite transfer service without specifying a target resource.</p> <p>Action: Requests for the intersite transfer service must include an id of the intended service provider to be authenticated as well as the target resource to be displayed. To avoid this error, provide an &TARGET="value" on the URL.</p>
300101035		Type: WARN:NIDP:USERMSG:035
300101036	Not enough memory to process request.	<p>Type: WARN:NIDP:USERMSG:036</p> <p>Cause: The system does not have enough memory to complete the requested action.</p> <p>Action: Wait a few moments for memory to free up and retry request. It may be necessary to add additional memory to the server.</p>
300101037	Server is not in a running state.	<p>Type: WARN:NIDP:USERMSG:037</p> <p>Cause: A request was made of the server that can only be performed when the server is in a running state.</p> <p>Action: Start the server.</p>
300101038	JSP file not found.	<p>Type: WARN:NIDP:USERMSG:038</p> <p>Cause: An attempt was made to load a JSP page that does not exist.</p> <p>Action: Determine the JSP not loading and make sure it is in the correct location.</p>
300101039	Invalid authentication credentials were provided.	<p>Type: WARN:NIDP:USERMSG:039</p> <p>Cause: A user has attempted to authenticate to the system with credentials that are not valid for the account.</p> <p>Action: User needs to enter correct credentials.</p>

Event Code	Message	Remedy
300101040	User password has expired.	<p>Type: WARN:NIDP:USERMSG:040</p> <p>Cause: A user has attempted to authenticate to the system with a password that is expired.</p> <p>Action: The user needs to create a new password.</p>
300101041	User account identification failed.	<p>Type: WARN:NIDP:USERMSG:041</p> <p>Cause: Account identification can fail due to: 1. User cancels authentication request 2. User cannot be uniquely identified by Matching Expression 3. Necessary attributes to do user matching or provisioning were not obtained.</p> <p>Action: Check Account Identification configuration for the trusted provider and make sure that necessary attributes are available. If using Matching Expressions, make sure that they include attributes that can resolve to a single user. If using Provisioning, make sure required attributes are all available in the defined attribute set for the trusted provider.</p> <p>For more information, see Access Manager Error 300101041 Provisioning New Users Using SAML2 (https://secure-support.novell.com/KanisaPlatform/Publishing/810/3219302_f.SAL_Public.html)</p>
300101042	Invalid assertion conditions.	<p>Type: WARN:NIDP:USERMSG:042</p> <p>Cause: A set of conditions that are not understood were sent as part of an assertion.</p> <p>Action: Check with the provider of the assertion to determine what these conditions are and why they are being sent.</p>
300101046	Unknown URL host.	<p>Type: WARN:NIDP:USERMSG:046</p> <p>Action: Use logs to determine the problematic host and determine why DNS is failing.</p>
300101047	An untrusted provider is being referenced in a request or a response.	<p>Type: WARN:NIDP:USERMSG:047</p> <p>Action: Use logs to determine the provider that is untrusted and then create a trusted relationship if desired.</p>
300101048	The LDAP servers are too busy to accept more users.	<p>Type: WARN:NIDP:USERMSG:048</p> <p>Cause: There are too many threads waiting to get an available LDAP connection. The LDAP servers are too busy to accept more users.</p> <p>Action: Wait a few moments for the LDAP requests to be processed and retry the request. It may be necessary to add additional LDAP servers or upgrade the hardware specifications of the existing LDAP servers.</p>

Event Code	Message	Remedy
300102001	No Discovery Service Configured! Unable to create the requested resource offering!	Type: WARN:NIDP:WSF:001 Cause: The system administrator did not create or enable a Discovery service. Action: Create or enable a Discovery web service.
300102002	Unable to find user object with identifier.	Type: WARN:NIDP:WSF:002 Cause: An LDAP search was performed for a user object with a given identifier. This identifier may be a GUID. The search resulted in zero hits. This usually means that web service data cannot be read or written for the user. Action: The user needs to login again.
300102003	Unrecognized select string for service.	Type: WARN:NIDP:WSF:003 Cause: The select string (XPath) is either incorrectly formed or not supported by the web service. Action: The system administrator must enable services to support the select string.
300102004	Unable to process web service query request! Select string missing!	Type: WARN:NIDP:WSF:004 Cause: The select string (XPath) is not in the web service query request. Action: Inform your system administrator that an improperly formatted web service request is being made.
300102005	Unable to perform trusted user interaction service request. Web service authority was not found.	Type: WARN:NIDP:WSF:005 Cause: An internal system error. Action: The system has encountered an invalid configuration and should be restarted by the system administrator.
300102006	Unable to perform trusted user interaction service request. Unable to obtain trusted user interaction service description from SOAP headers.	Type: WARN:NIDP:WSF:006 Cause: The web service making the request did not provide valid or complete information about the trusted user interaction service. Action: The system administrator must complete the definition of the trusted interaction service.
300102007	Unable to perform trusted user interaction service request. No trusted user interaction service description provided in SOAP headers.	Type: WARN:NIDP:WSF:007 Cause: The web service making the request did not provide valid or complete information about the trusted user interaction service. Action: The system administrator must complete the definition of the trusted interaction service.

Event Code	Message	Remedy
300102008	Trusted user interaction service failed.	<p>Type: WARN:NIDP:WSF:008</p> <p>Cause: There are various unexpected reasons for the failure of a trusted user interaction service request to fail.</p> <p>Action: Evaluate the reason and take the appropriate actions.</p>
300102009	Error creating user interaction redirection request.	<p>Type: WARN:NIDP:WSF:009</p> <p>Cause: There was an error converting the redirect request to an XML DOM.</p> <p>Action: Evaluate the reason and take the appropriate actions.</p>
300102010	Unable to perform user interaction redirection request. User intervention service not found.	<p>Type: WARN:NIDP:WSF:010</p> <p>Cause: There must be an interaction service on the IDP creating the user interaction redirection request.</p> <p>Action: If it does not exist, using Access Manager management tools, create one.</p>
300102011	Error reading data from LDAP data attribute plugin.	<p>Type: WARN:NIDP:WSF:011</p> <p>Cause: If a web service's data locations includes LDAP, then LDAP data attribute plugins are used to read data from the LDAP user store. This error provides descriptions of various errors that can happen while doing this.</p> <p>Action: Evaluate the reason and take the appropriate actions.</p>
300102012	Error writing data to LDAP data attribute plugin.	<p>Type: WARN:NIDP:WSF:012</p> <p>Cause: If a web service's data locations includes LDAP, then LDAP data attribute plugins are used to write data to the LDAP user store. This error provides descriptions of various errors that can happen while doing this.</p> <p>Action: Evaluate the reason and take the appropriate actions.</p>
300102013	Cannot read/write Credential Profile data because the user's LDAP user store distinguished name is not available.	<p>Type: WARN:NIDP:WSF:013</p> <p>Cause: All Credential Profile reads and writes end up operating on a user object in a user store. If this user object cannot be found, then the operation must fail. This may happen if a temporary identifier is being used for the authentication.</p> <p>Action: Use a permanent federation to the service provider if your system allows it.</p>

Event Code	Message	Remedy
300102014	A Web Service request was received for a user, but the session for that user is not found.	Type: WARN:NIDP:WSF:014 Cause: The user's login has timed out and has been removed from the system. Action: The user must login again.
300102015	A Web Service request was received for a user, but the session for that user has insufficient data in it.	Type: WARN:NIDP:WSF:015 Cause: An internal error has occurred. Action: The user must login again.
300102016	A Web Service request was received for a user, but the Liberty User Profile object for that user is unavailable.	Type: WARN:NIDP:WSF:016 Cause: An internal error has occurred. Action: Make sure the administrator user has rights to read, write and create Liberty User Profile objects in the configuration data store.
300102017	A Web Service request was received for a user, and attempt to read the requested attributes from the Liberty User Profile object was made, but an error occurred.	Type: WARN:NIDP:WSF:017 Cause: An internal error has occurred. Action: Evaluate the reason and take the appropriate actions.
300102018	A Web Service request was received for a user, While reading user data from an LDAP user object, a mismatch occurred because the LDAP attribute is multi-valued, but the Liberty attribute is single-valued.	Type: WARN:NIDP:WSF:018 Cause: A multi-valued LDAP attribute has been mapped to a single-valued Liberty attribute. Action: Change the attribute mapping.
300102019	The user used an X509 Certificate to authenticate and we tried to put the cert into the SecretStore as a Base64 DER encoded cert, but we got an encoding error from the security layer when trying to get the DER encoded cert. Result is that there will not be a X509 Certificate in Secret Store for this user.	Type: WARN:NIDP:WSF:019 Cause: The X509 certificate cannot be encoded. Action: Review the type of X509 certificates that are being used for authentication.
300102020	A SAMLAssertion was requested for a given user. While generating the SAMLAssertion an error occurred.	Type: WARN:NIDP:WSF:020 Cause: The SAMLAssertion cannot be created. Action: Review the reason for the failure and take appropriate actions.
300102021		Type: WARN:NIDP:WSF:021
300102022		Type: WARN:NIDP:WSF:022

Event Code	Message	Remedy
300103001	The web service request did not return a response within the protocol timeout limit. Request abandoned.	<p>Type: WARN:NIDP:WSC:001</p> <p>Cause: The web service consumer waited for the web service request to return a response, but it did not during the allowed waiting period.</p> <p>Action: This waiting period may be increased by click Access Manager > Identity Servers > Edit > Liberty > Web Service Consumer, and setting the Protocol Timeout to a higher value.</p>
300103002	An unexpected error happened in the web service consumer while processing a web service request.	<p>Type: WARN:NIDP:WSC:002</p> <p>Cause: There are various reasons why a web service request could fail.</p> <p>Action: Evaluate the reason and take appropriate actions.</p>
300103003	Web service consumer request pending data packet id is not available in request.	<p>Type: WARN:NIDP:WSC:003</p> <p>Cause: After user interaction, processing of the original request returns to the web service consumer. A data packet containing information about how to continue the request is cached on the web service consumer. The id of that packet must be passed through all redirections and requests associated with the user interaction. If that id is not available when the web service consumer regains control, then the request cannot continue.</p> <p>Action: Submit the request again.</p>
300103004	The Web service consumer request pending data packet with the indicated id is not available in web service consumer's cache.	<p>Type: WARN:NIDP:WSC:004</p> <p>Cause: After user interaction, processing of the original request returns to the web service consumer. A data packet containing information about how to continue the request is cached on the web service consumer. The id of that packet must be passed through all redirections and requests associated with the user interaction. That id will be used to access the pending data packet when the web service consumer regains control. If the pending data packet with the corresponding id is no longer available on the system, then the request cannot continue. The data packet may have timed out.</p> <p>Action: Submit the request again.</p>
300104049	Could not find NIDP PKIX Certificate Path Checker Class.	<p>Type: WARN:NIDP:USERAUTH:049</p> <p>Cause: PKIX Certificate Path Checker Class not found.</p> <p>Action: Warning message that PKIX Certificate Path Checker Class not found. This optional class is used to process custom certificate extensions. If required, this class needs to be in NIDP classpath. It may not be present on ESP.</p>

Event Code	Message	Remedy
300104050	Could not instantiate NIDP PKIX Certificate Path Checker Class.	Type: WARN:NIDP:USERAUTH:050 Cause: Incorrect class constructor. Action: Make sure the class has the right constructor.
300105001	No user Login Policy Check LDAP Extension method available on user store.	Type: WARN:NIDP:APP:001 Cause: User authenticated using X509. An additional check of the directory's user login policy needs to be made using an LDAP method extension. However, the directory indicated does not support the required LDAP extension method. Action: Make sure the LDAP extension method with OID 2.16.840.1.113719.1.39.42.100.25 is present in the user store. Versions 8.7.3 and greater of eDirectory should support this method.
300105002		Type: WARN:NIDP:APP:002
300105003		Type: WARN:NIDP:APP:003
300105004		Type: WARN:NIDP:APP:004
300105005		Type: WARN:NIDP:APP:005
300105006		Type: WARN:NIDP:APP:006
300105007		Type: WARN:NIDP:APP:007
300105008		Type: WARN:NIDP:APP:008
300105009		Type: WARN:NIDP:APP:009
300105010		Type: WARN:NIDP:APP:010
300105011		Type: WARN:NIDP:APP:011
300105012		Type: WARN:NIDP:APP:012
300105013		Type: WARN:NIDP:APP:013
300105014		Type: WARN:NIDP:APP:014
300105015		Type: WARN:NIDP:APP:015
300105016		Type: WARN:NIDP:APP:016
300105017		Type: WARN:NIDP:APP:017
300105018		Type: WARN:NIDP:APP:018
300105019		Type: WARN:NIDP:APP:019
300105020		Type: WARN:NIDP:APP:020
300106001		Type: WARN:NIDP:IDFF:001
300106002		Type: WARN:NIDP:IDFF:002
300106003		Type: WARN:NIDP:IDFF:003

Event Code	Message	Remedy
300106004		Type: WARN:NIDP:IDFF:004
300106005		Type: WARN:NIDP:IDFF:005
500102001	The authentication information for the user was successfully found.	Type: INFO:NIDP:WSF:001 Scenario: A Web Service request was made to query or modify user attributes. The user's authentication information was successfully found. See Also: 600102001
500102002	The Liberty User Profile object for the associated user was found in the configuration datastore.	Type: INFO:NIDP:WSF:002 Scenario: A Web Service request was made to query or modify user attributes. One of the data locations specified for the service is the Liberty User Profile object and that object was successfully found.
500102003	Created new user profile object.	Type: INFO:NIDP:WSF:003 Scenario: A request was made to query or modify user's attributes. A Liberty User Profile object did not yet exist for this user, so one was created.
500102004	Read data from user profile object.	Type: INFO:NIDP:WSF:004 Scenario: A Web Service request was made to query user attributes. One of the data locations specified for the service is the Liberty User Profile object and that object was successfully read. See Also: 600102002
500102005	Attempted to read data from the Liberty User Profile object, but it did not contain the requested data.	Type: INFO:NIDP:WSF:005 Scenario: A Web Service request was made to query user attributes. One of the data locations specified for the service is the Liberty User Profile object. That object was successfully accessed but did not contain the requested data.
500102006	Read data from attributes obtained when a remote authentication source pushed the attributes to the NIDP.	Type: INFO:NIDP:WSF:006 Scenario: When a user authenticates, the authentication entity can push user attributes to the NIDP as part of the response to the authentication. The NIDP remembers these attributes for the life of that user session. If one of the data locations specified for a Web Service is remote, then these attributes may be returned as part of a query. See Also: 600102005

Event Code	Message	Remedy
500102007	Read data by making a call to a remote service made available through a user authentication.	Type: INFO:NIDP:WSF:007 Scenario: A request was made to query a user's attributes. One of the data locations for the Web Service was remote. So, a request was made to a remote service to read attributes. See Also: 600102006
500102008	Completed building composite data that was read from all data locations for user.	Type: INFO:NIDP:WSF:008 Scenario: A request was made to query a user's attributes. If multiple data locations are specified for the Web Service, then attributes may be read from multiple data locations and then aggregated into a composite data structure. See Also: 600102007
500102009	Initiating a user interaction redirect.	Type: INFO:NIDP:WSF:009 Scenario: A request was made to query or modify user's attributes. Policy indicates that the user must be asked if the attribute operation is permitted. The request indicated that a redirect user interaction service should be used to perform user interaction, so redirection is being invoked using the redirection user interaction service protocol.
500102010	Initiating a user interaction call to a trusted user interaction service.	Type: INFO:NIDP:WSF:010 Scenario: A request was made to query or modify user's attributes. Policy indicates that the user must be asked if the attribute operation is permitted. The request indicated that a trusted user interaction service should be used to perform user interaction, so that service is being invoked using the trusted user interaction service protocol.
500102011	Read Credential Profile data from Novell Secret Store.	Type: INFO:NIDP:WSF:011 Scenario: A request was made to query data from a user's Credential Profile. The data was successfully read. See Also: 600102008
500102012	Read Credential Profile data from an extended user authentication object attribute.	Type: INFO:NIDP:WSF:012 Scenario: A request was made to query data from a user's Credential Profile. The data was read from an extended schema attribute on the user's authenticated user object. See Also: 600102010
500102013	Web service data write denied because the LDAP attribute plugin access for the named data item is read only!	Type: INFO:NIDP:WSF:013 Scenario: The system administrator has marked this data item as read only in the LDAP Attribute Plugin.

Event Code	Message	Remedy
500102014	Override not allowed. Cannot override existing data.	Type: INFO:NIDP:WSF:014 Scenario: The data that is being written already exists in the user's profile. Data override is not allowed so this data cannot be written.
500102015	Existing data changed since notChangedSince time.	Type: INFO:NIDP:WSF:015 Scenario: User profile data is marked with the last time the data changed. The query request indicated that it did not want the data written if the current data in the profile has been changed since an indicated time. The system determined that the current data in the profile has been changed since the time provided, so this data cannot be written.
500103001	Filled the user attribute request from data already in the web service consumer cache.	Type: INFO:NIDP:WSC:001 Scenario: When the WSC reads user attributes, it caches the results of each read. In this case, a subsequent request queried attributes already read, so they were provided from the WSC cache.
500103002	Web service consumer request complete.	Type: INFO:NIDP:WSC:002 Scenario: The WSC was asked to query or modify data for a given user. That request is complete.
500103003	Web service consumer request requires user interaction.	Type: INFO:NIDP:WSC:003 Scenario: The WSC was asked to query or modify data for a given user. The entity called to perform the operation indicated that the user must be asked if the attribute operation is acceptable.
500103004	User interaction policy and data values received.	Type: INFO:NIDP:WSC:004 Scenario: A Web Service request was made to query or modify user attributes. It was determined that the user must be asked if the attribute operation is acceptable. The user's answers have been returned to the NIDP.
500104002	Getting properties from file (informational)	Type: INFO:NIDP:USERAUTH:002 Scenario: Getting properties from file
500104007	X509 Authentication matched principal (informational)	Type: INFO:NIDP:USERAUTH:007 Scenario: X509 Authentication matched principal
500104013	No CRL/OCSP defined by the administrator	Type: INFO:NIDP:USERAUTH:013 Cause: No CRL/OCSP defined by the administrator

Event Code	Message	Remedy
500104014	No CRL/OCSP found in the certificate.	Type: INFO:NIDP:USERAUTH:014 Cause: No CRL/OCSP found in the certificate Action: CRL/OCSP validations are enabled but no CRL/OCSP responder URL was defined by the administrator. CRL/OCSP URLs may be defined if needed.
500104016	Could not fetch CRL from the local cache (informational)	Type: INFO:NIDP:USERAUTH:016 Scenario: Could not fetch CRL from the local cache, getting it from the CDP
500104048	Successfully loaded NIDP PKIX Certificate Path Checker Class (informational)	Type: INFO:NIDP:USERAUTH:048 Scenario: Successfully loaded NIDP PKIX Certificate Path Checker Class
500104113	Kerberos Principal match found in the user store (informational)	Type: INFO:NIDP:USERAUTH:113 Scenario: Kerberos Principal found in the user store
500105001	Forwarding HTTP request to cluster member.	Type: INFO:NIDP:APP:001 Scenario: A request was received on a cluster member that does not own the authentication information for the associated user. The request must be processed on the cluster member that does own the user authentication information, so the request is being forwarded to that cluster member.
500105002	Successfully initialized JNDI connections.	Type: INFO:NIDP:APP:002 Scenario: NIDP attempts to create JNDI connections to each user store replica during NIDP startup. In this case, NIDP was able to establish connections with the indicated host.
500105003	Failed X509 authentication due to Login Policy Check Extension Method evaluation.	Type: INFO:NIDP:APP:003 Scenario: The directory login policy for the indicated user denied login.
500105004	An recoverable error happened while forwarding a login request.	Type: INFO:NIDP:APP:004 Scenario: The request landed on the wrong cluster member. An attempt was made to proxy the request, but an error occurred! However, this ESP can process this request, so let execution proceed on this box.
500105005		Type: INFO:NIDP:APP:005
500105006		Type: INFO:NIDP:APP:006
500105007		Type: INFO:NIDP:APP:007
500105008		Type: INFO:NIDP:APP:008
500105009		Type: INFO:NIDP:APP:009

Event Code	Message	Remedy
500105010		Type: INFO:NIDP:APP:010
500105011		Type: INFO:NIDP:APP:011
500105012		Type: INFO:NIDP:APP:012
500105013		Type: INFO:NIDP:APP:013
500105014		Type: INFO:NIDP:APP:014
500105015		Type: INFO:NIDP:APP:015
500105016		Type: INFO:NIDP:APP:016
500105017		Type: INFO:NIDP:APP:017
500105018		Type: INFO:NIDP:APP:018
500105019		Type: INFO:NIDP:APP:019
500105020		Type: INFO:NIDP:APP:020
500105021		Type: INFO:NIDP:APP:021
500105022		Type: INFO:NIDP:APP:022
500105023		Type: INFO:NIDP:APP:023
500105024		Type: INFO:NIDP:APP:024
500105025		Type: INFO:NIDP:APP:025
500105026		Type: INFO:NIDP:APP:026
500105027		Type: INFO:NIDP:APP:027
500105028		Type: INFO:NIDP:APP:028
500105029		Type: INFO:NIDP:APP:029
500105030		Type: INFO:NIDP:APP:030
500105031		Type: INFO:NIDP:APP:031
500105032		Type: INFO:NIDP:APP:032
500105033		Type: INFO:NIDP:APP:033
500105034		Type: INFO:NIDP:APP:034
500105035		Type: INFO:NIDP:APP:035
500105036		Type: INFO:NIDP:APP:036
500105037		Type: INFO:NIDP:APP:037
500105038		Type: INFO:NIDP:APP:038
500105039		Type: INFO:NIDP:APP:039
500105040		Type: INFO:NIDP:APP:040
500105041		Type: INFO:NIDP:APP:041

Event Code	Message	Remedy
500105042		Type: INFO:NIDP:APP:042
500105043		Type: INFO:NIDP:APP:043
500105044		Type: INFO:NIDP:APP:044
500105045		Type: INFO:NIDP:APP:045
500106001		Type: INFO:NIDP:IDFF:001
500106002		Type: INFO:NIDP:IDFF:002
500106003		Type: INFO:NIDP:IDFF:003
500106004		Type: INFO:NIDP:IDFF:004
500106005		Type: INFO:NIDP:IDFF:005
500106006		Type: INFO:NIDP:IDFF:006
500106007		Type: INFO:NIDP:IDFF:007
500106008		Type: INFO:NIDP:IDFF:008
600102001	Verbose user authentication information.	Type: DEBUG:NIDP:WSF:001 Scenario: Adds verbose authentication data to the fact that the user associated with the attribute request was found in the internal databases of the web service provider. See Also: 500102001
600102002	Verbose user authentication information, attribute select string, and data.	Type: DEBUG:NIDP:WSF:002 Scenario: A Web Service request was made to query user attributes. One of the data locations specified for the service is the Liberty User Profile object. The data listed in this message was successfully read for the indicated user using the indicated XPath. See Also: 500102004
600102003	Read single-valued attribute from user authentication LDAP object.	Type: DEBUG:NIDP:WSF:003 Scenario: A Web Service request to query user attribute data was received. One of the data locations was LDAP. This message displays the value read from the indicated LDAP attribute for the indicated user.
600102004	Read multi-valued attribute from user authentication LDAP object.	Type: DEBUG:NIDP:WSF:004 Scenario: A Web Service request to query user attribute data was received. One of the data locations was LDAP. This message displays the value read from the indicated LDAP attribute for the indicated user.

Event Code	Message	Remedy
600102005	Verbose user authentication and attribute information.	Type: DEBUG:NIDP:WSF:005 Scenario: When a user authenticates, the authenticating entity can push user attributes to the NIDP as part of the response to the authentication. The NIDP remembers these attributes for the life of that user session. If one of the data locations specified for a Web Service is remote, then these attributes may be returned as part of a query. See Also: 500102006
600102006	Adds verbose user and attribute information to attributes read from a remote service whose description was obtained at authentication time.	Type: DEBUG:NIDP:WSF:006 Scenario: A request was made to query a user's attributes. One of the data locations for the Web Service was remote. So, a request was made to a remote service to read attributes. See Also: 500102007
600102007	Adds verbose user and attribute information to the final aggregated result of a web service query!	Type: DEBUG:NIDP:WSF:007 Scenario: A request was made to query a user's attributes. If multiple data locations are specified for the Web Service, then attributes may be read from multiple data locations and then aggregated into a composite data structure. See Also: 500102008
600102008	Adds verbose data to reading Credential Profile data from Novell Secret Store.	Type: DEBUG:NIDP:WSF:008 Scenario: A request was made to query data from a user's Credential Profile. The data was successfully read. See Also: 500102011
600102009	The user successfully logged into Novell Secret Store using SAML/SASL.	Type: DEBUG:NIDP:WSF:009 Scenario: To access secrets from Novell Secret Store, the user must authenticate to Novell Secret Store.
600102010	Adds verbose data to reading Credential Profile data from an extended user authentication object attribute.	Type: DEBUG:NIDP:WSF:010 Scenario: A request was made to query data from a user's Credential Profile. The data was read from an extended schema attribute on the user's authenticated user object. See Also: 500102012
600105001	Do not need to proxy HTTP request to other cluster member. Well known URL that does not require the use of a proxy.	Type: DEBUG:NIDP:APP:001 Scenario: The request is one of a well known list of request types that may be processed on any cluster member, so it does not need to be forwarded to another cluster member.

Event Code	Message	Remedy
600105002	Do not need to proxy HTTP request to other cluster member. This cluster member can handle requests for this user.	Type: DEBUG:NIDP:APP:002 Scenario: The request arrived at the cluster member that owns the authentication information for the user. The request may have come straight from the router to this cluster member, or the request may have been forwarded here by another cluster member.
600105003	Obtained IP address of cluster member handling this users requests from URL parameter.	Type: DEBUG:NIDP:APP:003 Scenario: Each request must be processed on the cluster member that owns the user authentication information. The IP address of that cluster member was found in a URL parameter.
600105004	Obtained IP address of cluster member handling this users requests from HTTP cookie.	Type: DEBUG:NIDP:APP:004 Scenario: Each request must be processed on the cluster member that owns the user authentication information. The IP address of that cluster member was found in an HTTP cookie.
600105005	Obtained IP address of cluster member handling this user's requests by asking cluster members which one handles this user session.	Type: DEBUG:NIDP:APP:005 Scenario: Each request must be processed on the cluster member that owns the user authentication information. The IP address of that cluster member was found by asking all cluster members which one knew about the user's session.
600105006	Must proxy HTTP request to other cluster member.	Type: DEBUG:NIDP:APP:006 Scenario: Each request must be processed on the cluster member that owns the user authentication information. It has been determined that this cluster member is not the correct cluster member to process this request, so the request must be forwarded to another cluster member.
600105007	Response of proxy HTTP request.	Type: DEBUG:NIDP:APP:007 Scenario: Each request must be processed on the cluster member that owns the user authentication information. It was determined that this cluster member is not the correct cluster member to process this request, so the request was forwarded to another cluster member. The results of the request, as processed on the other cluster member, are displayed here.
600105008	Successfully obtained SOAP response document.	Type: DEBUG:NIDP:APP:008 Scenario: A SOAP request was made and a response was expected, the response was successfully obtained.
600105009		Type:DEBUG:NIDP:APP:009
600105010		Type: DEBUG:NIDP:APP:010
600105011		Type: DEBUG:NIDP:APP:011

1.1.2 Linux Access Gateway (045)

Component 045

Event Code	Description	Remedy
[1-9]04501000	Multi-homing	See the string value in the message for a description of the cause.
[1-9]04502000	Service manager	See the string value in the message for a description of the cause.
[1-9]04503000	Browser request processing	See the string value in the message for a description of the cause.
[1-9]04504000	Authentication processing	See the string value in the message for a description of the cause.
[1-9]04505000	Authorization processing	See the string value in the message for a description of the cause.
[1-9]04506000	Identity Injection processing	See the string value in the message for a description of the cause.
[1-9]04507000	Form Fill processing	See the string value in the message for a description of the cause.
[1-9]04508000	Caching	See the string value in the message for a description of the cause.
[1-9]04509000	Processing of Web server responses and of responses to browser requests	See the string value in the message for a description of the cause.
[1-9]04511000	Rewriter processing	See the string value in the message for a description of the cause.
[1-9]04512000	SOAP back channel processing	See the string value in the message for a description of the cause.
[1-9]04513000	Device communication channel (VCC)	See the string value in the message for a description of the cause.
[1-9]04514000	VM controller processing	See the string value in the message for a description of the cause.
[1-9]04515000	Connection management	See the string value in the message for a description of the cause.
[1-9]04516000	Core utilities (VXE)	See the string value in the message for a description of the cause.
[1-9]04517000	Data Stream processing	See the string value in the message for a description of the cause.
[1-9]04518000	SSL processing	See the string value in the message for a description of the cause.
[1-9]04519000	Command processing	See the string value in the message for a description of the cause.
[1-9]04520000	Profiler	See the string value in the message for a description of the cause.

Event Code	Description	Remedy
[1-9]04521000	Proxy start	See the string value in the message for a description of the cause.
[1-9]04522000	Audit event processing	See the string value in the message for a description of the cause.

1.1.3 SSL VPN (005)

Component 005

- ◆ Sub group 01: Server
- ◆ Sub group 02: Client. For a description of these event codes, see “**Error Messages**” in the *Novell Access Manager 3.0 SP 2 SSL VPN User Guide*.

Event Code	Description	Remedy
Server Event Codes		
20050101200	Error executing sockd	<p>Cause: The <code>/opt/novell/sslvpn/bin/sockd</code> file may not be present, or not executable or corrupted</p> <p>Action: Check if the binary is present and has correct permissions. Installation may be a problem</p>
20050101201	Error spawning stunnel	<p>Cause: The <code>/opt/novell/sslvpn/bin/stunnel</code> file may not be present, or not executable or corrupted</p> <p>Action: Check if the binary is present and has correct permissions. Installation may be a problem</p>
20050101202	Server stunnel conf file could not be opened	<p>Cause: The <code>/etc/opt/novell/sslvpn/stunnel.conf</code> file may be corrupted or not present</p> <p>Action: Configuration may be bad. Check for other configuration errors in the logs</p>
20050101203	Server sockd conf file could not be opened	<p>Cause: The <code>/etc/opt/novell/sslvpn/sockd.conf</code> file may be corrupted or not present</p> <p>Action: Configuration may be bad. Check for other configuration errors in the logs</p>
20050101204	Could not find core config file	<p>Cause: The <code>/etc/opt/novell/sslvpn/config.xml</code> file is not present or corrupted</p> <p>Action: Restart the sslvpn service. Apply the changes from device manager and observe for any other errors while applying the changes on the device</p>

Event Code	Description	Remedy
40050101205	Configuration file does not have proper contents. Parsing configuration failed. Connection Manager has bad configuration data. Could not add new connection	<p>Cause: The <code>/etc/opt/novell/sslvpn/config.xml</code> file is not properly formatted. XML data corruption could have happened</p> <p>Action: Restart the sslvpn service. Apply the changes from device manager and observe for any other errors while applying the changes on the device</p>
20050101206	Resource allocation failed	<p>Cause: Might be a potential issue</p> <p>Action: Collect all error logs and report to Support</p>
20050101207	Failed to send stunnel response "1231" to fd "5"	<p>Cause: Stunnel program may have been stop or not running correctly</p> <p>Action: Collect error log reports Restart the sslvpn service</p>
20050101208	Could not open the file <code>/opt/novell/sslvpn/connmansocket</code> exiting! Could not get File Lock for ConnMan. Another instance may be already running	<p>Cause: The <code>/opt/novell/sslvpn/connmansocket</code> file may have been locked by another instance</p> <p>Action: Forcefully delete this file and restart sslvpn service</p>
20050101209	Could not open the Unix domain socket	<p>Cause: The <code>/opt/novell/sslvpn/connman</code> file may have been locked</p> <p>Action: Forcefully delete this file and restart sslvpn service</p>
4005010120A	Could not bind the Local socket. TCP socket could not be opened	<p>Cause: Invalid configuration or that particular port may be being used by another service</p> <p>Action: Check the service running on that port. Change the port in the configuration and restart sslvpn service</p>
4005010120B	VCC has not been started. May be VCC port is invalid	<p>Cause: The VCC port is either invalid or some other service is running on that port</p> <p>Action: Check <code>/etc/opt/novell/sslvpn/config.xml</code> file and verify the VCC port is valid. If it is not, change it to the correct value, delete the device from the Administration Console, then restart the JCC-proxy using the <code>/etc/init.d/novell-jcc restart</code> command.</p>
2005010120C	Failed to parse Stunnel certificate. error code = XXXX	<p>Cause: Stunnel Certificate is in bad format</p> <p>Action: Recreate the Stunnel certificate in device manager and apply changes to the device</p>

Event Code	Description	Remedy
2005010120D	SOCKD is not running/registered... cannot add a new connection request. Failed to send disconnect notification to sockd. Failed to send the new connection notification to sockd. Failed to send servlet response to fd. Failed to send servlet init success response to fd, fd. Failed to send servlet response %x to fd %d msgType, fd. Failed to send socks response %x to fd %d msgType, fd	<p>Cause: One of the programs of SSLVPN service is not running. And the SSLVPN Gateway is in bad state</p> <p>Action: Restart the sslvpn service and restart the novell-tomcat where sslvpn servlet is running</p>
2005010120E	Restricting the number of policies for the role %s to %d .. because of insufficient buffer size, tmp->rolename, numRules Restricting the number of policies for the role	<p>Cause: Too many number of traffic rules for that particular role</p> <p>Action: Revisit the configuration and reduce the number of traffic rules for that particular role</p>
2005010120F	Error: Servlet is already registered. Servlet_connect_connection: Servlet is not registered. Received disconnect from servlet. But servlet is not registered	<p>Cause: Communication channel between servlet and connection manager have gone bad</p> <p>Action: Restart the sslvpn service and restart the novell-tomcat where sslvpn servlet is running</p>
30050101210	Cannot add new connection. Maximum number of connections reached	<p>Cause: Maximum number of connections reached. No more connections can be added</p> <p>Action: Contact system administrator</p>
50050101400	Failed to connect to connection Manager	<p>Cause: Connection manager may not be running</p> <p>Action: Start the connection using the <code>sslvpc -up</code> command.</p>
20050101401	Error in sending message to Connection Manager	<p>Cause: Connection Manager socket would have closed</p> <p>Action: Make sure connection Manager running</p>
20050101402	Error in receiving message	<p>Cause: May be connection socket would have closed</p> <p>Action: Make sure connection Manager running</p>
20050101403	Failed to get the lock of the connection Manager socket. Service cannot be stopped	<p>Cause: This happens with down command and If connmanSocket lock is not available</p> <p>Action: Retry</p>
20050101404	Failed to update SSLVPN Server Configuration	<p>Cause: This happens if the <code>config.xml</code> is not well formed</p> <p>Action: Make sure that <code>config.xml</code> is correct and well formed</p>

Event Code	Description	Remedy
50050101405	Too many arguments	<p>Cause: User entered the more arguments than the command can use.</p> <p>Action: Type <code>sslvpn -help</code>, read the command syntax, and use it.</p>
50050101406	Too few arguments	<p>Cause: User entered fewer arguments than the command requires.</p> <p>Action: Type <code>sslvpn -help</code>, read the command syntax, and use it.</p>
50050101407	Invalid command	<p>Cause: User entered the wrong command</p> <p>Action: Type <code>sslvpn -help</code>, read the command syntax, and use it.</p>
30050101408	Failed to start SSL VPN service. Check log(/var/log/messages)	<p>Cause: The <code>config.xml</code> file is probably invalid.</p> <p>Action: Check the <code>config.xml</code> file and correct it.</p>
50050101409	Invalid argument	<p>Cause: The user has entered invalid arguments.</p> <p>Action: Use the <code>sslvpnc -help</code> command to discover the valid arguments.</p>

1.1.4 J2EE Agents (006)

Component 006

- ◆ Sub group 01: Management
- ◆ Sub group 02: Authentication (JAAS)
- ◆ Sub group 03: Authorization (JACC)
- ◆ Sub group 99: Policy PEP

Event Code	Message	Remedy
100601001	Could not find initial XML configuration in classPath	<p>Cause: An initial XML configuration should exist in the <code>NidsCommonAgent.jar</code> but doesn't when this error occurs.</p> <p>Action: Verify that Agent files are in the proper place.</p>
100601002	Could not add agent specific information to initial configuration	<p>Cause: Unexpected XML error, possibly from faulty XML libraries.</p> <p>Action: Submit requested logs and data.</p>
100601003	Configuration of agent failed	<p>Cause: Invalid configuration was sent to the agent.</p> <p>Action: Submit requested logs and data.</p>

Event Code	Message	Remedy
100601004	Could not create an LDAP connection	<p>Cause: LDAP connection failed due to: 1) Network Outage, 2) DNS configuration, 3) port configurations, 4) Firewall configurations, etc.</p> <p>Action: Verify that the management server can be contacted.</p>
100601005	Could not read JCC id file	<p>Cause: File rights to the JCC ID file are denied.</p> <p>Action: Verify that the JCC ID file (named <code>JBoss.id</code> or <code>WebSphere.id</code>) is present and the application server has read access to the file.</p>
100601006	Could not write to JCC id file	<p>Cause: File creation rights to the <code>jcc</code> directory are denied to the application server.</p> <p>Action: Verify that the JCC ID file (named <code>JBoss.id</code> or <code>WebSphere.id</code>) is present and the application server has write access to the file.</p>
100601007	Could not log configuration	<p>Cause: Missing or outdated log jar files.</p> <p>Action: Check that logging utilities are present</p>
100601008	Could not determine Agent Type	<p>Cause: Agent Type property not set and/or JACC not configured properly.</p> <p>Action: Verify that these properties are set.</p>
100602000	A Severe error occurred in the authentication module (JAAS)	<p>Cause: The session might have timed out.</p> <p>Action: Submit requested logs/data.</p>
100602001	The identity server returned a null or empty user name	<p>Cause: The session might have timed out.</p> <p>Action: Retry</p>
100602002	Returned -503 due to unconfigured identityServerBaseURL	<p>Cause: The application server URL has not been configured.</p> <p>Action: Configure the agent to have the correct base URL</p>
100602003	Couldn't configure SAX parser	<p>Cause: Something is wrong with the Java environment, or the XML libraries are not configured.</p> <p>Action: Obtain latest XML libraries from apache.org and put them into the classpath.</p>
100602004	Couldn't communicate with the identity server due to a null URL for the server	<p>Cause: No trusted identity server is configured.</p> <p>Action: Configure the agent to have a trusted Identity Server.</p>

Event Code	Message	Remedy
100602005	Couldn't open an URL connection to the embedded server provider	<p>Cause: Invalid or missing application URL.</p> <p>Action: Configure the agent to have a valid application URL. Restart the agent or application server where the agent resides.</p>
100602006	Couldn't read response from the identity server	<p>Cause: Connection might have been interrupted.</p> <p>Action: Retry, verify network connectivity, DNS resolution, etc.</p>
100602007	Couldn't parse the XML document from the identity server	<p>Cause: Unexpected response from the Identity Server</p> <p>Action: Submit requested logs/data.</p>
100602008	Could not build the WebSphere principal and credential	<p>Cause: Unexpected error in WebSphere</p> <p>Action: Submit requested logs/data.</p>
100602009	WebSphere is not configured with global and server security	<p>Cause: WebSphere does not have global security enabled.</p> <p>Action: Enable WebSphere for global and server security.</p>
100602010	Could not parse system property 'com.novell.nids.agent.sessionVerificationMinutes'	<p>Cause: This property is set to override the default time of 5 minutes. The set value for this property was not a valid Integer and could not be parsed.</p> <p>Action: Check the system property com.novell.nids.agent.sessionVerificationMinutes has a valid number.</p>
100602011	AuthSessionCache cleanup thread existing	<p>Cause: The session cache cleanup thread was terminated.</p> <p>Action: Check logs to see if other events may have caused this. Send logs to support.</p>
100602012	An error was encountered in reflection code to get moduleID from HttpServletRequest	<p>Cause: WebLogic API has been changed.</p> <p>Action: Contact Novell Support.</p>
100602013	An Error occurred decoding a soap response	<p>Cause: Java is corrupt and does not support UTF-8</p>
500602001	Event occurred: Agent sent a redirect to nesp	
500602002	Event occurred: Login Servlet received login from nesp	
500602003	Event occurred: Verifying nidsID	
500602004	Event occurred: Contacted esp for session and attributes	

Event Code	Message	Remedy
500602005	Event occurred: esp session successfully verified, posting login	
500602006	Event occurred: LoginModule received login	
500602007	Event occurred: LoginModule successfully logged in the user	
500603008	Event occurred: JACC called for permission	
500603009	Event occurred: JACC decision: permission allowed	
500603010	Event occurred: JACC decision: permission denied	
100603001	Failed to construct the policy enforcement points	<p>Cause: An erroneous policy may have been sent from the management console.</p> <p>Action: Search for errors from the 099 subcomponent.</p>
100603002	An error was encountered during policy evaluation	<p>Cause: An erroneous policy may have been sent from the management console.</p> <p>Action: Search for errors from the 099 subcomponent.</p>
100603003	Could not obtain a request object during policy evaluation	<p>Cause: Unexpected error occurred evaluating a policy.</p> <p>Action: Submit requested logs/data. Search for errors from the 099 subcomponent.</p>
100603004	Exception occurred persisting policies/roles to file	<p>Cause: File rights denied access to read/write policy and roles file in WebSphere.</p> <p>Action: Verify that the file exists and can be written to by the application server.</p>
200601000	A Warning message occurred in the management of the agent	<p>Cause: A Warning message might indicate incorrect configuration.</p> <p>Action: If condition persists, submit requested logs/data.</p>
200602000	A Warning message occurred in the authentication module (JAAS)	<p>Cause: A Warning message might indicate incorrect configuration.</p> <p>Action: If condition persists, submit requested logs/data.</p>
200603000	A Warning message occurred in the authorization module (JACC)	<p>Cause: A Warning message might indicate incorrect configuration.</p> <p>Action: Submit requested logs/data.</p>

Event Code	Message	Remedy
300601000	Generic trace/debug message from agent management	Action: A trace/debug message does not indicate failure or misconfiguration, but it might help diagnosing a problem.
030060200	Generic trace/debug message from authentication module (JAAS)	Action: A trace/debug message does not indicate failure or misconfiguration, but it might help diagnosing a problem.
300603000	Generic trace/debug message from authorization module (JACC)	Action: A trace/debug message does not indicate failure or misconfiguration, but it might help diagnosing a problem.
200699002	Invalid input data. Invalid data has been received which prevents policy from being evaluated.	Action: See supplementary messages in logs for indication of specific problem.
200699003	PEP Configuration Error: invalid policy configuration data.	<p>Cause: The Administration Console has produced an invalid policy configuration document</p> <p>Action: You can take any or all of the following actions:</p> <ol style="list-style-type: none"> 1) Submit the log file (which includes an AM#500699030 log entry containing the policy configuration) to Novell Support to facilitate fixing the Administration Console. 2) Back up to a previous policy configuration that worked until the Administration Console has been fixed. 3) Examine the AM#500699030 log entry and determine the particular policy statement in error and remove it from your configuration until a fix for the Administration Console is available.
200699073	Policy Evaluation Error: condition data unavailable.	Action: See supplementary message in logs for indication of specific problem.
200699075	Invalid API arguments. Indicates an internal software error.	Action: See supplementary messages in logs for indication of specific problem.
500699030	J2EE Agent PEP Configuration: the J2EE Agent PEP has been configured without error.	<p>Cause: Initial policy configuration applied from the Administration Console.</p> <p>Action: None. Informational only.</p>
500699031	J2EE Agent PEP Policy Evaluation.	<p>Cause: The J2EE Agent PEP has evaluated an access control policy for a protected resource.</p> <p>Action: None. Informational only.</p>
500699032	J2EE Agent PEP SSL Required Evaluation.	<p>Cause: The J2EE Agent PEP has evaluated if SSL is required for access to a protected resource.</p> <p>Action: No Action. Informational only.</p>

Event Code	Message	Remedy
500699033	J2EE Agent Startup.	Cause: J2EE Agent started. Action: No Action. Informational only.
500699034	J2EE Agent Shutdown.	Cause: J2EE Agent shutdown. Action: No Action. Informational only.
500699035	J2EE Agent Reconfigured.	Cause: New policy configuration applied from Access Manager Administration Console. Action: None. Informational only.
500699036	J2EE Agent Authentication Successful.	Cause: A user requesting access to a protected resource has been successfully authenticated with the Identity Server. Action: None. Informational only.
500699037	J2EE Agent Authentication Failed.	Cause: A user requesting access to a protected resource has been denied authentication by the Identity Server. Action: None. Informational only.
500699038	J2EE Agent Web Resource Access Allowed.	Cause: A user has been granted access to a protected web resource. Action: None. Informational only.
500699039	J2EE Agent Web Resource Access Denied.	Cause: A user has been denied access to a protected web resource. Action: None. Informational only.
500699040	J2EE Agent Clear Text Access Allowed.	Cause: A user has been granted clear text access to a protected web resource. Action: None. Informational only.
500699041	J2EE Agent Clear Text Access Denied.	Cause: A user has been denied clear text access to a protected web resource. Action: None. Informational only.
500699042	J2EE Agent EJB Access Allowed.	Cause: A user has been granted access to a protected EJB resource. Action: None. Informational only.
500699043	J2EE Agent EJB Access Denied.	Cause: A user has been denied access to a protected EJB resource. Action: None. Informational only.

1.1.5 Server Communications (JCC) (007)

Component 007

- ♦ Sub group 01: Package com.novell.jcc.cert

- ◆ Sub group 02: Package com.novell.jcc.client
- ◆ Sub group 03: Package com.novell.jcc.handler
- ◆ Sub group 04: Package com.novell.jcc.proxy
- ◆ Sub group 05: Package com.novell.jcc.schedule
- ◆ Sub group 06: Package com.novell.jcc.server
- ◆ Sub group 07: Package com.novell.jcc.servlet
- ◆ Sub group 08: Package com.novell.jcc.sockets
- ◆ Sub group 09: Package com.novell.jcc.util

Event Code	Description	Remedy
100701002	Cannot interpret PKCS12 data for CertCommand	<p>Cause: The PKCS12 package was corrupted in transit or contained a certificate with a unsupported level encryption for the Java security provider (such as 4096 bit support).</p> <p>Action: Verify that you are using a supported certificate size and try the operation again.</p>
100701003	Set key entry failed on [store name]	<p>Cause: The Java keystore password became out of sync with the admin server, or an IO error occurred.</p> <p>Action: Try operation again, otherwise submit the <code>app_sc.0.log</code> and <code>jcc-0.log.0</code> files for resolution.</p>
100701004	KeyStoreException - set certificate entry failed	<p>Cause: The Java keystore password became out of sync with the admin server, or an IO error occurred.</p> <p>Action: Try operation again, otherwise submit the <code>app_sc.0.log</code> and <code>jcc-0.log.0</code> files for resolution.</p>
100701005	KeyStoreException - delete entry failed	<p>Cause: A keystore entry for the specified alias does not exist.</p> <p>Action: Verify the previous key import commands were successful. Otherwise, submit the <code>app_sc.0.log</code> and <code>jcc-0.log.0</code> files for resolution.</p>
100701006	Exception - key usage extension failed	<p>Cause: The key usage extension specified by the administration console was invalid.</p> <p>Action: Submit the <code>app_sc.0.log</code> and <code>jcc-0.log.0</code> files for resolution.</p>
100701007	Exception - get alternate name extension failed	<p>Cause: Alternate name format specified by the administration console was invalid.</p> <p>Action: Submit the <code>app_sc.0.log</code> and <code>jcc-0.log.0</code> files for resolution.</p>

Event Code	Description	Remedy
100701008	KeystoreInfo class has not been initialized	<p>Cause: Likely a previous error occurred during keystore initialization.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution.</p>
100701009	[key file] is missing required information for keystore named [keystore name]	<p>Cause: The keystore information supplied at installation is missing or corrupt.</p> <p>Action: Reinstall. Otherwise submit the <code>jcc-0.log.0</code> file for resolution.</p>
100701010	[key file] is missing	<p>Cause: The keystore information supplied at installation is missing or corrupt.</p> <p>Action: Uninstall and reinstall the server component. Otherwise submit the <code>jcc-0.log.0</code> file for resolution.</p>
100701011	Exception - close keystore (persisting) failed	<p>Cause: Could not write the key to the keystore.</p> <p>Action: Try the operation again. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100701012	Exception - eDirectory keystore initialization failed	<p>Cause: Could not connect to the config store.</p> <p>Action: Restart the server.</p>
100701013	Exception - Java keystore initialization failed	<p>Cause: The password to the keystore was incorrect, or the keystore file could not be opened.</p> <p>Action: Verify the keystore exists, and try the operation again. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100701014	Exception PKCS12 keystore initialization failed	<p>Cause: The password to the PKCS12 key was incorrect.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution.</p>
100701015	Exception - loading keystore failed	<p>Cause: The encrypted keystore_info.xml file could not be read.</p> <p>Action: Reinstall the server component. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
Package com.novell.jcc.client		
100702001	Exception sending alert	<p>Cause: Alert could not be sent to the Admin Console.</p> <p>Action: Make sure the server can communicate with the administration console. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>

Event Code	Description	Remedy
100702002	Could not create default response XML	<p>Cause: A problem occurred creating the default XML document.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution.</p>
100702003	Exception while building alert request: [exception], retrying	<p>Cause: The alert information was not saved in XML correctly.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution.</p>
100702004	Configuration for Device Manager not set	<p>Cause: The settings file determining where to send the alert was not found.</p> <p>Action: Restart the <code>novell-jcc</code> service. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100702005	Error getting configuration for Device Manager	<p>Cause: There was a problem reading the settings file.</p> <p>Action: Restart the <code>novell-jcc</code> service. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100702006	Alert could not be sent	<p>Cause: The response from the administration console was not successful.</p> <p>Action: The system will try indefinitely to resend the alert. Make sure the administration console is functioning. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100702007	Bad health URL	<p>Cause: The IP address or port setting for the administration console has been corrupted.</p> <p>Action: Make sure the <code>settings.properties</code> file contains correct information. Restart the <code>novell-jcc</code> service.</p>
100702008	Error sending alert	<p>Cause: The system cannot communicate with the administration console.</p> <p>Action: Make sure the system can communicate with the administration console and that it is functioning properly.</p>
100702009	Error sending alert	<p>Cause: The system cannot communicate with the administration console, or some other communication error occurred.</p> <p>Action: Make sure the system can communicate with the administration console and that it is functioning properly.</p>

Event Code	Description	Remedy
100702010	Exception - connection disconnect failed	<p>Cause: An error occurred with reading the alert response or a disconnect error occurred.</p> <p>Action: Make sure the system can communicate with the administration console and that it is functioning properly.</p>
100702011	Queued alerts cannot be saved	<p>Cause: The class structure has likely changed or the alertdispatch.dat file could not be created.</p> <p>Action: The error is non-fatal, continue running service.</p>
100702012	Queued alerts cannot be restored	<p>Cause: The code has likely changed or the alertdispatch.dat file could not be read.</p> <p>Action: The error is non-fatal, continue running service.</p>
100702013	Exception - setting keystore or trust store failed	<p>Cause: The keystore_info.xml file was corrupt or does not exist.</p> <p>Action: Reinstall the server component. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100702014	Exception getting health from [service name]	<p>Cause: Could not communicate to obtain the health from named component.</p> <p>Action: Restart the service. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100702015	Exception creating health XML	<p>Cause: A problem occurred reading health data while creating the health XML.</p> <p>Action: The operation will retry. If it persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100702016	MalformedURLException - Bad health URL	<p>Cause: The IP address or port setting for the administration console has been corrupted.</p> <p>Action: Make sure the settings.properties file contains correct information. Restart the novell-jcc service.</p>
100702017	Error sending periodic health	<p>Cause: The system cannot communicate with the administration console.</p> <p>Action: Make sure the system can communicate with the administration console and that it is functioning properly.</p>
100702018	Error sending periodic health	<p>Cause: The system cannot communicate with the administration console, or some other communication error occurred.</p> <p>Action: Make sure the system can communicate with the administration console and that it is functioning properly.</p>

Event Code	Description	Remedy
100702019	Crypto key not found	<p>Cause: The jcc.keystore file was not found.</p> <p>Action: Make sure the installation completed successfully, and that the novell-jcc service is running. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100702020	Error calling initializationComplete/ serviceStopComplete	<p>Cause: An RMI error occurred communicating with the novell-jcc service.</p> <p>Action: Make sure the installation completed successfully, and that the novell-jcc service is running. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100702021	Server is not connected	<p>Cause: The novell-jcc service is not running.</p> <p>Action: Make sure the installation completed successfully, and that the novell-jcc service is running. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100702022	Error binding to RMI port	<p>Cause: The novell-jcc service is not running, or the RMI ports are already bound by some other process.</p> <p>Action: Make sure the installation completed successfully, and that the novell-jcc service is running. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100702023	Error registering with server	<p>Cause: The component could not register with the novell-jcc service. Likely and RMI communication error.</p> <p>Action: Restart the novell-jcc service. If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100702024	Cannot contact server; retrying	<p>Cause: The novell-jcc service was stopped, likely temporarily.</p> <p>Action: Make sure that the novell-jcc service is running. Otherwise, restart it. If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100702025	Error sending alert to server	<p>Cause: An RMI communication error likely occurred while sending an alert to the novell-jcc service.</p> <p>Action: Make sure that the novell-jcc service is running. Otherwise, restart it. If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>

Event Code	Description	Remedy
100702026	Queued alerts cannot be saved	<p>Cause:</p> <p>An RMI communication error likely occurred while saving alerts through the novell-jcc service.</p> <p>Action:</p> <p>Make sure that the novell-jcc service is running. Otherwise, restart it. If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100702027	Queued alerts cannot be restored	<p>Cause: The <code>[name]-alerts.dat</code> file was corrupted.</p> <p>Action: The error is non-fatal, but monitor the file system for further problems.</p>
	Package com.novell.jcc.handler	
100703001	Exception - Response creation failed	<p>Cause: A problem occurred creating the default XML document.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution.</p>
100703002	Exception - Response creation failed	<p>Cause: The default response information was not saved in XML correctly.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution.</p>
100703003	Error executing command: response is null	<p>Cause: Command response from a server component was not set.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution.</p>
100703004	Bad URL from Device Manager "+responseURL+	<p>Cause: The URL given by the administration server was incorrect.</p> <p>Action: Submit the <code>jcc-0.log.0</code> and <code>app_sc.0.log</code> files from the admin console for resolution.</p>
100703005	Command error	<p>Cause: The protocol used in response to the command was malformed.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution.</p>
100703006	Command response error, retry #	<p>Cause: The Administration Console is likely temporarily down or restarting.</p> <p>Action: Allow for retry to occur. If all retries fail, ensure that the Administration Console is up and functioning.</p>

Event Code	Description	Remedy
100703007	Major or minor version not supplied [version]	<p>Cause: A server component did not supply the required version information.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution.</p>
100703009	Content-Length header [total] and actual data length [read] mismatch	<p>Cause: The data read did not match the expected length.</p> <p>Action: Restart the server component. If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100703010	Could not connect to [URL]	<p>Cause: Could not communicate with the Administration Console or the server component.</p> <p>Action: Make sure the system can communicate with the Administration Console and is operating. If the URL is 127.0.0.1, restart the server component.</p>
100703011	Exception - stats response creation failed	<p>Cause: Could not convert stats XML to be sent to the Administration Console.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution.</p>
100703012	Exception - version response creation failed	<p>Cause: Could not convert version XML to be sent to the Administration Console.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution.</p>
	Package com.novell.jcc.proxy	
100704001	Exception - Cipher socket create key failed	<p>Cause: Could not create socket cipher key.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution.</p>
100704002	AGProxy has not initialized as client is null	<p>Cause: The proxy subcomponent is not initialized.</p> <p>Action: Restart the novell-jcc service. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100704003	Command returned: [response code] [response message], Retry #	<p>Cause: The Access Gateway is processing a previous command.</p> <p>Action: Allow the retry to occur. If it persists, restart the server.</p>
100704004	Error sending [name] command	<p>Cause: Could not send the command to the Access Gateway.</p> <p>Action: If the problem persists, restart the server. Otherwise submit the <code>jcc-0.log.0</code> file for resolution.</p>

Event Code	Description	Remedy
100704005	Could not send alert	<p>Cause: A problem occurred while sending alert.</p> <p>Action: This is a non-fatal error. If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100704006	Exception - update password failed	<p>Cause: Could not read the config user password.</p> <p>Action: Restart the server. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100704007	ecc.cfg does not exist!	<p>Cause: A problem during the installation process occurred.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution, then reinstall the server.</p>
100704008	Error loading ecc.cfg	<p>Cause: Could not read the <code>ecc.cfg</code> file.</p> <p>Action: Allow the operation to retry, otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100704009	Stopped waiting for JCC server	<p>Cause: The server didn't initialize in a timely manner.</p> <p>Action: Restart the <code>novell-jcc</code> service.</p>
100704010	Cannot write ecc.cfg	<p>Cause: Could not write the specified config file.</p> <p>Action: Allow the operation to retry. If it persists, restart the server.</p>
100704011	Error reading configuration	<p>Cause: Could not parse Access Gateway configuration data.</p> <p>Action: Allow the operation to retry. If it persists, submit the <code>jcc-0.log.0</code> file for resolution and restart the server.</p>
100704012	Cannot write ecc.cfg	<p>Cause: Could not write specified file.</p> <p>Action: Allow the operation to retry. If it persists, submit the <code>jcc-0.log.0</code> file for resolution and restart the server.</p>
100704013	Exception - check esp status failed	<p>Cause: An RMI error occurred while communicating to the ESP component.</p> <p>Action: Allow the operation to retry. If it persists, submit the <code>jcc-0.log.0</code> file for resolution and restart the server.</p>
100704014	Error reading password	<p>Cause: Could not read the config user password.</p> <p>Action: Restart the server. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>

Event Code	Description	Remedy
100704015	Exception - Cipher socket create key failed	<p>Cause: Could not create socket cipher key.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution.</p>
100704016	Load settings failed	<p>Cause: The settings could not be loaded for Linux AG.</p> <p>Action: Restart the <code>novell-jcc</code> service. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100704017	LAGProxy has not initialized as client is null	<p>Cause: The proxy subcomponent is not initialized.</p> <p>Action: Restart the <code>novell-jcc</code> service. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100704018	Could not send alert	<p>Cause: An error occurred while sending an alert.</p> <p>Action: This is a non-fatal error. If it persists, restart the <code>novell-jcc</code> service.</p>
100704019	Stopped waiting for JCC server	<p>Cause: The server didn't initialize in a timely manner.</p> <p>Action: Restart the <code>novell-jcc</code> service.</p>
100704020	Error reading configuration	<p>Cause: Could not parse Access Gateway configuration data.</p> <p>Action: Allow the operation to retry. If it persists, submit the <code>jcc-0.log.0</code> file for resolution and restart the server.</p>
100704021	Exception - setting VCC ID failed	<p>Cause: Could not write the <code>config.xml</code> file with the original ID.</p> <p>Action: This error would occur during the re-import process. Click <i>Repair Import</i> on the Administration Console to resolve. Otherwise, submit <code>jcc-0.log.0</code> file for resolution.</p>
100704022	Linux Proxy is not running	<p>Cause: The proxy <code>novell-vmc</code> service has stopped responding.</p> <p>Action: to restart the proxy service, enter the following command as root user: <code>/etc/init.d/novell-vmc restart</code></p>
100704023	SSL VPN load settings failed	<p>Cause: The settings could not be loaded for SSLVPN.</p> <p>Action: Restart the <code>novell-jcc</code> service. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>

Event Code	Description	Remedy
100704024	Exception - Cipher socket create key failed	<p>Cause: Could not create socket cipher key.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution.</p>
100704025	Stopped waiting for JCC server	<p>Cause: The server didn't initialize in a timely manner.</p> <p>Action: Restart the <code>novell-jcc</code> service.</p>
100704026	Exception - setting change failed	<p>Cause: The settings could not be loaded for SSLVPN.</p> <p>Action: Restart the <code>novell-jcc</code> service. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100704027	Exception - override settings failed	<p>Cause: The settings were changed on the Linux AG, which were to override the SSLVPN settings, but did not.</p> <p>Action: Restart the <code>novell-jcc</code> service. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100704028	Error reading <code>sslvpn.id</code>	<p>Cause: Could not find the <code>sslvpn.id</code> file for reading.</p> <p>Action: The system should have recovered from this error automatically. If it persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100704029	Error writing <code>sslvpn.id</code>	<p>Cause: An IO error occurred while writing the <code>sslvpn.id</code> file.</p> <p>Action: Restart the <code>novell-jcc</code> service. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100704030	Error writing [file name]	<p>Cause: An IO error occurred while writing the <code>sslvpn.id</code> file during the reimport process.</p> <p>Action: Restart the <code>novell-jcc</code> service. Click <i>Repair Import</i> in the Administration Console to resolve. Otherwise, submit <code>jcc-0.log.0</code> file for resolution.</p>
100704031	Error getting SSLVPN stats	<p>Cause: Could not communicate with SSLVPN service to obtain statistics.</p> <p>Action: To restart the SSLVPN service, enter the following commands:</p> <pre>/etc/init.d/novell-sslvpn stop /etc/init.d/novell-sslvpn start</pre>

Event Code	Description	Remedy
100704032	Error getting SSLVPN health	<p>Cause: Could not communicate with SSLVPN service to obtain the health.</p> <p>Action: To restart the SSLVPN service, enter the following commands:</p> <pre>/etc/init.d/novell-sslvpn stop /etc/init.d/novell-sslvpn start</pre>
100704033	Cannot communicate with SSLVPN	<p>Cause: Could not communicate with SSLVPN service, which may affect auto-import and other functions from working correctly.</p> <p>Action: To restart the SSLVPN service, enter the following commands:</p> <pre>/etc/init.d/novell-sslvpn stop /etc/init.d/novell-sslvpn start</pre> <p>You might need to kill the process manually. Do this, enter the following commands:</p> <pre>ps ax grep connman</pre> <p>If you see any entries displayed other than <code>grep connman</code>, enter the following command:</p> <pre>killall -9 connman</pre> <p>Then restart the SSL VPN service with the following command:</p> <pre>/etc/init.d/novell-sslvpn start</pre>
Package com.novell.jcc.schedule		
100705001	Error getting client details	<p>Cause: An RMI communication error likely occurred.</p> <p>Action: Allow the system to retry the operation. If it persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100705002	Error getting client details	<p>Cause: An RMI communication error likely occurred.</p> <p>Action: Allow the system to retry the operation. If it persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100705003	Exception getting stats from [name]	<p>Cause: The periodic statistics subsystem was not able to get the stats from the server component.</p> <p>Action: Make sure the component is running. If it persists, restart the component.</p>
100705004	Exception creating stats XML	<p>Cause: An error occurred while creating statistics XML data.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution.</p>

Event Code	Description	Remedy
100705005	Bad stats URL	<p>Cause: The IP address or port setting for the Administration Console has been corrupted.</p> <p>Action: Make sure the settings.properties file contains correct information. Restart the novell-jcc service.</p>
100705006	Error sending periodic stats	<p>Cause: The system cannot communicate with the Administration Console.</p> <p>Action: Make sure the system can communicate with the Administration Console and that it is functioning properly.</p>
100705007	Error sending periodic stats	<p>Cause: The system cannot communicate with the Administration Console, or some other communication error occurred.</p> <p>Action: Make sure the system can communicate with the Administration Console and that it is functioning properly.</p>
100705008	Error sending statistics	<p>Cause: The system cannot communicate with the Administration Console, or some other communication error occurred.</p> <p>Action: Make sure the system can communicate with the Administration Console and that it is functioning properly.</p>
Package com.novell.jcc.server		
100706001	[service name] not registered	<p>Cause: The server component was already disconnected.</p> <p>Action: This is a non-fatal error.</p>
100706002	[service name] not found in registry	<p>Cause: The specified server component was not found so it could not be unregistered.</p> <p>Action: This is a non-fatal error.</p>
100706003	Client list cannot be saved	<p>Cause: An IO error occurred while saving the list of registered server components.</p> <p>Action: Make sure the file has write access. If the problem persists, submit the jcc-0.log.0 file for resolution.</p>
100706004	Client list cannot be restored	<p>Cause: An IO error occurred while reading the list of registered server components.</p> <p>Action: Make sure the file has read access. If an upgrade has been performed, make sure all components on the system have also been upgraded. If the problem persists, submit the jcc-0.log.0 file for resolution.</p>

Event Code	Description	Remedy
100706005	Could not stop connector	<p>Cause: The embedded HTTP server could not be stopped.</p> <p>Action: Allow the system to retry the operation. If it persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100706006	No HTTP connectors were added	<p>Cause: An internal software problem occurred.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution.</p>
100706007	Exception - setting keystore properties on http connector failed	<p>Cause: The <code>keystore_info.xml</code> file could not be read, or was corrupted.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution. Reinstall if necessary.</p>
100706008	Could not start HTTP server. Retry Number: [n]	<p>Cause: Some other application may be using the port we require to be open.</p> <p>Action: Allow the system to retry the operation. If it persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100706009	Exception during jcc shutdown	<p>Cause: A problem shutting down the embedded HTTP server occurred.</p> <p>Action: This is a non-fatal error. If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100706010	Exception in testing HTTP server	<p>Cause: An error testing the HTTP server occurred.</p> <p>Action: This is a non-fatal error.</p>
100706011	MalformedURLException - HTTP server	<p>Cause: An error testing the HTTP server occurred.</p> <p>Action: This is a non-fatal error.</p>
100706012	Failed to load eDirectory keystore provider	<p>Cause: Service could not register handler into keystore Java environment handler set.</p> <p>Action: This is a non-fatal error. If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100706013	Missing keystore information file: [key information file]. Certificate Management functions are unavailable	<p>Cause: An install-time problem occurred where the keystore information file was not created, or was deleted after installation.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution.</p>
100706014	Exception - command failed	<p>Cause: The post-keystore update command failed.</p> <p>Action: Try the operation again. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>

Event Code	Description	Remedy
100706015	Exception - cert command failed	<p>Cause: A certificate operation was unsuccessful.</p> <p>Action: Try the operation again. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100706016	Error during execution	<p>Cause: The external command did not execute properly.</p> <p>Action: Try the operation again. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100706017	Exception - delete info failed	<p>Cause: A problem occurred deleting internal information.</p> <p>Action: This is a non-fatal error.</p>
100706018	JCC Server startup failed	<p>Cause: A critical error occurred during the startup of the novell-jcc service.</p> <p>Action: To restart the novell-jcc service, enter the following command: <code>/etc/init.d/novell-jcc restart</code></p> <p>If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100706019	Embedded HTTP Server already started	<p>Cause: The internal HTTP server was already started when asked to start.</p> <p>Action: This is a non-fatal error.</p>
100706020	Error starting embedded tomcat	<p>Cause: Another process is likely using the novell-jcc service port (default 1443).</p> <p>Action: Make sure there are no other processes using this port, then restart the service.</p>
100706021	RMI problem	<p>Cause: An error occurred during the shutdown process.</p> <p>Action: This is a non-fatal error.</p>
100706022	RMI exception	<p>Cause: An error occurred during the shutdown process.</p> <p>Action: This is a non-fatal error.</p>
100706023	Server did not initialize within 60 seconds	<p>Cause: A server component initialization message could not be completed as the novell-jcc service is not finished initializing.</p> <p>Action: To restart the novell-jcc service, enter the following command: <code>/etc/init.d/novell-jcc restart</code></p> <p>If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>

Event Code	Description	Remedy
100706024	Exception - JCC server initialization failed	<p>Cause: A server component initialization message could not be completed.</p> <p>Action: To restart the novell-jcc service, enter the following command: <pre>/etc/init.d/novell-jcc restart</pre></p> <p>If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100706025	Error binding to RMI [port]	<p>Cause: Another process is likely using the novell-jcc service port (default 1197).</p> <p>Action: Make sure there are no other processes using this port, then restart the service.</p>
100706026	Error registering remote object	<p>Cause: A problem occurred during the RMI bind process.</p> <p>Action: Make sure that all components are of the same build of Access Manager. Then restart novell-jcc service.</p>
100706027	Error sending alert	<p>Cause: A problem occurred sending the import command to the Administration Console.</p> <p>Action: Allow the system to retry the operation. If it persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100706028	Error getting client details for import	<p>Cause: An RMI communication error has occurred between the server component and the novell-jcc service.</p> <p>Action: Make sure the server component is functioning properly and try the operation again. If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100706029	Error sending alert command	<p>Cause: Problem sending a command-type alert to the Administration Console.</p> <p>Action: Make sure the Administration Console is running. Allow the system to retry the operation. If it persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100706030	Exception - get keystore information failed	<p>Cause: A problem occurred sending the keystore information from the <code>keystore_info.xml</code> file.</p> <p>Action: If the server shows up in the Administration Console, click <i>Repair Import</i>. Otherwise, submit <code>jcc-0.log.0</code> and <code>app_sc.0.log</code> files for resolution.</p>

Event Code	Description	Remedy
100706031	Error getting key [key name] to [key file]	<p>Cause: A problem occurred receiving the assigned keys during a reimport operation.</p> <p>Action: Ensure the Administration Console is operational, perform the steps to re-trigger an auto-import. Otherwise, submit the <code>jcc-0.log.0</code> and <code>app_sc.0.log</code> files for resolution.</p>
100706032	Could not get keystore information for reimport of [service name]	<p>Cause: A problem occurred receiving the assigned keystore information during a reimport operation.</p> <p>Action: Ensure the admin console is operational, perform the steps to re-trigger an auto-import. Otherwise, submit the <code>jcc-0.log.0</code> and <code>app_sc.0.log</code> files for resolution.</p>
100706033	Exception	<p>Cause: A problem occurred during a reimport operation.</p> <p>Action: Ensure the admin console is operational, perform the steps to re-trigger an auto-import. Otherwise, submit the <code>jcc-0.log.0</code> and <code>app_sc.0.log</code> files for resolution.</p>
100706034	Exception - get key failed	<p>Cause: An assigned key could not be obtained during a reimport operation.</p> <p>Action: Allow the operation to retry. Ensure the admin console is operational, perform the steps to re-trigger an auto-import. Otherwise, submit the <code>jcc-0.log.0</code> and <code>app_sc.0.log</code> files for resolution.</p>
100706035	RMI exception during execution of [command name]	<p>Cause: An RMI communication error occurred while executing a command from the administration console.</p> <p>Action: Try the operation again. If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100706036	RMI exception	<p>Cause: An RMI communication error occurred while executing a command from the administration console.</p> <p>Action: Try the operation again. If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>

Event Code	Description	Remedy
100706037	Error collecting health from [service name]	<p>Cause: An RMI communication error occurred while obtaining the health information from a server component.</p> <p>Action: Allow the operation to try again. Make sure the server component is running properly. If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100706038	Error collecting stats from [service name]	<p>Cause: An RMI communication error occurred while obtaining the stats information from a server component.</p> <p>Action: Allow the operation to try again. Make sure the server component is running properly. If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100706039	RMI exception	<p>Cause: A communication error occurred.</p> <p>Action: Make sure the server component is running properly. If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100706040	RMI exception	<p>Cause: A communication error occurred.</p> <p>Action: Make sure the server component is running properly. If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100706041	RMI exception	<p>Cause: A communication error occurred.</p> <p>Action: Make sure the server component is running properly. If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100706042	RMI exception	<p>Cause: A communication error occurred.</p> <p>Action: Make sure the server component is running properly. If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
Package com.novell.jcc.servlet		
100707001	Servlet error in [handler name]	<p>Cause: An error occurred responding to a administration console request.</p> <p>Action: Try the operation again. If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100707002	IO error in [handler name]	<p>Cause: An IO error occurred while responding to a administration console request.</p> <p>Action: Try the operation again. If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>

Event Code	Description	Remedy
100707003	No client found with ID [service name]	<p>Cause: The specified server component known to the administration console is not currently running, or cannot communicate with the novell-jcc service.</p> <p>Action: Make sure the server component is running properly. Ensure all components on the system are of the same version and build. Restart the server component. If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100707004	[appliance id] header missing from [IP address]	<p>Cause: An invalid request was submitted to the novell-jcc service.</p> <p>Action: This is likely an un-authorized login attempt. Locate the remote IP address and follow proper security procedures.</p>
100707005	No handler is registered for [query string]	<p>Cause: An invalid request was submitted to the novell-jcc service.</p> <p>Action: This is likely an un-authorized login attempt. Locate the remote IP address and follow proper security procedures.</p>
100707006	Exception registering handler	<p>Cause: A problem occurred during start up of the novell-jcc service.</p> <p>Action: Make sure the <code>jcc/webapps/jcc/WEB-INF/web.xml</code> file is not corrupt.</p>
	Package com.novell.jcc.sockets	
100708001	Could not initialize the cipher	<p>Cause: The cipher could not be initialized.</p> <p>Action: Try restarting the novell-jcc service.</p>
100708002	Could not initialize the cipher	<p>Cause: The cipher could not be initialized.</p> <p>Action: Try restarting the novell-jcc service.</p>
100708003	Error creating socket factory	<p>Cause: A possible security problem has been attempted, or the <code>jcc.keystore</code> file is corrupt.</p> <p>Action: Check the <code>jcc.keystore</code> timestamp of last the modification, and if it is different than install-time, you might have a security problem.</p>
100708004	Could not find keystore_info.xml	<p>Cause: The install process did not complete successfully.</p> <p>Action: Restart the novell-jcc service. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution and reinstall the server component.</p>
	Package com.novell.jcc.util	

Event Code	Description	Remedy
100709001	Error saving settings	<p>Cause: An IO error occurred while saving install-time settings.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution and reinstall the server component.</p>
100709002	Error loading settings	<p>Cause: An IO error occurred while reading install-time settings.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution and reinstall the server component.</p>
100709003	Error creating JCC key	<p>Cause: A critical error occurred while creating the certificate for communicating with the administration server.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution and reinstall the server component.</p>
100709004	Error saving settings	<p>Cause: An IO error occurred while saving install-time settings.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution and reinstall the server component.</p>
100709005	Exception - install trusted roots failed	<p>Cause: A communication error occurred while sending trusted roots to the administration server.</p> <p>Action: Ensure the admin console is running properly. Otherwise, submit the <code>jcc-0.log.0</code> file for resolution and reinstall the server component.</p>
100709006	Could not get keys	<p>Cause: The default keys could not be obtained from the administration server.</p> <p>Action: Allow the system to retry the operation. If the problem persists, make sure the admin console is operational. Otherwise, submit the <code>jcc-0.log.0</code> and <code>app_sc.0.log</code> files for resolution.</p>
100709007	Error getting esp ID	<p>Cause: The server component install likely terminated before completion.</p> <p>Action: Reinstall server component.</p>
100709008	Exception - configure LAG failed	<p>Cause: A problem occurred while setting up keystore information for the Access Gateway.</p> <p>Action: Reinstall the server.</p>
100709009	Could not get admin name/password from NW	<p>Cause: An install-time error occurred during the CD-install process.</p> <p>Action: Reinstall the server.</p>

Event Code	Description	Remedy
100709010	Could not create keystores	<p>Cause: An error occurred while creating the keystore information during the configuration process.</p> <p>Action: Reinstall the server component.</p>
100709011	Exception - get key failed	<p>Cause: The default key could not be obtained from the administration console during the initial configuration.</p> <p>Action: Ensure the Administration Console is operational, and reinstall the server component.</p>
100709012	Exception - Cert not valid	<p>Cause: The default trusted root obtained from the Administration Console is not yet valid.</p> <p>Action: Make sure the system time and time zone matches that of the Administration Console, then reinstall.</p>
100709013	Exception - Cert not valid	<p>Cause: The default trusted root obtained from the Administration Console is not yet valid.</p> <p>Action: Make sure the system time and time zone matches that of the Administration Console, then reinstall.</p>
100709014	Error creating key	<p>Cause: A critical error occurred writing the <code>jcc.keystore</code> file.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution, reinstall the server component.</p>
100709015	Exception during configuration	<p>Cause: A fatal problem occurred during installation.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution, reinstall the server component.</p>
100709016	Could not open [jcc log file]	<p>Cause: Make sure the installation succeeded.</p> <p>Action: Restart the server. If the problem persists, submit the <code>jcc-0.log.0</code> file for resolution.</p>
100709017	[path]/settings.properties file does not exist	<p>Cause: An install-time error occurred.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution, reinstall the server component.</p>
100709018	No remote management address is set.	<p>Cause: An IP address has not been specified for the administration console.</p> <p>Action: On the server command-line, set an administration console IP address.</p>
100709019	JCC server certificate was not found in: [keystore file]	<p>Cause: An install-time error occurred.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution, reinstall the server component.</p>

Event Code	Description	Remedy
100709020	Exception reading keystore information	<p>Cause: The <code>keystore_info.xml</code> file is missing, or corrupt. Or, the internal keystore has been tampered with, or the certificate is expired.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution, reinstall the server component.</p>
100709021	Exception - get JCC keystore information failed	<p>Cause: The <code>keystore_info.xml</code> file is missing, or corrupt.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution, reinstall the server component.</p>
100709022	IllegalArgumentException	<p>Cause: An internal component made an invalid call.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution.</p>
100709023	IllegalStateException	<p>Cause: An internal component made an invalid call.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution.</p>
100709024	Object could not be saved	<p>Cause: A system setting file cannot be saved.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution.</p>
100709025	Object cannot be restored	<p>Cause: A system setting file cannot be restored.</p> <p>Action: Submit the <code>jcc-0.log.0</code> file for resolution.</p>

1.1.6 Policy Engine (008)

Component 008

- ◆ Sub group 01: Engine
- ◆ Sub group 02: Condition Handler
- ◆ Sub group 03: Action Handler
- ◆ Sub group 04: Configure Information Context
- ◆ Sub group 05: Information Context
- ◆ Sub group 06: Response Context

* = any Sub group

Event Code	Description	Remedy	
100801001	Error No Memory: Memory allocation failed.	Cause: Low system memory. Resource allocation failed.	
100802001		Action: Determine cause for low system memory and resolve.	
100803001			
100804001			
100805001			
100806001			
200801002	Error Bad Data: Policy configuration contains an invalid policy parameter list enumerative value.	Cause: The Administration Console has produced an invalid policy configuration document.	
200802002		Cause: Policy configuration document has been corrupted.	
200803002			
200804002			
200805002			Action: Take any or all of the following actions:
200806002			<ol style="list-style-type: none"> 1. Submit the log file to Novell Support to aid in determining and fixing the source of the problem. 2. Back up to a previously working policy configuration until the problem has been fixed. 3. Examine the policy configuration document (available in PEP trace entries) to determine the erroneous policy document element and remove the corresponding policy statement from your policy configuration until a fix for the problem is available.
200801003	Error Configuration. The policy configuration is syntactically incorrect or malformed.	Cause: The Administration Console has produced an invalid policy configuration document.	
200802003		Cause: Policy configuration document has been corrupted.	
200803003			
200804003			
200805003			Action: Take any or all of the following actions:
200806003			<ol style="list-style-type: none"> 1. Submit the log file to Novell Support to aid in determining and fixing the source of the problem. 2. Back up to a previously working policy configuration until the problem has been fixed. 3. Examine the policy configuration document (available in PEP trace entries) to determine the erroneous policy document element and remove the corresponding policy statement from your policy configuration until a fix for the problem is available.

Event Code	Description	Remedy		
200801004	General Failure: Internal software error.	Cause: Unexpected exception caught during policy evaluation.		
200802004		Action: Submit log file to Novell Support for analysis and problem resolution.		
200803004				
200804004				
200805004				
200806004				
200801072	Interface Unavailable: Invalid InformationContext or ResponseContext enumerative value.	Cause: The Administration Console has produced an invalid policy configuration document.		
200802072		Invalid PolicyTypeSpec schema.		
200803072				
200804072			Cause: Policy configuration document has been corrupted.	
200805072			Action: Take any or all of the following actions:	
200806072				<ol style="list-style-type: none"> 1. Submit the log file to Novell Support to aid in determining and fixing the source of the problem. 2. Back up to a previously working policy configuration until the problem has been fixed. 3. Examine the policy configuration document (available in PEP trace entries) to determine the erroneous policy document element and remove the corresponding policy statement from your policy configuration until a fix for the problem is available.
200801073				Data Unavailable: Policy Engine could not obtain needed information to complete policy evaluation.
200802073	Action: Ensure user store or database is available.			
200803073	Cause: Network connectivity problems.			
200804073		Action: Ensure network is operational.		
200805073				
200806073				
200801074			Illegal State: Policy Engine caught NullPointerException during policy configuration or evaluation.	
200802074	Action: Submit log to Novell Support for analysis and resolution.			
200803074				
200804074				
200805074				
200806074				

Event Code	Description	Remedy
200801075	Illegal Argument: Internal software error.	Cause: Invalid method argument received.
200802075		Action: Submit log to Novell Support for analysis and resolution.
200803075		
200804075		
200805075		
200806075		
300801071	Evaluation Canceled: Active policy evaluation canceled.	Cause: May occur during system shutdown.
300802071		Action: If not caused by system shutdown, submit log to Novell Support for analysis and resolution.
300803071		
300804071		
300805071		
300806071		
500801000	Success: Policy operation completed without error.	Cause: Policy Evaluation.
500802000		Action: No Action. Informational only.
500803000		
500804000		
500805000		
500806000		
500801005	Operation Pending: Policy operation is in progress	Cause: Policy Evaluation.
500802005		Action: No Action. Informational only.
500803005		
500804005		
500805005		
500806005		
500803064	Permit Action: Policy evaluation rendered a Permit Action.	Cause: Permit action executed. Action: No Action. Informational only.
500803065	Deny Action: Policy evaluation rendered a Deny Action.	Cause: Deny action executed. Action: No Action. Informational only.
500803066	Obligation Action: Policy evaluation rendered an Obligation Action.	Cause: Obligation action executed. Action: No Action. Informational only.

Event Code	Description	Remedy
500801067	No Action: Policy evaluation rendered no Action.	Cause: No action was executed during a policy evaluation. Action: No Action. Informational only.
500802067		
500803067		
500804067		
500805067		
500806067		
500802068	Condition False: Policy condition returned FALSE.	Cause: Policy Evaluation. Action: No Action. Informational only.
500802069	Condition True: Policy condition returned TRUE.	Cause: Policy Evaluation. Action: No Action. Informational only.
200802070	Condition Unknown. Policy configuration contains an unsupported condition handler definition.	Cause: The Administration Console has produced an invalid policy configuration document. Cause: Policy configuration document has been corrupted. Action: Take any or all of the following actions: <ol style="list-style-type: none"> 1. Submit the log file to Novell Support to aid in determining and fixing the source of the problem. 2. Back up to a previously working policy configuration until the problem has been fixed. 3. Examine the policy configuration document (available in PEP trace entries) to determine the erroneous policy document element and remove the corresponding policy statement from your policy configuration until a fix for the problem is available.

1.1.7 Administration Console (009)

Component 009

- ◆ Sub group 01: Certificate Manager
- ◆ Sub group 02: Application
- ◆ Sub group 03: Platform
- ◆ Sub group 04: Web UI
- ◆ Sub group 05: Roma Application

Event Code	Description	Remedy
Application		
10090100 1	Error getting web manager.	<p>Cause: The Administration Console was not installed correctly or has become corrupt.</p> <p>Action: Verify installation.</p>
10090100 2	Error in initializing the dirCerts APIs.	<p>Cause: The Administration Console was not installed correctly or has become corrupt. Specifically, the PKI and/or certificate management jars may be missing or have mismatched versions.</p> <p>Action: Verify that the <code>certmgr.jar</code> file is contained in the <code>/var/opt/novell/tomcat4/webapps/roma/WEB-INF/lib</code> directory and that PKI has been installed.</p> <p>Verify that the Java command line contains the following:</p> <pre>-Djava.library.path=/opt/novell/lib</pre> <p>Verify that <code>npki.jar</code> is in the classpath.</p>
10090100 3	Error in init.	<p>Cause: The Administration Console was not installed correctly or has become corrupt.</p> <p>Action: Verify installation.</p>
10090100 4	Error in CertHandler.getMultipartParamValue.	<p>Cause: Servlet error when retrieving data from a multipart form.</p> <p>Action: Submit log to Novell Support for analysis and resolution.</p>
10090100 8	Could not remove certificate with the given alias from the keystore.	<p>Cause: The keystore that contains the certificate might not exist or might have become corrupt.</p> <p>Action: View the configuration store and find the keystore object and check that the certificate is no longer in the key list. If it is there, manually remove it.</p> <p>Also, find the keystore on the file system of the device and remove the key manually, using the Java keytool program for JKS keystores.</p>

Event Code	Description	Remedy
10090101 0	Error In CertHandler.doGetSigningCertDN.	<p>Cause: Unable to retrieve the DN of the signing cert.</p> <p>Cause: The signing cert does not exist.</p> <p>Cause: The signing keystore does not exist.</p> <p>Action: View the Identity Server Configuration's Signing keystore to verify that it exists and contains a certificate. If the signing keystore does not exist, there has been an error during the import of an Identity Server or during the creation of an Identity Server Configuration.</p> <p>Check to make sure that there are no corrupt Identity Server configurations. If the signing keystore does exist, add or replace a certificate.</p>
100901011	Error in creating or configuring one or more of the Identity Server Configuration cluster keystores.	<p>Cause: Test certificates might have been accidentally deleted from the file system.</p> <p>Cause: Error communicating with the Identity Server(s) while pushing down the test certificates.</p> <p>Action: Use the exception stack trace to discover a more detailed description of the error. Go to the Certificates tab and verify that the test-connector, test-signing, test-encryption, test-provider, test-consumer certificates have not been deleted.</p> <p>Also verify they still exist on the file system. Go to the Trusted Roots tab and verify that the configCA trusted root has not been deleted and that it exists in the configuration store. These test certificates are pushed down to each Identity Server during the creation of an Identity Server configuration.</p> <p>You can delete the Identity Server configuration and create a new one and add the Identity Servers back into the new configuration.</p>
10090101 2	keystore already exists.	<p>Cause: You are trying to create a keystore that already exists on the device.</p> <p>Action: Use the existing keystore.</p>
10090101 3	Error in init (using reflection to call a method has failed in init).	<p>Cause: The java class is unable to locate another java class through reflection.</p> <p>Action: Submit log to Novell Support for analysis and resolution.</p>

Event Code	Description	Remedy
70090101 4	Cannot add non-existent key to keystore.	<p>Cause: The certificate you are trying to add to a keystore does not exist.</p> <p>Action: Specify a valid key to be added to the keystore.</p>
70090101 5	Cannot add key to non-existent keystore.	<p>Cause: The keystore does not exist.</p> <p>Action: Specify a valid keystore or create the keystore.</p>
70090101 6	Could not add key to keystore because the alias was too long.	<p>Cause: Some platforms and keystore formats only support a limited number of characters in the alias name.</p> <p>Action: Use a shorter alias.</p>
70090101 7	Could not add key to keystore because the maximum number of keys has been reached.	<p>Cause: Many keystores allow only one key to be contained in it because the keystore has a specific purpose in Access Manager.</p> <p>Action: Remove unused keys from the keystore and try again.</p>
70090102 0	Cannot remove non-existent key from keystore.	<p>Cause: The key no longer exists in Access Manager.</p> <p>Action: View the configuration store and find the keystore object and manually remove the key from the key list.</p>
70090102 1	Cannot remove key from non-existent keystore.	<p>Cause: The keystore does not exist.</p> <p>Action: Specify a valid keystore.</p>
10090102 3	CertHandler.doGetCertFromServer: Could not connect to server IP and port.	<p>Cause: The server IP or DNS name and port combination is not reachable.</p> <p>Action: Verify that the IP address or DNS name exists and that the port is correct. You can try connecting to it with a web browser or other utility.</p>
10090102 4	CertHandler.doGetCertFromServer: certificate was not obtained from server IP and port.	<p>Cause: The server IP or DNS name and port combination had no certificate to be presented.</p> <p>Action: Verify that the IP address or DNS name exists and that the port is correct. Verify that the server you are attempting to import the certificate from has a certificate. You can try connecting to it with a web browser or other utility.</p>

Event Code	Description	Remedy
10090102 5	Error in handleException.	<p>Cause: The exception reported has no details associated with it.</p> <p>Action: Scroll up in the log to see if there is a stack trace immediately above this error, determine what steps you had taken to create this error condition, and submit the log and steps to Novell Support.</p>
10090102 6	The node keystore does not exist. Cannot add cluster keys to a non-existent keystore.	<p>Cause: The grouping of Identity Servers (Identity Server Configuration) or Access Gateways is trying to locate a keystore on one of the Identity Server or Access Gateway devices but the keystore cannot be found.</p> <p>Action: Verify that the Identity Servers and Access Gateway devices had no errors during import to the Administration Console. Try to re-import the devices.</p>
10090102 7	Error in CertHandler.getNIDPDeviceKeystoreName (The name of the device's keystore was not found).	<p>Cause: The cluster keystore representation object was not found.</p> <p>Cause: The cluster keystore representation did not have a device type specified.</p> <p>Action: Delete and recreate the Identity Server Configuration or Access Gateway Group that is causing the problem and then re-add the members.</p>
10090102 8	Error in CertHandler.isTomcatCert (Unable to determine if the specified certificate is the one being used by Tomcat).	<p>Cause: The certificate representation has missing or invalid attributes.</p> <p>Action: Delete this certificate and re-import it.</p>
10090103 0	Error in CertHandler.getNodeKeystoreNames (The cluster object was not found in the configuration store, or the cluster server list was empty).	<p>Cause: The cluster object was not found in the configuration store, the type of the cluster could not be determined, or the cluster server list was empty.</p> <p>Action: No action needed unless your devices are unable to communicate. If you are having problems with communication, delete and recreate the Identity Server configuration or Access Gateway cluster that is causing the problem.</p>
10090103 1	Error in CertHandler.getClusterDisplayName (The cluster object was not found in the configuration store).	<p>Action: Delete and recreate the Identity Server configuration or Access Gateway cluster that is causing the problem and then re-add the members.</p>
10090103 2	The device does not exist but the certificate is in a keystore assigned to that device.	<p>Cause: It's possible the device is in a partially-imported state.</p> <p>Action: Delete the keystore, if possible, and re-import the device.</p>

Event Code	Description	Remedy
10090103 3	The device does not exist but the keystore is assigned to that device.	<p>Cause: It's possible the device is in a partially-imported state.</p> <p>Action: Delete the keystore, if possible, and re-import the device.</p>
10090103 4	Unable to retrieve the primary member of the group.	<p>Cause: The group is corrupt.</p> <p>Action: Delete the group, re-create it, and re-add the members.</p>
10090103 5	Unable to remove the node keystore setting off the Access Gateway group device.	<p>Cause: Could not locate the keystore object in the configuration store.</p> <p>Action: No action required.</p>
70090103 6	Unable to set the Update Servers status.	<p>Cause: Communication error.</p> <p>Action: Manually restart or update the device.</p>
70090103 7	Unable to remove all keys from keystore.	<p>Cause: The keystore doesn't exist.</p> <p>Cause: There is a corrupt key in the keystore.</p> <p>Action: Manually remove each certificate from the keystore.</p>
70090103 8	Unable to reinitialize keystore contents for a particular device in a group or configuration.	<p>Cause: One of the device keystores does not exist.</p> <p>Action: Re-create the keystore or delete and recreate the group or configuration and then re-add the devices to it.</p> <p>Cause: There was an error either removing all certificates from a keystore.</p> <p>Action: Manually remove all certificates from the keystore and then remove and re-add that device to the group/configuration.</p> <p>Cause: There was an error adding the test certificates to a keystore.</p> <p>Action: Verify that the test certificates exist (see error 1.009.01.011 for more detail). Manually add the test certificates to the keystore. Or remove the device from the group/configuration and re-add it.</p>
70090103 9	Unable to assess whether the keystore contains a tomcat connector certificate.	<p>Cause: The cluster keystore representation does not exist or is corrupt.</p> <p>Cause: Unable to locate the devices in the group/configuration.</p> <p>Action: Delete and recreate the group/configuration and re-add the devices to it.</p>

Event Code	Description	Remedy
70090104 0	Error adding a key to keystore during the renew certificate process.	<p>Cause: The original certificate information could not be located.</p> <p>Action: Manually create a new certificate and place it into all the keystores which previously held the certificate being renewed.</p>
10090104 1	Unable to extract the public key from a key during the auto-import public certificate process.	<p>Cause: The source keystore does not exist.</p> <p>Action: Select a valid keystore.</p> <p>Cause: The specified source key does not exist.</p> <p>Action: Verify that the key you have specified to export the public certificate from exists.</p>
10090104 2	Unable to set up the initial keys for the cluster.	<p>Cause: When trying to locate the cluster keystores so that their contents can be initialized, one or more of those keystore representations could not be found.</p> <p>Action: Delete and recreate the Identity Server configuration or Access Gateway cluster.</p>
10090104 3	The source keystore does not exist. Cannot push keys from a non-existent keystore.	<p>Cause: The source keystore does not exist.</p> <p>Action: Usually the source keystore is a cluster keystore representation. Try deleting and recreating the Identity Server configuration or Access Gateway cluster to ensure those cluster keystore representations get created.</p>
Application		
10090200 1	Error - Exception thrown in eventOccurred of vcdn.application.sc.alert.AlertEventListener	<p>Cause: Cannot post alert to internal subsystem.</p> <p>Action: Non-fatal error. No action required.</p>
10090200 2	Error - Exception thrown in eventOccurred of vcdn.application.sc.alert.AlertEventListener.	<p>Cause: Cannot post alert to internal subsystem.</p> <p>Action: Submit the <code>app_sc.0.log</code> file for resolution.</p>
10090200 3	Error - Exception thrown in logAlert of vcdn.application.sc.alert.AlertLogger.	<p>Cause: Problem occurred update the Identity Server Alert count.</p> <p>Action: Non-fatal error. May be a symptom of a more serious condition. Submit the <code>app_sc.0.log</code> file for resolution.</p>

Event Code	Description	Remedy
10090200 4	Error - Exception thrown in the execute method of vcdn.application.sc.alert.CertUpdateWork.	<p>Cause: Could not update or read the list of trusted server certificates.</p> <p>Action: Be sure the <code>/var/opt/novell/novlwww/devman.cacerts</code> file exists, is a valid Java keystore, and is not corrupted. To check its status, enter the following command:</p> <pre>/opt/novell/java/bin/keytool -v -list -keystore devman.cacerts</pre> <p>Otherwise, be sure the config store is running and functioning properly.</p>
10090200 5	Error - (The specified device) has not been imported. Failed to start device.	<p>Cause: The Identity Server was not properly imported.</p> <p>Action: Go to Access Gateway Server List and click <i>Repair Import</i>. (The repair import functionality works for any server type.) Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090200 6	Error importing device (with the specified ID).	<p>Cause: The Server was not properly imported.</p> <p>Action: Go to Access Gateway Server List and click <i>Repair Import</i>. (The repair import functionality works for any server type.) If this fails, reinstall the server component.</p>
10090200 7	Error - Import failed. Retrying.	<p>Cause: Unable to communicate with the Server being imported.</p> <p>Action: Be sure the firewall is allowing port 1443 traffic. Otherwise allow the system to retry for several minutes. If the server does not appear in the Server List, click <i>Repair Import</i> to resolve the issue. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090200 8	Error auto importing. Retry.	<p>Cause: Unable to communicate with the Server being imported.</p> <p>Action: Be sure the firewall is allowing port 1443 traffic. Otherwise allow the system to retry for several minutes. If the server does not appear in the Server List, click <i>Repair Import</i> to resolve the issue. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>

Event Code	Description	Remedy
10090200 9	Error - Could not create subcontext: cn=(The specified Context)	<p>Cause: Error creating Server object in config store during import.</p> <p>Action: Go to Access Gateway Server List and click <i>Repair Import</i>. (The repair import functionality works for any server type.) Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090201 0	Error - (The given ESP) does not exist!	<p>Cause: There was a error during the Administration Console installation.</p> <p>Action: Reinstall the Administration Console.</p>
100902011	Error - Exception reading (the given ESP)	<p>Cause: The file required during the import process could not be read.</p> <p>Action: Be sure the indicated file can be read by the <code>novlwww</code> user.</p>
10090201 2	Error - Could not import LDIF.	<p>Cause: The error occurred while creating the configuration for the Embedded Service Provider.</p> <p>Action: Go to Access Gateway Server List and click <i>Repair Import</i>. (The repair import functionality works for any server type.) Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090201 3	Error - Could not find (the specified DN)	<p>Cause: Error connecting to the config store while importing the Embedded Service Provider.</p> <p>Action: Go to Access Gateway Server List and click <i>Repair Import</i>. (The repair import functionality works for any server type.) Otherwise, submit the <code>app_sc.0.log</code> file for resolution. You might need to restart the Administration Console.</p>
10090201 4	Error - ESP Configuration was not found, so auto-import failed.	<p>Cause: Could not find the configuration for the imported Embedded Service Provider.</p> <p>Action: Go to Access Gateway Server List and click <i>Repair Import</i>. (The repair import functionality works for any server type.) Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090201 5	Error - Exception thrown in importDevice of vcdn.application.sc.alert.RegisterCommand.	<p>Cause: Error during import of server component.</p> <p>Action: Go to Access Gateway Server List and click <i>Repair Import</i>. (The repair import functionality works for any server type.) Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>

Event Code	Description	Remedy
10090201 6	Error - ImportThread null member vars.	<p>Cause: Internal error occurred during import.</p> <p>Action: Go to Access Gateway Server List and click <i>Repair Import</i>. (The repair import functionality works for any server type.) Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090201 7	Error - Could not connect to eDir for certs.	<p>Cause: Either the primary Administration Console is down (if this is a secondary console), or the config store is down.</p> <p>Action: Be sure the config store is operating properly and that port 554 is not blocked by a firewall.</p>
10090201 8	Error during execution.	<p>Cause: Error executing an external program during import process.</p> <p>Action: Go to Access Gateway Server List and click <i>Repair Import</i>. (The repair import functionality works for any server type.) Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090201 9	Error - Could not get (the given number of) bytes of payload data.	<p>Cause: An error occurred while trying to read data for a command.</p> <p>Action: Ensure the server component is operating properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090202 0	Error - VException thrown while executing command in <code>vcdn.application.sc.alert.AlertCommandHandler</code> .	<p>Cause: Problem executing a command from a server component.</p> <p>Action: Ensure the server component is operating properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090202 1	Error - VCDNException thrown in <code>performConfiguration</code> of <code>vcdn.application.sc.config.AGApplyWork</code>	<p>Cause: Problem occurred while sending configuration to Access Gateway server.</p> <p>Action: Ensure the server component is operating properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090202 2	Error - VCDNException thrown in <code>responseReceived</code> method of <code>vcdn.application.sc.config.AGApplyWork</code>	<p>Cause: Error occurred in processing the response from an Access Gateway server.</p> <p>Action: Ensure the server component is operating properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090202 3	Error - VCDNException thrown in <code>performConfiguration</code> method of <code>vcdn.application.sc.config.AGConfigWork</code>	<p>Cause: Error occurred while sending configuration to Access Gateway server.</p> <p>Action: Ensure the server component is operating properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>

Event Code	Description	Remedy
10090202 4	Error - VCDNException thrown in responseReceived method of vcdn.application.sc.config.AGConfigWork	<p>Cause: Error occurred in processing the response from an Access Gateway server.</p> <p>Action: Ensure the server component is operating properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090202 5	Error - Exception thrown in processAGResponse method of vcdn.application.sc.config.AGConfigWork	<p>Cause: Error occurred in processing the response from an Access Gateway server.</p> <p>Action: Ensure the server component is operating properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090202 6	Error - VCDNException thrown in performConfiguration method of vcdn.application.sc.config.AgentApplyWork	<p>Cause: Error occurred while sending configuration to J2EE Agent server.</p> <p>Action: Ensure the server component is operating properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090202 7	Error - VCDNException thrown in responseReceived method of vcdn.application.sc.config.AgentApplyWork	<p>Cause: Error occurred in processing the response from an J2EE Agent server.</p> <p>Action: Ensure the server component is operating properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090202 8	Error - VCDNException thrown in performConfiguration method of vcdn.application.sc.config.AgentConfigWork	<p>Cause: Error occurred while sending configuration to J2EE Agent server.</p> <p>Action: Ensure the server component is operating properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090202 9	Error - VCDNException thrown in responseReceived method of vcdn.application.sc.config.AgentConfigWork	<p>Cause: Error occurred in processing the response from an J2EE Agent server.</p> <p>Action: Ensure the server component is operating properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090203 0	Error - VCDNException thrown in processAgentResponse method of vcdn.application.sc.config.AgentConfigWork	<p>Cause: Error occurred in processing the response from an J2EE Agent server.</p> <p>Action: Ensure the server component is operating properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090203 1	Error - SchedulerException thrown in configureDeviceNow method of vcdn.application.sc.config.ConfigManager	<p>Cause: Error occurred while scheduling an immediate apply of the current configuration.</p> <p>Action: Submit the <code>app_sc.0.log</code> file for resolution.</p>
10090203 2	Error - Exception thrown in the execute method of vcdn.application.sc.config.ConfigWork	<p>Cause: Error occurred while performing pending actions.</p> <p>Action: Submit the <code>app_sc.0.log</code> file for resolution.</p>

Event Code	Description	Remedy
10090203 3	Error setting LDAP attribute in performPendingActions of vcdn.application.sc.config.ConfigWork	<p>Cause: Pending actions could not be completed because of a problem communicating with the config store.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090203 4	Error invoking method in performPendingActions of vcdn.application.sc.config.ConfigWork	<p>Cause: Problem occurred while invoking a method during a pending action.</p> <p>Action: Submit the <code>app_sc.0.log</code> file for resolution.</p>
10090203 5	Error executing pending action (name) in performPendingActions of vcdn.application.sc.config.ConfigWork	<p>Cause: Problem occurred while displaying a pending dialog message.</p> <p>Action: This is a non-fatal error. If the problem persists, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090203 6	Error - Exception thrown in getConfigXML of vcdn.application.sc.config.ConfigWork	<p>Cause: Error occurred while retrieving XML data from the config store.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090203 7	Error - VException thrown in saveInDB method of vcdn.application.sc.config.ConfigWork	<p>Cause: Error occurred while saving the applied configuration in the config store.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090203 8	Error - VException thrown in configFinished method of vcdn.application.sc.config.DeviceConfigApplyWork	<p>Cause: Error occurred while sending the Audit event for a changed configuration.</p> <p>Action: Ensure the Audit server and the config store are functioning properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090203 9	Error - VException thrown in configFinished method of vcdn.application.sc.config.DeviceConfigWork	<p>Cause: Error occurred while sending the Audit event for a changed configuration.</p> <p>Action: Ensure the Audit server and the config store are functioning properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090204 0	Error - Exception thrown in processConfigDiff method of vcdn.application.sc.config.DeviceGroupConfigWork	<p>Cause: Error occurred while parsing the XML for a group configuration.</p> <p>Action: Error occurred while sending the Audit event for a changed configuration.</p> <p>Action: Submit the <code>app_sc.0.log</code> file for resolution.</p>

Event Code	Description	Remedy
10090204 1	Error - Exception thrown in memberConfigFinished method of vcdn.application.sc.config.DeviceGroupConfigWork	Cause: Error occurred while processing a group member configuration apply response. Action: Ensure the server component is functioning properly. Otherwise, submit the app_sc.0.log file for resolution.
10090204 2	Error - Exception thrown in removePendingFromFailedList method of vcdn.application.sc.config.DeviceGroupConfigWork	Cause: Error occurred while re-applying a server configuration. Action: Submit the app_sc.0.log file for resolution.
10090204 3	Error - SchedulerException thrown in scheduleMultiDeviceWorks method of vcdn.application.sc.config.DeviceGroupConfigWork	Cause: Error occurred while scheduling a group configuration. Action: Submit the app_sc.0.log file for resolution.
10090204 4	Error - Exception thrown in the execute method of vcdn.application.sc.config.DeviceGroupConfigWork	Cause: Error occurred while scheduling a group configuration. Action: Submit the app_sc.0.log file for resolution.
10090204 5	Error - VException thrown in performWork method of vcdn.application.sc.config.MultiDeviceConfigWork	Cause: Error occurred while applying configuration to a group member. Action: Ensure the server component is functioning properly. Otherwise, submit the app_sc.0.log file for resolution.
10090204 6	Error - Exception thrown in performWork method of vcdn.application.sc.config.MultiDeviceConfigWork	Cause: Error occurred while applying configuration to a group member. Action: Ensure the server component is functioning properly. Otherwise, submit the app_sc.0.log file for resolution.
10090204 7	Error - SchedulerException thrown in getDeviceGroupConfigWork method of vcdn.application.sc.config.MultiDeviceConfigWork	Cause: Error occurred while trying to get the scheduled configuration. Action: Ensure the config store is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
10090204 8	Error - VException thrown in configFinished method of vcdn.application.sc.config.MultiDeviceConfigWork	Cause: Error occurred while importing status from a group member. Action: Ensure the config store is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
10090204 9	Error - VCDNException thrown in the execute method of vcdn.application.sc.command.AGCommandWork	Cause: Error occurred while sending a command to an Access Gateway server. Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.

Event Code	Description	Remedy
10090205 0	Error - Exception thrown in the sendCommand method of vcdn.application.sc.command.AGCommandWork	Cause: Error occurred while sending a command to an Access Gateway server. Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
10090205 1	Error - Exception thrown in the processAGResponse method of vcdn.application.sc.command.AGCommandWork	Cause: Error occurred while processing a command response from an Access Gateway server. Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
10090205 2	Error - VCDNException thrown in the execute method of vcdn.application.sc.command.AgentCommandWork	Cause: Error occurred while sending a command to a J2EE Agent server. Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
10090205 3	Error - Exception thrown in the sendCommand method of vcdn.application.sc.command.AgentCommandWork	Cause: Error occurred while sending a command to a J2EE Agent server. Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
10090205 4	Error - Exception thrown in the processAgentResponse method of vcdn.application.sc.command.AgentCommandWork	Cause: Error occurred while processing a command response from a J2EE Agent server. Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
10090205 5	Error - IOException thrown in the addCommand method of vcdn.application.sc.command.CertCommand	Cause: Error generating certificate command. Action: Submit the app_sc.0.log file for resolution.
10090205 6	Error - IOException thrown in the generateCmd method of vcdn.application.sc.command.CertCommand	Cause: Error generating certificate command. Action: Submit the app_sc.0.log file for resolution.
10090205 7	Error - IOException thrown in the setCertChainData method of vcdn.application.sc.command.CertCommand	Cause: Error generating chained certificate command. Action: Submit the app_sc.0.log file for resolution.

Event Code	Description	Remedy
10090205 8	Error - VCDNException thrown in the execute method of vcdn.application.sc.command.IDPCommandWork	Cause: Error occurred while sending a command to an Identity Server ESP server. Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
10090205 9	Error - VCDNException thrown in the sendCommand method of vcdn.application.sc.command.IDPCommandWork	Cause: Error occurred while sending a command to an Identity Server or ESP server. Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
10090206 0	Error - NamingException thrown in the updateNIDPCommandStatus method of vcdn.application.sc.command.IDPCommandWork	Cause: Error occurred while processing a command response from an Identity Server or ESP. Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
01009026 1	Error - VException thrown in the updateNIDPCommandStatus method of vcdn.application.sc.command.IDPCommandWork	Cause: Error occurred while processing a command response from an Identity Server or ESP. Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
10090206 2	Error - Exception thrown in the processIDPResponse method of vcdn.application.sc.command.IDPCommandWork	Cause: Error occurred while processing a command response from an Identity Server or ESP. Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
10090206 3	Error - VCDNException thrown in the execute method of vcdn.application.sc.command.JCCCommandWork	Cause: Error occurred while executing a server command. Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
10090206 4	Error - Exception thrown in the sendCommand method of vcdn.application.sc.command.JCCCommandWork	Cause: Error occurred while sending a server command. Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
10090206 5	Error - Exception thrown in the processResponse method of vcdn.application.sc.command.JCCCommandWork	Cause: Error occurred while processing a response from a server command. Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.

Event Code	Description	Remedy
10090206 6	Error - VCDNException thrown in the execute method of vcdn.application.sc.command.SSLVPNCommandWork	Cause: Error occurred while sending an SSLVPN server command. Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
10090206 7	Error - Exception thrown in the sendCommand method of vcdn.application.sc.command.SSLVPNCommandWork	Cause: Error occurred while sending an SSLVPN server command. Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
10090206 8	Error - Exception thrown in the processSSLVPNResponse method of vcdn.application.sc.command.SSLVPNCommandWork	Cause: Error occurred while processing a command response from an SSLVPN Server. Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
30090206 9	Exception changing factory LocalAddress.	Cause: Error occurred while changing factory XML during configuration import. Action: Submit the app_sc.0.log file for resolution.
10090207 0	Error - ConverterException thrown in the getCurrentDeviceXML method of vcdn.application.sc.core.AGDevice	Cause: Error occurred during translation of NetWare Access Gateway configuration. Action: Submit the app_sc.0.log file for resolution.
10090207 1	Error - NamingException thrown in the importDevice method of vcdn.application.sc.core.AGDevice	Cause: Config store could not be accessed or an internal error occurred. Action: Ensure the config store is functioning properly. Otherwise, submit the app_sc.0.log file for resolution.
10090207 2	Error - VException thrown in the importDevice method of vcdn.application.sc.core.AGDevice	Cause: Config store could not be accessed or an internal error occurred. Action: Ensure the config store is functioning properly. Otherwise, submit the app_sc.0.log file for resolution.
10090207 3	Error - Exception thrown in the importDevice method of vcdn.application.sc.core.AGDevice	Cause: Config store could not be accessed or an internal error occurred. Action: Ensure the config store is functioning properly. Otherwise, submit the app_sc.0.log file for resolution.

Event Code	Description	Remedy
10090207 4	Error - NamingException thrown in the vcdn.application.sc.core.AuditManager constructor.	<p>Cause: Config store could not be accessed or an internal error occurred.</p> <p>Action: Ensure the config store is functioning properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090207 5	Error - JDOMException thrown in the processDocument method of vcdn.application.sc.core.AuditManager	<p>Cause: Audit XML data could not be parsed.</p> <p>Action: Submit the <code>app_sc.0.log</code> file for resolution.</p>
10090207 6	Error - Exception thrown in the processDocument method of vcdn.application.sc.core.AuditManager	<p>Cause: Invalid data format.</p> <p>Action: Attempt the operation again. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090207 7	Error - Exception thrown in the setDefaultServer method of vcdn.application.sc.core.AuditManager	<p>Cause: Config store could not be accessed or an internal error occurred.</p> <p>Action: Ensure the config store is functioning properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090207 8	Error - VException thrown in the writeConfig method of vcdn.application.sc.core.AuditManager	<p>Cause: Config store could not be accessed or an internal error occurred.</p> <p>Action: Ensure the config store is functioning properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090207 9	Error - NamingException thrown in the writeConfig method of vcdn.application.sc.core.AuditManager	<p>Cause: Config store could not be accessed or an internal error occurred.</p> <p>Action: Ensure the config store is functioning properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090208 0	Error - Exception thrown in the writeConfig method of vcdn.application.sc.core.AuditManager	<p>Cause: Config store could not be accessed or an internal error occurred.</p> <p>Action: Ensure the config store is functioning properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090208 1	Error - SException thrown in the getIDPConfigObject method of vcdn.application.sc.core.AuditManager	<p>Cause: Config store could not be accessed or an internal error occurred.</p> <p>Action: Ensure the config store is functioning properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090208 2	Error - NamingException thrown in the getIDPConfigObject method of vcdn.application.sc.core.AuditManager	<p>Cause: Config store could not be accessed or an internal error occurred.</p> <p>Action: Ensure the config store is functioning properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>

Event Code	Description	Remedy
10090208 3	Error - Exception thrown in the getIDPConfigObject method of vcdn.application.sc.core.AuditManager	Cause: Config store could not be accessed or an internal error occurred. Action: Ensure the config store is functioning properly. Otherwise, submit the app_sc.0.log file for resolution.
10090208 4	Error - NullPointerException thrown in the logEvent method of vcdn.application.sc.core.AuditManager	Cause: Error logging Novell Audit event. Action: Ensure the Novell Audit server is functioning properly. Otherwise, submit the app_sc.0.log file for resolution.
10090208 5	Error - Exception thrown in the createElement method of vcdn.application.sc.core.DeviceConfig	Cause: Internal XML error. Action: Submit the app_sc.0.log file for resolution.
10090208 6	Error - Exception thrown in the setLastModified method of vcdn.application.sc.core.DeviceConfig	Cause: Internal XML error. Action: Submit the app_sc.0.log file for resolution.
30090208 7	Warning - Exception thrown in the getLastScheduledWorkID method of vcdn.application.sc.core.DeviceGroupManager	Cause: The last executed command status ID could not be read. Action: Non-fatal error.
10090208 8	Error - Could not get version from device. Make sure it is running properly.	Cause: Could not get version from device. Action: Make sure the server component is running properly, then click <i>Repair Import</i> to resolve the issue. Otherwise, submit the app_sc.0.log file for resolution.
10090208 9	Error - NamingException thrown in the importDevice method of vcdn.application.sc.core.DeviceManager	Cause: Error importing device. Action: Make sure the server component is running properly, then click <i>Repair Import</i> to resolve the issue. Otherwise, submit the app_sc.0.log file for resolution.
10090209 0	Error - VException thrown in the importDevice method of vcdn.application.sc.core.DeviceManager	Cause: Error importing device. Action: Make sure the server component is running properly, then click <i>Repair Import</i> to resolve the issue. Otherwise, submit the app_sc.0.log file for resolution.
10090209 1	Error - InvocationTargetException thrown in the importDevice method of vcdn.application.sc.core.DeviceManager	Cause: Error importing device. Action: Make sure the server component is running properly, then click <i>Repair Import</i> to resolve the issue. Otherwise, submit the app_sc.0.log file for resolution.

Event Code	Description	Remedy
10090209 2	Error - Exception thrown in the importDevice method of vcdn.application.sc.core.DeviceManager	<p>Cause: Error importing device.</p> <p>Action: Make sure the server component is running properly, then click <i>Repair Import</i> to resolve the issue. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090209 3	Error - Could not find esp cfg SCC to remove in cluster container.	<p>Cause: Error deleting improperly imported server.</p> <p>Action: Non-fatal error.</p>
10090209 4	Error deleting the trusted IDP entry for ESP.	<p>Cause: Error accessing config store.</p> <p>Action: Ensure the config store is functioning properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090209 5	Error - NamingException thrown in the setHealthCheck method of vcdn.application.sc.core.DeviceManager	<p>Cause: Error saving health status in config store.</p> <p>Action: Ensure the config store is functioning properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090209 6	Error - Could not find the DN specified.	<p>Cause: Error saving health status in config store.</p> <p>Action: Ensure the server component imported correctly and the config store is functioning properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090209 7	Error - Exception thrown in the deleteDevice method of vcdn.application.sc.core.DeviceManager	<p>Cause: Error occurred while deleting the server objects.</p> <p>Action: Ensure the config store is functioning properly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090209 8	Error - Exception thrown in the setHealthCheck method of vcdn.application.sc.core.DeviceManager	<p>Cause: Error updating the version following an upgrade of a server component.</p> <p>Action: Allow the operation to try again. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
30090209 9	Warning - Exception thrown in the getLastScheduledWorkID method of vcdn.application.sc.core.DeviceManager	<p>Cause: The last executed command status ID could not be read.</p> <p>Action: Non-fatal error.</p>
30090210 0	Device is not imported.	<p>Cause: Server component is sending health to Administration console that does not recognize the server.</p> <p>Action: Click <i>Repair Import</i> to resolve the issue. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>

Event Code	Description	Remedy
30090210 1	Identity configuration not found for device.	<p>Cause: Identity server configuration not found in config store.</p> <p>Action: Non-fatal error.</p>
10090210 2	Error - Exception thrown in the createCertEntry method of vcdn.application.sc.core.KeyManager	<p>Cause: The config store is not reachable or the user doesn't have rights to modify the config store</p> <p>Action: Verify the config store is up and that the user has rights to create objects in the following container: ou=KeyContainer, ou=Partition, ou=PartitionsContainer, ou=VCDN_root, ou=accessManagerContainer, o=novell</p>
10090210 3	Error - Exception thrown in the deleteCertEntry method of vcdn.application.sc.core.KeyManager	<p>Cause: The config store is not reachable or the user doesn't have rights to modify the config store</p> <p>Action: Verify the config store is up and that the user has rights to delete objects in the following container: ou=KeyContainer, ou=Partition, ou=PartitionsContainer, ou=VCDN_root, ou=accessManagerContainer, o=novell</p>
10090210 4	Error - Exception thrown in the modifyCertEntryXml method of vcdn.application.sc.core.KeyManager	<p>Cause: The config store is not reachable or the user doesn't have rights to modify the config store</p> <p>Action: Verify the config store is up and that the user has rights to modify objects in the following container: ou=KeyContainer, ou=Partition, ou=PartitionsContainer, ou=VCDN_root, ou=accessManagerContainer, o=novell</p>
10090210 5	Error - Exception thrown in the createKeyStoreEntry method of vcdn.application.sc.core.KeyManager	<p>Cause: The config store is not reachable or the user doesn't have rights to modify the config store</p> <p>Action: Verify the config store is up and that the user has rights to create objects in the following container: ou=KeyContainer, ou=Partition, ou=PartitionsContainer, ou=VCDN_root, ou=accessManagerContainer, o=novell</p>

Event Code	Description	Remedy
10090210 6	Error - Exception thrown in the deleteKeyStoreEntry method of vcdn.application.sc.core.KeyManager	<p>Cause: The config store is not reachable or the user doesn't have rights to modify the config store</p> <p>Action: Verify the config store is up and that the user has rights to delete objects in the following container: ou=KeyContainer,ou=Partition,ou=PartitionsContainer,ou=VCDN_root,ou=accessManagerContainer,o=novell</p>
10090210 7	Error - Exception thrown in the modifyKeyStoreEntryXml method of vcdn.application.sc.core.KeyManager	<p>Cause: The config store is not reachable or the user doesn't have rights to modify the config store</p> <p>Action: Verify the config store is up and that the user has rights to modify objects in the following container: ou=KeyContainer,ou=Partition,ou=PartitionsContainer,ou=VCDN_root,ou=accessManagerContainer,o=novell</p>
10090210 8	Error - Exception thrown in the createElement method of vcdn.application.sc.core.PolicyConfig	<p>Cause: Error creating an element in the specified XML document.</p> <p>Action: Submit the app_sc.0.log file for resolution.</p>
10090210 9	Error - Exception thrown in the setLastModified method of vcdn.application.sc.core.PolicyConfig	<p>Cause: Error setting an attribute value on modified elements.</p> <p>Action: Submit the app_sc.0.log file for resolution.</p>
100902110	Error - NamingException thrown in the importDevice method of vcdn.application.sc.core.SSLVPNDevice	<p>Cause: Error importing device.</p> <p>Action: Click <i>Repair Import</i> to resolve the issue. Otherwise, submit the app_sc.0.log file for resolution.</p>
100902111	Error - VException thrown in the importDevice method of vcdn.application.sc.core.SSLVPNDevice	<p>Cause: Error importing device.</p> <p>Action: Click <i>Repair Import</i> to resolve the issue. Otherwise, submit the app_sc.0.log file for resolution.</p>
100902112	Error - Exception thrown in the importDevice method of vcdn.application.sc.core.SSLVPNDevice	<p>Cause: Error importing device.</p> <p>Action: Click <i>Repair Import</i> to resolve the issue. Otherwise, submit the app_sc.0.log file for resolution.</p>

Event Code	Description	Remedy
100902113	Error - Exception thrown in the sendData method of vcdn.application.sc.core.work.DeleteDeviceWork	<p>Cause: Error communicating with component.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.</p>
100902114	Error - Exception thrown in the execute method of vcdn.application.sc.core.work.ReimportDeviceWork	<p>Cause: Error occurred while executing a server command.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.</p>
100902115	Error - Exception thrown in the getHealth method of vcdn.application.sc.health.HealthCheck	<p>Cause: Error occurred while executing a server command.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.</p>
100902116	Error - Inner Exception thrown in the execute method of vcdn.application.sc.health.HealthCheck	<p>Cause: Error occurred while executing a server command.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.</p>
100902117	Error - Outer Exception thrown in the execute method of vcdn.application.sc.health.HealthCheck	<p>Cause: Error occurred while executing a server command.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.</p>
100902118	Error - VException thrown in the eventOccurred method of vcdn.application.sc.health.HealthEventListener	<p>Cause: Error occurred while receiving/logging a health event.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.</p>
100902119	Error getting Health Module or Service	<p>Cause: Error occurred while executing a server command.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.</p>
100902120	Error - Exception thrown in the execute method of vcdn.application.sc.health.HealthUpdateWork	<p>Cause: Error occurred while executing a server command.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.</p>

Platform

Event Code	Description	Remedy
10090300 1	Error - Unable to find a trusted client certificate.	<p>Cause: There was a problem during the import of the device.</p> <p>Action: Consult the documentation to re-import the device into the Administration Console.</p>
10090300 2	Error building delayed response.	<p>Cause: Error occurred while processing a request.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090300 3	Error setting return code in HttpServletResponse.	<p>Cause: Error occurred while processing a request.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090300 4	Error - DelayedResponseListener thread failed to start.	<p>Cause: Error occurred while processing a delayed response.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090300 5	Error in the ResponseHandler thread of the DelayedResponseListener.	<p>Cause: Error occurred while processing a response.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090300 6	Error creating XML Element in ResponseBuilder.	<p>Cause: Error occurred while editing XML.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090300 7	Error waiting on mutex in RequestDispatcher.	<p>Cause: Error occurred while getting responses.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090300 8	Error notifying mutex in RequestDispatcher.	<p>Cause: Error occurred while receiving a response.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>

Event Code	Description	Remedy
100903009	Error receiving in SendInternal of VConnection.	<p>Cause: Error occurred while receiving an internal response.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
100903010	Error getting response code in VConnection.	<p>Cause: Error occurred while getting the code.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
100903011	Error in stopScheduledResponses of VConnection.	<p>Cause: Error occurred while attempting to stop scheduled responses.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
100903012	Error in ConsumeData of VConnection.	<p>Cause: Error occurred while reading data.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
100903013	Error in sendData of VConnection.	<p>Cause: Error occurred while sending data.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
100903014	Error in getHeaders of VConnection.	<p>Cause: Error occurred while getting headers.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
100903015	Error in receive of VConnection.	<p>Cause: Error occurred while receiving a response.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
Web UI		
100904001	Error reading manager data in UIManager.	<p>Cause: Error occurred while reading data.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
100904002	Error during auto authentication in WebApplicaitonFilter.	<p>Cause: Error occurred while authenticating.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>

Event Code	Description	Remedy
10090400 3	Error - Exception thrown in doFilter of WebApplicationFilter.	<p>Cause: Error getting panel data.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090400 4	Error - Exception thrown in logout of WebApplicationFilter.	<p>Cause: Error occurred while logging out.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090400 5	Error - VException thrown in getUserInfo of WebManager.	<p>Cause: Error occurred while getting user information.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090400 6	Error - Exception thrown in getDeviceInfo of WebManager.	<p>Cause: Error occurred while getting device information.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090400 7	Error - Exception thrown in getPolicyInfo of WebManager.	<p>Cause: Error occurred while getting policy information.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090400 8	Error - Exception thrown in getTypeSpecificationInfo of WebManager.	<p>Cause: Error occurred while getting policy type specification information.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090400 9	Error - Exception thrown in getDeviceConfig of WebManager.	<p>Cause: Error occurred while getting device configuration.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090401 0	Error - Exception thrown in getPolicyConfig of WebManager.	<p>Cause: Error occurred while getting device configuration.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
100904011	Error - Exception thrown in getTypeSpecificationConfig of WebManager.	<p>Cause: Error occurred while getting policy type specification configuration.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>

Event Code	Description	Remedy
10090401 2	Error - Exception thrown in parameterMapToString of WebManager.	<p>Cause: Error occurred while getting parameter information.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090401 3	Error while logging out user {0}.	<p>Cause: Error occurred while logging out NDS user object.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090401 4	Error - Exception thrown in getSelectionCriteria of WebPanel.	<p>Cause: Error occurred while getting selection criteria.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090401 5	Error - Exception thrown in getPanelVersion of WebPanel.	<p>Cause: Error occurred while getting panel version.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090401 6	Error - Group Config failed.	<p>Cause: Error occurred while applying group configuration.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090401 7	Error - Schedule Group Config failed.	<p>Cause: Error occurred while scheduling group configuration.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090401 8	Error - Update XML and Device Config failed.	<p>Cause: Error occurred while updating configuration.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090401 9	Error - Unlock Config failed.	<p>Cause: Error occurred while unlocking the configuration.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>

Event Code	Description	Remedy
10090402 0	Error - Exception thrown in do_cancelPendingConfig of ConfigWorkDispatcher.	<p>Cause: Error occurred while canceling a pending configuration.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.</p>
10090402 1	Error - Exception thrown in do_cancelPendingConfig of ConfigWorkDispatcher.	<p>Cause: Error occurred while canceling a pending configuration.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.log file for resolution.</p>
10090402 2	Error - Exception thrown in do_reapplyPendingConfig of ConfigWorkDispatcher.	<p>Cause: Error occurred while reapplying a pending configuration.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.</p>
10090402 3	Error - Exception thrown in do_deviceConfig of ConfigWorkDispatcher.	<p>Cause: Error occurred while applying configuration.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.</p>
10090402 4	Error - Exception thrown in do_scheduleDeviceConfig of ConfigWorkDispatcher.	<p>Cause: Error occurred while scheduling configuration.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.</p>
20090402 5	Error - XML VALIDATION FAILED. PLEASE CHECK APP_SC LOG.	<p>Cause: XML created by GUI does not match the XML schema and fails validation.</p> <p>Action: Cancel the changes that were made and try again. In any case, submit the app_sc.0.log file for resolution.</p>
10090402 6	Error applying settings in ConfigXmlUpdateDispatcher.	<p>Cause: Error occurred while applying configuration.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.</p>
10090402 7	Error - Exception thrown in do_save of ConfigXmlUpdateDispatcher.	<p>Cause: Error occurred while saving configuration.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.</p>

Event Code	Description	Remedy
10090402 8	Error - Exception thrown in do_cancel of ConfigXmlUpdateDispatcher.	<p>Cause: Error occurred while canceling configuration changes.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090402 9	Error - Exception thrown in do_refreshConfig of ConfigXmlUpdateDispatcher.	<p>Cause: Error occurred while refreshing configuration manager panel.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090403 0	Error - Exception thrown in setLastModParams of ConfigXmlUpdateDispatcher.	<p>Cause: Error occurred while setting an XML attribute.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090403 1	Error - IOException thrown in getXPathMap of ConfigXmlUpdateDispatcher.	<p>Cause: Error occurred while xpath mapping on the current panel.</p> <p>Action: Ensure the server component is functioning correctly. Cancel changes on the current panel, return, and try again. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090403 2	Error decoding: {0}.	<p>Cause: Error occurred while xpath mapping on the current panel.</p> <p>Action: Ensure the server component is functioning correctly. Cancel changes on the current panel, return, and try again. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090403 3	Error - Exception thrown in processRequest of ExceptionDispatcher.	<p>Cause: Error occurred while processing request.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090403 4	Error - Exception thrown in the service method of ServletDispatcher.	<p>Cause: Error occurred while processing request.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090403 5	Error - Exception thrown in ServletDispatcher.	<p>Cause: Error occurred while inserting dispatchers.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>

Event Code	Description	Remedy
10090403 6	Error - Exception thrown in processRequest of DeviceCommandHandler.	<p>Cause: Error occurred while processing request.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090403 7	Error - VException thrown in setNIDPCommandState of DeviceCommandHandler.	<p>Cause: Error occurred while accessing data store.</p> <p>Action: Ensure the data store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090403 8	Error - NamingException thrown in setNIDPCommandState of DeviceCommandHandler.	<p>Cause: Error occurred while accessing data store.</p> <p>Action: Ensure the data store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090403 9	Error - Could not find signing keystore for {0}.	<p>Cause: An error occurred during the import of the device.</p> <p>Action: Consult the documentation and re-import the device into the Administration Console.</p>
10090404 0	Error - Could not find encryption keystore for {0}.	<p>Cause: An error occurred during the import of the device.</p> <p>Action: Consult the documentation and re-import the device into the Administration Console.</p>
10090404 1	Error - Could not find connector keystore for {0}.	<p>Cause: An error occurred during the import of the device.</p> <p>Action: Consult the documentation and re-import the device into the Administration Console.</p>
10090404 2	Error - Could not find trust keystore for {0}.	<p>Cause: An error occurred during the import of the device.</p> <p>Action: Consult the documentation and re-import the device into the Administration Console.</p>
10090404 3	Error - Could not find OCSP trust keystore for {0}.	<p>Cause: An error occurred during the import of the device.</p> <p>Action: Consult the documentation and re-import the device into the Administration Console.</p>

Event Code	Description	Remedy
10090404 4	Error - No keys were assigned to keystore: {0}.	<p>Cause: The keystore does not have any certificates in it. This may or may not be a bad condition. For instance, the OCSP trust store can be empty and that should not cause a problem. The signing, encryption, connector, provider, and consumer keystores should have one certificate in them. If it is empty, either the device import failed or the user manually removed the certificate from the keystore.</p> <p>Action: Check the keystore using the UI. If the keystore shows that it has a certificate, then the device import probably failed. Consult the documentation and re-import the device and also try deleting and re-creating the NIDP configuration. Also, try replacing the certificate in the keystore through the UI.</p>
10090404 5	Error - Exception thrown in processRequest of UpgradeDeviceGroupHandler.	<p>Cause: Error occurred while processing request.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090404 6	Error - Exception thrown in processRequest of UpgradeDeviceHandler.	<p>Cause: Error occurred while processing request.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090404 7	Error - Exception thrown in getUpgradeInfo of UpgradeDeviceHandler.	<p>Cause: Error occurred while getting update information.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
Application Handlers		
10090500 1	Error during repair import.	<p>Cause: Error occurred while attempting to repair import.</p> <p>Action: Delete the server from the list and reinstall. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090500 2	Error - Failed to remove server.	<p>Cause: Error occurred while attempting to remove server.</p> <p>Action: Submit the <code>app_sc.0.log</code> file for resolution.</p>

Event Code	Description	Remedy
10090500 3	Error setting device groups.	<p>Cause: Error occurred while attempting to mark a server as a member of a group.</p> <p>Action: Delete the server from the group and retry or delete the group and recreate. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090500 4	Error setting device admin.	<p>Cause: Error occurred while attempting to give an Administrator access to a server.</p> <p>Action: Submit the <code>app_sc.0.log</code> file for resolution.</p>
10090500 5	Error - Exception thrown while importing appliance.	<p>Cause: Error occurred while importing a server.</p> <p>Action: Delete the server from the list and reinstall. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090500 6	Error getting health info.	<p>Cause: Error occurred while getting health information for a server.</p> <p>Action: Ensure the server component and the config store are functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090500 7	Error canceling appliance creation.	<p>Cause: Internal error.</p> <p>Action: Submit the <code>app_sc.0.log</code> file for resolution.</p>
10090500 8	Error creating new CDN.	<p>Cause: Internal error.</p> <p>Action: Submit the <code>app_sc.0.log</code> file for resolution.</p>
10090500 9	Error removing CDN.	<p>Cause: Internal error.</p> <p>Action: Submit the <code>app_sc.0.log</code> file for resolution.</p>
10090501 0	Error creating new Admin.	<p>Cause: Internal error.</p> <p>Action: Submit the <code>app_sc.0.log</code> file for resolution.</p>
100905011	Error while changing the cached device port.	<p>Cause: Internal error while processing request.</p> <p>Action: Ensure the Management IP Address is correct or edit as needed. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>

Event Code	Description	Remedy
10090501 2	Error while changing the cached device password.	<p>Cause: Internal error while processing request.</p> <p>Action: Ensure the Management Password is correct or edit as needed. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090501 3	Error - Exception thrown while processing request in EditApplianceHandler	<p>Cause: Internal error while processing request.</p> <p>Action: Ensure all values on the Server Details Edit page are correct and edit as needed. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090501 4	Error - Exception thrown while modifying device handler in EditDeviceHandler.	<p>Cause: Error occurred while processing a request.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090501 5	Error - Exception thrown while changing password in EditDeviceHandler.	<p>Cause: Error occurred while processing a request.</p> <p>Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
20090501 6	Error - Exception thrown while editing CDN in EditPublisherHandler.	<p>Cause: Internal error.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
20090501 7	Error - Exception thrown while updating CDN in EditPublisherHandler.	<p>Cause: Internal error.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
20090501 8	Error - Failed to update the device groups for this user.	<p>Cause: Internal error.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
20090501 9	Error - Failed to update the devices for this user.	<p>Cause: Internal error.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
20090502 0	Error - Failed to update the cdns for this user.	<p>Cause: Internal error.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>

Event Code	Description	Remedy
20090502 1	Error - Failed to update user data.	Cause: Internal error. Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.
10090502 2	Error processing client certs in GenericPipeHandler.	Cause: Internal error while processing request. Action: Ensure the server component is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.
20090502 3	Error accessing XML data item in generic pipe: {0}	Cause: Internal error. Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.
20090502 4	Error parsing XML data item in generic pipe: {0}	Cause: Internal error. Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.
20090502 5	Error processing XML data item in generic pipe: {0}	Cause: Internal error. Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.
10090502 6	Error - Exception thrown in processRequest of GenericPipeHandler: {0}	Cause: Internal error. Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.
10090502 7	Error occurred while creating group {0} : {1}.	Cause: Internal error. Action: Ensure the config store is functioning correctly or delete the group and recreate it. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.
10090502 8	Error getting device manager in doGroupRemove of GroupCreateHandler.	Cause: Internal error. Action: Ensure the config store is functioning correctly or delete the group again. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.
10090502 9	Error occurred while removing group {0} : {1}.	Cause: Internal error. Action: Ensure the config store is functioning correctly or delete the group again. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.

Event Code	Description	Remedy
10090503 0	Error occurred while getting device manager in doGroupAlertStatus of GroupCreateHandler.	<p>Cause: Unable to get alert status for the group.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090503 1	Error occurred while setting alert status for group {0} : {1}.	<p>Cause: Unable to set alert status for the group.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090503 2	Error occurred while updating group {0} : {1}.	<p>Cause: Unable to make updates to the group.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090503 3	Error occurred while removing devices from group {0} : {1}.	<p>Cause: Unable to remove servers from the group.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090503 4	Error - Naming Exception thrown in removeDeviceFromCluster of GroupCreateHandler.	<p>Cause: Unable to remove servers from the cluster.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090503 5	Error - Exception thrown in removeDeviceFromCluster of GroupCreateHandler.	<p>Cause: Error occurred while removing servers from the cluster.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090503 6	Error - Exception thrown in removeDeviceFromCluster of GroupCreateHandler.	<p>Cause: Error occurred while removing servers from the cluster.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090503 7	Error occurred while adding devices to group {0} : {1}.	<p>Cause: Error occurred while adding servers to the group.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>

Event Code	Description	Remedy
10090503 8	Error - Naming Exception thrown in addDeviceToCluster of GroupCreateHandler.	<p>Cause: Error occurred while adding servers to the cluster.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090503 9	Error - Exception thrown in addDeviceToCluster of GroupCreateHandler.	<p>Cause: Error occurred while adding servers to the cluster.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090504 0	Error - Exception thrown in addDeviceToCluster of GroupCreateHandler.	<p>Cause: Error occurred while adding servers to the cluster.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090504 1	Error occurred while adding devices to group {0} : {1}.	<p>Cause: Error occurred while adding servers to the cluster.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090504 2	Error - VCDNException thrown in processRequest of SyncHandler.	<p>Cause: Internal error.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090504 3	Error - Exception thrown in processRequest of SyncHandler.	<p>Cause: Internal error.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090504 4	Error - Exception thrown in modifySystemSync of SyncHandler.	<p>Cause: Internal error.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090504 5	Error - WSEException thrown in isAssignedUser of GroupCreateBean.	<p>Cause: Internal error.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090504 6	Error - WSEException thrown in isAssignedDevice of GroupCreateBean.	<p>Cause: Internal error.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>

Event Code	Description	Remedy
10090504 7	Error - WSEException thrown in getApplianceByUrl of GroupCreateBean.	Cause: Internal error. Action: Ensure the config store is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
10090504 8	Error - WSEException thrown in generateMembershipList of GroupCreateBean.	Cause: Internal error. Action: Ensure the config store is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
10090504 9	Error - WSEException thrown in getAppGroupByName of GroupCreateBean.	Cause: Internal error. Action: Ensure the config store is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
10090505 0	Error - WSEException thrown in getDescForThisGroup of GroupCreateBean.	Cause: Internal error. Action: Ensure the config store is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
10090505 1	Error - Exception thrown in getDescForThisGroup of GroupCreateBean.	Cause: Internal error. Action: Ensure the config store is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
10090505 2	Error - WSEException thrown in getLastModifiedDate of GroupCreateBean.	Cause: Internal error. Action: Ensure the config store is functioning correctly. Otherwise, submit the app_sc.0.log file for resolution.
10090505 3	Error - Get appliance groups failed in GroupCreateBean.	Cause: Internal error. Action: Ensure the config store is functioning correctly or delete group and recreate it. Otherwise, submit the app_sc.0.log file for resolution.
10090505 4	Error - WSEException thrown in hasAMembershipIn of GroupCreateBean.	Cause: Internal error. Action: Ensure the config store is functioning correctly or delete group and recreate it. Otherwise, submit the app_sc.0.log file for resolution.
10090505 5	Error - Get appliances failed in GroupCreateBean.	Cause: Internal error. Action: Ensure the config store is functioning correctly or delete group and recreate it. Otherwise, submit the app_sc.0.log file for resolution.

Event Code	Description	Remedy
10090505 6	Error - Get admins failed in GroupCreateBean.	Cause: Internal error. Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.
10090505 7	Error - WSEException thrown in getPerDeviceProperties of GroupCreateBean.	Cause: Internal error. Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.
10090505 8	Error - WSEException thrown in getPerUserProperties of GroupCreateBean.	Cause: Internal error. Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.
10090505 9	Error - WSEException thrown in getDeviceGroupProperties of GroupCreateBean.	Cause: Internal error. Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.
10090506 0	Error - NamingException thrown in setDeviceClusterConfig of GroupCreateBean.	Cause: Internal error. Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.
10090506 1	Error - Exception thrown in setDeviceClusterConfig of GroupCreateBean.	Cause: Internal error. Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.
10090506 2	Error - VException thrown in clusterServers of GroupCreateBean.	Cause: Internal error. Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.
10090506 3	Error - Exception thrown in clusterServers of GroupCreateBean.	Cause: Internal error. Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.
10090506 4	Error - VException thrown in getAdminList of GroupCreateBean.	Cause: Internal error. Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.
10090506 5	Error - Exception thrown in callRestartESP of SPConfigHandler.	Cause: Error occurred while restarting Embedded Service Provider. Action: Ensure the server component and ESP are functioning correctly or restart ESP again. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.

Event Code	Description	Remedy
10090506 6	Error restarting {0}.	<p>Cause: Error occurred while restarting Embedded Service Provider.</p> <p>Action: Ensure the server component and ESP are functioning correctly or restart ESP again. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090506 7	Error - Could not lookup {0}.	<p>Cause: Error occurred while looking up DN in config store.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090506 8	{0}.	<p>Cause: Error occurred while accessing config store.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090506 9	Error - Exception thrown in createTrustedIDP of SPConfigHandler.	<p>Cause: Error occurred while accessing config store.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090507 0	Error getting the esp trusted IDP.	<p>Cause: Error occurred while accessing config store.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090507 1	espTrustAccessDN not set.	<p>Cause: Error occurred while accessing config store.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090507 2	Error deleting trusted IDP config.	<p>Cause: Error occurred while accessing config store.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090507 3	Error - VCDNException thrown in processRequest of ScheduleHandler.	<p>Cause: Error occurred while processing request.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>

Event Code	Description	Remedy
10090507 4	Error - Exception thrown in processRequest of SchedulerHandler.	<p>Cause: Error occurred while processing request.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090507 5	Error - Exception thrown in setEnable of SchedulerHandler.	<p>Cause: Error occurred while processing request.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090507 6	Error - Exception thrown while removing scheduled work in SchedulerHandler.	<p>Cause: Error occurred while processing request.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090507 7	Error - Exception thrown while releasing config lock in SchedulerHandler.	<p>Cause: Error occurred while unlocking configuration.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090507 8	Error - Exception thrown in modify method of SchedulerHandler.	<p>Cause: Error occurred while modifying scheduled work.</p> <p>Action: Ensure the config store is functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090507 9	Error - Exception thrown in executeNow method of SchedulerHandler.	<p>Cause: Error occurred while scheduling work.</p> <p>Action: Ensure the config store and server component are functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090508 0	Error - ParamNotFoundException thrown in createSchedule method of SchedulerHandler.	<p>Cause: Error occurred while scheduling work.</p> <p>Action: Ensure the config store and server component are functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090508 1	Error - Can not forward the request to return page. Nothing can be done.	<p>Cause: Internal error.</p> <p>Action: Ensure server component is functioning correctly and attempt to navigate to desired panels. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>

Event Code	Description	Remedy
10090508 2	Error - Exception thrown in create method of ScheduleHandler.	<p>Cause: Error occurred while scheduling work.</p> <p>Action: Ensure the config store and server component are functioning correctly. Otherwise, submit the <code>app_sc.0.log</code> file for resolution.</p>
10090508 3	Config store Error	<p>Cause: The connection to the config store is experiencing problems.</p> <p>Action: To diagnose time synchronization issues with multiple Administration Consoles, run the following command on the primary server command-line:</p> <pre>/opt/novell/eDirectory/bin/ndsrepair -T</pre> <p>This will check the overall time synchronization status. If the time is not in sync, then you might want to consider configuring NTP on each server.</p>

1.1.8 Backup and Restore (010)

Backup and restore are invoked by script files:

- ◆ `defbkparm.sh`: Created by install. This has the default values for the scripts.
- ◆ `getparams.sh`: Prompts administrator for information needed to do the backup or restore operation.
- ◆ `ambkup.sh`: Script to run to perform a backup.
- ◆ `amrestore.sh`: Script to run to perform a restore.

Other programs used by backup and restore:

- ◆ `ICE`: This is the Novell eDirectory utility to import and export LDIF file in and out of eDirectory.
- ◆ `ldifReverse`: This is a program that reverses the order of the records in the LDIF file exported from eDirectory. Reversing the order of records allows the LDIF file to be imported without errors.
- ◆ `certtool.jar`: This is a eDirectory certificate utility that backs up and restores the CA key, server keys, and trusted roots to a zip file.

Component 010

- ◆ Sub group 01: Backup
- ◆ Sub group 02: Restore
- ◆ Sub group 03: `certtool` (certificate backup and restore)

Messages are logged to the `ambkup.log` file.

Event Code	Description	Remedy
Backup		
201001001	Backup failed to export data from the configuration store.	<p>Cause: The ICE utility failed to export directory information to an LDIF file.</p> <p>Action: Make sure that ICE is in the proper location (Linux: /opt/novell/eDirectory/bin).</p> <p>Action: Make sure that the host IP address, port, administrator, password are all correct.</p> <p>Action: Make sure the back up file is writable</p>
201001002	Backup failed to format data for a successful restore.	<p>Cause: The ldifReverse utility failed to sort the LDIF records.</p> <p>Action: Make sure that ldifReverse is in the proper location (Same directory as backup command).</p> <p>Action: Make sure the back up file is writable</p> <p>Action: Check for the backup file you specified with "_pre" appended to the file name.</p> <p>If the file exists, run the following command:</p> <pre>ldifReverse bkupfile_pre bkupfile</pre> <p>Replace <code>bkupfile</code> with the filename you specified for the backup file. It should create <code>bkupfile</code> which is the desired back up file.</p>
201001003	Backup failed to export certificates to the backup zip file.	<p>Cause: The certtool utility failed to export the certificates to a zip file.</p> <p>Action: Make sure that <code>certtool.jar</code> is in the proper location (Same directory as backup command).</p> <p>Action: Make sure the back up file is writable.</p> <p>Action: Manually export the certificates to a zip file:</p> <pre>java -Djava.library.path=/opt/novell/lib -jar certtool.jar -edirTree your_tree -edirIP 000.000.000.000 -edirServer cn=!ServerName.0=novell -edirUser cn=admin.o=novell -edirPwd secret -bkup -file ServerName_20060828_0930.zip -pwd certsecret -trcontainer trustedRoots.access ManagerContainer.novell -caName "your_tree CA"</pre>
Restore		
201002001	Backup file does not exist.	<p>Cause: The backup file does not exist. The name of the backup file specified in answer to the prompt should not include the final the <code>.ldif</code> or <code>.zip</code> extension.</p> <p>Action: Specify the correct name of the back up file.</p>

Event Code	Description	Remedy
201002002	Backup file does not appear to be valid.	<p>Cause: An simple analysis of the backup file indicates that the LDIF file specified backup file (with <code>.ldif</code> appended to the name) is not a valid backup file.</p> <p>Action: Make sure to specify a backup file that was created by the Access Manager Backup utility.</p>
201002003	Restore failed to access the configuration store.	<p>Cause: The ICE utility failed to access the eDirectory configuration store.</p> <p>Action: Make sure that ICE is in the proper location (Linux: <code>/opt/novell/eDirectory/bin</code>). Make sure that the host IP address, port, administrator, password are all correct.</p>
201002004	Restore failed to format the current configuration store data.	<p>Cause: Restore was not able to save a current copy of the configuration store. A current copy of the config store is saved before the import in case the import fails.</p> <p>Action: Make sure that <code>ldifReverse</code> is in the proper location (Same directory as backup command).</p>
201002005	Restore failed to prepare the configuration store for data import.	<p>Cause: ICE failed. Unknown reason because it has previously been invoked successfully in the restore script.</p>
201002006	Restore failed to prepare the configuration store for data import.	<p>Cause: ICE failed. Unknown reason because it has previously been invoked successfully in the restore script.</p>
101002007	Restore failed to restore the backup data.	<p>Cause: ICE failed. Unknown reason because it has previously been invoked successfully in the restore script.</p> <p>Action: Check the configuration store for the following container:</p> <pre>ou=accessManagerContainer,o=novell</pre> <p>If it is not there, locate the <code>recover.ldif</code> file. It should be in the directory where you ran the restore command. Run ICE to recover the configuration store to the state it was in before you attempted the restore. Enter the following command:</p> <pre>/opt/novell/eDirectory/bin/ice -SLDIF -f recover.ldif -C -n -DLdap -sxxx.xxx.xxx.xxx -p636 -k -dcn=admin,o=novell -wadmin_password -F</pre>

Event Code	Description	Remedy
101002008	Failed to restore certificate from backup file.	<p>Cause: The java program restores the certificate failed. The java program is certtool.jar which provides command line access to various eDirectory certificate functions.</p> <p>Action: See the log file (<code>ambkup.log</code>) for more specific details. The log file contains a listing of relevant parameters with each error message. Assuming the back up from which you are trying to restore was successful, failure to restore is probably an incorrectly supplied parameter. Enter the following command:</p> <pre>JAVA -classpath vcdnbkup.jar:cert tool.jar com.novell.nids.bkuputil. Util -userid cn=admin,o=novell -pwd secret -vcdnUser</pre>
101002009	Failed to reconfigure VCDN user objects.	<p>Cause: The VCDN user objects were not restored with their passwords. Device Manager will not start up until the passwords have been properly set.</p> <p>Action: This is accompanied with an error x01004xxx. Please refer to that error.</p> <p>certtool utility</p>
201003002	IP address is missing.	<p>Cause: The certtool.jar was launched without the -edirIP option. A script file might have been incorrectly modified.</p> <p>Action: Make sure the -edirIP option is specified in the script when it launches the certtool utility.</p>
201003005	eDirectory user id missing.	<p>Cause: The certtool.jar was launched without the -edirUser option. A script file might have been incorrectly modified.</p> <p>Action: Make sure the -edirUser cn=admin.o=novell option is specified in the script when it launches the certtool utility.</p>
201003006	eDirectory user password missing.	<p>Cause: The certtool.jar was launched without the -edirPwd option. A script file may have been incorrectly modified.</p> <p>Action: Make sure the -edirPwd option is specified in the script when it launches the certtool utility.</p>
201003009	File name missing.	<p>Cause: The certtool.jar was launched without the -file (name of backup file) option. A script file may have been incorrectly modified.</p> <p>Action: Make sure the -file option is specified in the script when it launches the certtool utility.</p>
201003011	Encryption password missing.	<p>Cause: The certtool.jar was launched without the -pwd option. A script file may have been incorrectly modified.</p> <p>Action: Make sure the -pwd option is specified in the script when it launches the certtool utility.</p>

Event Code	Description	Remedy
201003013	Name of trusted root container missing.	<p>Cause: The certtool.jar was launched without the -trContainer (trusted root container) option. A script file may have been incorrectly modified.</p> <p>Action: Make sure the -trcontainer option is specified in the script when it launches the certtool utility.</p>
201003040	Failed to open backup file for writing.	<p>Cause: Backup was unable to create or access the backup file in which to save certificate information.</p> <p>Action: Ensure that user running backup sufficient rights.</p>
201003041	Failed to retrieve certificate names from eDirectory.	<p>Cause: A PKI or eDirectory error.</p> <p>Action: This error will be accompanied by an error string.</p>
201003042	Failed to retrieve certificate xxxx from eDirectory.	<p>Cause: The certtool failed to retrieve the certificate identified in the error. Problems have been seen trying to export certificate with pending CSRs.</p> <p>Action: This error will be accompanied by an error string.</p>
201003043	Failed to write certificate xxxx to backup file.	<p>Cause: The certificate identified in the error message did not get saved to the backup file.</p> <p>Action: An exception string included in the message my provide additional information.</p>
301003044	Error closing backup.	<p>Cause: Likely will not cause a problem.</p> <p>Action: Try extracting the contents of the zip file created by backup to verify the integrity of the zip file.</p>
201003045	Failed to write trusted root xxxx to backup file.	<p>Cause: The trusted root identified in error messages did not get saved to the backup file.</p> <p>Action: An exception string included in the message might provide additional information.</p>
201003046	Failed to retrieve trusted root xxxx from eDirectory.	<p>Cause: The certtool failed to retrieve the trusted root identified in the error. Likely a PKI or eDirectory error.</p> <p>Action: This error will be accompanied by an error string.</p>
201003048	Not all items were backed up.	<p>Cause: See accompanying errors.</p> <p>Action: Refer to previous error messages to identify which certificates or trusted roots were not backed up.</p>
201003049	Failed to retrieve the CA xxxx from eDirectory. Likely a PKI or eDirectory error.	<p>Cause: The certtool failed to retrieve the CA key identified in the error.</p> <p>Action: This error will be accompanied by an error string.</p>

Event Code	Description	Remedy
201003050	Failed to write CA key xxxx to backup file.	<p>Cause: The CA key identified in the error did not get written to the backup file.</p> <p>Action: An exception string included in the message may provide additional information.</p>
201003051	Failed to open backup file for reading.	<p>Action: Make sure the backup file exists. Do not include <code>.ldif</code> or <code>.zip</code> in the name of the backup file.</p> <p>Action: Make sure the user logged in has sufficient rights to access the file.</p>
201003052	Not all items were restored.	<p>Cause: See accompanying errors.</p> <p>Action: Refer to previous error messages to identify which certificates or trusted roots were not backed up.</p>
301003053	Error closing backup.	<p>Action: This error occurred after all restore operations had completed. Should not cause any problem.</p>
201003056	Error importing CA key: xxxx	<p>Action: The CA key was not restored. See the accompanying Error for more information. Likely a PKI error.</p> <p>Action: Make sure the password you provided matches the encryption password used when backing up the data.</p>
201003057	Error importing key: xxxx	<p>Cause: The CA key was not restored. See the accompanying Error for more information. Likely a PKI error.</p> <p>Action: Make sure the password you provided matches the encryption password used when backing up the data.</p>
201003058	Error importing trusted root: xxxx	<p>Cause: The trusted root was not restored. See the accompanying Error for more information. Likely a PKI error.</p>
	VCDN configuration	
201004001	Failed to configure VCDN objects for data store access.	<p>The VCDN user objects were not restored with their passwords. Device Manager will not start up until the passwords have been properly set.</p> <p>Cause: The <code>vcdnbkup.jar</code> utility failed to reset passwords for VCDN objects. This causes errors starting up device manager.</p> <p>Action: Make sure <code>/opt/volera/roma/conf/vcdn.conf</code> file is present and has the correct information.</p> <p>To fix enter the following command in the <code>/opt/novell/devman/bin</code> directory:</p> <pre>java -jar vcdnbkup.jar -userid cn=admin,o=novell -pwd admin_password -vcdnUser</pre>

Event Code	Description	Remedy
201004002	Application Error.	<p>The VCDN user objects were not restored with their passwords. Device Manager will not start up until the passwords have been properly set. Accompanied by a stack trace with more information.</p> <p>Cause: vcdnbkup.jar utility failed to reset passwords for VCDN objects. This will cause errors starting up device manager.</p> <p>Action: Make sure the information in <code>/opt/volera/roma/conf/vcdn.conf</code> file is correct:</p> <p>Fix the file by running the following command (in <code>/opt/novell/devman/bin</code>):</p> <pre>java -jar vcdnbkup.jar -userid cn=admin,o=novell -pwd admin_password -vcdnUser</pre>

1.1.9 SOAP Policy Enforcement Point (011)

The SOAP Policy Enforcement Point (PEP) interface is used by the NetWare and Linux Access Gateways for policy evaluation.

Component 011

- ◆ Sub group 01: General/Configuration
- ◆ Sub group 02: Authorization PEP
- ◆ Sub group 03: Identity Injection PEP
- ◆ Sub group 04: Form Fill PEP

Messages are logged to the catalina.out for trace and application level logging when Identity Server logging is enabled.

Event Code	Description	Remedy
General/Configuration		
501101010	Start Policy Soap Handler	<p>Policy Soap Message Handler received start command.</p> <p>Cause: Embedded Service Provider has been started</p> <p>Action: None. Informational message only.</p>
501101011	Stop Policy Soap Handler	<p>Policy Soap Message Handler received stop command.</p> <p>Cause: Embedded Service Provider has been stopped</p> <p>Action: None. Informational message only.</p>

Event Code	Description	Remedy
101101012	Policy Evaluator Not Running	<p>The Policy Evaluator has been stopped.</p> <p>Cause: The Embedded Service Provider has been stopped by an administrator</p> <p>Action: Restart the Embedded Service Provider for the device.</p>
101101013	General Failure	<p>General failure processing policy request.</p> <p>Cause: Most often caused by incorrectly formatted XML.</p> <p>Action: Check catalina.out for stack trace and possibly more detailed information regarding the failure.</p>
501101020	Request Received	<p>Soap request received.</p> <p>Cause: Informational message which logs the type of request received</p> <p>Action: None. Informational message used for checking soap handler interactions.</p>
501101021	Response Sent	<p>Soap response sent.</p> <p>Cause: Informational message regarding soap response to a request</p> <p>Action: None. Informational message used for checking soap handler interactions.</p>
101101022	Unsupported request received	<p>A NXPES command other than configure, evaluate or terminate was received.</p> <p>Cause: The policy engine revision is incompatible with the application.</p> <p>Action: Validate the software installation.</p>
201101023	Unrecognized Policy Identifier	<p>Policy evaluation was requested for an unknown policy.</p> <p>Cause: The policy identifier known to the Access Gateway is stale.</p> <p>Action: Most often, this problem is detected by the Access Gateway and the policies are reconfigured. If the problem persists, send an Apply or Apply Changes to the device from the CLI or Administrative Console.</p>
501101030	Configure Success	<p>Successful policy configuration.</p> <p>Cause: Policy configuration succeeded</p> <p>Action: None. Informational message used for checking policy configuration.</p>

Event Code	Description	Remedy
201101030	Configure Warning	<p>Policy Configuration Warning.</p> <p>Cause: Policy configuration request reported a problem in retrieving configuration data from the config store</p> <p>Action: Check the policy definitions in the Administration Console to ensure the configuration store is working properly, then reapply the configuration to the device.</p>
101101031	Configure Failure	<p>The policy requested is malformed or causes an exception during the configuration process.</p> <p>Cause: This is accompanied with a possible reason for the failure.</p> <p>Action: Check the policy configuration in the administrative console and reapply the configuration to the device.</p>
501101032	Configure - Empty Policy Set	<p>The set of policies requested either do not apply to the policy enforcement point or the set of policies do not match the categories selected in the policy enforcement list.</p> <p>Cause: This may be normal operation.</p> <p>Action: If a policy is expected, check the category of the policy and make sure the policy is enabled for the device.</p>
501101040	Terminating policy	<p>The set of policies represented by the policy ID are no longer needed and will be removed from the operating policy set.</p> <p>Cause: This happens each time a configuration is applied to the device.</p> <p>Action: None. This is an informational message only.</p>
501101050	Evaluating policy	<p>An evaluation request has been received for the set of policies represented by the policy ID.</p> <p>Cause: This happens at least once per user session per configured policy enforcement point.</p> <p>Action: None. This is an informational message only.</p>

Event Code	Description	Remedy
501101051	Policy Evaluation - Invalid User Error	<p>User session received for policy evaluation was not found or contains invalid data.</p> <p>Cause: The Identity Service Provider which authenticated the user is not accessible from the Embedded Service Provider.</p> <p>Action: Most often, this error will automatically restart the user identification process for the Access Gateway.</p> <p>If that doesn't occur:</p> <p>Administrator: If problem persists, check health status of Identity Service Provider and take appropriate action.</p> <p>End User: Retry request. If not redirected to the Identity Service Provider, force a refresh of the current browser page and the Access Gateway/Embedded Service Provider will reinitiate the authentication process.</p>
501101052	Policy Evaluation - Information Query Error	<p>The Policy Evaluator is unable to gain access to information required by the policy.</p> <p>Cause: This is accompanied with a possible reason for failure.</p> <p>Action: As the administrator, check the health status of Identity Service Provider and take appropriate action.</p>
501101053	Policy Evaluation - WSC Query Error	<p>An attempt to use the WSC query mechanism of the ESP failed, the requested policy data is unavailable.</p> <p>Cause: This is accompanied with a possible reason for failure.</p> <p>Action: As the administrator, check the health status of Identity Service Provider and take appropriate action.</p>

Event Code	Description	Remedy
501101054	Policy Evaluation - Cluster Data Query Error	<p>Attempt to retrieve user session data from ESP cluster member failed.</p> <p>Cause: The Embedded Service Provider which authenticated the user may not be accessible from the Embedded Service Provider evaluating the policy.</p> <p>Action: Most often, this error will automatically restart the user identification process for the Access Gateway.</p> <p>If that doesn't occur:</p> <p>End User: Close browser and retry request.</p> <p>Administrator: Check the health status of Embedded Service Provider referenced by IP address in the log and take appropriate action.</p>
501101055	Policy Evaluation - Cluster Query Retry Count	<p>Informational message containing the number of retries the ESP has made to request policy information from another cluster member.</p> <p>Cause: The Embedded Service Provider which authenticated the user may not be accessible from the Embedded Service Provider evaluating the policy.</p> <p>Action: None, this is an informational message only.</p>
Authorization PEP		
501102050	Policy Evaluation Trace	<p>Trace of an individual policy evaluation.</p> <p>Cause: Policy evaluation.</p> <p>Action: None. Informational message used for checking policy evaluation.</p>
Identity Injection PEP		
501103050	Policy Evaluation Trace	<p>Trace of an individual policy evaluation.</p> <p>Cause: Policy evaluation.</p> <p>Action: None. Informational message used for checking policy evaluation.</p>
Form Fill PEP		
501104050	Policy Evaluation Trace	<p>Trace of an individual policy evaluation.</p> <p>Cause: Policy evaluation.</p> <p>Action: None. Informational message used for checking policy evaluation.</p>

1.1.10 Novell Modular Authentication Class (012)

The Novell Modular Authentication Service (NMAS) Class provides access to a number of advanced authentication mechanisms available from Novell, Inc. and Novell partners.

Component 012

- ◆ Sub group 01: General/Configuration
- ◆ Log file: catalina.out for trace and application level logging as enabled by the Identity Server > Edit > Logging settings

Event Code	Description	Remedy
General/Configuration		
301201001	NMAS Authentication Class	<p>The log message language resource file could not be located.</p> <p>Cause: The log message language resource file was not found</p> <p>Action: Verify installation.</p>
101201002	NMAS Authentication Class	<p>Error getting LDAP host address.</p> <p>Cause: System configuration.</p> <p>Action: Verify installation and availability of LDAP host server.</p>
101201003	NMAS Authentication Class	<p>The NMAS_LOGIN_SEQUENCE initialization property were not provided.</p> <p>Cause: The NMAS_LOGIN_SEQUENCE property was not defined for the authentication class.</p> <p>Action: Use the management interface to add the NMAS_LOGIN_SEQUENCE property to either the class or the method, and assign it the name of a valid NMAS login sequence.</p>
101201004	NMAS Authentication Class	<p>Unable to write to HTTPResponse</p> <p>Cause: Unknown</p> <p>Action: Check system status.</p>
501201005	NMAS Authentication Class	<p>UserID not found.</p> <p>Cause: Invalid User ID.</p> <p>Action: Verify username</p>
101201006	NMAS Authentication Class	<p>Invalid NMAS Login state.</p> <p>Cause: Unknown</p> <p>Action: Check server status.</p>

Event Code	Description	Remedy
101201007	NMAS Authentication Class	NMAS Login Error. Cause: See NMAS Error codes. Action: Indicated by NMAS error code.
