

# Novell GroupWise®

7

August 15, 2005

---

TROUBLESHOOTING 3: MESSAGE  
FLOW AND DIRECTORY STRUCTURE

[www.novell.com](http://www.novell.com)

# N

Novell®

## Legal Notices

Novell, Inc. makes no representations or warranties with respect to the contents or use of this documentation, and specifically disclaims any express or implied warranties of merchantability or fitness for any particular purpose. Further, Novell, Inc. reserves the right to revise this publication and to make changes to its content, at any time, without obligation to notify any person or entity of such revisions or changes.

Further, Novell, Inc. makes no representations or warranties with respect to any software, and specifically disclaims any express or implied warranties of merchantability or fitness for any particular purpose. Further, Novell, Inc. reserves the right to make changes to any and all parts of Novell software, at any time, without any obligation to notify any person or entity of such changes.

Any products or technical information provided under this Agreement may be subject to U.S. export controls and the trade laws of other countries. You agree to comply with all export control regulations and to obtain any required licenses or classification to export, re-export, or import deliverables. You agree not to export or re-export to entities on the current U.S. export exclusion lists or to any embargoed or terrorist countries as specified in the U.S. export laws. You agree to not use deliverables for prohibited nuclear, missile, or chemical biological weaponry end uses. Please refer to [www.novell.com/info/exports/](http://www.novell.com/info/exports/) for more information on exporting Novell software. Novell assumes no responsibility for your failure to obtain any necessary export approvals.

Copyright © 1993-2005 Novell, Inc. All rights reserved. No part of this publication may be reproduced, photocopied, stored on a retrieval system, or transmitted without the express written consent of the publisher.

Novell, Inc. has intellectual property rights relating to technology embodied in the product that is described in this document. In particular, and without limitation, these intellectual property rights may include one or more of the U.S. patents listed at <http://www.novell.com/company/legal/patents/> and one or more additional patents or pending patent applications in the U.S. and in other countries.

Novell, Inc.  
404 Wyman Street, Suite 500  
Waltham, MA 02451  
U.S.A.  
[www.novell.com](http://www.novell.com)

**Online Documentation:** To access the online documentation for this and other Novell products, and to get updates, see [www.novell.com/documentation](http://www.novell.com/documentation).

## **Novell Trademarks**

ConsoleOne is a registered trademark of Novell, Inc., in the United States and other countries.

eDirectory is a trademark of Novell, Inc.

GroupWise is a registered trademark of Novell, Inc., in the United States and other countries.

NetWare is a registered trademark of Novell, Inc., in the United States and other countries.

NLM is a trademark of Novell, Inc.

Novell is a registered trademark of Novell, Inc., in the United States and other countries.

QuickFinder is a trademark of Novell, Inc.

## **Third-Party Materials**

All third-party trademarks are the property of their respective owners.



# Contents

- About This Guide** **9**
  
- Part I Message Flow Diagrams** **11**
  
- 1 Message Delivery in the Local Post Office** **13**
  - 1.1 Online Mode .....13
  - 1.2 Caching Mode .....15
  - 1.3 Remote Mode .....18
  
- 2 Message Delivery to a Different Post Office** **19**
  - 2.1 TCP/IP Link Open: Transfer between Post Offices Successful.....19
  - 2.2 TCP/IP Link Closed: Transfer between Post Offices Delayed.....22
  
- 3 Message Delivery to a Different Domain** **27**
  - 3.1 TCP/IP Link Open: Transfer between Domains Successful .....27
  - 3.2 TCP/IP Link Closed: Transfer between Domains Delayed .....30
  
- 4 Message Delivery to and from the Internet** **35**
  - 4.1 TCP/IP Link: Outbound Transfer to the Internet Successful .....35
  - 4.2 TCP/IP Link: Outbound Transfer to the Internet Delayed or Unsuccessful .....38
  - 4.3 Mapped/UNC Link: Outbound Transfer to the Internet Successful .....41
  - 4.4 Mapped/UNC Link: Outbound Transfer to the Internet Delayed or Unsuccessful.....43
  - 4.5 TCP/IP Link: Inbound Transfer from the Internet Successful .....46
  - 4.6 Mapped/UNC Link: Inbound Transfer from the Internet Successful .....48
  
- 5 Message Delivery through a Modem Connection** **51**
  - 5.1 “Hit the Road” Process in Online Mode.....51
  - 5.2 Modem Link through the Async Gateway in Remote Mode .....52
  
- 6 Administrative Database Update** **59**
  
- Part I Directory Structure Diagrams** **61**
  
- 7 Message Transfer/Storage Directories** **63**
  - 7.1 Domain Directory.....63
    - 7.1.1 domain directory .....64
    - 7.1.2 wpcsin directory .....64

7.1.3	wptools directory	67
7.1.4	wpgate directory	67
7.1.5	wpcsout directory	67
7.1.6	mtaname file	69
7.1.7	wpdomain.db file	69
7.1.8	wpdomain.dc file	69
7.1.9	wphost.dc file	70
7.1.10	gwdom.dc file	70
7.1.11	gwpo.dc file	70
7.1.12	viewcopy.log file	70
7.2	Post Office Directory	70
7.2.1	post_office directory	73
7.2.2	wpcsin directory	73
7.2.3	gwdms directory	75
7.2.4	ofmsg directory	76
7.2.5	ofuser directory	77
7.2.6	offiles directory	78
7.2.7	ofviews directory	78
7.2.8	ofwork directory	78
7.2.9	ofdirect directory	78
7.2.10	oftemp directory	79
7.2.11	wpcsout directory	79
7.2.12	wphost.db file	82
7.2.13	gwpo.dc file	82
7.2.14	ngwguard.db file	82
7.2.15	ngwguard.dc file	82
7.2.16	ngwguard.fbk file	83
7.2.17	ngwguard.rfl file	83
7.2.18	ngwcheck.db	83
7.3	MTA Local Queue Directory	83
7.3.1	mslocal directory	84
7.3.2	msglog directory	85
7.3.3	gwinprog directory	85
7.3.4	mshold directory	85
7.3.5	domainms directory	85
7.3.6	postx directories	86
7.3.7	gatewayx directories	86
7.3.8	domainx directories	86
7.3.9	0-7 directories	86
7.3.10	mtaname files	86
7.3.11	gwvsscan directory	87
7.3.12	mtaconv directory	87
7.4	Internet Agent Queue Directory	87
7.4.1	domain\wpgate\gwia directory	88
7.4.2	gwia directory	92
7.5	WebAccess Agent Queue Directory	93
7.5.1	domain\wpgate\webac70a directory	94
7.5.2	000.prc directory	94
7.5.3	wpcsin directory	94
7.5.4	wpcsout directory	94
7.5.5	gwhold directory	95
7.5.6	gwprob directory	95
7.5.7	template directory	95
7.5.8	commgr.cfg file	95
7.5.9	comint.cfg file	95
7.5.10	mimetype.cfg file	95
7.5.11	gwac.db file	95
7.5.12	gwac.dc file	95
7.6	Caching Mailbox Directory	96
7.6.1	\novell\groupwise\gwxxxxxx directory	97

7.6.2	rofd data directory	.97
7.6.3	wpcsin directory	.99
7.6.4	wpcout\ofs directory	.99
7.6.5	wpgwsend directory	100
7.6.6	wpgwrecv directory	100
7.6.7	remoten.log	100
7.7	Remote Mailbox Directory	100
7.7.1	remote_mailbox directory	101
7.7.2	rofd data directory	101
7.7.3	wpcsin directory	103
7.7.4	wpcout\ofs directory	104
7.7.5	wpgwsend directory	104
7.7.6	wpgwrecv directory	104
7.7.7	remoten.log	105

**8 Agent Installation Directories 107**

8.1	GroupWise Agent Installation (POA and MTA)	107
8.1.1	NetWare Installation Directory	107
8.1.2	Linux Installation Directory	110
8.1.3	Windows Installation Directory	116
8.2	Internet Agent Installation	119
8.2.1	NetWare Installation Directory	119
8.2.2	Linux Installation Directory	120
8.2.3	Windows Installation Directory	124
8.3	WebAccess Agent Installation	126
8.3.1	NetWare Installation Directory	126
8.3.2	Linux Installation Directory	128
8.3.3	Windows Installation Directory	134
8.3.4	Document Viewer Agent Working Directory	137
8.4	Monitor Agent Installation	138
8.4.1	Linux Installation Directory	138
8.4.2	Windows Installation Directory	141
8.5	Apache/Tomcat Installation	143
8.5.1	NetWare Installation Directory	143
8.5.2	Linux Installation Directory	148

**9 Software Distribution Directory 153**

9.1	NetWare/Windows Software Distribution Directory	153
9.1.1	\grpwise\software directory	154
9.1.2	agents directory	154
9.1.3	domain directory	155
9.1.4	po directory	156
9.1.5	client directory	157
9.1.6	gwcheck directory	158
9.1.7	ofviews directory	158
9.1.8	ppforms directory	158
9.1.9	admin directory	158
9.1.10	internet directory	159
9.1.11	license directory	159
9.1.12	common directory	159
9.1.13	docs directory	160
9.2	Linux Software Distribution Directory	160
9.2.1	/opt/novell/groupwise/software directory	163
9.2.2	agents directory	163
9.2.3	domain directory	164
9.2.4	po directory	165
9.2.5	client directory	165

9.2.6	ofviews directory	166
9.2.7	admin directory	166
9.2.8	internet directory	167
9.2.9	license directory	169
9.2.10	docs directory	169
9.2.11	gwinst directory	169

## **10 GroupWise Client Installation Directories** **171**

10.1	Windows Client	171
10.1.1	c:\novell\groupwise	172
10.1.2	grpwise.exe file	172
10.1.3	gwtip.exe file	172
10.1.4	notify.exe file	172
10.1.5	addrbook.exe file	172
10.1.6	htrsetup.exe file	172
10.1.7	gwimpexe.exe file	173
10.1.8	gwmailto.exe file	173
10.1.9	gwreload.exe file	173
10.1.10	gwsync.exe file	173
10.1.11	pdaconnect.exe file	173
10.1.12	ngwguard.dc file	173
10.1.13	wprof.dc file	173
10.1.14	*.dll files	173
10.1.15	*.ocx files	174
10.1.16	*.flt files	174
10.1.17	*.chm files	174
10.1.18	gwcheck directory	174
10.1.19	ofviews directory	174
10.1.20	ppforms directory	174
10.2	Cross-Platform Client on Linux	175
10.2.1	/opt/novell/groupwise/client directory	175
10.2.2	bin directory	175
10.2.3	lib directory	176
10.2.4	jre directory	176
10.2.5	logs directory	176
10.3	Cross-Platform Client on Macintosh	176
10.3.1	/Applications/GroupWise.app directory	177
10.3.2	Contents directory	177
10.3.3	MacOS directory	177
10.3.4	Resources directory	177
10.3.5	lib directory	177
10.3.6	Java directory	178



# About This Guide

This Novell® *GroupWise® Troubleshooting 3 Guide* provides diagrams to help you understand the structure and functioning of your GroupWise system. The guide is divided into the following sections:

- [Part I, “Message Flow Diagrams,” on page 11](#)
- [Part I, “Directory Structure Diagrams,” on page 61](#)

Other sources of troubleshooting assistance include:

- [Novell Support \(http://support.novell.com\)](http://support.novell.com)
- [Novell Support Knowledgebase \(http://support.novell.com/search/kb\\_index.jsp\)](http://support.novell.com/search/kb_index.jsp)
- [GroupWise 7 Support Forums \(http://support.novell.com/forums/2gw.html\)](http://support.novell.com/forums/2gw.html)
- [Novell GroupWise Support Community \(http://support.novell.com/products/groupwise\)](http://support.novell.com/products/groupwise)
- [GroupWise Cool Solutions \(http://www.novell.com/coolsolutions/gwmag/index.html\)](http://www.novell.com/coolsolutions/gwmag/index.html)

## Audience

This guide is intended for \*\*\*\*\*.

## Feedback

We want to hear your comments and suggestions about this manual and the other documentation included with this product. Please use the User Comments feature at the bottom of each page of the online documentation, or go to [www.novell.com/documentation/feedback.html](http://www.novell.com/documentation/feedback.html) and enter your comments there.

## Documentation Updates

For the most recent version of the *GroupWise 7 Troubleshooting 3 Guide*, visit the [GroupWise 7 Documentation Web site \(http://www.novell.com/documentation/gw7\)](http://www.novell.com/documentation/gw7).

## Additional Documentation

For additional GroupWise documentation, see the following guides at the [GroupWise 7 Documentation Web site \(http://www.novell.com/documentation/gw7\)](http://www.novell.com/documentation/gw7):

- *Installation Guide*
- *Administration Guide*
- *Multi-System Administration Guide*
- *Interoperability Guide*
- *Troubleshooting 1: Error Messages*
- *Troubleshooting 2: Solutions to Common Problems*
- *GroupWise Client User Guides*

## Documentation Conventions

In Novell documentation, a greater-than symbol (>) is used to separate actions within a step and items in a cross-reference path.

A trademark symbol (™, ®, etc.) denotes a Novell trademark. An asterisk denotes a third-party trademark.

When a single pathname can be written with a backslash for some platforms or a forward slash for other platforms, the pathname is presented with a backslash. Users of platforms that require a forward slash, such as Linux\*, should use forward slashes as required by your software.

When a startup switch can be written with a forward slash for some platforms or a double hyphen for other platforms, the startup switch is presented with a forward slash. Users of platforms that require a double hyphen, such as Linux, should use double hyphens as required by your software.

# Message Flow Diagrams

This part of *Troubleshooting 3: Message Flow and Directory Structure* helps you understand how messages travel between GroupWise® users and how administrative updates to GroupWise databases occur.

- “Message Delivery in the Local Post Office” on page 13
- “Message Delivery to a Different Post Office” on page 19
- “Message Delivery to a Different Domain” on page 27
- “Message Delivery to and from the Internet” on page 35
- “Message Delivery through a Modem Connection” on page 51
- “Administrative Database Update” on page 59



# Message Delivery in the Local Post Office

The GroupWise® 7 client always uses client/server access to the post office but it can interact with the POA for the post office in different ways. For a review, see “Using Different GroupWise Modes (Online, Caching, and Remote)” in “Getting Started” in the *GroupWise 7 Windows Client User Guide*.

- Section 1.1, “Online Mode,” on page 13
- Section 1.2, “Caching Mode,” on page 15
- Section 1.3, “Remote Mode,” on page 18

## 1.1 Online Mode

This message flow diagram illustrates how a GroupWise message travels from one user to another in the local post office when the client and POA communicate by way of TCP/IP and the users are accessing their Online mailboxes.

Figure 1-1 Message Flow in Online Mode













Table 1-1 Message Flow in Online Mode Stages

Stage	Icon	Description
1 Sender		The user sends a message to recipients in the same post office. The access mode setting for the post office is Client/Server Only.

Stage	Icon	Description
2 Sender's GroupWise Client		The GroupWise client communicates with the POA by way of TCP/IP.
3 POA for Local Post Office		<p>The POA receives the message from the GroupWise client and performs the following actions for the sender:</p> <ul style="list-style-type: none"> <li>• Adds the message to the message database (<i>msgnnn.db</i>) assigned to the sender.</li> <li>• Creates a pointer in the sender's user database (<i>userxxx.db</i>) so the message appears in the sender's mailbox as a sent item.</li> <li>• Places attachments larger than 2 KB in one of the <i>post_office\offiles\fd0-F6</i> subdirectories and creates pointers from the message to its attachments. (For database efficiency, messages and distribution lists larger than 2 KB are also handled as attachments.)</li> </ul> <p>The POA also performs the following actions for the recipient:</p> <ul style="list-style-type: none"> <li>• Creates a pointer in each recipient's user database (<i>userxxx.db</i>) to the message in the message database (<i>msgnnn.db</i>) so the new message appears in the recipient's mailbox.</li> <li>• Updates the message in the message database (<i>msgnnn.db</i>) with a Delivered status for each recipient.</li> </ul>
4 POA for Local Post Office		The POA communicates to the GroupWise client by way of TCP/IP that a new message has arrived.
5 Recipient's GroupWise Client		The Notify component of the recipient's GroupWise client notifies the recipient that a new message has arrived.
6 Recipient		Each recipient opens the message in the GroupWise client.
7 Recipient's GroupWise Client		Each recipient's GroupWise client communicates the Opened status to the POA by way of TCP/IP.
8 POA for Local Post Office		The POA receives the Opened status from the GroupWise client and updates the message in the message database with the Opened status for each recipient who opens the message.
9 POA for Local Post Office		The POA communicate the Opened status to the sender's GroupWise client by way of TCP/IP.
10 Sender		When the sender checks the sent items in his or her mailbox in the GroupWise client, the message displays a status of Delivered for each recipient (and possibly Opened as well if the recipient has opened the message).

# 1.2 Caching Mode

This message flow diagram illustrates how a GroupWise message travels from one user to another in the local post office when the users are accessing their Caching mailboxes.

Figure 1-2 Message Flow in Caching Mode


















Table 1-2 Message Flow in Caching Mode Stages



Stage	Icon	Description
1 Sender		The user sends a message to recipients in the same post office. The user is in Caching mode.

Stage	Icon	Description
<p>2</p> <p>Sender's GroupWise Client</p>		<p>The GroupWise client updates the sender's Caching mailbox (<code>\novell\groupwise\gwxxxxxxx\rofdata</code>) by performing the following actions:</p> <ul style="list-style-type: none"> <li>• Adds the message to the message database (<code>rofdata\msg.db</code>) in the Caching mailbox. This database is local equivalent of the <code>msgnnn.db</code> database in the post office.</li> <li>• Creates a pointer in the sender's user database (<code>rofdata\user.db</code>) in the Caching mailbox so the message appears in the sender's mailbox as a sent item. This database is the local equivalent of the <code>userxxx.db</code> database in the post office.</li> <li>• Places attachments larger than 2 KB in the <code>rofdata</code> subdirectory in the Caching mailbox and creates pointers from the message to its attachments. (For database efficiency, messages and distribution lists larger than 2 KB are also handled as attachments.) There is no local equivalent to the <code>offiles</code> subdirectory in the post office, so attachments are placed directly in the <code>rofdata</code> subdirectory in the Caching mailbox.</li> <li>• Places a copy of the message in the <code>rofdata\wpcsin\1</code> priority subdirectory to await the next connection to the POA.</li> </ul>
<p>3</p> <p>Sender's GroupWise Client</p>		<p>In Caching mode, sending a message always initiates an immediate connection with the POA in order to send the message. The GroupWise client communicates the message to the POA and deletes the copy in the <code>rofdata\wpcsin\1</code> priority subdirectory when the POA has processed the message.</p>
<p>4</p> <p>POA for Local Post Office</p>		<p>The POA receives the message from the GroupWise client and performs the following actions for the sender to update the sender's Online mailbox:</p> <ul style="list-style-type: none"> <li>• Adds the message to the message database (<code>msgnnn.db</code>) assigned to the sender in the post office.</li> <li>• Creates a pointer in the sender's user database (<code>userxxx.db</code>) in the post office.</li> <li>• Places attachments larger than 2 KB in one of the <code>post_office\offiles\fd0-F6</code> subdirectories in the post office and creates pointers from the message to its attachments. (For database efficiency, messages and distribution lists larger than 2 KB are also handled as attachments.)</li> </ul> <p>The POA also performs the following actions for the recipients to update their Online mailboxes:</p> <ul style="list-style-type: none"> <li>• Creates a pointer in each recipient's user database (<code>userxxx.db</code>) to the message in the message database (<code>msgnnn.db</code>) in the post office so that the new message appears in each recipient's mailbox.</li> <li>• Updates the message in the message database (<code>msgnnn.db</code>) in the post office with a Delivered status for the recipients.</li> </ul>



Stage	Icon	Description
5 POA for Local Post Office		Because the recipients are also in Caching mode, they do not receive immediate notification that a new message has arrived in their Online mailboxes. Based on the <i>Send/Retrieve All Marked Accounts Every nn Minutes</i> option under <i>Accounts &gt; Account Options &gt; General</i> , each recipient's GroupWise client sends a request to the POA for items that have arrived in the recipient's Online mailbox since the last connection with the POA.
6 POA for Local Post Office		The POA responds by sending information to update each recipient's Caching mailbox and communicates to the GroupWise client that a new message has arrived.
7 Recipient's GroupWise Client		Each recipient's GroupWise client updates the recipient's Caching mailbox by performing the following actions: <ul style="list-style-type: none"> <li>• Adds the message to the message database (<i>rofdata\msg.db</i>) in the recipient's Caching mailbox.</li> <li>• Creates a pointer in the recipient's user database (<i>rofdata\user.db</i>) to the message in the message database (<i>rofdata\msg.db</i>) so the new message appears in the recipient's Caching mailbox.</li> </ul>
8 Recipient's GroupWise Client		The Notify component of each recipient's GroupWise client notifies the recipient that a new message has arrived.
9 Recipient		Each recipient opens the message in the GroupWise client.
10 Recipient's GroupWise Client		Each recipient's GroupWise client generates an Opened status and places it in the <i>rofdata\wpcsin\1</i> priority subdirectory to await the next connection with the POA.
11 Recipient's GroupWise Client		When each recipient sends a message or the time specified by the <i>Send/Receive All Marked Accounts Every nn Minutes</i> option has elapsed, each recipient's GroupWise client connects with the POA and communicates the Opened status to the POA, along with any other data that needs to be uploaded to the recipient's Online mailbox.
12 POA for Local Post Office		The POA receives the Opened status from the GroupWise client and updates the message in the sender's message database with the Opened status.
13 Recipient's GroupWise Client		Because the sender is in Caching mode, the sender does not immediately receive the Opened status. Based on the sender's actions and caching schedule, the sender's GroupWise client eventually sends a request to the POA for items that have arrived in the sender's Online mailbox since the last synchronization of the Caching mailbox.
14 POA for Local Post Office		The POA responds by sending information to update the sender's Caching mailbox and communicates the Opened status to the sender's GroupWise client.

---

Stage	Icon	Description
15 Recipient's GroupWise Client		The sender's GroupWise client updates the sender's Caching mailbox by performing the following action: <ul style="list-style-type: none"><li>• Updates the message in the message database (<code>rofdata\msg.db</code>) with a Delivered and Opened status for each recipient.</li></ul>
16 Sender		When the sender checks the sent items in his or her mailbox in the GroupWise client, the message displays a status of Delivered and Opened for each recipient.

---

## 1.3 Remote Mode

Before you can use Remote mode, you must create a Remote mailbox on your computer and have a connection to your master GroupWise system. See [Chapter 5, "Message Delivery through a Modem Connection,"](#) on page 51.

# Message Delivery to a Different Post Office

The MTA handles message transfer between post offices.


- Section 2.1, “TCP/IP Link Open: Transfer between Post Offices Successful,” on page 19
- Section 2.2, “TCP/IP Link Closed: Transfer between Post Offices Delayed,” on page 22

The message flow diagrams in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure* focus on TCP/IP links because they are the most common and convenient (unless you have a post office and a domain on the same server). For diagrams that include mapped/UNC links, see *GroupWise 6.5 Troubleshooting 3: Message Flow and Directory Structure*. For an explanation of link types and link protocols, see “Understanding Link Configuration” in “Domains” in the *GroupWise 7 Administration Guide*.







## 2.1 TCP/IP Link Open: Transfer between Post Offices Successful









This message flow diagram illustrates how a GroupWise® message travels from one user to another between post offices in the same domain when the TCP/IP link between the post office and the domain is open.




Figure 2-1 Message Flow When the TCP/IP Link is Open



**Table 2-1** Message Flow When the TCP/IP Link is Open Stages

Stage	Icon	Description
1 Sender		The user sends a message to recipients in a different post office in the same domain.  In this diagram, the access mode setting in the local post office is Client/Server Only.
2 Sender's GroupWise Client		The GroupWise client communicates the message to the POA by way of TCP/IP.
3 POA for Sender's Post Office		The POA receives the message from the GroupWise client and performs the following actions for the sender: <ul style="list-style-type: none"> <li>• Adds the message to the message database (<code>msgnnn.db</code>) assigned to the sender.</li> <li>• Creates a pointer in the sender's user database (<code>userxxx.db</code>) so the message appears in the sender's mailbox as a sent item.</li> <li>• Places attachments larger than 2 KB in one of the <code>post_office\offiles\fd0-F6</code> subdirectories and creates pointers from the message to its attachments. (For database efficiency, messages and distribution lists larger than 2 KB are also handled as attachments.)</li> <li>• Creates a copy of the message in the appropriate priority 0-7 subdirectory of the MTA input queue in the sender's post office, in case the TCP/IP link to the MTA is currently closed.</li> </ul>
4 POA for Sender's Post Office		The POA then communicates the message to the MTA by way of TCP/IP, and deletes the copy in the MTA input queue because the TCP/IP transfer to the MTA was successful.  To see what happens if the TCP/IP link to the MTA is closed, see <a href="#">Section 2.2, "TCP/IP Link Closed: Transfer between Post Offices Delayed," on page 22.</a>
5 MTA for Local Domain		The MTA receives the message and places it into the MTA "in progress" ( <code>gwinprog</code> ) queue.
6 MTA for Local Domain		The MTA then communicates the message to the POA in the recipient's post office by way of TCP/IP. When the transmission is successful, the MTA deletes the message from the MTA "in progress" queue.  If the TCP/IP link to the recipient's post office is closed, the message is placed in the closed post office's holding queue in the MTA's <code>mslocal</code> directory for later transfer. The resulting message flow is parallel to what occurs when a domain is closed. See <a href="#">Section 3.2, "TCP/IP Link Closed: Transfer between Domains Delayed," on page 30</a> for a similar message flow that illustrates how messages to closed locations are handled.


Stage	Icon	Description
7 POA for Recipient's Post Office		<p>When the POA receives the new message from the MTA, it places it into the MTA output queue in the post office (<code>wpcsoout\ofs\0-7</code>) on behalf of the MTA. Then, the POA for the recipient's post office performs the following actions:</p> <ul style="list-style-type: none"> <li>• Adds the message to the message database (<code>msgnnn.db</code>) corresponding to the one assigned to the sender.</li> <li>• Creates a pointer in the recipient's user database (<code>userxxx.db</code>) so the new message appears in the recipient's mailbox and updates the notification information in the user database so the recipient can be notified of the message.</li> <li>• Places attachments larger than 2 KB in one of the <code>post_office\offiles\fd0-F6</code> subdirectories and creates pointers from the message to its attachments. (For database efficiency, messages and distribution lists larger than 2 KB are also handled as attachments.)</li> <li>• Creates a Delivered status message in the appropriate priority <code>0-7</code> subdirectory of the MTA input queue in the recipient's post office. It also communicates the Delivered status message directly to the MTA by way of TCP/IP. When that transmission is successful, the copy in the MTA input queue is deleted.</li> </ul>
8 POA for Local Post Office		The POA communicates to the GroupWise client by way of TCP/IP that a new message has arrived.
9 Recipient's GroupWise Client		The Notify component of the recipient's GroupWise client notifies the recipient that a new message has arrived.
10 Recipient		Each recipient opens the message in the GroupWise client.
11 Recipient's GroupWise Client		Each recipient's GroupWise client communicates the Opened status message to the POA by way of TCP/IP.
12 POA for Recipient's Post Office		The POA for the recipient's post office communicates the status message to the MTA by way of TCP/IP.
13 MTA for Local Domain		The MTA places the status message into the MTA "in progress" ( <code>gwinprog</code> ) queue.
14 MTA for Local Domain		The MTA communicates the status message to the POA for the sender's post office by way of TCP/IP.

Stage	Icon	Description
15 POA in Sender's Post Office		The POA for the sender's post office updates the sender's message database ( <code>msgnnn.db</code> ) with the Delivered status information (and possibly Opened as well if the recipient has opened the message).
16 POA for Local Post Office		The POA communicates the status to the sender's GroupWise client by way of TCP/IP.
17 Sender		When the sender checks the sent items in his or her mailbox in the GroupWise client, the message displays a status of Delivered for each recipient (and possibly Opened as well if the recipient has opened the message).







## 2.2 TCP/IP Link Closed: Transfer between Post Offices Delayed










This message flow diagram illustrates how a GroupWise message travels from one user to another between post offices in the same domain when the TCP/IP link between the post office and the domain is closed.

Figure 2-2 Message Flow When the TCP/IP Link is Closed





**Table 2-2** Message Flow When the TCP/IP Link is Closed Stages

Stage	Icon	Description
1 Sender		The user sends a message to recipients in a different post office in the same domain.  In this diagram, the access mode setting in the local post office is Client/Server Only.
2 Sender's GroupWise Client		The GroupWise client communicates the message to the POA by way of TCP/IP.
3 POA for Sender's Post Office		The POA receives the message from the GroupWise client and performs the following actions for the sender: <ul style="list-style-type: none"> <li>• Adds the message to the message database (<code>msgnnn.db</code>) assigned to the sender.</li> <li>• Creates a pointer in the sender's user database (<code>userxxx.db</code>) so the message appears in the sender's mailbox as a sent item.</li> <li>• Places attachments larger than 2 KB in one of the <code>post_office\offiles\fd0-F6</code> subdirectories and creates pointers from the message to its attachments. (For database efficiency, messages and distribution lists larger than 2 KB are also handled as attachments.)</li> <li>• Creates a copy of the message in the appropriate priority 0-7 subdirectory of the MTA input queue in the sender's post office, in case the TCP/IP link to the MTA is currently closed.</li> </ul>
4 POA for Sender's Post Office		The POA then attempts to communicate the message to the MTA by way of TCP/IP, but the MTA does not respond. The POA leaves the copy of the message in the MTA input queue and periodically attempts to contact the MTA. When the MTA responds again, the POA communicates the message and deletes the copy in the MTA input queue after the TCP/IP transmission to the MTA is successful.
5 MTA for Local Domain		The MTA receives the message and places it into the MTA "in progress" ( <code>gwinprog</code> ) queue.
6 MTA for Local Domain		The MTA then communicates the message to the POA in the recipient's post office by way of TCP/IP. When the transmission is successful, the MTA deletes the message from the MTA "in progress" ( <code>gwinprog</code> ) queue.  If the TCP/IP link to the recipient's post office is closed, the message is placed in the closed post office's holding queue in the MTA's <code>mslocal</code> directory for later transfer. The resulting message flow is parallel to what occurs when a domain is closed. For a similar message flow that illustrates how messages to closed locations are handled, see <a href="#">Section 3.2, "TCP/IP Link Closed: Transfer between Domains Delayed,"</a> on page 30.

Stage	Icon	Description
7 POA for Recipient's Post Office		<p>When it receives the new message, the POA for the recipient's post office performs the following actions:</p> <ul style="list-style-type: none"> <li>• Adds the message to the message database (<i>msgnnn.db</i>) corresponding to the one assigned to the sender.</li> <li>• Creates a pointer in the recipient's user database (<i>userxxx.db</i>) so the new message appears in the recipient's mailbox and updates the notification information in the user database so the recipient can be notified of the message.</li> <li>• Places attachments larger than 2 KB in one of the <i>post_office\offiles\fd0-F6</i> subdirectories and creates pointers from the message to its attachments. (For database efficiency, messages and distribution lists larger than 2 KB are also handled as attachments.)</li> <li>• Creates a Delivered status message in the appropriate priority 0-7 subdirectory of the MTA input queue in the recipient's post office. It also communicates the Delivered status message directly to the MTA by way of TCP/IP and when that transmission is successful, the copy in the MTA input queue is deleted.</li> </ul>
8 POA for Local Post Office		The POA communicates to the GroupWise client by way of TCP/IP that a new message has arrived.
9 Recipient's GroupWise Client		The Notify component of the recipient's GroupWise client notifies the recipient that a new message has arrived.
10 Recipient		Each recipient opens the message in the GroupWise client.
11 Recipient's GroupWise Client		Each recipient's GroupWise client communicates the Opened status message to the POA by way of TCP/IP.
12 POA for Recipient's Post Office		The POA for the recipient's post office communicates the status message to the MTA by way of TCP/IP.
13 MTA for Local Domain		The MTA places the status message into the MTA "in progress" ( <i>gwinprog</i> ) queue.
14 MTA for Local Domain		The MTA communicates the status message to the POA for the sender's post office by way of TCP/IP.
15 POA in Sender's Post Office		The POA for the sender's post office updates the sender's message database ( <i>msgnnn.db</i> ) with the Delivered status information (and possibly Opened as well if the recipient has opened the message).



---

Stage	Icon	Description
16 POA for Local Post Office		The POA communicates the Opened status to the sender's GroupWise client by way of TCP/IP.
17 Sender		When the sender checks the sent items in his or her mailbox in the GroupWise client, the message displays a status of Delivered for each recipient (and possibly Opened as well if the recipient has opened the message).

---



# Message Delivery to a Different Domain

The MTA handles message transfer between domains.


- Section 3.1, “TCP/IP Link Open: Transfer between Domains Successful,” on page 27
- Section 3.2, “TCP/IP Link Closed: Transfer between Domains Delayed,” on page 30

The message flow diagrams in *GroupWise 7 Troubleshooting 3: Message Flow and Directory Structure* focus on TCP/IP links because they are the most common and convenient (unless you have two domains on the same server). For diagrams that include mapped/UNC links, see *GroupWise 6.5 Troubleshooting 3: Message Flow and Directory Structure*. For an explanation of link types and link protocols, see “Understanding Link Configuration” in “Domains” in the *GroupWise 7 Administration Guide*.









## 3.1 TCP/IP Link Open: Transfer between Domains Successful









This message flow diagram illustrates how a GroupWise® message travels from one user to another when the domains are connected by a TCP/IP link and the link is open.






Figure 3-1 Message Flow When the TCP/IP Link is Open



**Table 3-1** Message Flow When the TCP/IP Link is Open Stages

Stage	Icon	Description
1 Sender		The user sends a message to recipients in a post office in a different domain.  In this diagram, the access mode setting for the local post office is Client/Server Only.
2 Sender's GroupWise Client		The GroupWise client communicates the message to the POA by way of TCP/IP.
3 POA for Sender's Post Office		The POA receives the message from the GroupWise client and performs the following actions for the sender: <ul style="list-style-type: none"> <li>• Adds the message to the message database (<i>msgnnn.db</i>) assigned to the sender.</li> <li>• Creates a pointer in the sender's user database (<i>userxxx.db</i>) so the message appears in the sender's mailbox as a sent item.</li> <li>• Places attachments larger than 2 KB in one of the <i>post_office\offiles\fd0-F6</i> subdirectories and creates pointers from the message to its attachments. (For database efficiency, messages and distribution lists larger than 2 KB are also handled as attachments.)</li> <li>• Creates a copy of the message in the appropriate priority 0-7 subdirectory of the MTA input queue in the sender's post office, in case the TCP/IP link to the MTA is currently closed.</li> </ul>
4 POA for Sender's Post Office		The POA then communicates the message to the MTA for the sender's domain by way of TCP/IP, and deletes the copy in the MTA input queue because the TCP/IP transfer to the MTA was successful.  To see what would happen if the TCP/IP link to the MTA is closed, see <a href="#">Section 2.2, "TCP/IP Link Closed: Transfer between Post Offices Delayed,"</a> on page 22.
5 MTA for Sender's Domain		The MTA for the sender's domain receives the message and places it into the MTA "in progress" ( <i>gwinprog</i> ) queue.
6 MTA for Sender's Domain		The MTA for the sender's domain then communicates the message to the MTA for the recipient's domain by way of TCP/IP.  If the TCP/IP link to the recipient's domain is closed, the message is placed in the closed domain's holding queue in the MTA's <i>mslocal</i> directory for later transfer. See <a href="#">Section 3.2, "TCP/IP Link Closed: Transfer between Domains Delayed,"</a> on page 30.
7 MTA for Recipient's Domain		The MTA for the recipient's domain receives the message and places it into the MTA "in progress" ( <i>gwinprog</i> ) queue.
8 MTA for Recipient's Domain		The MTA for the recipient's domain then communicates the message to the POA in the recipient's post office by way of TCP/IP.


Stage	Icon	Description
9 POA for Recipient's Post Office		<p>When it receives the new message, the POA for the recipient's post office performs the following actions:</p> <ul style="list-style-type: none"> <li>• Adds the message to the message database (<i>msgnnn.db</i>) corresponding to the one assigned to the sender.</li> <li>• Creates a pointer in the recipient's user database (<i>userxxx.db</i>) so the new message appears in the recipient's mailbox and updates the notification information in the user database so the recipient can be notified of the message.</li> <li>• Places attachments larger than 2 KB in one of the <i>post_office\offiles\fd0-F6</i> subdirectories and creates pointers from the message to its attachments. (For database efficiency, messages and distribution lists larger than 2 KB are also handled as attachments.)</li> <li>• Creates a Delivered status message in the appropriate priority 0-7 subdirectory of the MTA input queue in the recipient's post office. It also communicates the Delivered status message directly to the MTA by way of TCP/IP and when that transmission is successful, the copy in the MTA input queue is deleted.</li> </ul>
10 POA for Recipient's Post Office		The POA for the recipient's post office communicates to the GroupWise client by way of TCP/IP that a new message has arrived.
11 Recipient's GroupWise Client		The Notify component of the recipient's GroupWise client notifies the recipient that a new message has arrived.
12 Recipient		Each recipient opens the message in the GroupWise client.
13 Recipient's GroupWise Client		Each recipient's GroupWise client communicates the Opened status message to the POA by way of TCP/IP.
14 POA for Recipient's Post Office		The POA for the recipient's post office communicates the status message to the MTA for the recipient's domain by way of TCP/IP.
15 MTA for Recipient's Domain		The MTA for the recipient's domain places the status message into the MTA "in progress" ( <i>gwinprog</i> ) queue.
16 MTA for Recipient's Domain		The MTA for the recipient's domain communicates the status message to the MTA for the sender's domain by way of TCP/IP.

Stage	Icon	Description
17 MTA for Sender's Domain		The MTA for the sender's domain places the status message into the MTA "in progress" ( <i>gwinprog</i> ) queue.
18 MTA for Sender's Domain		The MTA for the sender's domain communicates the status message to the POA for the sender's post office by way of TCP/IP.
19 POA for Sender's Post Office		The POA for the sender's post office updates the sender's message database ( <i>msgnnn.db</i> ) with the Delivered status information (and possibly Opened as well if the recipient has opened the message).
20 POA for Sender's Post Office		The POA for the sender's post office communicates the status to the sender's GroupWise client by way of TCP/IP.
21 Sender		When the sender checks the sent items in his or her mailbox in the GroupWise client, the message displays a status of Delivered for each recipient (and possibly Opened as well if the recipient has opened the message).



## 3.2 TCP/IP Link Closed: Transfer between Domains Delayed







This message flow diagram illustrates how a GroupWise message travels from one user to another when the domains are connected by a TCP/IP link and the link is closed.

**Figure 3-2** Message Flow When the TCP/IP Link is Closed
















**Table 3-2** Message Flow When the TCP/IP Link is Closed Stages

Stage	Icon	Description
1 Sender		The user sends a message to recipients in a post office in a different domain. In this diagram, the access mode setting for the local post office is Client/Server Only.
2 Sender's GroupWise Client		The GroupWise client communicates the message to the POA by way of TCP/IP.

Stage	Icon	Description
3 POA for Sender's Post Office		<p>The POA receives the message from the GroupWise client and performs the following actions for the sender:</p> <ul style="list-style-type: none"> <li>• Adds the message to the message database (<i>msgnnn.db</i>) assigned to the sender.</li> <li>• Creates a pointer in the sender's user database (<i>userxxx.db</i>) so the message appears in the sender's mailbox as a sent item.</li> <li>• Places attachments larger than 2 KB in one of the <i>post_office\offiles\fd0-F6</i> subdirectories and creates pointers from the message to its attachments. (For database efficiency, messages and distribution lists larger than 2 KB are also handled as attachments.)</li> <li>• Creates a copy of the message in the appropriate priority <i>0-7</i> subdirectory of the MTA input queue in the sender's post office, in case the TCP/IP link to the MTA is currently closed.</li> </ul>
4 POA for Sender's Post Office		<p>The POA then communicates the message to the MTA for the sender's domain by way of TCP/IP, and deletes the copy in the MTA input queue because the TCP/IP transfer to the MTA was successful.</p> <p>To see what would happen if the TCP/IP link to the MTA is closed, see <a href="#">Section 2.2, "TCP/IP Link Closed: Transfer between Post Offices Delayed,"</a> on page 22.</p>
5 MTA for Sender's Domain		<p>The MTA for the sender's domain receives the message and places it into the MTA "in progress" (<i>gwinprog</i>) queue.</p>
6 MTA for Sender's Domain		<p>The MTA for the sender's domain then attempts to communicate the message to the MTA for the recipient's domain by way of TCP/IP, but the recipient MTA does not respond. Therefore, the MTA stores the message in its holding queue for the recipient's domain in the <i>mshold</i> directory.</p> <p>When the MTA in the recipient's domain responds again, the MTA for the sender's domain transfers the delayed message from the domain holding queue to the MTA in the recipient's domain by way of TCP/IP.</p>
7 MTA for Recipient's Domain		<p>The MTA for the recipient's domain receives the message and places it into the MTA "in progress" (<i>gwinprog</i>) queue.</p>
8 MTA for Recipient's Domain		<p>The MTA for the recipient's domain then communicates the message to the POA in the recipient's post office by way of TCP/IP.</p>



Stage	Icon	Description
9 POA for Recipient's Post Office		<p>When it receives the new message, the POA for the recipient's post office performs the following actions:</p> <ul style="list-style-type: none"> <li>• Adds the message to the message database (<i>msgnnn.db</i>) corresponding to the one assigned to the sender.</li> <li>• Creates a pointer in the recipient's user database (<i>userxxx.db</i>) so the new message appears in the recipient's mailbox and updates the notification information in the user database so the recipient can be notified of the message.</li> <li>• Places attachments larger than 2 KB in one of the <i>post_office\offfiles\fd0-F6</i> subdirectories and creates pointers from the message to its attachments. (For database efficiency, messages and distribution lists larger than 2 KB are also handled as attachments.)</li> <li>• Creates a Delivered status message in the appropriate priority 0-7 subdirectory of the MTA input queue in the recipient's post office. It also communicates the Delivered status message directly to the MTA by way of TCP/IP and when that transmission is successful, the copy the MTA input queue is deleted.</li> </ul>
10 POA for Recipient's Post Office		The POA for the recipient's post office communicates to the GroupWise client by way of TCP/IP that a new message has arrived.
11 Recipient's GroupWise Client		The Notify component of the recipient's GroupWise client notifies the recipient that a new message has arrived.
12 Recipient		Each recipient opens the message in the GroupWise client.
13 Recipient's GroupWise Client		Each recipient's GroupWise client communicates the Opened status message to the POA by way of TCP/IP.
14 POA for Recipient's Post Office		The POA for the recipient's post office communicates the status message to the MTA for the recipient's domain by way of TCP/IP.
15 MTA for Recipient's Domain		The MTA for the recipient's domain places the status message into the "in progress" ( <i>gwinprog</i> ) queue.
16 MTA for Recipient's Domain		The MTA for the recipient's domain communicates the status message to the MTA for the sender's domain by way of TCP/IP.

Stage	Icon	Description
17 MTA for Sender's Domain	 MTA	The MTA for the sender's domain places the status message into the MTA "in progress" ( <i>gwinprog</i> ) queue.
18 MTA for Sender's Domain	 MTA	The MTA for the sender's domain communicates the status message to the POA for the sender's post office by way of TCP/IP.
19 POA for Sender's Post Office	 POA	The POA for the sender's post office updates the sender's message database ( <i>msgnnn.db</i> ) with the Delivered status information (and possibly Opened as well if the recipient has opened the message).
20 POA for Sender's Post Office	 POA	The POA for the sender's post office communicates the status to the sender's GroupWise client by way of TCP/IP.
21 Sender		When the sender checks the sent items in his or her mailbox in the GroupWise client, the message displays a status of Delivered for each recipient (and possibly Opened as well if the recipient has opened the message).


## Message Delivery to and from the Internet

- Section 4.1, “TCP/IP Link: Outbound Transfer to the Internet Successful,” on page 35
- Section 4.2, “TCP/IP Link: Outbound Transfer to the Internet Delayed or Unsuccessful,” on page 38
- Section 4.3, “Mapped/UNC Link: Outbound Transfer to the Internet Successful,” on page 41
- Section 4.4, “Mapped/UNC Link: Outbound Transfer to the Internet Delayed or Unsuccessful,” on page 43
- Section 4.5, “TCP/IP Link: Inbound Transfer from the Internet Successful,” on page 46
- Section 4.6, “Mapped/UNC Link: Inbound Transfer from the Internet Successful,” on page 48









### 4.1 TCP/IP Link: Outbound Transfer to the Internet Successful










This message flow diagram shows how outbound messages travel through the GroupWise® directory structure to the Internet when there is a TCP/IP link between the MTA and the Internet Agent and when the Internet Agent can communicate successfully with the Internet host to which the message is addressed.

Figure 4-1 Message Flow When the TCP/IP Link is Open



**Table 4-1** Message Flow When the TCP/IP Link is Open Stages


Stage	Icon	Description
1 Sender		The user sends a message to recipients across the Internet by providing their Internet addresses.  In this diagram, the access mode setting for the local post office is Client/Server Only.
2 Sender's GroupWise Client		The GroupWise client communicates the message to the POA by way of TCP/IP.
3 POA for Sender's Post Office		The POA receives the message from the GroupWise client and performs the following actions for the sender: <ul style="list-style-type: none"> <li>• Adds the message to the message database (<code>msgnnn.db</code>) assigned to the sender.</li> <li>• Creates a pointer in the sender's user database (<code>userxxx.db</code>) so the message appears in the sender's mailbox as a sent item.</li> <li>• Places attachments larger than 2 KB in one of the <code>post_office\offiles\fd0-F6</code> subdirectories and creates pointers from the message to its attachments. (For database efficiency, messages and distribution lists larger than 2 KB are also handled as attachments.)</li> <li>• Creates a copy of the message in the appropriate priority 0-7 subdirectory of the MTA input queue in the sender's post office, in case the TCP/IP link to the MTA is currently closed.</li> </ul>
4 POA for Sender's Post Office		The POA then communicates the message to the MTA for the sender's domain by way of TCP/IP, and deletes the copy in the MTA input queue because the TCP/IP transfer to the MTA was successful.
5 MTA for Sender's Domain		The MTA for the sender's domain receives the message and places it into the MTA "in progress" ( <code>gwinprog</code> ) queue.
6 MTA for Sender's Domain		The MTA determines that the message must be sent out across the Internet. Because there is a TCP/IP link between the MTA and the Internet Agent, the MTA creates a copy of the message in the appropriate priority 0-7 subdirectory of the Internet Agent hold queue ( <code>mslocal\mshold\gatewayx\0-7</code> ), in case the TCP/IP link to the Internet Agent is currently closed.
7 MTA for Sender's Domain		The MTA then communicates the message to the Internet Agent for the sender's domain by way of TCP/IP, and deletes the copy in the Internet Agent holding queue because the TCP/IP transfer to the Internet Agent was successful.
8 Internet Agent for Sender's Domain		The Internet Agent receives the message and places it into the MTA output queue ( <code>wpcsout\gwid\0-7</code> ) on behalf of the MTA. The MTA output queue is the Internet Agent input queue.

Stage	Icon	Description
7 Internet Agent for Sender's Domain		<p>The Internet Agent scans its input queues according to the <i>Idle Sleep Duration</i> setting on the Gateway Time Settings page of the Internet Agent object in ConsoleOne®. The Internet Agent picks up the file in binary-encrypted format from the <code>wpcsout\gwid\0-7</code> directory and converts it.</p> <p>The Internet Agent encodes the message in MIME format with the appropriate encoding scheme.</p> <p>When the message file is built, the Internet Agent saves it with S as the first character of the filename and places the message file in the <code>domain\wpgate\gwia\send</code> directory for processing.</p>
10 Internet Agent for Sender's Domain		<p>While the Internet Agent is processing the message file in the send directory, it changes the first character of the filename to P. When processing is completed, the Internet Agent sends the message to the destination host across the Internet.</p>
11 Internet Agent for Sender's Domain		<p>If the Internet Agent receives a 250 OK SMTP reply code from the destination Internet host, it places a Transferred status message into the input queue of the MTA for the sender's domain in case the TCP/IP link to the Internet Agent is currently closed.</p>
12 Internet Agent for Sender's Domain		<p>The Internet Agent then communicates the Transferred status message to the MTA for the sender's domain by way of TCP/IP, and deletes the copy in the MTA input queue because the TCP/IP transfer to the MTA was successful.</p>
13 MTA for Sender's Domain		<p>The MTA for the sender's domain receives the Transferred status message and places it into the MTA "in progress" (<code>gwinprog</code>) queue for processing.</p>
14 MTA for Sender's Domain		<p>The MTA for the sender's domain communicates the Transferred status message to the POA for the sender's post office by way of TCP/IP.</p>
15 POA for Sender's Post Office		<p>The POA for the sender's post office updates the sender's message database (<code>msgnnn.db</code>) with the Transferred status information.</p>
16 POA for Sender's Post Office		<p>The POA for the sender's post office communicates the Transferred status to the sender's GroupWise client by way of TCP/IP.</p>
17 Sender		<p>When the sender checks the sent items in his or her mailbox in the GroupWise client, the message displays the Transferred status because the Internet Agent was able to sent it successfully.</p>



## 4.2 TCP/IP Link: Outbound Transfer to the Internet Delayed or Unsuccessful








This message flow diagram shows how outbound messages travel through the GroupWise directory structure to the Internet when there is a TCP/IP link between the MTA and the Internet Agent and when the Internet Agent cannot communicate successfully with the Internet host to which the message is addressed.









**Figure 4-2** Message Flow When the TCP/IP Link is Closed






**Table 4-2** Message Flow When the TCP/IP Link is Closed Stages

Stage	Icon	Description
1 Sender		The user sends a message to recipients across the Internet by providing their Internet addresses.  In this diagram, the access mode setting for the local post office is Client/Server Only.
2 Sender's GroupWise Client		The GroupWise client communicates the message to the POA by way of TCP/IP.

Stage	Icon	Description
3 POA for Sender's Post Office		<p>The POA receives the message from the GroupWise client and performs the following actions for the sender:</p> <ul style="list-style-type: none"> <li>• Adds the message to the message database (<i>msgnnn.db</i>) assigned to the sender.</li> <li>• Creates a pointer in the sender's user database (<i>userxxx.db</i>) so the message appears in the sender's mailbox as a sent item.</li> <li>• Places attachments larger than 2 KB in one of the <i>post_office\offiles\fd0-F6</i> subdirectories and creates pointers from the message to its attachments. (For database efficiency, messages and distribution lists larger than 2 KB are also handled as attachments.)</li> <li>• Creates a copy of the message in the appropriate priority 0-7 subdirectory of the MTA input queue in the sender's post office, in case the TCP/IP link to the MTA is currently closed.</li> </ul>
4 POA for Sender's Post Office		<p>The POA then communicates the message to the MTA for the sender's domain by way of TCP/IP, and deletes the copy in the MTA input queue because the TCP/IP transfer to the MTA was successful.</p>
5 MTA for Sender's Domain		<p>The MTA for the sender's domain receives the message and places it into the MTA "in progress" (<i>gwinprog</i>) queue.</p>
6 MTA for Sender's Domain		<p>The MTA determines that the message must be sent out across the Internet. Because there is a TCP/IP link between the MTA and the Internet Agent, the MTA creates a copy of the message in the appropriate priority 0-7 subdirectory of the Internet Agent hold queue (<i>mslocal\mshold\gatewayx\0-7</i>), in case the TCP/IP link to the Internet Agent is currently closed.</p>
7 MTA for Sender's Domain		<p>The MTA then communicates the message to the Internet Agent for the sender's domain by way of TCP/IP, and deletes the copy in the Internet Agent holding queue because the TCP/IP transfer to the Internet Agent was successful.</p>
8 Internet Agent for Sender's Domain		<p>The Internet Agent receives the message and places it into the MTA output queue (<i>wpcsout\gwid\0-7</i>) on behalf of the MTA. The MTA output queue is the Internet Agent input queue.</p>
9 Internet Agent for Sender's Domain		<p>The Internet Agent scans its input queues according to the <i>Idle Sleep Duration</i> setting on the Gateway Time Settings page of the Internet Agent object in ConsoleOne. The Internet Agent picks up the file in binary-encrypted format from the <i>wpcsout\gwid\0-7</i> directory and converts it.</p> <p>The Internet Agent encodes the message in MIME format with the appropriate encoding scheme.</p> <p>When the message file is built, the Internet Agent saves it with S as the first character of the filename and places the message file in the <i>domain\wpgate\gwia\send</i> directory for processing.</p>

Stage	Icon	Description
10 Internet Agent for Sender's Domain		While the Internet Agent is processing the message file in the send directory, it changes the first character of the filename to P. When processing is completed, the Internet Agent sends the message to the destination host across the Internet.
11 Internet Agent for Sender's Domain		If the Internet Agent does not receive a 250 OK SMTP reply code from the destination Internet host, the Internet Agent renames the P*. * message file back to S*. * and creates a file named R*. * that records the SMTP reply codes (error messages) in the <code>wpgate\gwia\result</code> directory. After the Internet Agent completes the communication with the destination host, it moves the S*. * message file from the send directory to the result directory along with the corresponding R*. * file.
12 Internet Agent for Sender's Domain		The Internet Agent analyzes the files in the result directory, comparing the SMTP reply codes in the R*. * file.  If the R*. * file has a temporary transmission error (meaning it has a 400-level SMTP reply code such as 450 Host Down), the Internet Agent moves the S*. * message file to the <code>defer</code> directory. Continue with Stage 13  If the R*. * file has a fatal error (meaning it has a 500-level SMTP reply code such as 550 Host Unknown), the Internet Agent deletes the S*. * file because it is undeliverable. Skip to Stage 14
13 Internet Agent for Sender's Domain		Based on the <i>Intervals to the Retry a Deferred Message</i> setting on the SMTP/MIME Settings property page of the Internet Agent object in ConsoleOne, the Internet Agent requeues the S*. * message file back into the send directory for reprocessing.
14 Internet Agent for Sender's Domain		After an S*. * message receives 400-level SMTP reply codes until the <i>Maximum Number of Hours to Retry a Deferred Message</i> setting is reached, or if a message receives 500-level SMTP reply codes, the Internet Agent deletes all related schedule files from the defer directory because the message is undeliverable. The Internet Agent then creates an Undeliverable status message in the MTA input queue ( <code>wpgate\gwia\wpcsin\0-7</code> ) in case the TCP/IP link to the MTA is currently closed.
15 Internet Agent for Sender's Domain		The Internet Agent then communicates the Transferred status message to the MTA for the sender's domain by way of TCP/IP, and deletes the copy in the MTA input queue because the TCP/IP transfer to the MTA was successful.
16 MTA for Sender's Domain		The MTA for the sender's domain receives the Transferred status message and places it into the MTA "in progress" ( <code>gwinprog</code> ) queue for processing.
17 MTA for Sender's Domain		The MTA for the sender's domain communicates the Transferred status message to the POA for the sender's post office by way of TCP/IP.




Stage	Icon	Description
18 POA for Sender's Post Office		The POA for the sender's post office updates the sender's message database ( <code>msgnnn.db</code> ) with the Transferred status information.
19 POA for Sender's Post Office		The POA for the sender's post office communicates the Transferred status to the sender's GroupWise client by way of TCP/IP.
20 Sender		When the sender checks the sent items in his or her mailbox in the GroupWise client, the message displays the Transferred status because the Internet Agent was able to send it successfully.








## 4.3 Mapped/UNC Link: Outbound Transfer to the Internet Successful








This message flow diagram shows how outbound messages travel through the GroupWise directory structure to the Internet when there is a mapped/UNC link between the MTA and the Internet Agent and when the Internet Agent can communicate successfully with the Internet host to which the message is addressed.

Figure 4-3 Message Flow When the Mapped Link is Open



**Table 4-3** Message Flow When the Mapped Link is Open Stages


Stage	Icon	Description
1 Sender		The user sends a message to recipients across the Internet by providing their Internet addresses.  In this diagram, the access mode setting for the local post office is Client/Server Only.
2 Sender's GroupWise Client		The GroupWise client communicates the message to the POA by way of TCP/IP.
3 POA for Sender's Post Office		The POA receives the message from the GroupWise client and performs the following actions for the sender: <ul style="list-style-type: none"> <li>• Adds the message to the message database (<code>msgnnn.db</code>) assigned to the sender.</li> <li>• Creates a pointer in the sender's user database (<code>userxxx.db</code>) so the message appears in the sender's mailbox as a sent item.</li> <li>• Places attachments larger than 2 KB in one of the <code>post_office\offiles\fd0-F6</code> subdirectories and creates pointers from the message to its attachments. (For database efficiency, messages and distribution lists larger than 2 KB are also handled as attachments.)</li> <li>• Creates a copy of the message in the appropriate priority 0-7 subdirectory of the MTA input queue in the sender's post office, in case the TCP/IP link to the MTA is currently closed.</li> </ul>
4 POA for Sender's Post Office		The POA then communicates the message to the MTA for the sender's domain by way of TCP/IP, and deletes the copy in the MTA input queue because the TCP/IP transfer to the MTA was successful.
5 MTA for Sender's Domain		The MTA for the sender's domain receives the message and places it into the MTA "in progress" ( <code>gwinprog</code> ) queue.
6 MTA for Sender's Domain		The MTA determines that the message must be sent out across the Internet. Because there is a mapped/UNC link between the MTA and the Internet Agent, the MTA places the message in its output queue in the Internet Agent's gateway directory ( <code>domain\wpgate\gwia\wpcout\gwid\0-7</code> ).
7 Internet Agent for Sender's Domain		The Internet Agent scans its input queues according to the <i>Idle Sleep Duration</i> setting on the Gateway Time Settings page of the Internet Agent object in ConsoleOne. The Internet Agent picks up the file in binary-encrypted format from the <code>wpcout\gwid\0-7</code> directory and converts it.  The Internet Agent encodes the message in MIME format with the appropriate encoding scheme.  When the message file is built, the Internet Agent saves it with S as the first character of the filename and places the message file in the <code>domain\wpgate\gwia\send</code> directory for processing.

Stage	Icon	Description
8 Internet Agent for Sender's Domain		While the Internet Agent is processing the message file in the send directory, it changes the first character of the filename to P. When processing is completed, the Internet Agent sends the message to the destination host across the Internet.
9 Internet Agent for Sender's Domain		If the Internet Agent receives a 250 OK SMTP reply code from the destination Internet host, it places a Transferred status message into the input queue of the MTA for the sender's domain.
10 MTA for Sender's Domain		Because of its mapped/UNC link with the Internet Agent, the MTA regularly scans its input queue in the Internet Agent's gateway directory based on the <i>Scan Cycle</i> setting on the Agent Settings page of the MTA object in ConsoleOne. It picks up the Transferred status messages and transfers them to its "in progress" ( <i>gwinprog</i> ) directory for processing.
11 MTA for Sender's Domain		The MTA for the sender's domain communicates the Transferred status messages to the POA for the sender's post office by way of TCP/IP.
12 POA for Sender's Post Office		The POA for the sender's post office updates the sender's message database ( <i>msgnnn.db</i> ) with the Transferred status information.
13 POA for Sender's Post Office		The POA for the sender's post office communicates the Transferred status to the sender's GroupWise client by way of TCP/IP.
14 Sender		When the sender checks the sent items in his or her mailbox in the GroupWise client, the message displays the Transferred status because the Internet Agent was able to sent it successfully.



## 4.4 Mapped/UNC Link: Outbound Transfer to the Internet Delayed or Unsuccessful








This message flow diagram shows how outbound messages travel through the GroupWise directory structure to the Internet when there is a mapped/UNC link between the MTA and the Internet Agent and when the Internet Agent cannot communicate successfully with the Internet host to which the message is addressed.









**Figure 4-4** Message Flow When the Mapped Link is Closed



**Table 4-4** Message Flow When the Mapped Link is Closed Stages

Stage	Icon	Description
1 Sender		The user sends a message to recipients across the Internet by providing their Internet addresses.  In this diagram, the access mode setting for the local post office is Client/Server Only.
2 Sender's GroupWise Client		The GroupWise client communicates the message to the POA by way of TCP/IP.

Stage	Icon	Description
3 POA for Sender's Post Office		<p>The POA receives the message from the GroupWise client and performs the following actions for the sender:</p> <ul style="list-style-type: none"> <li>• Adds the message to the message database (<code>msgnnn.db</code>) assigned to the sender.</li> <li>• Creates a pointer in the sender's user database (<code>userxxx.db</code>) so the message appears in the sender's mailbox as a sent item.</li> <li>• Places attachments larger than 2 KB in one of the <code>post_office\offiles\fd0-F6</code> subdirectories and creates pointers from the message to its attachments. (For database efficiency, messages and distribution lists larger than 2 KB are also handled as attachments.)</li> <li>• Creates a copy of the message in the appropriate priority 0-7 subdirectory of the MTA input queue in the sender's post office, in case the TCP/IP link to the MTA is currently closed.</li> </ul>
4 POA for Sender's Post Office		<p>The POA then communicates the message to the MTA for the sender's domain by way of TCP/IP, and deletes the copy in the MTA input queue because the TCP/IP transfer to the MTA was successful.</p>
5 MTA for Sender's Domain		<p>The MTA for the sender's domain receives the message and places it into the MTA "in progress" (<code>gwinprog</code>) queue.</p>
6 MTA for Sender's Domain		<p>The MTA determines that the message must be sent out across the Internet. Because there is a mapped/UNC link between the MTA and the Internet Agent, the MTA places the message in its output queue in the Internet Agent's gateway directory (<code>domain\wpgate\gwia\wpcsout\gwid\0-7</code>).</p>
7 Internet Agent for Sender's Domain		<p>The Internet Agent scans its input queues according to the <i>Idle Sleep Duration</i> setting on the Gateway Time Settings page of the Internet Agent object in ConsoleOne. The Internet Agent picks up the file in binary-encrypted format from the <code>wpcsout\gwid\0-7</code> directory and converts it.</p> <p>The Internet Agent encodes the message in MIME format with the appropriate encoding scheme.</p> <p>When the message file is built, the Internet Agent saves it with S as the first character of the filename and places the message file in the <code>domain\wpgate\gwia\send</code> directory for processing.</p>
8 Internet Agent for Sender's Domain		<p>While the Internet Agent is processing the message file in the send directory, it changes the first character of the filename to P. When processing is completed, the Internet Agent sends the message to the destination host across the Internet.</p>
9 Internet Agent for Sender's Domain		<p>If the Internet Agent does not receive a 250 OK SMTP reply code from the destination Internet host, the Internet Agent renames the P*.* message file back to S*.* and creates a file named R*.* that records the SMTP reply codes (error messages) in the <code>wpgate\gwia\result</code> directory. After the Internet Agent completes the communication with the destination host, it moves the S*.* message file from the send directory to the result directory along with the corresponding R*.* file.</p>

Stage	Icon	Description
10 Internet Agent for Sender's Domain		<p>The Internet Agent analyzes the files in the result directory, comparing the SMTP reply codes in the R*. * file.</p> <p>If the R*. * file has a temporary transmission error (meaning it has a 400-level SMTP reply code such as 450 Host Down), the Internet Agent moves the S*. * message file to the <code>defer</code> directory. Continue with Stage 11</p> <p>If the R*. * file has a fatal error (meaning it has a 500-level SMTP reply code such as 550 Host Unknown), the Internet Agent deletes the S*. * file because it is undeliverable. Skip to Stage 12</p>
11 Internet Agent for Sender's Domain		Based on the <i>Intervals to the Retry a Deferred Message</i> setting on the SMTP/MIME Settings property page of the Internet Agent object in ConsoleOne, the Internet Agent requeues the S*. * message file back into the send directory for reprocessing.
12 Internet Agent for Sender's Domain		After an S*. * message receives 400-level SMTP reply codes until the <i>Maximum Number of Hours to Retry a Deferred Message</i> setting is reached, or if a message receives 500-level SMTP reply codes, the Internet Agent deletes all related schedule files from the defer directory because the message is undeliverable. The Internet Agent then creates an Undeliverable status message for the MTA to pick up and return to the sender.
13 MTA for Sender's Domain		Because of its mapped/UNC link with the Internet Agent, the MTA scans its input queue in the Internet Agent's gateway directory based on the <i>Scan Cycle</i> setting on the Agent Settings page of the MTA object in ConsoleOne. The MTA picks up the Undeliverable status messages and transfers them to its "in progress" ( <code>gwinprog</code> ) directory for processing.
14 MTA for Sender's Domain		The MTA for the sender's domain communicates the Transferred status messages to the POA for the sender's post office by way of TCP/IP.
15 POA for Sender's Post Office		The POA for the sender's post office updates the sender's message database ( <code>msgnnn.db</code> ) with the Transferred status information.
16 POA for Sender's Post Office		The POA for the sender's post office communicates the Transferred status to the sender's GroupWise client by way of TCP/IP.
17 Sender		When the sender checks the sent items in his or her mailbox in the GroupWise client, the message displays the Transferred status because the Internet Agent was able to send it successfully.

## 4.5 TCP/IP Link: Inbound Transfer from the Internet Successful

This message flow diagram illustrates how inbound message flow from the Internet through the GroupWise directory structure to the GroupWise recipient. The link between the Internet Agent and the MTA for the recipient's domain is a TCP/IP link.

Figure 4-5 Message Flow in From the Internet









Table 4-5 Message Flow in From the Internet Stages

Stage	Actor	Action
1 Internet Agent for Recipient's Domain		An Internet user sends a message to a GroupWise user. The Internet Agent receives the message from the external Internet host and places the message file in the <code>wpgate\gwia\receive</code> directory.
2 Internet Agent for Recipient's Domain		The Internet Agent polls the receive directory according to the <i>Idle Sleep Duration</i> setting on the Gateway Time Settings page of the Internet Agent object in ConsoleOne. It picks up the message file, converts it to GroupWise format, and places a copy in the <code>wpgate\gwia\wpcsin\0-7</code> directory, where 0-7 is one of the priority subdirectories from 0-7. The Internet Agent puts messages only in the 4 directory, used for normal priority messages.
3 Internet Agent for Recipient's Domain		The Internet Agent then communicates the message to the MTA for the recipient's domain by way of TCP/IP. When the transmission is successful, it deletes the copy in the in the <code>wpgate\gwia\wpcsin\0-7</code> directory.
4 MTA for Recipient's Domain		The MTA for the recipient's domain receives the message and places it into the MTA "in progress" ( <code>gwinprog</code> ) queue.

Stage	Actor	Action
5 MTA for Recipient's Domain	 MTA	The MTA determines which post office in the domain the recipient is located in, then moves the message to that post office's hold queue ( <code>mslocal\mshold\postx\0-7</code> ).
6 MTA for Recipient's Domain	 MTA	The MTA for the recipient's domain then communicates the message to the POA in the recipient's post office by way of TCP/IP.
7 POA for Recipient's Post Office	 POA	When it receives the new message, the POA for the recipient's post office performs the following actions: <ul style="list-style-type: none"> <li>• Adds the message to the message database (<code>msgnnn.db</code> file) corresponding to the one assigned to the sender.</li> <li>• Creates a pointer in the recipient's user database (<code>userxxx.db</code> file), so the message appears in the recipient's Mailbox and updates the notification information in the user database so the recipient can be notified of the message.</li> <li>• Places attachments larger than 2 KB in one of the <code>post_office\offiles\fd0-F6</code> subdirectories and creates pointers from the message to its attachments. (For database efficiency, messages and recipient lists larger than 2 KB are also handled as attachments.)</li> </ul>
8 Recipient's GroupWise Client		The Notify component of the recipient's GroupWise client notifies the recipient that a new message has arrived.
8 Recipient		Each recipient opens the message in the GroupWise client.

## 4.6 Mapped/UNC Link: Inbound Transfer from the Internet Successful

This message flow diagram illustrates how inbound message flow from the Internet through the GroupWise directory structure to the GroupWise recipient. The link between the Internet Agent and the MTA for the recipient's domain is a mapped/UNC link.



Figure 4-6 Message Flow in From the Internet








Table 4-6 Message Flow in From the Internet Stages

Stage	Actor	Action
1 Internet Agent for Recipient's Domain		An Internet user sends a message to a GroupWise user. The Internet Agent receives the message from the external Internet host and places the message file in the <code>wpgate\gwia\receive</code> directory.
2 Internet Agent for Recipient's Domain		The Internet Agent polls the receive directory according to the <i>Idle Sleep Duration</i> setting on the Gateway Time Settings page of the Internet Agent object in ConsoleOne. It picks up the message file, converts it to GroupWise format, and places it in the <code>wpgate\gwia\wpcsin\0-7</code> directory, where 0-7 is one of the priority subdirectories from 0-7. The Internet Agent puts messages only in the 4 directory, used for normal priority messages.
3 MTA for Recipient's Domain		The MTA polls the <code>domain\wpgate\gwia\wpcsin\fd0-7F</code> directory based on the <i>Scan Cycle</i> setting on the Agent Settings page of the MTA object in ConsoleOne. It picks up the message file and moves it to its "in progress" ( <code>gwinprog</code> ) queue.
4 MTA for Recipient's Domain		The MTA determines which post office in the domain the recipient is located in, then moves the message to that post office's hold queue ( <code>mslocal\mshold\postx\0-7</code> ).

Stage	Actor	Action
5 MTA for Recipient's Domain	 MTA	The MTA for the recipient's domain then communicates the message to the POA in the recipient's post office by way of TCP/IP.
6 POA for Recipient's Post Office	 POA	<p>When it receives the new message, the POA for the recipient's post office performs the following actions:</p> <ul style="list-style-type: none"> <li>• Adds the message to the message database (<i>msgnnn.db</i> file) corresponding to the one assigned to the sender.</li> <li>• Creates a pointer in the recipient's user database (<i>userxxx.db</i> file), so the message appears in the recipient's Mailbox and updates the notification information in the user database so the recipient can be notified of the message.</li> <li>• Places attachments larger than 2 KB in one of the <i>post_office\offiles\fd0-F6</i> subdirectories and creates pointers from the message to its attachments. (For database efficiency, messages and recipient lists larger than 2 KB are also handled as attachments.)</li> </ul>
7 Recipient's GroupWise Client		The Notify component of the recipient's GroupWise client notifies the recipient that a new message has arrived.
8 Recipient		Each recipient opens the message in the GroupWise client.

# Message Delivery through a Modem Connection


GroupWise® client users can still access information in their mailboxes even when not connected to the network by running the GroupWise client in Remote mode.

- Section 5.1, ““Hit the Road” Process in Online Mode,” on page 51
- Section 5.2, “Modem Link through the Async Gateway in Remote Mode,” on page 52


## 5.1 “Hit the Road” Process in Online Mode






This message flow diagram illustrates how a user who will be away from the network prepares to access GroupWise from a remote location by downloading mailbox contents.

**Figure 5-1** Message Flow for Hit the Road



**Table 5-1** Message Flow for Hit the Road Stages


Stage	Icon	Description
1 Remote User		The GroupWise user runs Hit the Road in Online mode in order to request items from the master mailbox to be downloaded to the Remote mailbox in preparation for disconnecting from the master GroupWise system. For example, the user could be preparing a laptop computer for use away from the network.

Stage	Icon	Description
2 GroupWise Client in Online Mode		The GroupWise client prompts the user for the location to create the Remote mailbox and the types of items to download, then it transfers the request to the POA.
3 POA for Remote User's Post Office		The POA receives the request from the GroupWise client and performs the following actions: <ul style="list-style-type: none"> <li>• Gathers all folders from the GroupWise user's master mailbox (<code>msgnnn.db</code> and <code>userxxx.db</code>) so that it has somewhere to put the items requested by the user.</li> <li>• Gathers the requested items from the GroupWise user's master mailbox.</li> <li>• Gathers any attachments for requested items from the <code>post_office\offiles\fd0-F6</code> subdirectories in the GroupWise user's post office.</li> <li>• Gathers any other types of information requested by the GroupWise user, such as rules, address books, documents, and junk mail lists.</li> </ul>
4 POA for Remote User's Post Office		The POA compiles the information into a response file and transfers the response to the GroupWise client.
5 GroupWise Client in Online Mode		The GroupWise client receives the response and performs the following actions for the GroupWise user: <ul style="list-style-type: none"> <li>• Updates the GroupWise Remote message database (<code>msg.db</code>) with any items requested from the user's master mailbox.</li> <li>• Creates pointers in the GroupWise Remote user database (<code>user.db</code>) so the messages gathered from the master mailbox appear in the user's GroupWise mailbox when running in Remote mode.</li> <li>• Places any requested attachments larger than 2 KB in the <code>rofdata</code> directory and creates pointers from the message to its attachments. (For database efficiency, messages and distribution lists larger than 2 KB are also handled as attachments.)</li> <li>• Updates the Remote mailbox with any other types of information requested by the GroupWise user.</li> </ul> <p>The user's GroupWise Remote mailbox now contains current copies of requested items from the user's master mailbox.</p>
6 Remote User		The GroupWise client restarts in Remote mode and accesses the new Remote mailbox. The GroupWise user can now review current GroupWise mail in Remote mode after the connection to the master GroupWise system is no longer available.


## 5.2 Modem Link through the Async Gateway in Remote Mode








This message flow diagram illustrates how a GroupWise user in Remote mode can access the master GroupWise system through the GroupWise Async Gateway.





**Figure 5-2** Message Flow Through a Modem








**Table 5-2** Message Flow Through a Modem Stages



Stage	Icon	Description
1 Remote User		The GroupWise user, who is working in Remote mode, sends a message to another GroupWise user or creates a request for items from the master mailbox. The remote user's computer is not currently connected to the network or the user's master GroupWise system.

Stage	Icon	Description
2 GroupWise Client in Remote Mode		<p>When the remote GroupWise user sends a message to another GroupWise user, the GroupWise client performs the following actions in the user's Remote mailbox:</p> <ul style="list-style-type: none"> <li>• Adds the message to the message database (<code>msg.db</code>) on the user's remote computer.</li> <li>• Creates a pointer in the user database (<code>user.db</code>) so the message appears as a sent item in the Remote mailbox on the user's remote computer.</li> <li>• Places attachments larger than 2 KB in the <code>rofdata</code> directory and creates pointers from the message to its attachments on the user's remote computer. (For database efficiency, messages and distribution lists larger than 2 KB are also handled as attachments.)</li> <li>• Creates a copy of the message in the <code>wpcsin\1</code> subdirectory of the GroupWise client's remote input queue on the user's remote computer.</li> </ul> <p>When the remote GroupWise user sends a request for items from the master mailbox to be downloaded to the Remote mailbox, the GroupWise client places the request in the <code>wpcsin\1</code> subdirectory of the GroupWise client's remote input queue on the user's remote computer.</p>
3 GroupWise Client in Remote Mode		<p>When the remote GroupWise user initiates the modem connection, the GroupWise client polls its input queue (<code>wpcsin\1</code>) and compresses the outgoing messages and/or requests into a file. If the compressed file totals over 50 KB, additional compressed files are created.</p> <p>The GroupWise client moves the compressed message/request files into its output queue (<code>wpgwsend</code>) directory.</p>
4 GroupWise Client with Modem Connection		<p>The GroupWise client dials in to the gateway, logs in, then transmits the compressed message/request files across the modem connection to the GroupWise Async Gateway in the GroupWise system where the user's master mailbox is located.</p>
5 Async Gateway		<p>The GroupWise Async Gateway receives the message/request files and places them into its input queue (<code>wpgate\async\asyxxx\gwin\connection_id\cmp</code>) for processing.</p>
6 Async Gateway		<p>The Async Gateway decompresses the message/request files and moves them into the subdirectory for the remote user's connection with the master GroupWise system.</p>
7 Async Gateway		<p>With a TCP/IP link, the Async Gateway transfers the decompressed files to the MTA for the remote user's domain in the master GroupWise system.</p> <p>With a UNC/mapped link, the Async Gateway places the message/request files into the MTA's input queue (<code>wpgate\async\wpcsin\1</code>), where the MTA picks up the files.</p>
8 MTA for Remote User's Domain		<p>The MTA for the remote user's domain receives the message/request files and places them into the MTA "in progress" (<code>gwinprog</code>) queue.</p>

Stage	Icon	Description
9 MTA for Remote User's Domain		<p>The MTA for the remote user's domain then communicates the message/request files to the POA for the post office where the remote user's master mailbox is located.</p> <hr/> <p><b>NOTE:</b> This message flow diagram illustrates only the simplest case where the recipient is in the same post office as the remote user's master mailbox. If the remote user sends a message to a user in any other post office, the MTA routes the message to the appropriate destination.</p>
10 POA for Remote User's Post Office		<p>When the POA receives a message from the remote user, the POA performs the following actions to update the remote user's master mailbox:</p> <ul style="list-style-type: none"> <li>• Adds the message to the remote user's message database (<i>msgnnn.db</i>) in the Online mailbox.</li> <li>• Creates a pointer in the recipient's user database (<i>userxxx.db</i>) in the Online mailbox so that the new message appears in the recipient's mailbox and updates the notification information in the user database so the recipient can be notified of the message.</li> <li>• Places attachments larger than 2 KB in one of the <i>post_office\offiles\fd0-F6</i> subdirectories in the remote user's post office and creates pointers from the message to its attachments. (For database efficiency, messages and distribution lists larger than 2 KB are also handled as attachments.)</li> <li>• Creates a Delivered status message in the priority 1 subdirectory of the remote user's MTA input queue (<i>wpcsin</i>) in the post office.</li> </ul> <p>When the POA receives a request for items from the remote user's master mailbox, the POA performs the following actions:</p> <ul style="list-style-type: none"> <li>• Gathers the requested items from the remote user's master mailbox (<i>msgnnn.db</i>).</li> <li>• Gathers any attachments for requested items from the <i>post_office\offiles\fd0-F6</i> subdirectory in the remote user's post office.</li> <li>• Compiles the information into a response file and places it in the priority 1 subdirectory of the MTA input queue for return to the remote user.</li> </ul>
11 POA for Remote User's Post Office		<p>The POA for the remote user's post office communicates the Delivered status for messages and the response file for requests to the MTA for the remote user's domain. When the transfer is successful, the copies in the MTA input queue are deleted.</p>
12 MTA in Remote User's Domain		<p>The MTA for the remote user's domain places the status/response files into the MTA "in progress" (<i>gwinprog</i>) queue.</p>

Stage	Icon	Description
13 MTA in Remote User's Domain		<p>With a TCP/IP link, the MTA for the remote user's domain communicates the status/response files to the Async Gateway in the remote user's domain.</p> <p>With a UNC/mapped link, the MTA for the remote user's domain places the status/response files into the Async Gateway's input queue (<code>wpgate\async\asyxxx\wpcout\1</code>), where the Async Gateway picks up the files.</p> <p>When the MTA in the GroupWise Remote user's domain detects the response for the GroupWise Remote user, the MTA picks it up from its post office input queue and transfers it to its output queue in the Async Gateway directory under <code>wpgate</code> in the GroupWise Remote user's domain. The MTA output queue in the Async Gateway directory is the input queue for the Async Gateway.</p>
14 Async Gateway		<p>The Async Gateway places the status/response files into the MTA output queue (<code>wpgate\async\wpcout\asyxxx\connection_id\1</code>) of the Async Gateway directory.</p>
15 Async Gateway		<p>If the modem connection to the remote user is still active, the Async Gateway compresses the status/response files and moves them to the <code>cmp</code> directory.</p> <p>If the modem connection is no longer available, the status/response files wait in the <code>connection_id\1</code> subdirectory until a new connection is established by the remote user.</p>
16 Async Gateway with Modem Connection		<p>The Async Gateway transmits the status/response files through the modem connection to the input queue (<code>wpgwrecv</code>) for the GroupWise client on the user's remote computer.</p>
17 GroupWise Client in Remote Mode		<p>The GroupWise client on the remote computer decompresses the status/response files and places them in its input queue (<code>wpcout\ofs\1</code>) on the user's remote computer.</p>



Stage	Icon	Description
<p>18</p> <p>GroupWise Client in Remote Mode</p>		<p>Taking the items from its input queue, the GroupWise client performs the following actions to update the Remote mailbox on the user's remote computer:</p> <ul style="list-style-type: none"> <li>• Updates the message database (<code>msg.db</code>) with any items requested from the remote user's master mailbox.</li> <li>• Creates pointers in the user database (<code>user.db</code>) so the messages gathered from the master mailbox appear in the Remote mailbox.</li> <li>• Places any requested attachments larger than 2 KB in the <code>rofd</code> directory and creates pointers from the message to its attachments. (For database efficiency, messages and distribution lists larger than 2 KB are also handled as attachments.)</li> <li>• Updates the remote Address Book (<code>wprof.db</code>) to synchronize it with the Address Book in the remote user's master GroupWise system.</li> </ul> <p>The user's Remote mailbox now contains current copies of requested items from the remote user's master mailbox, plus any messages received in the user's master mailbox from other GroupWise users.</p>
<p>15</p> <p>Remote User</p>		<p>The GroupWise user can now review current GroupWise mail when the modem connection to the master GroupWise system is no longer available.</p>




# Administrative Database Update

# 6


ConsoleOne® and the agents handle database updates throughout the GroupWise® system.





This message flow diagram illustrates how an administrative message, such as a database update request, passes from ConsoleOne to the agents so that databases are updated throughout the GroupWise system.

**Figure 6-1** Administrative Message Flow through TCP/IP



**Table 6-1** Administrative Message Flow through TCP/IP Stages

Stage	Actor	Action
1 GroupWise Administrator		The administrator uses the GroupWise Administrator snap-in in ConsoleOne to add, modify, or delete a GroupWise object in a single-domain, single-post office GroupWise system.  An object could be a GroupWise user, resource, distribution list, post office, secondary domain, and so on.

Stage	Actor	Action
2 ConsoleOne		<p>ConsoleOne performs the following actions:</p> <ul style="list-style-type: none"> <li>• Updates the domain database (<code>wdomain.db</code>) to reflect the addition, modification, or deletion performed in ConsoleOne.</li> <li>• Creates an administrative message in the priority 2 subdirectory of the domain's MTA input queue (<code>wpcsin</code>) to replicate the update.</li> </ul>
3 MTA for Domain		<p>The MTA for the domain transfers the administrative message to the MTA “in progress” (<code>gwinprog</code>) queue. From there, the MTA communicates the administrative message to the POA in the post office by way of TCP/IP. The administrative message notifies the POA that a GroupWise object has been added, modified, or deleted.</p> <p>Historical Note: In earlier versions of GroupWise, this function of the POA was handled by a separate agent, the Administration Agent (ADA). The ADA no longer exists in GroupWise.</p>
4 POA for Post Office		<p>The POA creates a copy of the administrative message in the priority 2 subdirectory of the administrative input queue (<code>wpcout\ads</code>) in the post office. After the update is made successfully, the copy is deleted.</p>
5 POA for Post Office		<p>The POA updates the post office database (<code>wphost.db</code>) to reflect the addition, modification, or deletion performed in ConsoleOne and deletes the administrative message from its administrative input queue.</p>

# Directory Structure Diagrams

This part of *Troubleshooting 3: Message Flow and Directory Structure* helps you understand the structure of GroupWise® message transfer/storage directories (such as domains and post offices) and software installation directories.

- “Message Transfer/Storage Directories” on page 63
- “Agent Installation Directories” on page 107
- “Software Distribution Directory” on page 153
- “GroupWise Client Installation Directories” on page 171



# Message Transfer/Storage Directories

Message transfer and storage directories are the locations through which messages pass as they travel from user to user through your GroupWise® system.

- [Section 7.1, “Domain Directory,” on page 63](#)
- [Section 7.2, “Post Office Directory,” on page 70](#)
- [Section 7.3, “MTA Local Queue Directory,” on page 83](#)
- [Section 7.4, “Internet Agent Queue Directory,” on page 87](#)
- [Section 7.5, “WebAccess Agent Queue Directory,” on page 93](#)
- [Section 7.6, “Caching Mailbox Directory,” on page 96](#)
- [Section 7.7, “Remote Mailbox Directory,” on page 100](#)



























## 7.1 Domain Directory

---

 <i>domain</i>	Domain directory
 <i>wpcsin</i>	MTA input queue directory
 0	Live interactive requests
 1	Other interactive requests
 2	High priority messages
 3	High priority status responses
 4	Normal priority messages
 5	Normal priority status responses
 6	Low priority messages
 7	Low priority status responses
 <i>wptools</i>	Supporting program directory
 <i>wpgate</i>	GroupWise gateway directory
 <i>wpcout</i>	MTA output queue directory

---

---

 <code>ads</code>	MTA admin thread input queue directory
 <code>0</code>	Restart requests
 <code>1</code>	Directory synchronization requests
 <code>2</code>	Database updates
 <code>3</code>	Reserved; not currently used
 <code>4</code>	Reserved; not currently used
 <code>5</code>	Reserved; not currently used
 <code>6</code>	Reserved; not currently used
 <code>7</code>	Reserved; not currently used
 <code>css</code>	MTA input queue directory for administrative messages
 <code>0</code>	MTA restart requests
 <code>1</code>	Statistics requests
 <code>2</code>	Other non-priority administrative requests
 <code>3</code>	Reserved; not currently used
 <code>4</code>	Reserved; not currently used
 <code>5</code>	Reserved; not currently used
 <code>6</code>	Reserved; not currently used
 <code>7</code>	Reserved; not currently used
 <code>problem</code>	Directory for undeliverable messages
 <code>mtaname</code>	Domain name identifier
 <code>wpdomain.db</code>	Domain database
 <code>wpdomain.dc</code>	Data dictionary for 4.x domain databases
 <code>wphost.dc</code>	Data dictionary for 4.x post office databases
 <code>gwdom.dc</code>	Data dictionary for 5.x, 6.x, and 7 domain databases
 <code>gwpo.dc</code>	Data dictionary for 5.x, 6.x, and 7post office databases
 <code>viewcopy.log</code>	Log file recording view file updates for post offices

---

### 7.1.1 domain directory

Within the GroupWise system, a **domain** is hierarchically the highest level object. It organizes post offices into a logical grouping for addressing and routing purposes. Each user in the domain has an address that consists of the user's GroupWise user ID, the user's post office name, and the domain name (*user.post\_office.domain*). The explicit name is not displayed in the Address Book, but is stored in the domain database (`wpdomain.db`).

### 7.1.2 wpcsin directory

The `wpcsin` subdirectory in the **domain** is the MTA input queue in each domain. It contains eight priority subdirectories to handle different types of message traffic.



- Incoming user messages are queued by priority for routing to recipients' post offices in the local domain.
- Incoming status messages are queued by priority for routing to senders' post offices in the local domain.
- Outgoing administrative messages are queued for replication to other domains.
- In a routing domain, messages pass through this directory on their way to the next domain.

When a new message arrives, the MTA routes it to the appropriate destination.

For TCP/IP links, the MTA is notified immediately when a message arrives for processing. For mapped and UNC links, the MTA scans its input queue for messages to process. You can control the rate at which the MTA scans its input queues. See “[Adjusting MTA Polling of Input Queues in the Domain, Post Offices, and Gateways](#)” in “[Optimizing the MTA](#)” in the *GroupWise 7 Administration Guide*.

Historical Note: WP Office\*, the predecessor of GroupWise, was originally designed by WordPerfect Corporation\* (WPCorp\*). The Message Transfer Agent (MTA) was originally named the Connection Server (CS). Hence, the directory name `wpcs.in` for the MTA input queue. Some naming conventions were originally preserved for backward compatibility.

## 0 directory

The priority 0 subdirectory of the MTA input queue (`wpcs.in`) in the `domain` is for service requests that demand an immediate response from the MTA. For example:

- ConsoleOne<sup>®</sup> places restart requests and queue reconfiguration requests here for the MTA and gateways.
- MTAs for other domains route Busy Search requests through here when users in other domains check schedules of users in the local domain.

You can increase throughput for the priority 0 subdirectory. See “[Adjusting the Number of MTA Scanner Threads for the Domain and Post Offices](#)” in “[Optimizing the MTA](#)” in the *GroupWise 7 Administration Guide*.

## 1 directory

The priority 1 subdirectory of the MTA input queue (`wpcs.in`) in the `domain` is for service requests of the next highest priority. For example:

- ConsoleOne places directory synchronization requests here for the MTA admin thread.
- ConsoleOne places statistics requests here for the MTA to relay to the message logging module for processing.
- MTAs for other domains route remote GroupWise client requests through here when remote GroupWise users do not connect to the post office where their master mailboxes are located.

You can increase throughput for the priority 1 subdirectory. See “[Adjusting the Number of MTA Scanner Threads for the Domain and Post Offices](#)” in “[Optimizing the MTA](#)” in the *GroupWise 7 Administration Guide*.

## 2 directory

The priority 2 subdirectory of the MTA input queue (`wpcsin`) in the `domain` is for high priority messages. For example:

- MTAs for other domains place incoming high priority user messages here. The local MTA then routes the messages to recipients' post offices.
- MTAs for other domains place incoming administrative messages here to replicate database updates in the local domain.
- The MTA admin thread places outgoing administrative messages here to replicate database updates to other domains.

You can increase throughput for the priority 2 and 3 subdirectories. See “[Adjusting the Number of MTA Scanner Threads for the Domain and Post Offices](#)” in “[Optimizing the MTA](#)” in the *GroupWise 7 Administration Guide*.

## 3 directory

The priority 3 subdirectory of the MTA input queue (`wpcsin`) in the `domain` is for high priority status messages routed back to senders in local post offices.

For example, MTAs for other domains place status responses to high priority user messages here. The local MTA then routes the status messages to senders' post offices, so senders' mailboxes can be updated with current message status.

You can increase throughput for the priority 2 and 3 subdirectories. See “[Adjusting the Number of MTA Scanner Threads for the Domain and Post Offices](#)” in “[Optimizing the MTA](#)” in the *GroupWise 7 Administration Guide*.

## 4 directory

The priority 4 subdirectory of the MTA input queue (`wpcsin`) in the `domain` is for normal priority user messages routed to recipients in local post offices.

For example, MTAs for other domains place normal priority user messages here. The local MTA then routes the messages to recipients' post offices. Most messages in your GroupWise system pass through the priority 4 subdirectory.

You can increase throughput for the priority 4 subdirectory. See “[Adjusting the Number of MTA Scanner Threads for the Domain and Post Offices](#)” in “[Optimizing the MTA](#)” in the *GroupWise 7 Administration Guide*.

## 5 directory

The priority 5 subdirectory of the MTA input queue (`wpcsin`) in the `domain` is for normal priority status messages routed back to senders in local post offices.

For example, MTAs for other domains place status responses to normal priority user messages here. The local MTA then routes the status messages to senders' post offices, so senders' mailboxes can be updated with current message status.

## 6 directory

The priority 6 subdirectory of the MTA input queue (`wpcsin`) in the `domain` is for low priority user messages routed to recipients in local post offices.

For example, MTAs for other domains place low priority user messages here. The local MTA then routes the messages to recipients' post offices.

## 7 directory

The priority 7 subdirectory of the MTA input queue (`wpcsin`) in the `domain` is for low priority status messages routed back to senders in local post offices.

For example, MTAs for other domains place status responses to low priority user messages here. The local MTA then routes the status messages to senders' post offices, so senders' mailboxes can be updated with current message status.

### 7.1.3 wptools directory

The `wptools` subdirectory in the `domain` contains programs that support GroupWise administration.

Historical Note: WP Office, the predecessor of GroupWise, was originally designed by WordPerfect Corporation (WPCorp). Hence, the `wp` in `wptools`. Some naming conventions were originally preserved for backward compatibility.

### 7.1.4 wpgate directory

The `wpgate` subdirectory in the `domain` contains a subdirectory for each GroupWise gateway you have installed in your GroupWise system. For a list of gateways, see [GroupWise Gateways \(http://www.novell.com/documentation/gateways\)](http://www.novell.com/documentation/gateways). GroupWise 5.5 gateways can be used with GroupWise 6.x and 7.

### 7.1.5 wpcout directory

The `wpcout` subdirectory in the `domain` is the MTA output queue in each domain. It contains subdirectories that function as input queues for the processes to which the MTA delivers messages.

Historical Note: WP Office, the predecessor of GroupWise, was originally designed by WordPerfect Corporation (WPCorp). The Message Transfer Agent (MTA) was originally named the Connection Server (CS). Hence, the directory name `wpcout` for the MTA output queue. Some naming conventions were originally preserved for backward compatibility.

## ads directory

The `ads` subdirectory of the MTA output queue (`wpcout`) in the `domain` is the input queue for the MTA admin thread in each domain. It contains priority subdirectories where incoming administrative messages are queued for processing. When a new administrative message arrives, the MTA admin thread performs the requested action.

Historical Note: The MTA admin thread was previously part of a separate agent, the Administration Agent (ADA), which was originally named the Administration Server (ADS). Hence, the directory name `ads`. Some naming conventions were originally preserved for backward compatibility.

## 0 directory

The priority 0 subdirectory of the MTA admin thread input queue (`wpcsout\ads`) in the **domain** is for service requests that demand an immediate response from the MTA admin thread.

For example, when you create or delete a post office in ConsoleOne, a restart request is placed here. The domain MTA admin thread processes the request and then restarts.

## 1 directory

The priority 1 subdirectory of the MTA admin thread input queue (`wpcsout\ads`) in the **domain** is for service requests of the next highest priority.

## 2 directory

The priority 2 subdirectory of the MTA admin thread input queue (`wpcsout\ads`) in the **domain** is for high priority administrative messages. For example:

- The MTA places administrative messages from other domains here. The administrative messages might instruct the MTA admin thread to add, modify, or delete users, post offices, or other objects in the domain. The MTA admin thread then processes the messages and makes the specified updates.
- When you use the Synchronize utility in ConsoleOne, a synchronization request is placed here. The MTA admin thread then resends the specified administrative messages to produce the required database updates.

## css directory

The `css` subdirectory of the MTA output queue (`wpcsout`) in the **domain** is processed by a specialized MTA thread that responds to requests regarding its own configuration. It contains the eight standard priority subdirectories.

Historical Note: In an earlier version of GroupWise, the Message Transfer Agent (MTA) was called the Connection Server (CS) and this specialized subprocess was called the Connection Server Server (css). Some naming conventions were originally preserved for backward compatibility.

## 0 directory

The priority 0 subdirectory of the CSS input queue (`wpcsout\css`) in the **domain** is for service requests that demand an immediate response from the MTA.

For example, when you restart the MTA at the MTA agent console or in ConsoleOne, a restart request is placed here. The MTA processes the request and restarts.

## 1 directory

The priority 1 subdirectory of the CSS input queue (`wpcsout\css`) in the **domain** is for service requests of the next highest priority.

For example, each time the statistics are updated on the MTA agent console, a statistics request is placed here. The MTA then gathers the statistics and displays them on the MTA agent console.

## 2 directory

The priority 2 subdirectory of the css input queue (`wpcssout\css`) in the `domain` is for non-priority requests.

### problem directory

The `problem` subdirectory of the MTA output queue (`wpcssout`) in the `domain` is where the MTA places message files that cannot be delivered because they are damaged in some way. Message files in the problem directory must be handled by the GroupWise administrator. See “[Message Is Dropped in the problem Directory in the Domain](#)” in *GroupWise 7 Troubleshooting 2: Solutions to Common Problems*.

## 7.1.6 mtaname file

The `mtaname` file in the `domain` provides the domain name associated with the domain directory structure. This can help you locate the domain information for the directory structure in ConsoleOne. It can also help you check links between MTAs.

## 7.1.7 wpdomain.db file

The `wpdomain.db` file in the `domain` is the domain database. It contains all administrative information for the domain.

In the primary domain, the `wpdomain.db` file contains all administrative information for your entire GroupWise system (all its domains, post offices, users, and so on). Because the `wpdomain.db` file in the primary domain is so crucial, you should back it up regularly and keep it secure. (You can re-create your entire GroupWise system from the primary domain `wpdomain.db` file; however, if the primary domain `wpdomain.db` file becomes unusable, you can no longer make administrative updates to your GroupWise system.)

In a secondary domain, the `wpdomain.db` file contains administrative information about that secondary domain only.

In GroupWise 7, 6.x, and 5.x domains, the data dictionary for the `wpdomain.db` file is the `gwdom.dc` file. In GroupWise 4.x domains, the data dictionary is the `wpdomain.dc` file. As a result, `wpdomain.db` files have different structures (schemas) depending on whether they were created for 7/6.x/5.x or 4.x domains.

Historical Note: WP Office, the predecessor of GroupWise, was originally designed by WordPerfect Corporation (WPCorp). Hence, the `wp` in `wpdomain.db`. Some naming conventions were originally preserved for backward compatibility.

## 7.1.8 wpdomain.dc file

The `wpdomain.dc` file in the `domain` is the data dictionary for rebuilding GroupWise 4.x domain databases (`wpdomain.db` files) in secondary domains.

If the `wpdomain.dc` file is missing from the primary domain, you cannot rebuild GroupWise 4.x secondary domains. The original `wpdomain.dc` file is located in the `domain` subdirectory of the software distribution directory or on the GroupWise CD.

Historical Note: WP Office, the predecessor of GroupWise, was originally designed by WordPerfect Corporation (WPCorp). Hence, the `wp` in `wpdomain.dc`. Some naming conventions were originally preserved for backward compatibility.

## 7.1.9 wphost.dc file

The `wphost.dc` file in the `domain` is the data dictionary for rebuilding GroupWise 4.x post office databases (`wphost.db` files).

If the `wphost.dc` file is missing from a domain, you cannot rebuild GroupWise 4.x post offices in that domain. The original `wphost.dc` file is located in the `domain` directory of the software distribution directory or on the GroupWise CD.

Historical Note: WP Office, the predecessor of GroupWise, was originally designed by WordPerfect Corporation (WPCorp). Post offices were originally called hosts. Hence, the name `wphost.dc`. Some naming conventions were originally preserved for backward compatibility.

## 7.1.10 gwdom.dc file

The `gwdom.dc` file in the `domain` is the data dictionary for creating and rebuilding GroupWise 7, 6.x, and 5.x domain databases (`wpdomain.db` files) in secondary domains.

If the `gwdom.dc` file is missing from the primary domain, you cannot create or rebuild GroupWise 7/6.x/5.x secondary domains. The original `gwdom.dc` file is located in the `domain` directory of the software distribution directory or on the GroupWise distribution media.

## 7.1.11 gwpo.dc file

The `gwpo.dc` file in the `domain` is the data dictionary for creating and rebuilding GroupWise 7, 6.x, and 5.x post office databases (`wphost.db` files).

If the `gwpo.dc` file is missing from a domain, you cannot create or rebuild GroupWise 7/6.x/5.x post offices in that domain. The original `gwpo.dc` file is located in the `domain` directory of the software distribution directory or on the GroupWise distribution media.

## 7.1.12 viewcopy.log file

The `viewcopy.log` file in the `domain` is created by the GroupWise Installation program if you update the Windows client software and the Installation program is unable to copy the view files to any post offices in the domain. You can manually update the view files later, as described in “[Refreshing the Client View Files in the Post Office](#)” in “[Post Offices](#)” in the *GroupWise 7 Administration Guide*.

## 7.2 Post Office Directory



































`post_office`

Post office directory






























---

---

 wpcsin	MTA input queue directory
 0	Live interactive requests
 1	Other interactive requests
 2	High priority messages
 3	High priority status responses
 4	Normal priority messages
 5	Normal priority status responses
 6	Low priority messages
 7	Low priority status responses
 gwdms	Document Management Services directory
 dmsh.db	Shared Document Management Services database
 lib0001-ff	Library directories
 dmxxnn01-ff.db	Document databases
 index	QuickFinder™ index for library
 archive	Archive directory for library
 docs	Large document directory for library
 fd00-ff	Subdirectories for documents
 ofmsg	Message database directory
 msgnnn.db	As many as 255 message databases
 ngwdfrr.db	Deferred message database
 guardbak	Backup guardian database
 ofuser	User database directory
 userxxx.db	User databases (one per user)
 puxxxxxx.db	Databases for shared folders
 index	QuickFinder index for messages
 offiles	Attachment store directory
 fd0-f6	Subdirectories for attachments
 ofviews	GroupWise client view files
 ofwork	GroupWise working directory
 ofdirect	Remote direct connection directory
 oftemp	GroupWise temporary files
 wpcout	MTA output queue directory

---

---

 ofs	POA input queue directory
 0	Live interactive requests
 1	Other interactive requests
 2	High priority messages
 3	High priority status responses
 4	Normal priority messages
 5	Normal priority status responses
 6	Low priority messages
 7	Low priority status responses
 defer	Directory to temporarily store deferred messages
 mmdpqa.nnn	POA log files
 wprof50.db	Downloadable system Address Book
 ads	POA admin thread input queue directory
 0	Restart requests
 1	Directory synchronization requests
 2	Database updates
 3	Reserved; not currently used
 4	Reserved; not currently used
 5	Reserved; not currently used
 6	Reserved; not currently used
 7	Reserved; not currently used
 chk	GWCheck working directory
 0-3	GWCheck priority subdirectories
 defer	GWCheck subdirectory for deferred database maintenance requests
 problem	Directory for undeliverable messages
 wphost.db	Post office database
 gwpo.dc	Data dictionary for GroupWise 7/6.x/5.x post office databases
 ngwguard.db	Guardian database
 ngwguard.dc	Data dictionary for databases
 ngwguard.fbk	Guardian database backup
 ngwguard.rfl	Guardian database roll forward log
 ngwcheck.db	GWCheck control database

---



## 7.2.1 *post\_office* directory

Conceptually, a **post office** contains mailboxes for a set of network users. The users on the post office send and receive messages through their mailboxes.

Physically, a post office is a directory structure on a network file server. The directory structure contains subdirectories and databases that store messages and the information used to distribute the messages.

## 7.2.2 *wpcsin* directory

The *wpcsin* subdirectory in the **post office** is the MTA input queue in each post office. It contains eight priority subdirectories to handle different types of message traffic.

- Outgoing user messages are queued by priority for routing to recipients in other post offices.
- Outgoing status messages are queued by priority for routing back to senders' post offices.
- Outgoing Busy Search requests are queued for routing to other post offices so users' schedules can be checked.
- Remote GroupWise client requests are queued for routing to remote GroupWise users' master mailboxes.

When a new message arrives, the MTA routes it to the appropriate destination.

For mapped and UNC links, the MTA scans its input queue for messages to process. You can control the rate at which the MTA scans its input queues. See “[Adjusting MTA Polling of Input Queues in the Domain, Post Offices, and Gateways](#)” in “[Optimizing the MTA](#)” in the *GroupWise 7 Administration Guide*.

For TCP/IP links, the POA passes messages to the MTA via TCP/IP. A copy is kept in the MTA input queue until the POA has successfully transferred the message.

Historical Note: WP Office, the predecessor of GroupWise, was originally designed by WordPerfect Corporation (WPCorp). The Message Transfer Agent (MTA) was originally named the Connection Server (CS). Hence, the directory name *wpcsin* for the MTA input queue. Some naming conventions were originally preserved for backward compatibility.

### 0 directory

The priority 0 subdirectory of the MTA input queue (*wpcsin*) in the **post office** is for service requests that demand an immediate response from the MTA.

For example, the GroupWise client places Busy Search requests here. The MTA then routes the requests to the appropriate post offices, so users' schedules can be checked.

You can increase throughput for the priority 0 subdirectory. See “[Adjusting the Number of MTA Scanner Threads for the Domain and Post Offices](#)” in “[Optimizing the MTA](#)” in the *GroupWise 7 Administration Guide*.

### 1 directory

The priority 1 subdirectory of the MTA input queue (*wpcsin*) in the **post office** is for service requests of the next highest priority. For example:

- Remote with a direct connection places requests here for routing to remote GroupWise users' master mailboxes.
- The POA places outgoing status messages to remote GroupWise users here for routing to the Async Gateway.

You can increase throughput for the priority 1 subdirectory. See “[Adjusting the Number of MTA Scanner Threads for the Domain and Post Offices](#)” in “[Optimizing the MTA](#)” in the *GroupWise 7 Administration Guide*.

## 2 directory

The priority 2 subdirectory of the MTA input queue (`wpcs.in`) in the **post office** is for high priority user messages routed to recipients in other post offices, domains, or systems.

For example, the GroupWise client places high priority user messages here. The MTA then routes the messages to the appropriate destinations.

You can increase throughput for the priority 2 and 3 subdirectories. See “[Adjusting the Number of MTA Scanner Threads for the Domain and Post Offices](#)” in “[Optimizing the MTA](#)” in the *GroupWise 7 Administration Guide*.

## 3 directory

The priority 3 subdirectory of the MTA input queue (`wpcs.in`) in the **post office** is for high priority status messages routed back to senders in other post offices, domains, or systems.

For example, the GroupWise client and local POA place status responses to high priority user messages here. The MTA then routes the status messages to the appropriate post offices, so senders' mailboxes can be updated with current message status.

You can increase throughput for the priority 2 and 3 subdirectories. See “[Adjusting the Number of MTA Scanner Threads for the Domain and Post Offices](#)” in “[Optimizing the MTA](#)” in the *GroupWise 7 Administration Guide*.

## 4 directory

The priority 4 subdirectory of the MTA input queue (`wpcs.in`) in the **post office** is for normal priority user messages routed to recipients in other post offices, domains, or systems.

For example, the GroupWise client places normal priority user messages here. The MTA then routes the messages to the appropriate destinations. Most messages in your GroupWise system pass through the priority 4 subdirectory.

You can increase throughput for the priority 4 subdirectory. See “[Adjusting the Number of MTA Scanner Threads for the Domain and Post Offices](#)” in “[Optimizing the MTA](#)” in the *GroupWise 7 Administration Guide*.

## 5 directory

The priority 5 subdirectory of the MTA input queue (`wpcs.in`) in the **post office** is for normal priority status messages routed back to senders in other post offices, domains, or systems.

For example, the GroupWise client and local POA place status responses to normal priority user messages here. The MTA then routes the status messages to the appropriate post offices, so senders' mailboxes can be updated with current message status.

## 6 directory

The priority 6 subdirectory of the MTA input queue (`wpcsin`) in the **post office** is for low priority user messages routed to recipients in other post offices, domains, or systems.

For example, the GroupWise client places low priority user messages here. The MTA then routes the messages to the appropriate destinations.

## 7 directory

The priority 7 subdirectory of the MTA input queue (`wpcsin`) in the **post office** is for low priority status messages routed back to senders in other post offices, domains, or systems.

For example, the GroupWise client and local POA place status responses to low priority user messages here. The MTA then routes the status messages to the appropriate post offices, so senders' mailboxes can be updated with current message status.

### 7.2.3 gwdms directory

The `gwdms` subdirectory in the **post office** is the Document Management Services (DMS) directory in each post office. It contains the document libraries associated with the post office.

#### **dmsh.db file**

The `dmsh.db` file in the document management subdirectory (`gwdms`) in the **post office** is a database shared by all libraries in the post office. It contains a list of all available libraries and lookup tables for each library.

#### **lib0001-ff directories**

The `lib0001-ff` subdirectories in the `gwdms` subdirectory in the **post office** contain the libraries for the post office, with one library per directory. You can create a maximum of 256 libraries in a post office.

#### **dmxxnn01-ff.db files**

The `dmxxnn01-ff.db` files in the library subdirectories (`lib0001-ff`) in the **post office** are databases for library and document information.

The `nn` in the filenames represents the partition number, which is generated by a hashing algorithm to guarantee uniqueness.

The `01-ff` in the filenames represents the library number, matching the number on the library directory in which the database is found.

#### **dmsdnn01-ff.db file**

The `dmsdnn01-ff.db` file in each library holds system data for the library, such as library configuration information.

### **dmddnn01-ff.db file**

The `dmddnn01-ff.db` file in each library holds document data for the library. Document data is the document property information for documents in the library.

### **dmdl01-ff.db file**

The `dmdl01-ff.db` file in each library holds document logging data for the library. Document logging data records all activities performed on documents in the library.

### **index directory**

The `index` subdirectories in the library subdirectories (`lib0001-ff`) in the **post office** contain the QuickFinder index for the documents contained in the library.

### **archive directory**

The `archive` subdirectories in the library subdirectories (`lib0001-ff`) in the **post office** contain an array of subdirectories for holding archived documents. The subdirectories are numbered sequentially. When the first archive subdirectory reaches its maximum allowable size, archived documents are stored in the next sequential directory, and so on.

### **docs directory**

The `docs` subdirectories in the library subdirectories (`lib0001-ff`) in the **post office** contain an array of subdirectories for storing documents.

### **fd0-ff directories**

The `fd0-ff` subdirectories in the `docs` subdirectory in the **post office** store documents that are equal to or greater than 2 KB in size. The `0-ff` variable represents hexadecimal number 0 through `ff`, so the subdirectories are named `fd0` through `fdff`. The document databases (`dmxxnn01-ff.db` files) contain pointers to documents stored in the subdirectories of the `docs` directory.

## **7.2.4 ofmsg directory**

The `ofmsg` subdirectory in the **post office** contains as many as 255 databases where messages are stored. It serves as centralized storage for all users in the post office. A message must be stored only once to be delivered to any number of users in the same post office.

**Historical Note:** An earlier version of GroupWise, designed by WordPerfect Corporation (WPCorp), was named WP Office. Hence, the `of` in `ofmsg`. Some naming conventions were originally preserved for backward compatibility.

### **msgnnn.db file**

The `msgnnn.db` files in the `ofmsg` subdirectory in the **post office** are the message databases where users' messages smaller than 2 KB are stored. To increase database efficiency, messages, attachments, and recipient lists equal to or greater than 2 KB are stored outside the `msgnnn.db` files in an array of subdirectories in the `offiles` directory. After the 2 KB limit is reached, only pointers are stored in the message databases.

The `nnn` variable in the database names is a three-digit number from 0 to 254. A hashing algorithm takes each user's GroupWise file ID (FID) to derive which database the user's outgoing mail is assigned to. The contents of the messages databases are encrypted so the text of message can only be read through GroupWise.

Multiple users are assigned to the same message database. You can use GWCheck to determine which database a specific user has been assigned to. See “[GroupWise Check](#)” in “[Standalone Database Maintenance Programs](#)” in the *GroupWise 7 Administration Guide*.

### **ngwdfrr.db file**

The `ngwdfrr.db` file in the `ofmsg` subdirectory in the **post office** holds deferred messages that users have specified for delivery at a later time. When users delay delivery on messages, the messages are transferred to the receiving post office and held in the `ngwdfrr.db` file until the delay expires.

Historical Note: Earlier versions of GroupWise handled deferred messages through the `ofpend` directory in the post office.

### **guardbak directory**

The `guardbak` subdirectory in the `ofmsg` subdirectory in the **post office** holds a backup copy of the `ngwguard.fbz` file.

## **7.2.5 ofuser directory**

The `ofuser` subdirectory in the **post office** contains a separate database (mailbox) for each GroupWise user.

Historical Note: An earlier version of GroupWise, designed by WordPerfect Corporation (WPCorp), was named WP Office. Hence, the `of` in `ofuser`. Some naming conventions were originally preserved for backward compatibility.

### **userxxx.db file**

The `userxxx.db` files in the `ofuser` subdirectory in the **post office** are user databases where the contents of users’ mailboxes are stored, as displayed in the GroupWise client. In addition, each user database contains:

- Some personal GroupWise client program settings
- Personal appointments
- Personal groups
- Personal notes
- Rules

Personal client settings that remain the same regardless of what workstation a user logs in to are stored in the user database. Personal client settings that are customized for a particular workstation are stored in the Windows\* registry.

The `xxx` variable in the database names is each user’s GroupWise file ID (FID).

### **puxxxxx.db file**

The `puxxxxx.db` files in the `ofuser` subdirectory in the **post office** are databases for replicated items such as shared folders. These databases prevent conflicts between user names of shared items from users in other post offices and user names in the local post office.

## index directory

The `index` subdirectory in the `ofuser` subdirectory in the `post office` contains the QuickFinder index for users' messages stored in the post office.

## 7.2.6 offiles directory

The `offiles` subdirectory in the `post office` contains subdirectories for messages, attachments, and recipient lists that are equal to or greater than 2 KB in size. These larger messages, attachments, and recipient lists are stored outside the actual message databases in the `ofmsg` directory to increase database efficiency.

Historical Note: An earlier version of GroupWise, designed by WordPerfect Corporation (WPCorp), was named WP Office. Hence, the `of` in `offiles`. Some naming conventions were originally preserved for backward compatibility.

### fd0-f6 directories

The `fd0-f6` subdirectories in the `offiles` subdirectory in the `post office` store messages, attachments, and recipient lists that are equal to or greater than 2 KB in size. The `nm` variable represents hexadecimal number 0 through `f6`, so the subdirectories are named `fd0` through `fdf6`. The message databases (`msgnnn.db` files) contain pointers to messages, attachments, and recipient lists stored in the subdirectories of `offiles`.

## 7.2.7 ofviews directory

The `ofviews` subdirectory in the `post office` contains subdirectories for GroupWise client platforms. Within the platform-specific subdirectories (for example, `win`) are view (`*.vew`) files that create the various views displayed in the GroupWise client.

The `gwviewxx.ini` and `ofviewxx.ini` files configure the standard views on the menus where users select views. The `gwviewxx.ini` file configures GroupWise 7, 6.x, and 5.5 standard views. The `ofviewxx.ini` file configures standard views from earlier versions of GroupWise.

Historical Note: An earlier version of GroupWise, designed by WordPerfect Corporation (WPCorp), was named WP Office. Hence, the `of` in `ofviews`. Some naming conventions were originally preserved for backward compatibility.

## 7.2.8 ofwork directory

The `ofwork` subdirectory in the `post office` is a working directory for requests from the GroupWise client in Remote mode.

Historical Note: An earlier version of GroupWise, designed by WordPerfect Corporation (WPCorp), was named WP Office. Hence, the `of` in `ofwork`. Some naming conventions were originally preserved for backward compatibility.

## 7.2.9 ofdirect directory

The `ofdirect` subdirectory in the working directory (`ofwork`) in the `post office` is used by the GroupWise client in Remote mode for direct connections when the network is available.

Historical Note: An earlier version of GroupWise, designed by WordPerfect Corporation (WPCorp), was named WP Office. Hence, the `of` in `ofdirect`. Some naming conventions were originally preserved for backward compatibility.

## 7.2.10 ofttemp directory

The `ofttemp` subdirectory in the **post office** holds various temporary files such as the MIME files created during access by IMAP e-mail clients.

## 7.2.11 wpcout directory

The `wpcout` subdirectory in the **post office** is the MTA output queue in each post office. It contains subdirectories which function as input queues for the other agents to which the MTA delivers messages.

Historical Note: WP Office, the predecessor of GroupWise, was originally designed by WordPerfect Corporation (WPCorp). The Message Transfer Agent (MTA) was originally named the Connection Server (CS). Hence, the directory name `wpcout` for the MTA output queue. Some naming conventions were originally preserved for backward compatibility.

### ofs directory

The `ofs` subdirectory of the mta output queue (`wpcout`) in the **post office** is the POA input queue in each post office. It contains eight priority subdirectories to handle different types of message traffic.

- Incoming user messages are queued by priority for delivery to recipients' mailboxes in the local post office.
- Incoming status messages are queued by priority for delivery to senders' mailboxes in the local post office.
- Incoming Busy Search requests are queued for the POA to check users' schedules in the local post office.

The POA scans these priority subdirectories regularly. When a new message arrives, the POA processes the messages and performs the required actions.

### 0 directory

The priority 0 subdirectory of the POA input queue (`wpcout\ofs`) in the **post office** is for service requests that demand an immediate response from the POA.

For example, the MTA places Busy Search requests here so the POA can check recipients' schedules and quickly return the schedule information to the sender.

### 1 directory

The priority 1 subdirectory of the POA input queue (`wpcout\ofs`) in the **post office** is for service requests of the next highest priority.

For example, the MTA places requests from remote GroupWise users for items in their master mailboxes here. The POA then processes the messages and returns the requested items.

## 2 directory

The priority 2 subdirectory of the POA input queue (`wpcsout\ofs`) in the **post office** is for high priority user messages being delivered to recipients in the local post office.

For example, the MTA places high priority user messages here. The POA then updates the message databases and recipients' mailboxes.

## 3 directory

The priority 3 subdirectory of the POA input queue (`wpcsout\ofs`) in the **post office** is for high priority status messages coming back to senders in the local post office.

For example, the MTA places status responses to high priority user messages here. The POA then updates the message databases and senders' mailboxes with current message status.

## 4 directory

The priority 4 subdirectory of the POA input queue (`wpcsout\ofs`) in the **post office** is for normal priority user messages being delivered to recipients in the local post office.

For example, the MTA places normal priority user messages here. The POA then updates the message databases and recipients' mailboxes. Most messages in your GroupWise system pass through the priority 4 subdirectory.

## 5 directory

The priority 5 subdirectory of the POA input queue (`wpcsout\ofs`) in the **post office** is for normal priority status messages coming back to senders in the local post office.

For example, the MTA places status responses to normal priority user messages here. The POA then updates the message databases and senders' mailboxes with current message status.

## 6 directory

The priority 6 subdirectory of the POA input queue (`wpcsout\ofs`) in the **post office** is for low priority user messages being delivered to recipients in the local post office.

For example, the MTA places low priority messages here. The POA then updates the message databases and recipients' mailboxes.

## 7 directory

The priority 7 subdirectory of the POA input queue (`wpcsout\ofs`) in the **post office** is for low priority status messages coming back to senders in the local post office.

For example, the MTA places status responses to low priority user messages here. The POA then updates the message databases and senders' mailboxes with current message status.

## defer directory

The `defer` subdirectory of the POA input queue (`wpcsout\ofs`) in the **post office** is used to temporarily store deferred messages when the `ngwdfrr.db` database is locked. This might occur if backup software has locked the `ngwdfrr.db` database. After the `ngwdfrr.db` database is available again, deferred messages are written to the `ngwdfrr.db` database as usual.



## *mmdp*oa.*nnn* files

The *mmdp*oa.*nnn* files are POA log files. The POA creates log files to inform you of its processing and any problems it encounters. By default, these log files are created in the *wpc*sout\o*f*s directory. You can change the location if needed. See “Using POA Log Files” in “Post Office Agent” in the *GroupWise 7 Administration Guide* guide.

The first two digits of the filename represent the month, the next two digits represent the day of the month, and the next three characters indicate what program created the log. The three-digit extension is a sequence number for multiple log files created on the same day. For example, 0518p*o*a.002 is the second POA log file created on May 18.

## wprof50.db file

The wprov50.db file in the *wpc*sout\o*f*s directory is the downloadable system Address Book for Remote client users. By default, it is automatically re-created once a day to keep it up to date. See “Performing Nightly User Upkeep” in “Post Office Agent” in the *GroupWise 7 Administration Guide* guide.

## ads directory

The *ads* subdirectory of the MTA output queue (*wpc*sout) in the *post office* is the input queue for the POA admin thread in each post office. It contains priority subdirectories where administrative messages are queued for processing.

Historical Note: The POA admin thread was previously part of a separate agent, the Administration Agent (ADA), which was originally named the Administration Server (ADS). Hence, the directory name *ads*. Some naming conventions were originally preserved for backward compatibility.

### 0 directory

The priority 0 subdirectory of the POA admin thread input queue (*wpc*sout\*ads*) in the *post office* is for service requests that demand an immediate response from the POA admin thread.

### 1 directory

The priority 1 subdirectory of the POA admin thread input queue (*wpc*sout\*ads*) in the *post office* is for service requests of the next highest priority.

For example, a directory synchronization request that could not be performed when the POA admin thread received it in its domain input queue would be placed here in the post office for later processing.

### 2 directory

The priority 2 subdirectory of the POA admin thread input queue (*wpc*sout\*ads*) in the *post office* is for high priority administrative messages.

For example, a database update request that could not be performed when the POA admin thread received it in its domain input queue would be placed here in the post office for later processing.

## chk directory

The *chk* subdirectory of the MTA output queue (*wpc*sout) in the *post office* is the working directory where the multithreaded GWCheck process keeps temporary files during database

maintenance and where it tracks the activities of its various threads. The `defer` subdirectory is used when the `ngwcheck.db` database is locked, for example, by a backup program.

## problem directory

The `problem` subdirectory of the MTA output queue (`wpcsout`) in the **post office** is a holding area for damaged message files. Problem files are marked with an extension indicating which GroupWise agent placed each file in the problem directory.

You should check this directory periodically for problem files, resolve the problem, then place the files back into the appropriate queue for continued processing. For assistance, see “[Message Is Dropped in the problem Directory in the Post Office](#)” in “[Strategies for Message Delivery Problems](#)” in the *GroupWise 7 Troubleshooting 2: Solutions to Common Problems*.

## 7.2.12 wphost.db file

The `wphost.db` file in the **post office** is the post office database. It contains all administrative information for the post office. It also contains the Address Book for the post office.

In GroupWise 7, 6.x, and 5.x post offices, the data dictionary for the `wphost.db` file is the `gwpo.dc` file. In GroupWise 4.x post offices, the data dictionary is the `wphost.dc` file. As a result, `wphost.db` files have different structures (schemas) depending on whether they were created for GroupWise 7/6.x/5.x or 4.x post offices.

Historical Note: WP Office, the predecessor of GroupWise, was originally designed by WordPerfect Corporation (WPCorp). Post offices were originally called hosts. Hence, the name `wphost.db`. Some naming conventions were originally preserved for backward compatibility.

## 7.2.13 gwpo.dc file

The `gwpo.dc` file in the **post office** is the data dictionary for creating and rebuilding GroupWise 7, 6.x, and 5.x post office databases (`wphost.db` files).

If the `gwpo.dc` file is missing from a post office and its domain, you cannot create or rebuild GroupWise 7/6.x/5.x post offices in that domain. The original `gwpo.dc` file is located in the **domain** directory of the software distribution directory or on the GroupWise CD.

## 7.2.14 ngwguard.db file

The `ngwguard.db` file in the **post office** is the guardian database. See “[Information Stored in the Post Office](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.

## 7.2.15 ngwguard.dc file

The `ngwguard.dc` file in the **post office** is the data dictionary for building the following databases in the post office:

- `ngwguard.db` (guardian database)
- `dmxxxnn01-ff.db` (document management databases)
- `msgnnn.db` (message databases)
- `userxxx.db` (user databases)

- `puxxxxx.db` (databases for replicated items like shared folders)

## 7.2.16 ngwguard.fbk file

The `ngwguard.fbk` file in the **post office** is a “fall back” copy of the `ngwguard.db` file. If the `ngwguard.db` file becomes damaged, the `ngwguard.fbk` file, along with the `ngsguard.rfl` file, can be used to rebuild a valid, current `ngwguard.db` file. The `ngwguard.fbk` file is so important that an additional copy of it is kept in the `ofmsg\guardbak` subdirectory in case the copy in the post office directory is inadvertently deleted. See “Guardian Databases” in “Databases” in the *GroupWise 7 Administration Guide*.

## 7.2.17 ngwguard.rfl file














The `ngwguard.rfl` file in the **post office** is a roll-forward transaction log of every database transaction that has taken place since the last copy of the `ngwguard.fbk` file was created. See “Guardian Databases” in “Databases” in the *GroupWise 7 Administration Guide*.

## 7.2.18 ngwcheck.db

The `ngwcheck.db` file in the **post office** is the database that controls GWCheck’s multithreaded processing. It contains job and task records that are used to synchronize and summarize GWCheck requests as they progress.









## 7.3 MTA Local Queue Directory

---

 <code>mslocal</code>	MTA local working directory
 <code>mmdxxxx.nn</code>	MTA log files
 <code>msglog</code>	Message logging directory
 <code>mmdmsg.nn</code>	Message logging files
 <code>gwinprog</code>	MTA “in progress” queue directory
 <code>0-7</code>	Priority subdirectories
 <code>mshold</code>	MTA holding directory
 <code>domainms</code>	Processing directory for MTA
 <code>0-7</code>	Priority subdirectories
 <code>mtaname</code>	Location identifier
 <code>postx</code>	Holding directories for post offices
 <code>0-7</code>	Priority subdirectories
 <code>mtaname</code>	Location identifier

---

---

 <i>gatewayx</i>	Holding directories for gateways
 <i>0-7</i>	Priority subdirectories
 <i>mtaname</i>	Location identifier
 <i>domainx</i>	Holding directories for other domains
 <i>0-7</i>	Priority subdirectories
 <i>mtaname</i>	Location identifier
 <i>gmvscan</i>	Working directory for third-party virus scanning programs
 <i>mtaconv</i>	Work area for 5.x to 4.x conversion

---

### 7.3.1 mslocal directory

The `mslocal` directory is the MTA local working directory. The `/work` startup switch of the MTA specifies the location of the `mslocal` directory. It must be located on the hard disk of the server where the MTA runs so it is always accessible. Adequate disk space must be available to hold messages going to destinations that are temporarily closed.

Typical locations for the `mslocal` directory include:

- `sys:\system` on a NetWare® server
- `c:\` on a Windows server

To move the `mslocal` directory, stop the MTA, copy the `mslocal` directory, along with all of its subdirectories, to the new location. Then restart the MTA and specify the new location using the `/work` startup switch.

Historical Note: In earlier versions of GroupWise, the Message Transfer Agent (MTA) was called the Message Server (MS). Hence, the `ms` in `mslocal`. Some naming conventions were originally preserved for backward compatibility.

#### ***mmdxxx.nnn* files**

The `mmdxxx.nnn` files are MTA log files. The MTA creates log files to inform you of its processing and any problems it encounters. By default, these log files are created in the `mslocal` directory. You can change the location if needed. See “Using MTA Log Files” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*.

The first two digits of the filename represent the month; the next two digits represent the day of the month; the next three characters indicate what program created the log. The three-digit extension is a sequence number for multiple log files created on the same day. For example, `0518mta.002` is the second MTA log file created on May 18.

Historical Note: In earlier versions of GroupWise, the Message Transfer Agent (MTA) was called the Message Server (MS). Hence, the `ms` indicator representing the MTA. Some naming conventions were originally preserved for backward compatibility.

## 7.3.2 msglog directory

The `msglog` subdirectory contains message logging files. It is created when you turn on message logging. The MTA receiver threads log messages as they arrive so the MTA worker threads can process messages without having to scan the MTA input queues to look for work.

The resources used for message logging are configurable. See “[Optimizing the Routing Queue](#)” in “[Optimizing the MTA](#)” in the *GroupWise 7 Administration Guide*.

More detailed message logging by the MTA is also available, but is turned off by default. See “[Enabling MTA Message Logging](#)” in “[Configuring the MTA](#)” in the *GroupWise 7 Administration Guide*.

### **`mmdmsg.nnn` files**

The `mmdmsg.nnn` files in the message logging subdirectory (`msglog`) in the **MTA local directory** are used by the MTA to track messages in its “in progress” queue.

The first two digits of the filename represent the month; the next two digits represent the day of the month. The three-digit extension is a sequence number for multiple files created on the same day. For example, `0518msg.002` is the second message logging file created on May 18.

## 7.3.3 gwinprog directory

The `gwinprog` subdirectory is the MTA “in progress” queue. It contains eight priority subdirectories parallel to those found in `wpcsin`. All messages for recipients in the domain pass through `gwinprog`, no matter whether they arrived by way of TCP/IP or by way of message files deposited into the MTA input queue by a POA or another MTA.

The resources used to process the “in progress” queue are configurable. See “[Optimizing the Routing Queue](#)” in “[Optimizing the MTA](#)” in the *GroupWise 7 Administration Guide*.

## 7.3.4 mshold directory

The `mshold` subdirectory is a holding queue for messages addressed to domains, post offices, or gateways that are currently closed.

A location might be closed because its server is down or because the MTA is unable to communicate with it for any other reason. When a closed location is again open, the MTA moves messages from the holding queue back into the normal message flow.

Historical Note: In earlier versions of GroupWise, the Message Transfer Agent (MTA) was called the Message Server (MS). Hence, the `ms` in `mshold`. Some naming conventions were originally preserved for backward compatibility.

## 7.3.5 domainms directory

The `domainms` subdirectory in the holding directory (`mshold`) is used for internal processing by the MTA. It does not contain any files a GroupWise administrator needs to access.

Historical Note: In earlier versions of GroupWise, the Message Transfer Agent (MTA) was called the Message Server (MS). Hence, the `ms` in `domainms`. Some naming conventions were originally preserved for backward compatibility.

### 7.3.6 *postx* directories

The *postx* subdirectories in the holding directory (*mshold*) represent post offices in the domain. If a post office is closed, the MTA routes messages for that post office into its holding queue in *mshold*. When the post office is open, the MTA moves the messages from the holding queue back into the regular message flow. For more information, see [“Message Delivery to a Different Post Office” on page 19](#).

The name of the holding queue for each post office consists of the first three characters of the post office name, followed by four hashed characters to ensure uniqueness.

### 7.3.7 *gatewayx* directories

The *gatewayx* subdirectories in the holding directory (*mshold*) represent gateways in the domain. If a gateway is closed, the MTA routes messages for that gateway into its holding queue in *mshold*. When the gateway is open, the MTA moves the messages from the holding queue back into the regular message flow through the gateway.

The name of the holding queue for each gateway consists of the first three characters of the gateway name, followed by four hashed characters to ensure uniqueness.

### 7.3.8 *domainx* directories

The *domainx* subdirectories in the holding directory (*mshold*) represent domains to which the current domain has a direct link. If a domain is closed, the MTA routes messages for that domain into its holding queue in *mshold*. When the domain is open, the MTA moves the messages from the holding queue back into the regular message flow. For more information, see [“Message Delivery to a Different Domain” on page 27](#).

The name of the holding queue for each domain consists of the first three characters of the domain name, followed by four hashed characters to ensure uniqueness.

### 7.3.9 0-7 directories

The priority 0-7 subdirectories in each holding queue in the *mshold* subdirectory correspond to the priority 0-7 subdirectories located in each domain, post office, or gateway. See the following directory structures for more information about its priority 0-7 subdirectories:

- [Section 7.1, “Domain Directory,” on page 63](#)
- [Section 7.2, “Post Office Directory,” on page 70](#)

### 7.3.10 *mtaname* files

The *mtaname* files in the closed location holding queues provide the name associated with the domain, post office, or gateway holding queue. They can help you check links between MTAs in ConsoleOne without going to the MTA agent console to determine the location name. To associate a location name with its holding queue directory from the MTA agent console, click *Configuration Status* > select the location > click *Details*.

## 7.3.11 gvvscan directory

The `gvvscan` subdirectory is the working directory where third-party virus scanning programs that snap in to the MTA can perform their processing.






















## 7.3.12 mtaconv directory

The `mtaconv` subdirectory is the working directory where the MTA converts GroupWise 7, 6.x, and 5.x messages to 4.x format for transfer to a GroupWise 4.x system. After the conversion is finished, this directory should be empty.

# 7.4 Internet Agent Queue Directory














The following directories and files are found under the `\domain\wpgate\` structure for the Internet Agent after the software has been installed and the Internet Agent has processed messages.

---

 <code>domain\wpgate\gwia</code>	GroupWise Internet Agent home directory
 <code>000.prc</code>	Internet Agent message processing directory
 <code>cmd</code>	Not currently used
 <code>gwork</code>	Hold directory for temporary files used during processing
 <code>mmddlog.nnn</code>	Log files
 <code>acct</code>	Accounting file
 <code>set</code>	Settings file for screen colors, log levels, and so on
 <code>stat</code>	Statistics file for Internet Agent operation
 <code>proc</code>	Process lock file indicating that the Internet Agent is running
 <code>pulse.tmp</code>	Temporary file to verify Internet Agent operation
 <code>wpcsin</code>	MTA input queue directory
 <code>0-7</code>	Message priority subdirectories
 <code>wpcout</code>	MTA output queue
 <code>gwixxxx</code>	System-defined directory
 <code>0-7</code>	Message priority subdirectories
 <code>problem</code>	Hold directory for damaged outbound messages
 <code>gwhold</code>	Message hold directory
 <code>qfiles</code>	Delayed delivery hold directory
 <code>gwprob</code>	Hold directory for damaged inbound messages
 <code>gwchars</code>	Directory for character conversion tables
 <code>save</code>	Directory for old configuration files from reinstalls or upgrades

---








---

 <code>gwia.cfg</code>	Internet Agent configuration file for startup switches
 <code>route.cfg</code>	Route configuration file to customize routing
 <code>gwauth.cfg</code>	Host authentication configuration file
 <code>mimetype.cfg</code>	MIME encoding configuration file for various file types
 <code>exepath.cfg</code>	Configuration file pointing ConsoleOne to the <code>gwia.cfg</code> file
 <code>frgnames.cfg</code>	Foreign domain name configuration file
 <code>xspam.cfg</code>	Anti-spam configuration file
 <code>gwac.db</code>	Access control database
 <code>gwac.dc</code>	Database dictionary file used to create the access control database
 <code>preamble.txt</code>	Message for recipients who lack a MIME-compliant mail reader
 <code>preamble.all</code>	Preamble message in various languages
 <code>blocked.txt</code>	List of blocked Internet sites
 <code>statusxx.xml</code>	File for customizing status messages

---



---

 <code>gwia</code>	SMTP service (daemon) home directory
 <code>send</code>	Outbound hold directory for converting messages into Internet format
 <code>receive</code>	Incoming hold directory for converting messages into GroupWise format
 <code>result</code>	Send and result files to confirm transmission
 <code>defer</code>	Hold directory for re-queued and deferred messages
 <code>work</code>	Schedule files for SMTP service operations on deferred messages
 <code>dsnhold</code>	Delivery Status Notification (DSN) hold directory

---

## 7.4.1 `domain\wpgate\gwia` directory

The `domain\wpgate\gwia` directory is the GroupWise Internet Agent home directory where Internet Agent configuration files and queue directories are located. The name is established when you install the Internet Agent. The default is `wpgate\gwia` in the `domain` directory. You can change the location using the `/home` startup switch in the Internet Agent configuration file (`gwia.cfg`).

### 000.prc directory

The Internet Agent uses the `000.prc` directory to process messages.

### gwwork directory

The `gwwork` directory stores temporary files created by the Internet Agent as it converts and builds messages for transfer across the Internet.



### ***mddlog.nnn* file**

The *mddlog.nnn* files hold error and status messages about the functioning of the Internet Agent. The Internet Agent creates a log file each day with a unique name, where *mm* is the month, *dd* is the day, and *nnn* is a sequential number indicating the sequence of log files in a single day. For more information log files, see “Using Internet Agent Log Files” in “Internet Agent” in the *GroupWise 7 Administration Guide*.

### **acct file**

The *acct* file contains information about the messages the Internet Agent sends each day. It is e-mailed to the accounts each day at midnight. For more information about the accounting files, see “Tracking Internet Traffic with Accounting Data” in “Internet Agent” in the *GroupWise 7 Administration Guide*.

### **set file**

The *set* file stores Internet Agent console settings such as color, log settings, and so on. For more information, see “Using the Internet Agent Server Console”.

### **stat file**

The *stat* file stores statistics about the Internet Agent’s functioning. For information about the statistics provided by the Internet Agent, see “Statistics” in “Internet Agent” in the *GroupWise 7 Administration Guide*.

### **proc file**

The *proc* file is the lock file for the Internet Agent process. The *proc* file is opened and locked when the Internet Agent starts. This prevents multiple Internet Agents from being started for the same domain.

### **pulse.tmp file**

The *pulse.tmp* file is re-created by the Internet Agent every time it completes a cycle (after an idle loop). If you are not at the Internet Agent console but need to know if the Internet Agent is running, you can delete the *pulse.tmp* file. If the Internet Agent is running, it re-creates the file.

### **wpcsin directory**

For a mapped/UNC link, the Internet Agent places inbound messages in one of the *wpcsin* priority subdirectories (0–7). Most messages go in the 4 directory, although some administrative and status messages might go in other directories. The Message Transfer Agent retrieves the messages and delivers them to the proper destinations.

For a TCP/IP link, the Internet Agent and the MTA communicate by way of TCP/IP rather than by transferring message files. For a comparison, see [Chapter 4, “Message Delivery to and from the Internet,” on page 35](#).

### **wpcout directory**

For a mapped/UNC link, the *wpcout* directory is the MTA output queue as well as being the Internet Agent input queue.

For a TCP/IP link, the Internet Agent and the MTA communicate by way of TCP/IP rather than by transferring message files. For a comparison, see [Chapter 4, “Message Delivery to and from the Internet,” on page 35](#).

### **gwixxxx directory**

The `gwixxxx` directory is a system-defined directory, where `gwi` represents the first three letters of the Internet Agent object name as defined during installation and displayed in ConsoleOne, and `xxxx` is a randomly-generated string. Here, the Message Transfer Agent places outbound messages in the appropriate 0–7 priority subdirectory for the Internet Agent to retrieve and process.

### **problem directory**

The `problem` directory holds messages that the MTA cannot process.

You should check this directory periodically for problem files, resolve the problem, then place the files back into the appropriate queue for continued processing. For assistance, see [“Message Is Dropped in the problem Directory in the Domain”](#) in [“Strategies for Message Delivery Problems”](#) in the *GroupWise 7 Troubleshooting 2: Solutions to Common Problems*.

### **gwhold directory**

The `gwhold` directory holds messages that are scheduled for delayed delivery.

### **qfiles directory**

The `qfiles` directory holds messages that cannot be sent during the current Send/Receive cycle. The messages are queued to this directory until the next cycle.

The delayed delivery messages waiting in the `qfiles` directory remain in encrypted format until the Internet Agent transfers them to the `send` directory for processing by the SMTP service.

### **gwprob directory**

The Internet Agent uses the `gwprob` directory for messages it cannot process. These are usually messages that have been damaged during transmission or that contain incorrectly formed MIME data.

These messages cannot be recovered. You can delete them to conserve disk space.

### **gwchars directory**

This directory contains conversion tables that the Internet Agent uses to convert message attachments between character sets.

### **save directory**

If you reinstall or upgrade the Internet Agent, your old configuration files are copied to the `save` directory as a backup. If you reinstall or upgrade repeatedly, the files are overwritten each time.

## **gwia.cfg file**

The `gwia.cfg` file is the Internet Agent configuration file that contains startup switches. Some switches are set during installation. You can set others as needed. For more information, see “[Using Internet Agent Startup Switches](#)” in “[Internet Agent](#)” in the *GroupWise 7 Administration Guide*.

---

**NetWare:** The NetWare Internet Agent uses the `gwia.cfg` file created in `sys:\system` during installation. The `gwia.cfg` file under the domain is just a boilerplate file with no switches set during installation.

**Linux:** The Linux Internet Agent uses the `gwia.cfg` file created in `/opt/novell/groupwise/agents/share` during installation. The `gwia.cfg` file under the domain is just a boilerplate file with no switches set during installation.

**Windows:** Only the Windows Internet Agent actually uses the `gwia.cfg` file under the domain.

---

## **route.cfg file**

The `route.cfg` file enables you to customize routing for specific hosts. For more information, see “[Using a Route Configuration File](#)” in “[Internet Agent](#)” in the *GroupWise 7 Administration Guide*.

## **gwauth.cfg file**

The `gwauth.cfg` file enables the Internet Agent to log in to SMTP hosts that require authentication. For more information, see “[SMTP Host Authentication](#)” in “[Internet Agent](#)” in the *GroupWise 7 Administration Guide*.

## **mimetype.cfg file**

The `mimetype.cfg` file enables you to customize MIME content-type mappings for various attachment types. For more information, see “[Customizing MIME Content-Type Mappings](#)” in “[Internet Agent](#)” in the *GroupWise 7 Administration Guide*.

## **exepath.cfg file**

The `exepath.cfg` file is used by ConsoleOne to locate the `gwia.cfg` file. This enables ConsoleOne to write any configuration setting changes to the `gwia.cfg` file or update Novell® eDirectory™ with any changes from the file. The file must contain the path to the `gwia.cfg` file in the `sys:\system` directory on NetWare, the `/opt/novell/groupwise/agents/share` directory on Linux, or the `domain\wpgate\gwia` directory on Windows.

## **frgnames.cfg file**

The `frgnames.cfg` file lets you list more Internet domain names than can fit in the *Foreign ID* field on the Identification page of the Internet Agent object in ConsoleOne. For more information, see “[Configuring How the Internet Agent Handles E-Mail Addresses](#)” in “[Internet Agent](#)” in the *GroupWise 7 Administration Guide*.

## **xspam.cfg file**

The `xspam.cfg` file lists “X” header fields that your anti-spam service writes to the MIME header, along with the values that flag the message as spam. The Internet Agent examines the MIME header for any field listed in the `xspam.cfg` file. When a match occurs, the message is marked for

handling by the GroupWise client Junk Mail Handling feature. For more information, see “[Customized Spam Identification](#)” in “[Internet Agent](#)” in the *GroupWise 7 Administration Guide*.

### **gwac.db file**

The `gwac.db` file is the access control database that stores information about the classes of service you have created. For more information, see “[Maintaining the Access Control Database](#)” in “[Internet Agent](#)” in the *GroupWise 7 Administration Guide*.

### **gwac.dc file**

The `gwac.dc` file is the data dictionary file from which the `gwac.db` is created.

### **preamble.txt file**

The `preamble.txt` file is an ASCII text file that is automatically included with any MIME multipart message and is displayed when the message recipient lacks a MIME-compliant mail reader. For more information, see “[Customizing MIME Preamble Text](#)” in “[Internet Agent](#)” in the *GroupWise 7 Administration Guide*.

### **preamble.all file**

The `preamble.all` file contains the preamble text in multiple languages. For more information, see “[Customizing MIME Preamble Text](#)” in “[Internet Agent](#)” in the *GroupWise 7 Administration Guide*.

### **blocked.txt file**

The `blocked.txt` file contains a list of Internet sites that you have added to the Prevent Messages From list for your default class of service in ConsoleOne. For more information, see “[Controlling User Access to the Internet](#)” in “[Internet Agent](#)” in the *GroupWise 7 Administration Guide*.

### **statusxx.xml file**

The `statusxx.xml` file enables you to customize the messages that users receive regarding message delivery status. For more information, see “[Customizing Delivery Status Notifications](#)” in “[Internet Agent](#)” in the *GroupWise 7 Administration Guide*.

## **7.4.2 gwia directory**

The `gwia` directory is the SMTP service (daemon) home directory where messages are converted between GroupWise format and Internet format. On NetWare and Linux, the default location is `wpgate/gwia`, the same as the Internet Agent home directory. On Windows, the default location is the Internet Agent installation directory. You can change the location using the `/dhome` startup switch in the Internet Agent configuration file (`gwia.cfg`).

### **send directory**

The Internet Agent SMTP service places outbound messages in the `send` directory after they have been converted out of GroupWise format into SMTP format. The SMTP service polls the `send` directory and sends any messages to the destination SMTP host.

## receive directory

The Internet Agent SMTP service places inbound messages in the `receive` directory, converts them into GroupWise format, and then passes them to the Message Transfer Agent by placing them in the `wpcsin` directory.

## result directory

When the Internet Agent SMTP service processes the message, it builds a file, `r*. *`, in the `result` directory that contains several lines of comments and SMTP reply codes, which might indicate possible errors or confirm correct transmission. After the Internet Agent SMTP service has completed the transmission with the destination host, it moves another file, `s*. *` from the `send` directory to the `result` directory. The filenames for both files are identical, except for the first letter, which is either “s” or “r”. The `s*. *` file is the converted message file. The SMTP service looks at the “s” and “r” files in the `result` directory and compares the conversation. If the `r*. *` file contains the correct (250 OK) SMTP reply codes, the SMTP service deletes the file and sends a transferred status message to the user’s Sent Items folder in the GroupWise client.

## defer directory

The `defer` directory holds messages that are deferred and re-queued according to the Retry Schedule. If the Internet Agent SMTP service receives a temporary error, such as Host Down, it places the message in the `defer` directory for a specified time, then transfers the file to the `send` directory for another attempt at sending to the Internet. For more information, see “[Configuring Basic SMTP/MIME Settings](#)” in “[Internet Agent](#)” in the *GroupWise 7 Administration Guide*.







## dsnhold directory

The `dsnhold` directory stores header information for inbound messages that request delivery status notifications. For more information, see “[Using Extended SMTP \(ESMTP\) Options](#)” in “[Internet Agent](#)” in the *GroupWise 7 Administration Guide*.

## 7.5 WebAccess Agent Queue Directory













The following directories and files are found under the `\domain\wpgate\` structure for the WebAccess Agent after the software has been installed and the WebAccess Agent has processed messages.

---

 <code>domain\wpgate\webac70a</code>	GroupWise WebAccess Agent home directory
 <code>000.prc</code>	WebAccess Agent log file processing directory
 <code>gwork</code>	Hold directory for temporary files used during processing
 <code>mmdweb.nnn</code>	WebAccess Agent log files
 <code>wpcsin</code>	MTA input queue directory
 <code>0-7</code>	Message priority subdirectories

---

---

 <code>wpcnout</code>	MTA output queue
 <code>webxxxx</code>	System-defined directory for the WebAccess Agent
 <code>0-7</code>	Message priority subdirectories
 <code>problem</code>	Hold directory for damaged outbound messages
 <code>gwhold</code>	Hold directory for delayed delivery messages
 <code>gwprob</code>	Hold directory for damaged inbound messages
 <code>template</code>	Directory for templates for viewing documents
 <code>commgr.cfg</code>	Communications Manager configuration file
 <code>comint.cfg</code>	Communications initialization configuration file
 <code>mimetype.cfg</code>	MIME encoding configuration file for various file types
 <code>gwac.db</code>	Access control database
 <code>gwac.dc</code>	Database dictionary file used to create the gwac.db file

---

### 7.5.1 `domain\wpgate\webac70a` directory

The `domain\wpgate\webac70a` directory is the WebAccess Agent home directory where WebAccess Agent configuration files and queue directories are located. The name is established when you install the WebAccess Agent. The default is `wpgate\webac70a` in the `domain` directory. You can change the location using the `/home` startup switch in the WebAccess Agent configuration file (`webac70a.waa` in the WebAccess Agent installation directory).

### 7.5.2 `000.prc` directory

The NetWare and Windows WebAccess Agents use the `000.prc` directory to store log files.

On Linux, the `000.prc` directory is located under `/var/log`.

#### **`mmddlog.nnn` file**

The `mmddlog.nnn` files hold error and status messages about the functioning of the WebAccess Agent. The WebAccess Agent creates a log file each day with a unique name, where `mm` is the month, `dd` is the day, and `nnn` is a sequential number indicating the sequence of log files in a single day. For more information about log files, see “[Controlling WebAccess Agent Logging](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

### 7.5.3 `wpcsin` directory

No longer used. The WebAccess Agent and the MTA communicate by way of TCP/IP and do not need queue directories.

### 7.5.4 `wpcnout` directory

No longer used.

## 7.5.5 gwhold directory

No longer used.

## 7.5.6 gwprob directory

No longer used.

## 7.5.7 template directory

The `template` directory holds the HTML templates used for viewing documents in HTML format.

## 7.5.8 commgr.cfg file

The `commgr.cfg` file in the WebAccess Agent queue directory contains information for communication between the WebAccess Agent and the WebAccess Application, including the IP address and port where the WebAccess Agent is running, the number of threads that are running, and the encryption key for the WebAccess Agent. This communications information is gathered during installation. For more information, see “[Configuring the GroupWise Service Provider](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

As part of the installation process, the `commgr.cfg` file is automatically copied to the Web server installation (`sys:\novell\webaccess` on NetWare, `/opt/novell/groupwise/webaccess` on Linux, and `c:\novell\webaccess` on Windows). The copies are synchronized automatically by the WebAccess Application. The `commgr.cfg` file is also copied to the `webpublisher` subdirectory on the Web server.

## 7.5.9 comint.cfg file

The `comint.cfg` file in the WebAccess Agent queue directory is read by the WebAccess Agent on startup. It contains the same communications information as the `commgr.cfg` file and is synchronized with it automatically.

## 7.5.10 mimetype.cfg file

The `mimetype.cfg` file enables you to customize MIME content-type mappings for various attachment types. The WebAccess Agent handles this just as the Internet Agent does. For more information, see “[Customizing MIME Content-Type Mappings](#)” in “[Internet Agent](#)” in the *GroupWise 7 Administration Guide*.

## 7.5.11 gwac.db file



























The `gwac.db` file is the access control database that stores information about the classes of service you have created. For more information, see “[Maintaining the Access Database](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

## 7.5.12 gwac.dc file

The `gwac.dc` file is the data dictionary file from which the `gwac.db` is created.

## 7.6 Caching Mailbox Directory

---

 \novell\groupwise\gwxxxxxx	GroupWise Caching mailbox
 rofdata	Caching mailbox database directory
 msg.db	Cached message database
 user.db	Cached user database
 wprof.db	Cached Address Book
 wprof.dc	Data dictionary for cached Address Book
 ngwguard.db	Guardian database
 ngwguard.dc	Data dictionary for guardian database
 ngwguard.rfl	Guardian database roll forward log
 ngwguard.fbk	Guardian database "fall back" file
 puxxxxx.db	Database for shared folders
 ngwcheck.db	GroupWise Check database
 gwcheckn.log	Log file created by the Repair Mailbox feature
 gwdms	Document Management Services directory
 dmsh.db	Shared DMS database
 dmxxxxn01-FF.db	Document databases
 docs	Subdirectory for documents in the Caching mailbox
 index	QuickFinder index for documents in the Caching mailbox
 index	QuickFinder index for messages in the Caching mailbox
 wpcsin	Input queue for the Caching mailbox
 0-7	Priority subdirectories
 wpcout\ofs	Output queue for the Caching mailbox
 0-7	Priority subdirectories
 wpgwsend	Output queue to the Online mailbox
 wpgwrecv	Input queue from the Online mailbox
 remoten.log	Connection log

---



## 7.6.1 `\novell\groupwise\gwxxxxxx` directory

Your GroupWise Caching mailbox is a directory structure that functions similarly to a post office. Like a post office, it contains databases and input/output queues. It is created in the directory where the GroupWise client is installed, which is typically `\novell\groupwise`.

The same directory structure is used for a Caching mailbox as for a Remote mailbox. However, a Caching mailbox is a complete copy of your Online mailbox, but you can restrict what gets downloaded into your Remote mailbox.

## 7.6.2 `rofdata` directory

The `rofdata` directory contains the databases accessed by the GroupWise Windows client when running in Caching mode. The databases in `rofdata` are similar to the databases found in post offices. For comparison, see [Section 7.2, “Post Office Directory,” on page 70](#).

Historical Note: An earlier version of the GroupWise client Remote mode, designed by WordPerfect Corporation (WPCorp), was named WP Office Remote. Hence, the `rof` in `rofdata`. Some naming conventions were originally preserved for backward compatibility.

### **msg.db file**

The `msg.db` file is the cached equivalent of the `msgnnn.db` files in the `ofmsg` directory in your post office. The `msg.db` file contains copies of messages from your Online mailbox.

### **user.db file**

The `user.db` file is the cached equivalent of the `userxxx.db` files in the `ofuser` directory in your post office.

### **wprof.db file**

The `wprof.db` file contains the cached version of the GroupWise Address Book.

Historical Note: An earlier version of the GroupWise client Remote mode, designed by WordPerfect Corporation (WPCorp), was named WP Office Remote. Hence, the `wprof` in `wprof.db`. Some naming conventions have been preserved for backward compatibility.

### **wprof.dc file**

The `wprof.dc` file is the data dictionary for the cached Address Book (`wprof.db`).

Historical Note: An earlier version of the GroupWise client Remote mode, designed by WordPerfect Corporation (WPCorp), was named WP Office Remote. Hence, the `wprof` in `wprof.dc`. Some naming conventions have been preserved for backward compatibility.

### **ngwguard.db file**

The `ngwguard.db` file is the guardian database for your Caching mailbox. It is parallel in function to the `ngwguard.db` file in the post office.

### **ngwguard.dc file**

The `ngwguard.dc` file is the data dictionary for building the databases in the GroupWise Caching mailbox. It is parallel in function to the `ngwguard.dc` file in the post office.

### **ngwguard.rfl file**

The `ngwguard.rfl` file is a roll-forward transaction log of every database transaction that has taken place since the last copy of the `ngwguard.fbk` file was created. It is parallel in function to the `ngwguard.rfl` file in the post office.

### **ngwguard.fbk**

The `ngwguard.fbk` file “fall back” copy of the `ngwguard.db` file. It is parallel in function to the `ngwguard.fbk` file in the post office.

### **puxxxxx.db files**

The `puxxxxx.db` files are databases for replicated items such as shared folders. These databases prevent conflicts between user names of shared items from users in other post offices and user names in your own post office. They are parallel to the `puxxxxx.db` files in the post office.

### **ngwcheck.db file**

The `ngwcheck.db` file tracks GroupWise Check threads and the databases being checked. In the GroupWise client, GroupWise Check is run using *Tools > Repair Mailbox*.

### **gwcheckn.log**

The `gwcheckn.log` file records any errors that occurred during mailbox repair. For assistance with GroupWise Check errors, see “[GroupWise Check Error Codes](#)” in “[Administration Error Messages](#)” in the *GroupWise 7 Troubleshooting 1: Error Messages*.

### **gwdms directory**

The `gwdms` directory is the Document Management Services directory. It contains information about the libraries in your GroupWise system. It has the same structure as the `gwdms` subdirectory in the post office.

### **dmsh.db file**

The `dmsh.db` file is a database shared by all libraries that contains a list of all available libraries and lookup tables for each library.

### **dmxxxnn01-FF.db files**

The `dmxxxnn01-FF.db` files are databases for library and document information. They are parallel to the `dmxxxnn01-FF.db` files in the post office.

### **docs directory**

The `docs` directory holds cached copies of the documents in your Online mailbox.

## index directory

The `index` directory under the `gwdms` directory contains the QuickFinder index for the documents in your Caching mailbox.

## index directory

The `index` directory under the `rofdata` directory contains the QuickFinder index for the messages in your Caching mailbox.

### 7.6.3 wpcsin directory

The `wpcsin` subdirectory is the input queue for the connection that transfers messages to your GroupWise system for delivery. Messages from the GroupWise client in Caching mode are processed through the priority 1 subdirectory of `wpcsin`.

When you send a message in Caching mode, the GroupWise client connects to your GroupWise system. It polls the `wpcsin\1` directory and compresses any outgoing messages, requests, or both into a file. If the compressed file totals over 50 KB, additional compressed files are created. The GroupWise client then moves the compressed files into the `wpgwsend` directory.

Historical Note: WP Office, the predecessor of GroupWise, was originally designed by WordPerfect Corporation (WPCorp). The Message Transfer Agent (MTA) was originally named the Connection Server (CS). Hence, the directory name `wpcsin` for the input queue, although the MTA is not involved in processing messages in your Caching mailbox. Some naming conventions were originally preserved for backward compatibility.

#### 0-7 directories

The priority 0-7 subdirectories in the connection input queue (`wpcsin`) parallel those found in the `wpcsin` directory in your post office.

### 7.6.4 wpcout\ofs directory

The `wpcout\ofs` directory is the output queue for the connection that transfers messages from your Online mailbox. Messages from your GroupWise system are processed through the priority 1 subdirectory of `wpcout\ofs`.

The GroupWise client scans the `wpcout\ofs\1` subdirectory and updates the `user.db` and `msg.db` files with the information received from your Online mailbox.

Historical Note: WP Office, the predecessor of GroupWise, was originally designed by WordPerfect Corporation (WPCorp). The Message Transfer Agent (MTA) was originally named the Connection Server (CS). Hence, the directory names `wpcsin` and `ofs` for the input queue, though the MTA is not involved in processing messages in your Remote mailbox. Some naming conventions were originally preserved for backward compatibility.

#### 0-7 directories

The priority 0-7 subdirectories in the connection output queue (`wpcout\ofs`) parallel those found in the `ofs` directory in your post office.

## 7.6.5 wpgwsend directory

The `wpgwsend` directory holds compressed files that contain outgoing messages, requests, or both. When a connection to your GroupWise system is established, the GroupWise client uploads the files to your Online mailbox.

Historical Note: WP Office Remote, the predecessor of the GroupWise client Remote mode, was originally designed by WordPerfect Corporation (WPCorp). Hence, the name `wpgwsend`. Some naming conventions were originally preserved for backward compatibility.

## 7.6.6 wpgwrecv directory

The `wpgwrecv` directory holds compressed files that contain messages or other information that have been received from your Online mailbox. The GroupWise client decompresses the files and places the message files into the `wpcout\ofs\1` directory.

Historical Note: WP Office Remote, the predecessor of the GroupWise client Remote mode, was originally designed by WordPerfect Corporation (WPCorp). Hence, the name `wpgwrecv`. Some naming conventions were originally preserved for backward compatibility.

## 7.6.7 remoten.log

The `remoten.log` files are saved versions of the connection logs you can view in the GroupWise client by clicking *Accounts > Connection Log*. These log files can be useful for troubleshooting problems with your connection to your Online mailbox.














# 7.7 Remote Mailbox Directory

---

 <code>remote_mailbox</code>	GroupWise mailbox on a remote computer
 <code>rofdata</code>	Remote database directory
 <code>msg.db</code>	Remote message database
 <code>user.db</code>	Remote user database
 <code>wprof.db</code>	Remote Address Book
 <code>wprof.dc</code>	Data dictionary for Remote Address Book
 <code>ngwguard.db</code>	Remote guardian database
 <code>ngwguard.dc</code>	Data dictionary for Remote guardian database
 <code>ngwguard.rfl</code>	Guardian database roll forward log
 <code>ngwguard.fbz</code>	Guardian database “fall back” file
 <code>puxxxxx.db</code>	Database for shared folders
 <code>ngwcheck.db</code>	GroupWise Check database
 <code>gwcheckn.log</code>	Log file created by the Repair Mailbox feature

---

---

 <code>gwdms</code>	Document Management Services directory
 <code>dmsh.db</code>	Shared DMS database
 <code>dmxxxnn01-FF.db</code>	Document databases
 <code>docs</code>	Subdirectory for documents in the Remote mailbox
 <code>index</code>	QuickFinder index for Remote mailbox
 <code>index</code>	QuickFinder index for messages in the Remote mailbox
 <code>wpcsin</code>	Input queue for the GroupWise client in Remote mode
 <code>0-7</code>	Priority subdirectories
 <code>wpcout\ofs</code>	Output queue for the GroupWise client in Remote mode
 <code>0-7</code>	Priority subdirectories
 <code>wpgwsend</code>	Output queue to master mailbox
 <code>wpgwrecv</code>	Input queue from master mailbox
 <code>remoten.log</code>	Remote connection log

---

## 7.7.1 *remote\_mailbox* directory

The GroupWise **remote mailbox** is a directory structure that functions similarly to a post office. Like a post office, it contains databases and input/output queues.

## 7.7.2 *rofdata* directory

The `rofdata` subdirectory in the **remote mailbox directory** contains the databases accessed by the GroupWise client in Remote mode. The databases in `rofdata` are similar to the databases found in post offices.

Historical Note: An earlier version of the GroupWise client Remote mode, designed by WordPerfect Corporation (WPCorp), was named WP Office Remote. Hence, the `rof` in `rofdata`. Some naming conventions were originally preserved for backward compatibility.

### **msg.db** file

The `msg.db` file in the remote data directory (`rofdata`) in the **remote mailbox directory** is the remote equivalent of the `msgnnn.db` files in the `ofmsg` directory in the post office where your master mailbox is located. The `msg.db` file contains messages you have downloaded from your master mailbox.

### **user.db** file

The `user.db` file in the remote data directory (`rofdata`) in the **remote mailbox directory** is the remote equivalent of the `userxxx.db` files in the `ofuser` directory in the post office where your master mailbox is located. The `user.db` file contains user information you have downloaded from your master mailbox.

### **wprof.db file**

The `wprof.db` file in the remote data directory (`rofdata`) in the **Remote mailbox directory** contains the remote version of the GroupWise Address Book if you have downloaded it.

Historical Note: An earlier version of the GroupWise client Remote mode, designed by WordPerfect Corporation (WPCorp), was named WP Office Remote. Hence, the `wprof` in `wprof.db`. Some naming conventions have been preserved for backward compatibility.

### **wprof.dc file**

The `wprof.dc` file in the remote data directory (`rofdata`) in the **Remote mailbox directory** is the data dictionary for the remote Address Book (`wprof.db`).

Historical Note: An earlier version of the GroupWise client Remote mode, designed by WordPerfect Corporation (WPCorp), was named WP Office Remote. Hence, the `wprof` in `wprof.dc`. Some naming conventions have been preserved for backward compatibility.

### **ngwguard.db file**

The `ngwguard.db` file in the remote data directory (`rofdata`) in the **Remote mailbox directory** is the guardian database for the remote GroupWise mailbox. It is parallel in function to the `ngwguard.db` file in the post office.

### **ngwguard.dc file**

The `ngwguard.dc` file in the remote data directory (`rofdata`) in the **Remote mailbox directory** is the data dictionary for building the databases in the remote GroupWise mailbox. It is parallel in function to the `ngwguard.dc` file in the post office.

### **ngwguard.rfl file**

The `ngwguard.rfl` file is a roll-forward transaction log of every database transaction that has taken place since the last copy of the `ngwguard.fbk` file was created. It is parallel in function to the `ngwguard.rfl` file in the post office.

### **ngwguard.fbk**

The `ngwguard.fbk` file “fall back” copy of the `ngwguard.db` file. It is parallel in function to the `ngwguard.fbk` file in the post office.

### **puxxxxx.db files**

The `puxxxxx.db` files in the remote data directory (`rofdata`) in the **Remote mailbox directory** are databases for replicated items such as shared folders. These databases prevent conflicts between user names of shared items from users in other post offices and user names in the Remote user’s post office. They are parallel to the `puxxxxx.db` files in the post office.

### **ngwcheck.db file**

The `ngwcheck.db` file tracks GroupWise Check threads and the databases being checked. In Remote mode in the GroupWise client, GroupWise Check is run using *Tools > Repair Mailbox*.

## gwcheckn.log

The `gwcheckn.log` file records any errors that occurred during Remote mailbox repair. For assistance with GroupWise Check errors, see “[GroupWise Check Error Codes](#)” in “[Administration Error Messages](#)” in the *GroupWise 7 Troubleshooting 1: Error Messages*.

## gwdms directory

The `gwdms` subdirectory in the remote data directory (`rofdata`) in the [remote mailbox directory](#) is the Document Management Services directory. It contains the document libraries you have downloaded from your master GroupWise system. It has the same structure as the `gwdms` subdirectory in the post office.

## dmsh.db file

The `dmsh.db` file is a database shared by all libraries that have been downloaded to your remote GroupWise mailbox. It contains a list of all available libraries and lookup tables for each library.

## dmxxnn01-FF.db files

The `dmxxnn01-FF.db` files are databases for library and document information. They are parallel to the `dmxxnn01-FF.db` files in the post office.

## docs directory

The `docs` directory holds cached copies of the documents in your Remote mailbox.

## index directory

The `index` directory contains the QuickFinder index for the documents contained in the library.

## index directory

The `index` directory under the `rofdata` directory contains the QuickFinder index for the messages in your Remote mailbox.

## 7.7.3 wpcsin directory

The `wpcsin` subdirectory in the [remote mailbox directory](#) is the input queue for the connection that transfers messages to your master GroupWise system. Messages from the GroupWise client in Remote mode are processed through the priority 1 subdirectory of `wpcsin`.

When the user initiates the connection to the master GroupWise system, the GroupWise client polls the `wpcsin\1` directory and compresses the outgoing messages, requests, or both into a file. If the compressed file totals over 50 KB, additional compressed files are created. The GroupWise client then moves the compressed files into the `wpgwsend` directory.

Historical Note: WP Office, the predecessor of GroupWise, was originally designed by WordPerfect Corporation (WPCorp). The Message Transfer Agent (MTA) was originally named the Connection Server (CS). Hence, the directory name `wpcsin` for the input queue, although the MTA is not involved in processing messages in your Remote mailbox. Some naming conventions were originally preserved for backward compatibility.

## 0-7 directories

The priority 0–7 subdirectories in the connection input queue (`wpcsin`) in the **remote mailbox directory** parallel those found in the `wpcsin` directory in the remote user’s post office on the master GroupWise system.

### 7.7.4 wpcout\ofs directory

The `wpcout\ofs` subdirectory in the **remote mailbox directory** is the output queue for the connection that transfers messages from your master GroupWise system. Messages from the GroupWise client in Remote mode are processed through the priority 1 subdirectory of `wpcout\ofs`.

In Remote mode, the GroupWise client scans the `wpcout\ofs\1` subdirectory and updates the `user.db` and `msg.db` files with the information received from the master mailbox.

Historical Note: WP Office, the predecessor of GroupWise, was originally designed by WordPerfect Corporation (WPCorp). The Message Transfer Agent (MTA) was originally named the Connection Server (CS). Hence, the directory names `wpcsin` and `ofs` for the input queue, though the MTA is not involved in processing messages in your Remote mailbox. Some naming conventions were originally preserved for backward compatibility.

## 0-7 directories

The priority 0–7 subdirectories in the connection output queue (`wpcout\ofs`) in the **remote mailbox directory** parallel those found in the `ofs` subdirectory in the remote user’s post office on the master GroupWise system.

### 7.7.5 wpgwsend directory

The `wpgwsend` subdirectory in the **remote mailbox directory** holds compressed files that contain outgoing messages, requests, or both. When a connection to your master GroupWise system is established, the GroupWise client uploads the files across the link from the remote computer to the master GroupWise system.

Historical Note: WP Office Remote, the predecessor of the GroupWise client Remote mode, was originally designed by WordPerfect Corporation (WPCorp). Hence, the name `wpgwsend`. Some naming conventions were originally preserved for backward compatibility.

### 7.7.6 wpgwrecv directory

The `wpgwrecv` subdirectory in the **remote mailbox directory** holds compressed files that contain messages or other information that have been downloaded from your master mailbox. The GroupWise client decompresses the files and places the message files into the `wpcout\ofs\1` directory.

Historical Note: WP Office Remote, the predecessor of the GroupWise client Remote mode, was originally designed by WordPerfect Corporation (WPCorp). Hence, the name `wpgwrecv`. Some naming conventions were originally preserved for backward compatibility.



### 7.7.7 remoten.log

The `remoten.log` files in the connection output queue (`wpcout\ofs`) in the **remote mailbox directory** are saved versions of the connection logs you can view in the GroupWise client in Remote mode. These log files can be useful for troubleshooting problems with your modem or with your connection to your master GroupWise system.



- [Section 8.1, “GroupWise Agent Installation \(POA and MTA\),” on page 107](#)
- [Section 8.2, “Internet Agent Installation,” on page 119](#)
- [Section 8.3, “WebAccess Agent Installation,” on page 126](#)
- [Section 8.4, “Monitor Agent Installation,” on page 138](#)
- [Section 8.5, “Apache/Tomcat Installation,” on page 143](#)
















## 8.1 GroupWise Agent Installation (POA and MTA)

The Post Office Agent (POA) and the Message Transfer Agent (MTA) are always installed together. The agent installation directory differs depending on the platform where the agents are installed.

- [“NetWare Installation Directory” on page 107](#)
- [Section 8.1.2, “Linux Installation Directory,” on page 110](#)
- [“Windows Installation Directory” on page 116](#)







### 8.1.1 NetWare Installation Directory

---

 <code>sys:\system</code>	NetWare® agent installation directory
 <code>gwenn5.nlm</code>	GroupWise® 7 Agent Engine
 <code>gwpoa.nlm</code>	Post Office Agent (POA) program
 <code>gwmta.nlm</code>	Message Transfer Agent (MTA) program
 <code>strdupxx.poa</code>	Boilerplate POA startup file
 <code>strdupxx.mta</code>	Boilerplate MTA startup file
 <code>post_office.poa</code>	POA startup file for a specific post office
 <code>domain.mta</code>	MTA startup file for a specific domain
 <code>gwpoanxx.hlp</code>	POA online help files
 <code>gwmthanxx.hlp</code>	MTA online help files
 <code>gwpoanxx.fil</code>	POA language information files
 <code>gwmthanxx.fil</code>	MTA language information files
 <code>grpwise.ncf</code>	Agent load file
 <code>x*5.nlm</code>	XIS NLM™ programs
 <code>gwxis12.nlm</code>	GroupWise XIS NLM program

---

---

 <code>agent.xml</code>	XIS agent configuration files
 <code>gwtsa.nlm</code>	GroupWise Target Service Agent (GW TSA) program
 <code>gwtsaxx.fil</code>	GW TSA language information files
 <code>gwtsa.ncf</code>	GW TSA load file
 <code>gwtmstp.nlm</code>	GroupWise Time Stamp program
 <code>help</code>	Subdirectory for GroupWise agent Web console help files

---

## NetWare agent installation directory

When you first install GroupWise Administration, the GroupWise agents are installed in platform-specific subdirectories in the `agent` directory in the software distribution directory. However, the agents cannot be run from this initial location. They must be installed on the servers where they will run.

On a NetWare<sup>®</sup> server, the GroupWise agents are typically installed in the `sys:\system` directory. You can choose a different location during installation.

### gwenn5.nlm file

The `gwenn5.nlm` file is the GroupWise 7 Agent Engine, a program that is shared by all GroupWise agents. It provides the following services to the agents:

- Database management
- File operations
- Message handling
- Thread management
- Semaphores (file/record locking)
- Date/time services

The first agent loaded on a server automatically loads the GroupWise Agent Engine.

### gwpoa.nlm file

The `gwpoa.nlm` file is the Post Office Agent program. You load this NLM program to start the Post Office Agent. See “Starting the POA” in “Post Office Agent” in the *GroupWise 7 Administration Guide*.

### gwmta.nlm file

The `gwmta.nlm` is the Message Transfer Agent program. You load this NLM program to start the Message Transfer Agent. See “Starting the MTA” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*.

## **strtpxxx.poa file**

The POA startup file contains startup switches for the POA. Switch settings placed in the POA startup file override comparable options set for the POA in ConsoleOne®. The *xx* in the startup filename represents a two-letter language code.

During installation, a customized version of the POA startup file, named *post\_office.poa*, is created. This customized version has the */home* startup switch automatically set to the post office directory the POA will service. See “Using POA Startup Switches” in “Post Office Agent” in the *GroupWise 7 Administration Guide*.

## **strtpxxx.mta file**

The MTA startup file contains startup switches for the MTA. Switch settings placed in the MTA startup file override comparable options set for the MTA in ConsoleOne. The *xx* in the startup filename represents a two-letter language code.

During installation, a customized version of the MTA startup file, named *domain.mta*, is created. This customized version has the */home* startup switch automatically set to the domain directory the MTA will service. See “Using MTA Startup Switches” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*.

## **nlm\_agentnxx.hlp files**

Online help is available by pressing F1 at the agent console on the server where it runs. See “Using the POA Server Console” in “Post Office Agent” and “Using the MTA Server Console” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*

The first five characters of the filename are the agent name. The digit *n* is a version number. The last two characters *xx* are a language code.

## **nlm\_agentnxx.fil files**

These files contain all language-specific information for the POA and the MTA. The first five characters of the filename are the agent name. The digit *n* is a version number. The last two characters *xx* are a language code.

## **grpwise.ncf file**

The *grpwise.ncf* file is the NetWare configuration file that automatically loads the agents whenever the server is restarted. A typical *grpwise.ncf* file would look similar to the following:

```
load sys:\system\gwmta.nlm @corpdom.mta
load sys:\system\gwpoa.nlm @acctpo.poa
```

For more information, see “Starting the NetWare POA” in “Post Office Agent” and “Starting the NetWare MTA” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*.

## **x\*5.nlm and gwxis12.nlm files**

The *x\*5.nlm* and *gwxis12.nlm* programs provide XIS capability for the GroupWise agents, so that you can create XML documents to monitor and change the agents as needed.

## ***nlm\_agent.xml* files**

The *nlm\_agent.xml* files are specialized agent configuration files for use in the XIS environment.

## **gwtsa.nlm file**

The *gwtsa.nlm* is the GroupWise Target Service Agent (GWTSA), which provides reliable backups of a running GroupWise system by successfully backing up open files and locked files, rather than skipping them as some backup software does. For more information, see “[GroupWise Target Service Agent \(GWTSA\) for NetWare 5.1](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

## **gwtmstmp.nlm file**

If you use the GroupWise Target Service Agent (GWTSA) of the GroupWise Target Server Agent for File Systems (GWAFSGW) to back up your GroupWise system, the time stamping is an automatic part of the backup process. However, if you choose not to use one of these TSAs, you must still make sure that user databases are time-stamped so that items are not prematurely purged. The *gwtmstmp.nlm* accomplishes this task. For more information, see “[GroupWise Time Stamp Utility](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

## **gwtsaxx.fil file**

These files contain all language-specific information for the GWTSA. The last two characters, *xx*, are a language code.

## **gwtsa.ncf file**

The *gwtsa.ncf* file is the NetWare configuration file that automatically loads the GWTSA whenever the server is restarted. A typical *gwtsa.ncf* file would look similar to the following:

```
load sys:\system\smdr
load sys:\system\gwtsa /home-sys:\gwsystem\corpdom
    /home-sys:\gwsystem\acctpo
```

## **help directory**

The *help* directory contains language-specific subdirectories for the help files available from the POA and MTA Web consoles. See “[Using the POA Web Console](#)” in “[Post Office Agent](#)” and “[Using the MTA Web Console](#)” in “[Message Transfer Agent](#)” in the *GroupWise 7 Administration Guide*.






























## **8.1.2 Linux Installation Directory**

---



 `/opt/novell/groupwise/agents` Linux agent installation directory

---

---





 <code>bin</code>	Subdirectory for GroupWise agent executables
 <code>gwpoa</code>	Post Office Agent (POA) executable
 <code>gwmta</code>	Message Transfer Agent (MTA) executable
 <code>gwha</code>	GroupWise High Availability service executable
 <code>gwpoa.xml</code>	POA XIS configuration file
 <code>gwmta.xml</code>	MTA XIS configuration file
 <code>strdupxx.poa</code>	Boilerplate POA startup file
 <code>strdupxx.mta</code>	Boilerplate MTA startup file
 <code>gwcsrgen</code>	GroupWise Generate CSR utility
 <code>gwtmstamp</code>	GroupWise Time Stamp utility
 <code>lib</code>	Subdirectory for GroupWise agent library files
 <code>gwpoaxxx.fil</code>	POA language information file
 <code>gwmtaxxx.fil</code>	MTA language information file
 <code>libpoa.so*</code>	POA shared library files
 <code>libpoa_ui.so*</code>	POA shared library files for the optional user interface
 <code>libmta.so*</code>	MTA-specific library files
 <code>libmta_ui.so*</code>	MTA-specific library files for the optional user interface
 <code>libgwha.so*</code>	GroupWise High Availability service library files
 <code>*.so*</code>	Supporting library files
 <code>image</code>	Subdirectory for icon images
 <code>share</code>	Subdirectory for agent shared files
 <code>post_office.poa</code>	POA startup file for a specific post office
 <code>domain.mta</code>	MTA startup file for a specific domain
 <code>agtcon</code>	Subdirectory for agent console files
 <code>help</code>	Subdirectory agent console help files
 <code>webcon</code>	Subdirectory for agent Web console files
 <code>help</code>	Subdirectory for agent Web console help files
 <code>gwcsrgen</code>	Subdirectory for the GWCSRGEN utility files
 <code>help</code>	Subdirectory for GWCSRGEN utility help files

---






 <code>/etc/init.d</code>	Standard Linux location for application startup scripts
 <code>grpwise</code>	Startup script for the POA and MTA

---







---

 <code>rc3.d</code>	Standard Linux location for runlevel-3 symbolic links
 <code>S99grpwise</code>	Symbolic link to the startup script for the POA and MTA
 <code>rc5.d</code>	Standard Linux location for runlevel-5 symbolic links
 <code>S99grpwise</code>	Symbolic link to the startup script for the POA and MTA

---

 <code>/etc/opt</code>	Standard Linux location for application configuration files
 <code>novell/groupwise</code>	Subdirectory for GroupWise configuration files
 <code>gwha.conf</code>	GroupWise High Availability service configuration file
 <code>agents</code>	Subdirectory for GroupWise agents
 <code>uid.conf</code>	Agent configuration file for running as a non-root user

---

 <code>/var/log/</code>	Standard Linux location for application log files
 <code>novell/groupwise</code>	Subdirectory for GroupWise agent log files
 <code>post_office.poa</code>	Post office-specific subdirectory for POA log files
 <code>mmdp.poa.nnn</code>	POA log files
 <code>domain.mta</code>	Domain-specific subdirectory for MTA log files
 <code>mmdm.mta.nnn</code>	MTA log files

---

### agents directory

On a Linux server, the agents are always installed in subdirectories of `/opt/novell/groupwise/agents`.

### bin directory

The `bin` directory holds GroupWise executable files.

#### gwpoa file

The `gwpoa` file is the Post Office Agent executable. You run this executable file to start the Post Office Agent. See “Starting the POA” in “Post Office Agent” in the *GroupWise 7 Administration Guide*.

#### gwmta file

The `gwmta` file is the Message Transfer Agent executable. You run this executable file to start the Message Transfer Agent. See “Starting the MTA” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*.



## gwha file

The `gwha` file is the GroupWise High Availability service executable. If the POA or the MTA goes down for any reason, the High Availability service automatically restarts it. See “[Enabling the High Availability Service for the Linux Agents](#)” in “[Installing GroupWise Agents](#)” in the *GroupWise 7 Installation Guide*.

## \*.xml files

The `agent.xml` files are specialized agent configuration files for use in the XIS environment.

## strtpxx.poa file

The `strtpxx.poa` file is the boilerplate file from which a post office-specific `post_office.poa` file is created in the `share` directory. The `xx` in the startup filename represents a two-letter language code.

## strtpxx.mta file

The `strtpxx.mta` file is the boilerplate file from which a domain-specific `domain.poa` file is created in the `share` directory. The `xx` in the startup filename represents a two-letter language code.

## gwcsrgen file

The `gwcsrgen` file is the GroupWise Generate CSR utility. If you enable SSL for the agents, they need access to a server certificate and private key. You can use the GroupWise Generate CSR utility (GWCSRGEN) to generate a Certificate Signing Request (CSR) file and a Private Key file. For more information, see “[Server Certificates and SSL Encryption](#)” in “[Security](#)” in the *GroupWise 7 Administration Guide*.

## gwtmstmp file

The `gwtmstmp` file is the GroupWise Time Stamp utility. If you deselect Allow Purge of Items Not Backed Up in ConsoleOne, user databases (`userxxx.db`) must be time-stamped every time a backup is performed so that items can be purged only after being backed up. You can use the GroupWise Time Stamp (GWTMSTMP) utility to ensure that GroupWise user databases include the dates when they were last backed up, restored, and retained. For more information, see “[GroupWise Time Stamp Utility](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

## lib directory

The `lib` directory holds GroupWise library files.

## \*.fil files

These files contain all language-specific information for the POA and the MTA. The first five characters of the filename are the agent name. The last two characters `xx` are a language code.

## \*.so\* files

These files are Linux library files that provide information to the GroupWise executables.

## image directory

The `image` directory has subdirectories for agent icons for both color and monochrome displays.

## share directory

The `share` directory holds agent startup files and files that are used by the agent consoles and Web consoles.

### *post\_office.poa*

The POA startup file contains startup switches for the POA. Switch settings placed in the POA startup file override comparable options set for the POA in ConsoleOne.

During installation, a customized version of the `strdupxx.poa` file, named *post\_office.poa*, is created in the `share` directory. This customized version has the `--home` startup switch automatically set to the post office directory the POA will service. See “Using POA Startup Switches” in “Post Office Agent” in the *GroupWise 7 Administration Guide*.

### *domain.mta*

The MTA startup file contains startup switches for the MTA. Switch settings placed in the MTA startup file override comparable options set for the MTA in ConsoleOne.

During installation, a customized version of the `strdupxx.mta` file, named *domain.mta*, is created in the `share` directory. This customized version has the `--home` startup switch automatically set to the domain directory the MTA will service. See “Using MTA Startup Switches” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*.

## agtcon directory

The `agtcon` directory holds subdirectories and files used by the agent consoles, such as help files. See “Using the POA Server Console” in “Post Office Agent” and “Using the MTA Server Console” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*.

## webcon directory

The `webcon` directory holds subdirectories and files used by the agent Web consoles, such as help files. See “Using the POA Web Console” in “Post Office Agent” and “Using the MTA Web Console” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*.

## gwcsrgen directory

The `gwcsrgen` directory holds subdirectories and files used by the GroupWise Generate CSR (GWCSRGEN) utility, such as help files. See “Generating a Certificate Signing Request and Private Key” in “Security” in the *GroupWise 7 Administration Guide*.

## /etc/init.d directory

The `/etc/init.d` directory is the standard location for Linux startup scripts.

## grpwise file

The `grpwise` script is created automatically during installation. You can use the script to start, restart, stop, and display status information about the POA and MTA. For more information about starting the agents, see “Linux: Installing and Starting the GroupWise Agents” in “Installing a Basic GroupWise System” in the *GroupWise 7 Installation Guide*.

### rc3.d directory

The `rc3.d` directory holds symbolic links to scripts that you want your Linux server to run when it is booted to runlevel 3 (multi-user; boots to a text mode login prompt without the X Window System\*). The symbolic link to the `grpwise` script is `S99grpwise`. It is created if you choose during installation to have the agents start automatically when the server boots. See “Starting the Linux POA” in “Post Office Agent” and “Starting the Linux MTA” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*.

### rc5.d directory

The `rc5.d` directory holds symbolic links to scripts that you want your Linux server to run when it is booted to runlevel 5 (multi-user; boots to the X Window System login dialog box). The symbolic link to the `grpwise` script is `S99grpwise`. It is created if you choose during installation to have the agents start automatically when the server boots. See “Starting the Linux POA” in “Post Office Agent” and “Starting the Linux MTA” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*.

### **/etc/opt/novell/groupwise directory**

The `/etc/opt` directory is the standard location of application configuration files on Linux. Files that configure how the GroupWise agents interact with Linux are stored in the `novell/groupwise` subdirectory.

### gwha.conf file

The `gwha.conf` file is the GroupWise High Availability service configuration file. It is created automatically during installation and provides the information necessary for the High Availability service to restart the GroupWise agents if they go down unexpectedly. See “Enabling the High Availability Service for the Linux Agents” in “Installing GroupWise Agents” in the *GroupWise 7 Installation Guide*.

### uid.conf file

The `uid.conf` file configures the GroupWise agents to run as a non-root user. See “Running the Agents as a Non-root User” in “Installing GroupWise Agents” in the *GroupWise 7 Installation Guide*.

### **/var/log/novell/groupwise directory**

The `/var/log` directory is the standard location for log files on Linux. All GroupWise agent log files are created in the `novell/groupwise` subdirectory.

### *post\_office.poa* directory

The `post_office.poa` directory is a post office-specific location for POA log files.

Within the `post_office.poa` directory, the POA creates log files (`mmdapoa.nnn`) to inform you of its processing and any problems it encounters. For more information about log files, see “Using POA Log Files” in “Post Office Agent” in the *GroupWise 7 Administration Guide* guide.

The first two digits of the filename represent the month, the next two digits represent the day of the month, and the next three characters indicate what program created the log. The three-digit

extension is a sequence number for multiple log files created on the same day. For example, 0518poa.002 is the second POA log file created on May 18.

### *domain.mta* directory




















The *domain.mta* directory is a domain-specific location for MTA log files.

Within the *domain.mta* directory, the MTA creates log files (*mmdxxx.nnn*) to inform you of its processing and any problems it encounters. For more information about log files, see “[Using MTA Log Files](#)” in “[Message Transfer Agent](#)” in the *GroupWise 7 Administration Guide*.

The first two digits of the filename represent the month; the next two digits represent the day of the month; the next three characters indicate what program created the log. The three-digit extension is a sequence number for multiple log files created on the same day. For example, 0518mta.002 is the second MTA log file created on May 18.

## 8.1.3 Windows Installation Directory

---

 c:\grpwise	Windows agent installation directory
 gwenv1a.dll	GroupWise Agent Engine
 gwpoa.exe	Post Office Agent (POA) program
 gwmta.exe	Message Transfer Agent (MTA) program
 strtupxx.poa	Boilerplate POA startup file
 strtupxx.mta	Boilerplate MTA startup file
 post_office.poa	Customized POA startup file
 domain.mta	Customized MTA startup file
 post_office.poa	POA startup file for a specific post office
 domain.mta	MTA startup file for a specific domain
 gwpoanxx.chm	POA online help file
 gwmtanxx.chm	MTA online help file
 gwpoanxx.dll	POA language information files
 gwmtanxx.dll	MTA language information files
 gwsnmp.dll	Customized DLL program for SNMP
 gwwww1.dll	Customized DLL program for MIME
 x*10a.dll	XIS DLL programs
 gwxis10.dll	GroupWise XIS DLL program
 agent.xml	XIS agent configuration files

---

## **c:\grpwise**

When you first install GroupWise Administration, the GroupWise agents are initially installed in platform-specific subdirectories in the **agent** directory. However, the agents cannot be run from this initial location. They must be installed on the servers where they will run.

On a Windows server, the GroupWise agents can be installed in any directory you choose. The default is `c:\grpwise`. The agent icons are set up to include the full path to whatever directory you choose.

### **gwenv1a.dll file**

The `gwenv1a.dll` file is the GroupWise Agent Engine, a program that is shared by both GroupWise agents. It provides the following services to the agents:

- Database management
- File operations
- Message handling
- Thread management
- Semaphores (file/record locking)
- Date/time services

The first agent started on a server automatically starts the GroupWise Agent Engine DLL.

### **gwpoa.exe file**

The `gwpoa.exe` file is the Post Office Agent program. You run this executable file to start the Post Office Agent. See “[Starting the POA](#)” in “[Post Office Agent](#)” in the *GroupWise 7 Administration Guide*.

### **gwmta.exe file**

The `gwmta.exe` file is the Message Transfer Agent program. You run this executable file to start the Message Transfer Agent. See “[Starting the MTA](#)” in “[Message Transfer Agent](#)” in the *GroupWise 7 Administration Guide*.

### **gwsnmp.dll file**

The `gwsnmp.dll` file provides interaction with the Windows SNMP Service, so that you can monitor the GroupWise agents using an SNMP monitoring program.

### **gwww1.dll file**

The `gwww1.dll` file provides parsing of MIME messages received from the Internet.

### **strtpxx.poa file** **post\_office.poa file**

The POA startup file contains startup switches for the POA. Switch settings placed in the POA startup file override comparable options set for the POA in ConsoleOne. The *xx* in the startup filename represents a two-letter language code.

During installation, a customized version of the POA startup file, named *post\_office.poa*, is created. This customized version has the */home* startup switch automatically set to the post office directory the POA will service. See “Using POA Startup Switches” in “Post Office Agent” in the *GroupWise 7 Administration Guide*.

### **strtpxx.mta file** **domain.mta file**

The MTA startup file contains startup switches for the MTA. Switch settings placed in the MTA startup file override comparable options set for the MTA in ConsoleOne. The *xx* in the startup filename represents a two-letter language code.

During installation, a customized version of the MTA startup file, named *domain.MTA*, is created. This customized version has the */home* startup switch automatically set to the domain directory the MTA will service. See “Using MTA Startup Switches” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*.

### **agentnxx.chm files**

The *.chm* files contain the online documentation for the agents. Online Help is available by clicking Help in the agent consoles on the server where the agents are running. In addition, dialog boxes have a Help button for context-sensitive Help.

The first five characters of the filename are the agent name. The digit *n* is a version number. The last two characters *xx* are a language code.

### **agentnxx.dll files**

The *agentnxx.dll* files contain all language-specific information for the agents. The digit *n* is a version number. The last two characters *xx* are a language code.

### **x\*10a.dll and gwxis10.dll files**

The *x\*10a.dll* and *gwxis10.dll* programs provide XIS capability for the GroupWise agents, so that you can create XML documents to monitor and change the agents as needed.

### **agent.xml files**

The *agent.xml* files are specialized agent configuration files for use in the XIS environment.

### **help directory**











The *help* directory contains language-specific subdirectories for the help files available from the POA and MTA Web consoles. See “Using the POA Web Console” in “Post Office Agent” and “Using the MTA Web Console” in “Message Transfer Agent” in the *GroupWise 7 Administration Guide*.

## 8.2 Internet Agent Installation

- [Section 8.2.1, “NetWare Installation Directory,”](#) on page 119
- [Section 8.2.2, “Linux Installation Directory,”](#) on page 120
- [Section 8.2.3, “Windows Installation Directory,”](#) on page 124

### 8.2.1 NetWare Installation Directory

---

 <code>sys:\system</code>	NetWare Internet Agent installation directory
 <code>gwenn5.nlm</code>	GroupWise 7 Agent Engine
 <code>gwia.nlm</code>	Internet Agent NLM program
 <code>gwia.cfg</code>	Internet Agent configuration file
 <code>gwianxx.fil</code>	Internet Agent language information file
 <code>gwia.ncf</code>	Internet Agent load file
 <code>x*5.nlm</code>	XIS NLM programs
 <code>gwxis12.nlm</code>	GroupWise XIS NLM programs
 <code>gwia.xml</code>	XIS Internet Agent configuration file
 <code>help</code>	Subdirectory for GroupWise agent console help files

---

See also [Section 7.4, “Internet Agent Queue Directory,”](#) on page 87.

#### NetWare Internet Agent installation directory

On a NetWare server, the GroupWise Internet Agent is typically installed in the `sys:\system` directory. You can choose a different location during installation.

#### gwenn5.nlm file

The `gwenn5.nlm` file is the GroupWise 7 Agent Engine, a program that is shared by all GroupWise agents. It provides the following services to the agents:

- Database management
- File operations
- Message handling
- Thread management
- Semaphores (file/record locking)
- Date/time services

The first agent loaded on a server automatically loads the GroupWise Agent Engine.

## gwia.nlm file

The `gwia.nlm` file is the Internet Agent program. You load this NLM program to start the Internet Agent. See “[Starting the Internet Agent](#)” in “[Installing the GroupWise Internet Agent](#)” in the *GroupWise 7 Installation Guide*.

## gwia.cfg file

The Internet Agent configuration file contains startup switches for the Internet Agent. Switch settings placed in the Internet Agent startup file override comparable options set for the Internet Agent in ConsoleOne. The startup file is named the same as the Internet Agent object in ConsoleOne. The default is `gwia`.

During installation, a customized version of the Internet Agent startup file is created in `sys:\system`. This customized version has the `/home` startup switch automatically set to the domain directory where the Internet Agent’s queue directories are located. See “[Using Internet Agent Startup Switches](#)” in “[Internet Agent](#)” in the *GroupWise 7 Administration Guide*.

## gwianxx.fil files

This file contains all language-specific information for the Internet Agent. The digit *n* is a version number. The last two characters *xx* are a language code.

## gwia.ncf file

The `gwia.ncf` file is the NetWare configuration file that automatically loads the Internet Agent whenever the server is restarted. A typical `gwia.ncf` file would look similar to the following:

```
load sys:\system\gwia @gwia.cfg
```

## x\*5.nlm and gwxis12.nlm files






The `x*5.nlm` and `gwxis12.nlm` programs provide XIS capability for the GroupWise agents, so that you can create XML documents to monitor and change the agents as needed.

## gwia.xml file

The `gwia.xml` file is a specialized Internet Agent configuration file for use in the XIS environment.

## 8.2.2 Linux Installation Directory














---

 <code>/opt/novell/groupwise/agents</code>	Linux agent installation directory
 <code>bin</code>	Subdirectory for GroupWise agent executables
 <code>gwia</code>	Internet Agent executable
 <code>gwia.xml</code>	Internet Agent XIS configuration file
 <code>gwha</code>	GroupWise High Availability service executable

---









---

 <code>lib</code>	Subdirectory for GroupWise agent library files
 <code>gwiaxxx.fil</code>	Internet Agent language information file
 <code>libgwia.so</code>	Internet Agent shared library file
 <code>libgwia_ui.so</code>	Internet Agent user interface shared library file
 <code>libgwaha.so*</code>	GroupWise High Availability service library files
 <code>*.so</code>	Supporting shared library files
 <code>image</code>	Subdirectory for icon images
 <code>share</code>	Subdirectory for agent shared files
 <code>gwia.cfg</code>	Internet Agent configuration file
 <code>agtcon</code>	Subdirectory for agent console files
 <code>help</code>	Subdirectory agent console help files
 <code>webcon</code>	Subdirectory for agent Web console files
 <code>help</code>	Subdirectory for agent Web console help files

---








---

 <code>/etc/init.d</code>	Standard Linux location for application startup scripts
 <code>grpwise</code>	Startup script for the Internet Agent
 <code>rc3.d</code>	Standard Linux location for run-level-3 symbolic links
 <code>S99grpwise</code>	Symbolic link to the startup script for the Internet Agent
 <code>rc5.d</code>	Standard Linux location for run-level-5 symbolic links
 <code>S99grpwise</code>	Symbolic link to the startup script for the Internet Agent

---







---

 <code>/etc/opt</code>	Standard Linux location for application configuration files
 <code>novell/groupwise</code>	Subdirectory for GroupWise configuration files
 <code>gwha.conf</code>	GroupWise High Availability service configuration file
 <code>agents</code>	Subdirectory for GroupWise agents
 <code>uid.conf</code>	Agent configuration file for running as a non-root user

---



---

 <code>/var/log/</code>	Standard Linux location for application log files
 <code>novell/groupwise</code>	Subdirectory for GroupWise agent log files
 <code>domain.gwia</code>	Domain-specific subdirectory for Internet Agent log files
 <code>mmdgwia.nnn</code>	Internet Agent log files

---

See also [Section 7.4, “Internet Agent Queue Directory,”](#) on page 87.

## **agents directory**

On a Linux server, the Internet Agent is always installed in subdirectories of `/opt/novell/groupwise/agents`.

## **bin directory**

The `bin` directory holds GroupWise executable files.

### **gwia file**

The `gwia` file is the Internet Agent executable. You run this executable file to start the Internet Agent. See “[Starting the Internet Agent](#)” in “[Installing the GroupWise Internet Agent](#)” in the *GroupWise 7 Installation Guide*.

### **gwia.xml file**

The `gwia.xml` file is a specialized configuration file for use in the XIS environment.

### **gwha file**

The `gwha` file is the GroupWise High Availability service executable. If the Internet Agent goes down for any reason, the High Availability service automatically restarts it. See “[Enabling the High Availability Service for the Linux Agents](#)” in “[Installing GroupWise Agents](#)” in the *GroupWise 7 Installation Guide*.

## **lib directory**

The `lib` directory holds GroupWise shared library files.

### **gwixxx.fil files**

This file contains all language-specific information for the Internet Agent. The last two characters `xx` are a language code.

### **\*.so files**

These files are Linux shared library files that provide information to the Internet Agent executable.

## **image directory**

The `image` directory has subdirectories for agent icons for both color and monochrome displays.

## **share directory**

The `share` directory holds agent startup files and files that are used by the agent consoles and Web consoles.

### **gwia.cfg**

The Internet Agent configuration file contains startup switches for the Internet Agent. Switch settings placed in the Internet Agent configuration file override comparable configuration options

set for the Internet Agent in ConsoleOne. The startup file is named the same as the Internet Agent object in ConsoleOne. The default is `gwia`.

During installation, the Internet Agent startup file is created in the share directory with the `--home` startup switch automatically set to the domain directory where the Internet Agent queue directory is located. See “[Using Internet Agent Startup Switches](#)” in “[Internet Agent](#)” in the *GroupWise 7 Administration Guide*.

### agtcon directory

The `agtcon` directory holds subdirectories and files used by the agent consoles, such as help files.

### webcon directory

The `webcon` directory holds subdirectories and files used by the agent Web consoles, such as help files.

### **/etc/init.d directory**

The `/etc/init.d` directory is the standard location for Linux startup scripts.

### grpwise file

The `grpwise` script is created automatically during installation. You can use the script to start, restart, stop, and display status information about the Internet Agent. For more information about starting the Internet Agent, see “[Starting the Internet Agent](#)” in “[Installing the GroupWise Internet Agent](#)” in the *GroupWise 7 Installation Guide*.

### rc3.d directory

The `rc3.d` directory holds symbolic links to scripts that you want your Linux server to run when it is booted to runlevel 3 (multi-user; boots to a text mode login prompt without the X Window System). The symbolic link to the `grpwise` script is `S99grpwise`. It is created if you choose during installation to have the Internet Agent start automatically when the server boots.

### rc5.d directory

The `rc5.d` directory holds symbolic links to scripts that you want your Linux server to run when it is booted to runlevel 5 (multi-user; boots to the X Window System login dialog box). The symbolic link to the `grpwise` script is `S99grpwise`. It is created if you choose during installation to have the Internet Agent start automatically when the server boots.

### **/etc/opt/novell/groupwise directory**

The `/etc/opt` directory is the standard location of application configuration files on Linux. Files that configure how the GroupWise Internet Agent interacts with Linux are stored in the `novell/groupwise` subdirectory.

### gwha.conf file

The `gwha.conf` file is the GroupWise High Availability service configuration file. It is created automatically during installation and provides the information necessary for the High Availability service to restart the Internet Agent if it goes down unexpectedly. See “[Enabling the High Availability Service for the Linux Agents](#)” in “[Installing GroupWise Agents](#)” in the *GroupWise 7 Installation Guide*.

uid.conf file

The `uid.conf` file configures the Internet Agent to run as a non-root user. See “[Running the Agents as a Non-root User](#)” in “[Installing GroupWise Agents](#)” in the *GroupWise 7 Installation Guide*.

### **`/var/log/novell/groupwise` directory**

The `/var/log` directory is the standard location for log files on Linux. All GroupWise agent log files are created in the `novell/groupwise` subdirectory.

### **`domain.gwia` directory**











The `domain.gwia` directory is a domain-specific location for Internet Agent log files.

Within the `domain.gwia` directory, the Internet Agent creates log files (`mmdgwia.nnn`) to inform you of its processing and any problems it encounters. For more information about log files, see “[Using Internet Agent Log Files](#)” in “[Internet Agent](#)” in the *GroupWise 7 Administration Guide*.

The first two digits of the filename represent the month; the next two digits represent the day of the month. The three-digit extension is a sequence number for multiple log files created on the same day. For example, `0518gwia.002` is the second Internet Agent log file created on May 18.

## **8.2.3 Windows Installation Directory**

---

 <code>c:\grpwise\gwia</code>	Windows Internet Agent installation directory
 <code>gwenv1a.dll</code>	GroupWise Agent Engine
 <code>gwia.exe</code>	Internet Agent program
 <code>gwia.cfg</code>	Internet Agent configuration file
 <code>gwianxx.chm</code>	Internet Agent online help file
 <code>gwianxx.dll</code>	Internet Agent language information file
 <code>gwww1.dll</code>	Customized DLL program for MIME
 <code>x*10a.dll</code>	XIS DLL programs
 <code>gwxis10.dll</code>	GroupWise XIS DLL program
 <code>gwia.xml</code>	XIS agent configuration file

---

See also [Section 7.4, “Internet Agent Queue Directory,”](#) on page 87.

### **`c:\grpwise\gwia`**

On a Windows server, the Internet Agent can be installed in any directory you choose. The default location is `c:\grpwise\gwia`. The Internet Agent icon is set up to include the full path to whatever directory you choose.

## **gwenv1a.dll file**

The `gwenv1a.dll` file is the GroupWise Agent Engine, a program that is shared by both GroupWise agents. It provides the following services to the agents:

- Database management
- File operations
- Message handling
- Thread management
- Semaphores (file/record locking)
- Date/time services

The first agent started on a server automatically starts the GroupWise Agent Engine DLL.

## **gwia.exe file**

The `gwia.exe` file is the Internet Agent program. You run this executable file to start the Internet Agent. See “[Starting the Internet Agent](#)” in “[Installing the GroupWise Internet Agent](#)” in the *GroupWise 7 Installation Guide*.

## **gwia.cfg file**

On Windows, the `gwia.cfg` file in the installation directory is simply a pointer to the `gwia.cfg` file under the `domain` directory where the actual Internet Agent configuration file is located.

## **gwianxx.chm file**

The `.chm` files contain the online documentation for the Internet Agent. Online help is available by clicking *Help* in the Internet Agent console on the server where the agent is running. In addition, dialog boxes have a Help button for context-sensitive Help.

The digit *n* is a version number. The last two characters *xx* are a language code.

## **gwianxx.dll files**

The `gwianxx.dll` files contain all language-specific information for the Internet Agent. The digit *n* is a version number. The last two characters *xx* are a language code.

## **gwww1.dll file**

The `gwww1.dll` file provides parsing of MIME messages received from the Internet.

## **x\*10a.dll and gwxis10.dll files**

The `x*10a.dll` and `gwxis10.dll` programs provide XIS capability for the GroupWise agents, so that you can create XML documents to monitor and change the agents as needed.

## **gwia.xml file**


















The `gwia.xml` file is a specialized agent configuration file for use in the XIS environment.

## 8.3 WebAccess Agent Installation

- [Section 8.3.1, “NetWare Installation Directory,”](#) on page 126
- [Section 8.3.2, “Linux Installation Directory,”](#) on page 128
- [Section 8.3.3, “Windows Installation Directory,”](#) on page 134
- [Section 8.3.4, “Document Viewer Agent Working Directory,”](#) on page 137

### 8.3.1 NetWare Installation Directory

---

 <code>sys:\system</code>	NetWare WebAccess Agent installation directory
 <code>gwenn5.nlm</code>	GroupWise 7 Agent Engine
 <code>gwinter.nlm</code>	WebAccess Agent program
 <code>gwdva.nlm</code>	Document Viewer Agent program
 <code>strtweb.ncf</code>	WebAccess Agent load file
 <code>stopweb.ncf</code>	WebAccess Agent unload file
 <code>webac70a.waa</code>	WebAccess Agent startup file
 <code>gwdva.dva</code>	Document Viewer Agent startup file
 <code>x*5.nlm</code>	XIS NLM programs
 <code>gwxis12.nlm</code>	GroupWise XIS NLM program
 <code>gwinter.xml</code>	WebAccess Agent XIS configuration file
 <code>cache</code>	Subdirectory for WebAccess template file storage
 <code>template\xx</code>	Subdirectory for HTML template files
 <code>webacc.tpt</code>	WebAccess template files
 <code>publish.tpt</code>	WebPublisher template files
 <code>gwdva.dir</code>	Document Viewer Agent working directory
 <code>help</code>	Subdirectory for GroupWise agent console help files

---

Additional WebAccess files are integrated into your Web server to support the WebAccess client and the WebAccess Agent Web console. See [Section 8.5, “Apache/Tomcat Installation,”](#) on page 143. See also [Section 7.5, “WebAccess Agent Queue Directory,”](#) on page 93.

#### NetWare WebAccess Agent installation directory

On a NetWare server, the GroupWise WebAccess Agent is typically installed in the `sys:\system` directory. You can choose a different location during installation.

## **gwenn5.nlm file**

The `gwenn5.nlm` file is the GroupWise 7 Agent Engine, a program that is shared by all GroupWise agents. It provides the following services to the agents:

- Database management
- File operations
- Message handling
- Thread management
- Semaphores (file/record locking)
- Date/time services

The first agent loaded on a server automatically loads the GroupWise Agent Engine.

## **gwinter.nlm file**

The `gwinter.nlm` file is the WebAccess Agent program.

## **gwdva.nlm file**

The `gwdva.nlm` file is the Document Viewer Agent program.

## **strtweb.ncf file**

The `strtweb.ncf` file is the NetWare configuration file that automatically loads the WebAccess Agent whenever the server is restarted. A typical `strtweb.ncf` file would look similar to the following:

```
load sys:\system\gwinter @webac70a.waa
```

It includes the WebAccess Agent startup file in the load command. For more information, see “[NetWare and Windows: Starting GroupWise WebAccess](#)” in “[Installing GroupWise WebAccess](#)” in the *GroupWise 7 Installation Guide*.

## **stopweb.ncf**

The `stopweb.ncf` file is the NetWare configuration file that unloads the WebAccess Agent. A typical `stopweb.ncf` file would look similar to the following:

```
unload gwinter
```

## **webac70a.waa file**

The WebAccess Agent startup file contains startup switches for the WebAccess Agent. Switch settings placed in the WebAccess Agent startup file override comparable options set for the WebAccess Agent in ConsoleOne. The startup file is named the same as the WebAccess Agent object in ConsoleOne. The default is `webac70a`.

During installation, a customized version of the WebAccess Agent startup file is created. This customized version has the `/home` startup switch automatically set to the domain directory where the WebAccess Agent’s queue directories are located. See “[Using WebAccess Startup Switches](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

### **gwdva.dva file**

The `gwdva.dva` file is the Document Viewer Agent startup file. The Viewer Agent is currently configured completely by startup switches. For more information, see “[Document Viewer Agent Startup Switches](#)”.

### **x\*5.nlm and gwxis12.nlm files**

The `x*5.nlm` and `gwxis12.nlm` programs provide XIS capability for the GroupWise agents, so that you can create XML documents to monitor and change the agents as needed.

### **gwinter.xml file**

The `gwinter.xml` file is a specialized WebAccess Agent configuration file for use in the XIS environment.

### **cache\template\xx directory**

The `cache\template\xx` directory holds language-specific HTML template files that the WebAccess Agent passes to the Document Viewer Agent for viewing documents in documents in WebAccess and WebPublisher. The `xx` is a two-letter language code.

### **gwdva.dir directory**










See [Section 8.3.4, “Document Viewer Agent Working Directory,”](#) on page 137.

### **help directory**

The `help` directory holds help files and images used by the WebAccess Agent Web console. See “[Using the WebAccess Agent Web Console](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

## **8.3.2 Linux Installation Directory**






















---

 <code>/opt/novell/groupwise</code>	Novell GroupWise installation directory
 <code>agents</code>	Linux agent installation directory
 <code>bin</code>	Subdirectory for GroupWise agent executables
 <code>gwinter</code>	WebAccess Agent executable
 <code>gwinter.xml</code>	WebAccess Agent XIS configuration file
 <code>webac70axx.waa</code>	Boilerplate WebAccess startup file
 <code>template</code>	Subdirectory for HTML template files
 <code>gwdva</code>	Document Viewer Agent executable
 <code>gwdva.dir</code>	Document Viewer Agent working directory







---





---

 <code>lib</code>	Subdirectory for GroupWise agent library files
 <code>*.so</code>	Supporting shared library files
 <code>image</code>	Subdirectory for icon images
 <code>share</code>	Subdirectory for agent shared files
 <code>webac70a.waa</code>	WebAccess Agent startup file
 <code>gwdva.dva</code>	Document Viewer Agent startup file
 <code>webcon</code>	Subdirectory for agent Web console files
 <code>help</code>	Subdirectory for agent Web console help files
 <code>webaccess</code>	Subdirectory for WebAccess Application files
 <code>webacc.cfg</code>	WebAccess Application configuration file
 <code>commgr.cfg</code>	Communications Manager configuration file
 <code>spellchk.cfg</code>	Novell Speller Application configuration file
 <code>ldap.cfg</code>	LDAP service provider configuration file
 <code>default</code>	Subdirectory for boilerplate configuration files
 <code>logs</code>	Subdirectory for WebAccess Application log files
 <code>users</code>	Subdirectory for users' WebAccess session information
 <code>webpublisher</code>	Subdirectory for WebAccess Application files
 <code>webpub.cfg</code>	WebPublisher Application configuration file
 <code>commgr.cfg</code>	Communications Manager configuration file
 <code>default</code>	Subdirectory for boilerplate configuration files
 <code>logs</code>	Subdirectory for WebPublisher Application log files

---






 <code>/etc/init.d</code>	Standard Linux location for application startup scripts
 <code>grpwise-wa</code>	Startup script for the WebAccess Agent
 <code>rc3.d</code>	Standard Linux location for run-level-3 symbolic links
 <code>S99grpwise-wa</code>	Symbolic link to the startup script for the WebAccess Agent
 <code>rc5.d</code>	Standard Linux location for run-level-5 symbolic links
 <code>S99grpwise-wa</code>	Symbolic link to the startup script for the WebAccess Agent

---

 <code>/var/log/</code>	Standard Linux location for application log files
 <code>novell/groupwise</code>	Subdirectory for GroupWise agent log files

---

---

 <i>domain.webac70a</i>	Domain-specific subdirectory for WebAccess Agent log files
 <i>000.prc</i>	Processing directory for log files
 <i>mmddgwia.nnn</i>	WebAccess Agent log files
 <i>gwdva</i>	Subdirectory for Viewer Agent log files
 <i>mmdddva.nnn</i>	Viewer Agent log files

---

Additional WebAccess files are integrated into your Web server to support the WebAccess client and the WebAccess Agent Web console. See [Section 8.5, “Apache/Tomcat Installation,”](#) on page 143. See also [Section 7.5, “WebAccess Agent Queue Directory,”](#) on page 93.

### agents directory

On a Linux server, the WebAccess Agent is always installed in subdirectories of `/opt/novell/groupwise/agents`.

### bin directory

The `bin` directory holds GroupWise executable files.

#### gwinter file

The `gwinter` file is the WebAccess Agent executable. You run this executable file to start the WebAccess Agent. See “[Linux: Setting Up GroupWise WebAccess](#)” in “[Installing GroupWise WebAccess](#)” in the *GroupWise 7 Installation Guide*.

#### gwinter.xml file

The `gwinter.xml` file is a specialized configuration file for use in the XIS environment.

#### webac70axx.waa file

The `webac70axx.waa` file is the boilerplate file from which a domain-specific `webac70a.waa` file is created in the share directory. The `webac70a` represents the name of the WebAccess Agent object in eDirectory. The `xx` represents a two-letter language code.

#### template\xx directory

The `template\xx` directory holds language-specific HTML template files that the WebAccess Agent passes to the Document Viewer Agent for viewing documents in WebAccess and WebPublisher. The `xx` is a two-letter language code.

#### gwdva file

The `gwdva` file is the Document Viewer Agent executable. The WebAccess Agent starts and stops the Viewer Agent automatically whenever it starts and stops.

#### gwdva.dir directory

See [Section 8.3.4, “Document Viewer Agent Working Directory,”](#) on page 137.

## lib directory

The `lib` directory holds GroupWise shared library files.

### \*.so files

The \*.so files are Linux shared library files that provide information to the WebAccess Agent executable.

## image directory

The `image` directory has subdirectories for agent icons for both color and monochrome displays.

## share directory

The `share` directory holds agent startup files and files that are used by the agent consoles and Web consoles.

### webac70a.waa file

The WebAccess Agent startup file contains startup switches for the WebAccess Agent. Switch settings placed in the WebAccess Agent startup file override comparable options set for the WebAccess Agent in ConsoleOne. The startup file is named the same as the WebAccess Agent object in ConsoleOne. The default is `webac70a`.

During installation, a customized version of the WebAccess Agent startup file is created. This customized version has the `/home` startup switch automatically set to the domain directory where the WebAccess Agent's queue directories are located. See “[Using WebAccess Startup Switches](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

### gwdva.dva file

The `gwdva.dva` file is the Document Viewer Agent startup file. The Viewer Agent is currently configured completely by startup switches. For more information, see “[Document Viewer Agent Startup Switches](#)”.

## webcon directory

The `webcon` directory holds subdirectories and files used by the agent Web consoles, such as help files.

## webaccess directory

The `webaccess` directory holds files used by the WebAccess Application.

### webacc.cfg file

The `webacc.cfg` file holds the same configuration information that is stored on the WebAccess Application object (named GroupWiseWebAccess) in eDirectory. For more information, see “[Configuring the WebAccess Application](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

### commgr.cfg file

The `commgr.cfg` file holds the same configuration information that is stored on the GroupWise Provider object (named GroupWiseProvider) in eDirectory, including the IP address and encryption key for the WebAccess Agent. This information enables the WebAccess Application to communicate with the WebAccess Agent. For more information, see “[Configuring the GroupWise Service Provider](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

A copy of the `commgr.cfg` file is automatically maintained in the WebAccess Agent queue directory (`domain/wpgate/webac70a`).

### spellchk.cfg file

The `spellchk.cfg` file holds the same configuration information that is stored on the Novell Speller Application object (named NovellSpeller) in eDirectory. For more information, see “[Configuring the Novell Speller Application](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

### ldap.cfg file

The `ldap.cfg` file holds the same configuration information that is stored on the LDAP Provider object (named LDAPProvider) in eDirectory. For more information, see “[Configuring the LDAP Service Provider](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

### default directory

The `default` directory holds boilerplate versions of the various `.cfg` files.

### logs directory

The `logs` subdirectory holds WebAccess Application log files. For more information, see “[Controlling WebAccess Application Logging](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

### users directory

The `users` subdirectory holds session files for WebAccess users. If WebAccess times out after a period of user inactivity, the user’s session information is saved. When the user logs back in, the session information is retrieved so that the user can continue working without loss of data. Also, users’ message text is saved during each session, so that if the WebAccess Application is restarted or goes down, users do not lose the message text they were composing at the time. Session files are deleted when users log back in.

### webpublisher directory

The `webpublisher` directory holds files used by the WebPublisher Application.

### webpub.cfg

The `webpub.cfg` file holds the same configuration information that is stored on the WebPublisher Application object (named GroupWiseWebPublisher) in eDirectory. For more information, see “[Configuring the WebPublisher Application](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

## commgr.cfg file

The `commgr.cfg` file holds the same configuration information that is stored on the GroupWise Provider object (named GroupWiseProvider) in eDirectory, including the IP address, port number, number of threads, and encryption key for the WebAccess Agent. This information enables the WebAccess Application to communicate with the WebAccess Agent. For more information, see “[Configuring the GroupWise Service Provider](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

A copy of the `commgr.cfg` file is automatically maintained in the WebAccess Agent queue directory (`domain/wpgate/webac70a`).

## default directory

The `default` directory holds boilerplate versions of the `webpub.cfg` and `commgr.cfg` files.

## logs directory

The `logs` subdirectory holds WebPublisher Application log files. For more information, see “[Controlling WebAccess Application Logging](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

## /etc/init.d directory

The `/etc/init.d` directory is the standard location for Linux startup scripts.

## grpwise-wa file

The `grpwise-wa` script is created automatically during installation. You can use the script to start, restart, stop, and display status information about the WebAccess Agent. For more information about starting the WebAccess Agent, see “[Linux: Setting Up GroupWise WebAccess](#)” in “[Installing GroupWise WebAccess](#)” in the *GroupWise 7 Installation Guide*.

## rc3.d directory

The `rc3.d` directory holds symbolic links to scripts that you want your Linux server to run when it is booted to runlevel 3 (multi-user; boots to a text mode login prompt without the X Window System). The symbolic link to the `grpwise-wa` script is `S99grpwise-wa`. It is created if you choose during installation to have the WebAccess Agent start automatically when the server boots.

## rc5.d directory

The `rc5.d` directory holds symbolic links to scripts that you want your Linux server to run when it is booted to runlevel 5 (multi-user; boots to the X Window System login dialog box). The symbolic link to the `grpwise-wa` script is `S99grpwise-wa`. It is created if you choose during installation to have the WebAccess Agent start automatically when the server boots.

## /var/log/novell/groupwise directory

The `/var/log` directory is the standard location for log files on Linux. All GroupWise agent log files are created in the `novell/groupwise` subdirectory.

## domain.webac70a directory

The `domain.webac70a` directory is a domain-specific location for WebAccess Agent log files.

### 000.prc directory

Within the 000.prc directory, the WebAccess Agent creates log files (*mmddweb.nnn*) to inform you of its processing and any problems it encounters. For more information about log files, see “Controlling WebAccess Agent Logging” in “WebAccess” in the *GroupWise 7 Administration Guide*.



















The first two digits of the filename represent the month; the next two digits represent the day of the month. The three-digit extension is a sequence number for multiple log files created on the same day. For example, 0518web.002 is the second WebAccess Agent log file created on May 18.

### gwdva directory

The gwdva directory stores Viewer Agent log files. The first two digits of the filename represent the month; the next two digits represent the day of the month. The three-digit extension is a sequence number for multiple log files created on the same day. For example, 0518web.002 is the second Viewer Agent log file created on May 18.

## 8.3.3 Windows Installation Directory

---

 c:\webacc	Windows WebAccess Agent installation directory
 gwenv1a.dll	GroupWise Agent Engine
 gwinter.exe	WebAccess Agent program
 strtweb.bat	WebAccess Agent batch file
 webac70a.waa	WebAccess Agent startup file
 gwdva.exe	Document Viewer Agent program
 gwdva.dva	Document Viewer Agent startup file
 gwdva.dir	Document Viewer Agent working directory
 gwwanxx.dll	WebAccess Agent language information file
 gwwasnmp.dll	Customized DLL program for SNMP
 gwww1.dll	Customized DLL program for MIME
 x*10a.dll	XIS DLL programs
 gwxis10.dll	GroupWise XIS DLL program
 gwinter.xml	WebAccess Agent XIS configuration file
 cache\template\xx	Subdirectory for HTML template files
 webacc.tpt	WebAccess template files
 publish.tpt	WebPublisher template files
 help	Subdirectory for GroupWise agent console help files

---

Additional WebAccess files are integrated into your Web server to support the WebAccess client and the WebAccess Agent Web console. See [Section 8.5, “Apache/Tomcat Installation,” on page 143](#). See also [Section 7.5, “WebAccess Agent Queue Directory,” on page 93](#).

## **c:\webacc**

On a Windows server, the WebAccess Agent can be installed in any directory you choose. The default location is `c:\webacc`. The WebAccess Agent desktop icon is set up to include the full path to whatever directory you choose.

## **gwenv1a.dll file**

The `gwenv1a.dll` file is the GroupWise Agent Engine, a program that is shared by all GroupWise agents. It provides the following services to the agents:

- Database management
- File operations
- Message handling
- Thread management
- Semaphores (file/record locking)
- Date/time services

The first agent started on a server automatically starts the GroupWise Agent Engine DLL.

## **gwinter.exe file**

The `gwinter.exe` file is the WebAccess Agent program.

## **strtweb.bat file**

The `strtweb.bat` file is used to start the WebAccess Agent. The batch file specifies the WebAccess startup file. A typical `strtweb.bat` file includes the following:

```
title Novell GroupWise WebAccess
@echo off
cls
gwinter.exe @webac70a.waa
```

You run this batch file to start the WebAccess Agent. See [“NetWare and Windows: Starting GroupWise WebAccess”](#) in [“Installing GroupWise WebAccess”](#) in the *GroupWise 7 Installation Guide*.

## **webac70a.waa file**

The WebAccess Agent startup file contains startup switches for the WebAccess Agent. Switch settings placed in the WebAccess Agent startup file override comparable configuration options set for the WebAccess Agent in ConsoleOne. The startup file is named the same as the WebAccess Agent object in eDirectory. The default is `webac70a`.

During installation, the WebAccess Agent startup file is created with the `/home` startup switch automatically set to the domain directory where the WebAccess Agent queue directory

(*domain\wpgate\webac70a*) is located. See “Using WebAccess Startup Switches” in “WebAccess” in the *GroupWise 7 Administration Guide*.

### **gwdva.exe file**

The `gwdva.exe` file is the Document Viewer Agent program. The WebAccess Agent automatically starts and stops the Viewer Agent whenever the WebAccess Agent starts and stops.

### **gwdva.dva file**

The `gwdva.dva` file is the Document Viewer Agent startup file. The Viewer Agent is currently configured completely by startup switches. See “Document Viewer Agent Startup Switches”.

### **gwdva.dir directory**

See [Section 8.3.4, “Document Viewer Agent Working Directory,”](#) on page 137.

### **gwwanxx.dll files**

The `gwwanxx.dll` files contain all language-specific information for the WebAccess Agent. The digit *n* is a version number. The last two characters *xx* are a language code.

### **gwwasntp.dll file**

The `gwwasntp.dll` file provides interaction with the Windows SNMP Service, so that you can monitor the WebAccess Agent using an SNMP monitoring program. This file is not installed unless you enable SNMP during installation. It cannot be installed if the SNMP Service is not installed on the Windows server.

### **gwww1.dll file**

The `gwww1.dll` file provides parsing of MIME messages received from the Internet.

### **x\*10a.dll and gwxis10.dll files**

The `x*10a.dll` and `gwxis10.dll` programs provide XIS capability for the GroupWise agents, so that you can create XML documents to monitor and change the agents as needed.

### **gwinter.xml file**

The `gwia.xml` file is a specialized agent configuration file for use in the XIS environment.

### **cache\template\xx directory**

The `cache\template\xx` directory holds language-specific HTML template files that the WebAccess Agent passes to the Document Viewer Agent for viewing documents in WebAccess and WebPublisher. The *xx* is a two-letter language code.

### **help directory**

The `help` directory holds help files and images used by the WebAccess Agent Web console. See “Using the WebAccess Agent Web Console” in “WebAccess” in the *GroupWise 7 Administration Guide*.



## 8.3.4 Document Viewer Agent Working Directory










The Document Viewer Agent creates its working directory as a subdirectory of its installation directory. The default location varies by platform:

---

NetWare:	<code>sys:\system\gwdva.dir</code>
Linux:	<code>/opt/novell/groupwise/agents/bin/gwdva.dir</code>
Windows:	<code>c:\webacc\gwdva.dir</code>

---

---

 <code>gwdva.dir</code>	Document Viewer Agent working directory
 <code>cache</code>	Subdirectory for caching converted documents for repeated display
 <code>000</code>	Subdirectory for converted GroupWise library documents
 <code>tran</code>	Subdirectory for converted attachment documents
 <code>problem</code>	Subdirectory for information about documents that failed conversion
 <code>hold</code>	Subdirectory for quarantined documents that failed HTML conversion
 <code>log</code>	Subdirectory for Document Viewer Agent log files
 <code>temp</code>	Subdirectory for the temporary files using during HTML conversion
 <code>template</code>	(not currently used)

---

### **gwdva.dir directory**

The `gwdva.dir` directory is the working directory for the Document Viewer Agent.

### **cache directory**

The `cache` directory contains subdirectories for managing the documents that the Viewer Agent has already converted. See “[Document Cache](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

### **000 directory**

The `000` directory holds GroupWise library documents that have been converted to HTML. Because these documents belong to a GroupWise library, they are retained for a longer period of time. If the documents in the `000` directory exceed the established maximum cache size, a new directory, `001`, is created. Additional library cache directories are created as needed.

### **tran directory**

The `tran` directory holds attachment documents that have been converted to HTML. Attached documents are more transitory than GroupWise library documents and are retained for a shorter period of time.

## problem directory

The `problem` directory stores information about documents that have failed conversion. This prevents the Viewer Agent from needlessly attempting to convert the same failed documents.

## hold directory

The `hold` directory is the document quarantine directory. Here the Viewer Agent places documents that have failed HTML conversion. You can configure the Viewer Agent to notify an administrator when a document fails conversion. See “[Document Quarantine](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*

## log directory

The `log` directory stores log files produced by the Viewer Agent. See “[Agent Log Files](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

---

**NOTE:** On Linux, Viewer Agent log files are stored in the typical location for log files on Linux (`/var/log/novell/groupwise/gwdva`), rather than under the `gwdva.dir` directory.

---

## temp directory

The `temp` directory is used for the temporary files created during HTML conversion. See “[Document Conversion](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

# 8.4 Monitor Agent Installation

- [Section 8.4.1, “Linux Installation Directory,”](#) on page 138
- [Section 8.4.2, “Windows Installation Directory,”](#) on page 141





## 8.4.1 Linux Installation Directory

---







 <code>/opt/novell/groupwise</code>	GroupWise installation directory
 <code>agents</code>	Linux agent installation directory
 <code>bin</code>	Subdirectory for GroupWise agent executables
 <code>gwmon</code>	Monitor Agent executable
 <code>lib</code>	Subdirectory for GroupWise agent library files
 <code>*.so</code>	Supporting shared library files
 <code>share</code>	Subdirectory for agent shared files
 <code>monitor.xml</code>	Monitor Agent configuration file
 <code>gwmonitor</code>	Subdirectory for Monitor Application files

---






---

 <code>gwmonitor.cfg</code>	Monitor Application configuration file
 <code>default</code>	Subdirectory for boilerplate configuration files
 <code>logs</code>	Subdirectory for Monitor Application log files
 <code>users</code>	Directory for Monitor users' session files

---

 <code>/etc/init.d</code>	Standard Linux location for application startup scripts
 <code>grpwise-ma</code>	Startup script for the Monitor Agent
 <code>rc3.d</code>	Standard Linux location for run-level-3 symbolic links
 <code>S99grpwise-ma</code>	Symbolic link to the startup script for the Monitor Agent
 <code>rc5.d</code>	Standard Linux location for run-level-5 symbolic links
 <code>S99grpwise-ma</code>	Symbolic link to the startup script for the Monitor Agent

---

 <code>/var/log/</code>	Standard Linux location for application log files
 <code>novell/groupwise</code>	Subdirectory for GroupWise agent log files
 <code>gwmon</code>	Subdirectory for Monitor Agent log files
 <code>mmdmon.nnn</code>	Monitor Agent event log files
 <code>mmdhist.nnn</code>	Monitor Agent history log files

---

## agents directory

On a Linux server, the Monitor Agent is always installed in subdirectories of `/opt/novell/groupwise/agents`.

## bin directory

The `bin` directory holds GroupWise executable files.

### gwmon file

The `gwmon` file is the Monitor Agent executable. You run this executable file to start the Monitor Agent. See “[Starting the Monitor Agent](#)” in “[Monitor](#)” in the *GroupWise 7 Administration Guide*.

## lib directory

The `lib` directory holds GroupWise shared library files.

### \*.so files

These files are Linux shared library files that provide information to the Monitor Agent executable.

## share directory

The `share` directory holds agent startup files and files that are used by the agent consoles and Web consoles.

### monitor.xml file

The `monitor.xml` file is a specialized configuration file for use in the XIS environment.

## gwmonitor directory

The `gwmonitor` directory holds files used by the Monitor Application.

### gwmonitor.cfg file

The `gwmonitor.cfg` file holds the same configuration information that is stored on the Monitor Application object (named GroupWiseMonitor) in eDirectory. For more information, see “[Configuring the Monitor Application](#)” in “[Monitor](#)” in the *GroupWise 7 Administration Guide*.

### default directory

The `default` directory holds boilerplate versions of the `gwmonitor.cfg` file and the `monitor.xml` file.

### logs directory

The `logs` subdirectory holds Monitor Application log files. For more information, see “[Modifying Monitor Application Log Settings](#)” in “[Monitor](#)” in the *GroupWise 7 Administration Guide*.

### users directory

The `users` subdirectory holds session files for Monitor users.

## /etc/init.d directory

The `/etc/init.d` directory is the standard location for Linux startup scripts.

### grpwise-ma file

The `grpwise-ma` script is created automatically during installation. You can use the script to start, restart, stop, and display status information about the Monitor Agent. For more information about starting the Monitor Agent, see “[Starting the Monitor Agent](#)” in “[Monitor](#)” in the *GroupWise 7 Administration Guide*.

### rc3.d directory

The `rc3.d` directory holds symbolic links to scripts that you want your Linux server to run when it is booted to runlevel 3 (multi-user; boots to a text mode login prompt without the X Window System). The symbolic link to the `grpwise-ma` script is `S99grpwise-ma`. It is created if you choose during installation to have the Monitor Agent start automatically when the server boots.

### rc5.d directory

The `rc5.d` directory holds symbolic links to scripts that you want your Linux server to run when it is booted to runlevel 5 (multi-user; boots to the X Window System login dialog box). The symbolic

link to the `grpwise-ma` script is `S99grpwise-ma`. It is created if you choose during installation to have the Monitor Agent start automatically when the server boots.

## **`/var/log/novell/groupwise` directory**

The `/var/log` directory is the standard location for log files on Linux. All GroupWise agent log files are created in the `novell/groupwise` subdirectory.










### **gwmon directory**

Within the `gwmon` directory, the Monitor Agent creates two different types of log files. The `mmdmon.nnn` log files inform you of its processing and any problems it encounters. The `mmdchist.nnn` log files record dumps of all MIB values gathered during each poll cycle. For more information about log files, see “[Configuring Monitor Agent Log Settings](#)” in “[Monitor](#)” in the *GroupWise 7 Administration Guide*.

The first two digits of the filename represent the month; the next two digits represent the day of the month. The three-digit extension is a sequence number for multiple log files created on the same day. For example, `0518mon.002` is the second Monitor Agent log file created on May 18.

## **8.4.2 Windows Installation Directory**

---

 <code>c:\gwmon</code>	Windows Monitor Agent installation directory
 <code>gwenv1a.dll</code>	GroupWise Agent Engine
 <code>gwmon.exe</code>	Monitor Agent program
 <code>monitor.xml</code>	Monitor Agent configuration file
 <code>gwmonxx.dll</code>	Monitor Agent language information file
 <code>gwsnmp.dll</code>	Customized DLL program for SNMP
 <code>x*10a.dll</code>	XIS DLL programs
 <code>gwxis10.dll</code>	GroupWise XIS DLL program
 <code>gwmon.xml</code>	Monitor Agent XIS configuration file
 <code>monwork</code>	Monitor Agent working directory

---

Additional Monitor files are integrated into your Web server to support the Monitor Web console. For an example, see [Section 8.5, “Apache/Tomcat Installation,” on page 143](#).

### **`c:\gwmon`**

On a Windows server, the Monitor Agent can be installed in any directory you choose. The default location is `c:\gwmon`. The Monitor Agent desktop icon is set up to include the full path to whatever directory you choose.

### **gwenv1a.dll file**

The `gwenv1a.dll` file is the GroupWise Agent Engine, a program that is shared by all GroupWise agents. It provides the following services to the agents:

- Database management
- File operations
- Message handling
- Thread management
- Semaphores (file/record locking)
- Date/time services

The first agent started on a server automatically starts the GroupWise Agent Engine DLL.

### **gwmon.exe file**

The `gwmon.exe` file is the Monitor Agent program. You run this executable file to start the Monitor Agent. See “[Starting the Monitor Agent](#)” in “[Monitor](#)” in the *GroupWise 7 Administration Guide*.

### **monitor.xml**

The `monitor.xml` file stores the Monitor Agent configuration information that you establish in the Monitor Agent console, as described in “[Configuring the Monitor Agent](#)” in “[Monitor](#)” in the *GroupWise 7 Administration Guide*.

### **gwmonxx.dll files**

The `gwmonxx.dll` files contain all language-specific information for the WebAccess Agent. The last two characters `xx` are a language code.

### **gwsnmp.dll file**

The `gwsnmp.dll` file provides interaction with the Windows SNMP Service, so that the Monitor Agent can throw SNMP traps. See “[Configuring SNMP Trap Notification for Agent Problems](#)” in “[Monitor](#)” in the *GroupWise 7 Administration Guide*.

### **x\*10a.dll and gwxis10.dll files**

The `x*10a.dll` and `gwxis10.dll` programs provide XIS capability for the GroupWise agents, so that you can create XML documents to monitor and change the agents as needed.

### **gwmon.xml file**

The `gwmon.xml` file is a specialized agent configuration file for use in the XIS environment.

### **monwork directory**

The `monwork` directory is used for temporary files used in calculating system performance, as described in “[Measuring Agent Performance](#)” in “[Monitor](#)” in the *GroupWise 7 Administration Guide*.












## 8.5 Apache/Tomcat Installation

WebAccess, WebPublisher, and Monitor rely on the presence of a Web server in order to fulfil their functions. A number of Web servers are supported. See “[GroupWise System Requirements](#)” in “[Installing a Basic GroupWise System](#)” in the *GroupWise 7 Installation Guide*. In this section, the Apache Web server and the Tomcat Servlet Engine used to illustrate how GroupWise integrates with your Web server.

- [Section 8.5.1, “NetWare Installation Directory,” on page 143](#)
- [Section 8.5.2, “Linux Installation Directory,” on page 148](#)










### 8.5.1 NetWare Installation Directory

---

 sys:\apache2	Apache installation directory
 bin	Standard Apache directory
 cgi-bin	Standard Apache directory
 conf	Standard Apache directory
 httpd.conf	Main Apache configuration file
 GWApache2.conf	Specialized Apache configuration file for use with GroupWise
 error	Standard Apache directory
 htdocs	Apache document root directory
 index.html	Web server default Web page
 icons	Standard Apache directory
 logs	Standard Apache directory
 man	Standard Apache directory
 manual	Standard Apache directory
 modules	Standard Apache directory
































---

---

 sys:\tomcat\4	Tomcat installation directory
 bin	Standard Tomcat directory
 common	Standard Tomcat directory
 conf	Standard Tomcat directory
 examples	Standard Tomcat directory
 logs	Standard Tomcat directory
 server	Standard Tomcat directory
 shared	Standard Tomcat directory
 temp	Standard Tomcat directory

---


---

 webapps/ROOT	Standard Tomcat document root directory
 webapps/gw	GroupWise-specific document root directory
 index.html	GroupWise default Web services page
 com/novell	Directory for Novell product files
 collection	Directory for Novell class files and properties files
 GWMonitor	Directory for GroupWise Monitor files
 help	Subdirectory for Monitor Web console help files
 images	Subdirectory for Monitor Web console image files
 images	Directory for Novell product image files
 inso	Directory for Inso* viewer files for viewing attachments
 webaccess	Directory for GroupWise WebAccess files
 applets	Subdirectory for WebAccess client properties files
 help	Subdirectory for WebAccess client help files
 images	Subdirectory for WebAccess client image files
 webconsole	Subdirectory for WebAccess Application Web console help files
 webpublisher	Directory for GroupWise WebPublisher files
 help	Subdirectory for WebPublisher help files
 images	Subdirectory for WebPublisher image files
 WEB-INF	Web server information directory
 web.xml	Web server configuration file
 classes/com/novell	Directory for Novell product files
 collection	Directory for language-specific morphology files
 GWMonitor	Directory for GroupWise Monitor files
 providers	Subdirectory for service provider files
 templates	Subdirectory for template files
 webaccess	Directory for GroupWise WebAccess files
 providers	Subdirectory for service provider files
 templates	Subdirectory for template files
 webpublisher	Directory for GroupWise WebPublisher files
 providers	Subdirectory for service provider files
 templates	Subdirectory for template files


















---



---

 work	Standard Tomcat directory
--	---------------------------

---

 sys:\novell	Directory for Novell product configuration files
 gwmonitor  gwmonitor.cfg  logs	Subdirectory for GroupWise Monitor Monitor Application configuration file Directory for Monitor Application log files
 webaccess  webacc.cfg  commgr.cfg  spellchk.cfg  ldap.cfg  logs  temp  users	Subdirectory for WebAccess WebAccess Application configuration file Communications Manager configuration file Novell Speller Application configuration file LDAP service provider configuration file Directory for WebAccess Application log files Temporary working directory Directory for WebAccess users' session files
 webpublisher  webpub.cfg  commgr.cfg  default  logs	Subdirectory for WebAccess Application files WebPublisher Application configuration file Communications Manager configuration file Subdirectory for boilerplate configuration files Subdirectory for WebPublisher Application log files

---

### conf/httpd.conf file

The `httpd.conf` file is the main Apache configuration file. On NetWare, the GroupWise Installation program modifies it to include a reference to the `GWApache2.conf` file.

### conf/GWApache2.conf file

The `GWApache2.conf` file includes the `jkmount` command that enables Apache and Tomcat to communicate with each other.

### htdocs/index.html file

The `index.html` file in the `htdocs` directory is the default HTML file that displays in your Web browser when you go to the IP address or hostname of the server.

### webapps/gw/index.html file

The `index.html` file in the `gw` directory is the default HTML file for GroupWise Web services (WebAccess, WebPublisher, and Monitor) and displays when you go to the following URL:

`http://web_server_address/gw`

From this default page, specific GroupWise URLs can be easily accessed:

`http://web_server_address/gw/webacc`  
`http://web_server_address/gw/webpub`  
`http://web_server_address/gw/gwmonitor`

### **WEB-INF/web.xml file**

The `web.xml` file tells the Web server where the various GroupWise service providers and their configuration files are located. By default, they are located in subdirectories under `sys:\novell`.

### **GWMonitor/providers directory**

The `providers` directory holds the Java\* class and properties files for the Monitor provider. For more information, see “[Adding or Removing Service Providers](#)” in “[Monitor](#)” in the *GroupWise 7 Administration Guide*.

### **GWMonitor/templates directory**

The `templates` directory holds subdirectories for the various file formats used in various browser environments. For more information, see “[Modifying Monitor Application Template Settings](#)” in “[Monitor](#)” in the *GroupWise 7 Administration Guide*.

### **webaccess/providers directory**

The `providers` directory holds the Java class and properties files for the WebAccess providers. For more information, see “[Adding or Removing Service Providers](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

### **webaccess/templates directory**

The `templates` directory holds subdirectories for the various file formats used in various browser environments. For more information, see “[Modifying WebAccess Application Template Settings](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

### **webpublisher/providers directory**

The `providers` directory holds the Java class and properties files for the WebPublisher providers. For more information, see “[Adding or Removing Service Providers](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

### **webpublisher/templates directory**

The `templates` directory holds subdirectories for the various file formats used in various browser environments. For more information, see “[Modifying WebPublisher Application Template Settings](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

### **sys:\novell directory**

The `sys:\novell` directory holds subdirectories for each Novell product that uses application configuration files.

## **gwmonitor directory**

The `gwmonitor` directory is created when you install GroupWise Monitor.

### **gwmonitor.cfg file**

The `gwmonitor.cfg` file holds the same configuration information that is stored on the Monitor Application object (named GroupWiseMonitor) in eDirectory. For more information, see “[Configuring the Monitor Application](#)” in “[Monitor](#)” in the *GroupWise 7 Administration Guide*.

### **logs directory**

The `logs` subdirectory holds Monitor Application log files. For more information, see “[Modifying Monitor Application Log Settings](#)” in “[Monitor](#)” in the *GroupWise 7 Administration Guide*.

## **webaccess directory**

The `webaccess` directory holds files used by the WebAccess Application.

### **webacc.cfg file**

The `webacc.cfg` file holds the same configuration information that is stored on the WebAccess Application object (named GroupWiseWebAccess) in eDirectory. For more information, see “[Configuring the WebAccess Application](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

### **commgr.cfg file**

The `commgr.cfg` file holds the same configuration information that is stored on the GroupWise Provider object (named GroupWiseProvider) in eDirectory, including the IP address, port number, number of threads, and encryption key for the WebAccess Agent. This information enables the WebAccess Application to communicate with the WebAccess Agent. For more information, see “[Configuring the GroupWise Service Provider](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

A copy of the `commgr.cfg` file is automatically maintained in the WebAccess Agent queue directory (`domain\wpgate\webac70a`).

### **spellchk.cfg file**

The `spellchk.cfg` file holds the same configuration information that is stored on the Novell Speller Application object (named NovellSpeller) in eDirectory. For more information, see “[Configuring the Novell Speller Application](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

### **ldap.cfg file**

The `ldap.cfg` file holds the same configuration information that is stored on the LDAP Provider object (named LDAPProvider) in eDirectory. For more information, see “[Configuring the LDAP Service Provider](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

## logs directory

The `logs` subdirectory holds WebAccess Application log files. For more information, see “[Controlling WebAccess Application Logging](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

## users directory

The `users` subdirectory holds session files for WebAccess users. If WebAccess times out after a period of user inactivity, the user’s session information is saved. When the user logs back in, the session information is retrieved so that the user can continue working without loss of data. Also, users’ message text is saved during each session, so that if the WebAccess Application is restarted or goes down, users do not lose the message text they were composing at the time.

## webpublisher directory

The `webpublisher` directory holds files used by the WebPublisher Application.

## webpub.cfg

The `webpub.cfg` file holds the same configuration information that is stored on the WebPublisher Application object (named `GroupWiseWebPublisher`) in eDirectory. For more information, see “[Configuring the WebPublisher Application](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

## commgr.cfg file

The `commgr.cfg` file holds the same configuration information that is stored on the GroupWise Provider object (named `GroupWiseProvider`) in eDirectory, including the IP address, port number, number of threads, and encryption key for the WebAccess Agent. This information enables the WebAccess Application to communicate with the WebAccess Agent. For more information, see “[Configuring the GroupWise Service Provider](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

A copy of the `commgr.cfg` file is automatically maintained in the WebAccess Agent queue directory (`domain\wpgate\webac70a`).

## default directory



The `default` directory holds boilerplate versions of the `webpub.cfg` and `commgr.cfg` files.

## logs directory

The `logs` subdirectory holds WebAccess Application log files. For more information, see “[Controlling WebAccess Application Logging](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.





## 8.5.2 Linux Installation Directory

---








 <code>/opt/novell/httpd</code>	Novell Apache installation directory
 <code>modules</code>	Standard Apache directory

---












---

 /etc/opt/novell/httpd	Novell Apache configuration directory
 conf.d	Standard Apache directory
 gconf.d	Standard Apache directory
 sslconf.d	Standard Apache directory

---


























 /etc/opt/novell/tomcat4	Novell Tomcat configuration directory
 catalina.properties	Standard Tomcat file
 jk2.properties	Standard Tomcat file
 server.xml	Standard Tomcat file
 tomcat-users.xml	Standard Tomcat file
 tomcat4.conf	Standard Tomcat file
 web.xml	Web server configuration file
 init.d	Standard Tomcat directory
 logrotate.d	Standard Tomcat directory

---

 /var/opt/novell	Novell subdirectory under /var
 gw	Apache document root directory for WebAccess and WebPublisher
 index.html	Web server default Web page
 com/novell	Directory for Novell product files
 collexion	Directory for Novell class files and properties files
 images	Directory for Novell product image files
 inso	Directory for Inso viewer files for viewing attachments
 webaccess	Directory for GroupWise WebAccess files
 applets	Subdirectory for WebAccess client properties files
 help	Subdirectory for WebAccess client help files
 images	Subdirectory for WebAccess client image files
 webconsole	Subdirectory for WebAccess Application Web console help files
 webpublisher	Directory for GroupWise WebPublisher files
 help	Subdirectory for WebPublisher help files
 images	Subdirectory for WebPublisher image files

---

---

 WEB-INF	Web server information directory
 web.xml	Web server configuration file
 classes/com/novell	Web server configuration file
 collexion	Directory for language-specific morphology files
 webaccess	Directory for GroupWise WebAccess files
 providers	Subdirectory for service provider files
 templates	Subdirectory for template files
 webpublisher	Directory for GroupWise WebPublisher files
 providers	Subdirectory for service provider files
 templates	Subdirectory for template files
 gwmon	Apache document root directory for Monitor
 index.html	Web server default page
 com/novell	Directory for Novell product files
 gwmonitor	Directory for GroupWise WebPublisher files
 help	Subdirectory for WebPublisher help files
 images	Subdirectory for WebPublisher image files
 WEB-INF	Web server information directory
 web.xml	Web server configuration file
 gwmonitor	Directory for GroupWise Monitor files
 providers	Subdirectory for service provider files
 templates	Subdirectory for template files
 httpd	Standard Apache directory
 log	Standard Apache directory
 novlwww	Home directory for the novlwww user created at installation
 run	Standard Apache directory

---

---

tomcat4	Standard Tomcat directory
bin	Standard Tomcat directory
common	Standard Tomcat directory
conf	--> /etc/opt/novell/tomcat4
logs	Standard Tomcat directory
server	Standard Tomcat directory
shared	Standard Tomcat directory
temp	Standard Tomcat directory
webapps	Standard Tomcat directory
admin.xml	Standard Tomcat file
manager.xml	Standard Tomcat file
examples	Standard Tomcat directory
gw	--> /var/opt/novell/gw
gwmon	--> /var/opt/novell/gwmon
tomcat-docs	Standard Tomcat directory
webdav	Standard Tomcat directory

---

### gw/index.html file

The `index.html` file in the `gw` directory is the default HTML file for GroupWise Web services (WebAccess and WebPublisher) and displays when you go to the following URL:

`http://web_server_address/gw`

From this default page, specific GroupWise URLs can be easily accessed:

`http://web_server_address/gw/webacc`

`http://web_server_address/gw/webpub`

### gw/WEB-INF/web.xml file

The `web.xml` file in the `gw/WEB-INF` directory tells the Web server where the various WebAccess service providers and their configuration files are located. By default, they are located in `/opt/novell/groupwise/webaccess`.

### webaccess/providers directory

The `providers` directory holds the Java class and properties files for the WebAccess providers. For more information, see “[Adding or Removing Service Providers](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

### webaccess/templates directory

The `templates` directory holds subdirectories for the various file formats used in various browser environments. For more information, see “[Modifying WebAccess Application Template Settings](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

### webpublisher/providers directory

The `providers` directory holds the Java class and properties files for the WebPublisher providers. For more information, see “[Adding or Removing Service Providers](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

### webpublisher/templates directory

The `templates` directory holds subdirectories for the various file formats used in various browser environments. For more information, see “[Modifying WebPublisher Application Template Settings](#)” in “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

### gwmon/index.html file

The `index.html` file in the `gwmon` directory is the default HTML file for the GroupWise Monitor Web service and displays when you go to the following URL:

`http://web_server_address/gwmon`

From this default page, the GroupWise Monitor login page can be easily accessed:

`http://web_server_address/gwmon/gwmonitor`

### gwmon/WEB-INF/web.xml file

The `web.xml` file in the `gwmon/WEB-INF` directory tells the Web server where the Monitor service provider and its configuration file are located. By default, they are located in `/opt/novell/groupwise/gwmonitor`.

### gwmonitor/providers directory

The `providers` directory holds the Java class and properties files for the Monitor provider. For more information, see “[Adding or Removing Service Providers](#)” in “[Monitor](#)” in the *GroupWise 7 Administration Guide*.

### gwmonitor/templates directory

The `templates` directory holds subdirectories for the various file formats used in various browser environments. For more information, see “[Modifying Monitor Application Template Settings](#)” in “[Monitor](#)” in the *GroupWise 7 Administration Guide*.




















# Software Distribution Directory

- Section 9.1, “NetWare/Windows Software Distribution Directory,” on page 153
- Section 9.2, “Linux Software Distribution Directory,” on page 160

## 9.1 NetWare/Windows Software Distribution Directory

---

 <code>software_distribution_directory</code>	Master copy of GroupWise® software
 <code>agents</code>	GroupWise agent software
 <code>install.exe</code>	GroupWise Agent Installation program
 <code>nlm</code>	NetWare® agent software
 <code>nt</code>	Windows agent software
 <code>startups</code>	Agent startup files
 <code>snmp</code>	GroupWise MIB files
 <code>help</code>	Agent Web console help files
 <code>domain</code>	Domain data dictionary files
 <code>wpdomain.dc</code>	Data dictionary for GroupWise 4.x domain databases
 <code>gwdom.dc</code>	Data dictionary for GroupWise 7, 6.x, and 5.x domain databases
 <code>wphost.dc</code>	Data dictionary for GroupWise 4.x post office databases
 <code>gwpo.dc</code>	Data dictionary for GroupWise 7, 6.x, and 5.x post office databases
 <code>po</code>	Post office data dictionary files
 <code>ngwguard.dc</code>	Data dictionary for message store databases
 <code>wphost.dc</code>	Data dictionary for GroupWise 4.x post office databases
 <code>gwpo.dc</code>	Data dictionary for GroupWise 7, 6.x, and 5.x post office databases

---

---

client	GroupWise client software
win32	GroupWise client for Windows
setup.exe	GroupWise client installation program
setup.cfg	Configuration file for the AutoUpdate feature
addons	GroupWise client addon programs
gwmailto	Program to make GroupWise your browser e-mail program
gwtip	Program to display tips each time GroupWise starts
pdaconnect	Program to synchronize your PDA with GroupWise
gwcheck	GroupWise Check utility
ofviews	GroupWise client view files
ppforms	GroupWise client day planner forms
admin	GroupWise administrator software
cladmin	GroupWise snap-ins to ConsoleOne®
monitor	GroupWise Monitor software
utility	GroupWise administrative utilities
gwcheck	GroupWise Check utility
gwcsrgen	GroupWise Generate CSR utility
setupip	GroupWise TCP/IP Setup utility
internet	Internet connectivity software
gwia	GroupWise Internet Agent software
webaccess	GroupWise WebAccess software
license	GroupWise Software License Agreement in multiple languages
common	Java files used by GroupWise programs
docs	GroupWise <i>Installation Guide</i>

---

### 9.1.1 \grpwise\software directory

The GroupWise software distribution directory resides initially on the GroupWise distribution CD. GroupWise Administration is installed directly from the CD. In addition, during installation, you create a software distribution directory on your network from which you subsequently install the GroupWise agents and GroupWise client software.

The default software distribution directory is `\grpwise\software`.

### 9.1.2 agents directory

The `agents` subdirectory contains all files associated with GroupWise agents:

- Post Office Agent (POA)
- Message Transfer Agent (MTA)
- GroupWise Target Service Agent (GWTSA)

### **install.exe file**

The `install.exe` file in the `agent` subdirectory is the installation program you run to install the GroupWise agents on the servers where you will run the POA and/or MTA. For instructions, see “[Installing and Starting the POA](#)” in “[Post Office Agent](#)” and “[Installing and Starting the MTA](#)” in “[Message Transfer Agent](#)” in the *GroupWise 7 Administration Guide*.

### **nlm directory**

The `nlm` subdirectory in the `agent` subdirectory contains the GroupWise agent NLM™ files installed on NetWare servers. See “[NetWare Installation Directory](#)” on page 107.

### **nt directory**

The `nt` subdirectory contains the GroupWise agent files installed on Windows servers. See “[Windows Installation Directory](#)” on page 116.

### **startups directory**

The `startups` subdirectory contains the default startup files for the GroupWise agents. During installation, a customized startup file is created for each agent that includes the location of the domain or post office serviced by that agent. The customized startup files are named after the domain or post office for which they are created. See “[NetWare Installation Directory](#)” on page 107 or “[Windows Installation Directory](#)” on page 116.

### **snmp directory**

The `snmp` subdirectory contains GroupWise MIB files. For more information, see “[Using an SNMP Management Console](#)” in “[Post Office Agent](#)” and “[Message Transfer Agent](#)” in the *GroupWise 7 Administration Guide*.

### **help directory**

The `help` directory holds the help files that you can view from the agent Web consoles. See “[Using the POA Web Console](#)” in “[Post Office Agent](#)” and “[Using the MTA Web Console](#)” in “[Message Transfer Agent](#)” in the *GroupWise 7 Administration Guide*.

## **9.1.3 domain directory**

The `domain` subdirectory contains the files from which domains are created.

### **wpdomain.dc file**

The `wpdomain.dc` file is the distribution copy of the data dictionary for rebuilding GroupWise 4.x domain databases (`wpdomain.db` files) in secondary domains.

If the `wpdomain.dc` file is missing from the primary domain, you cannot rebuild GroupWise 4.x secondary domains. The original `wpdomain.dc` file is located in the `domain` directory of the GroupWise distribution media.

Historical Note: WordPerfect Office (WP Office), the predecessor of GroupWise, was originally designed by WordPerfect Corporation (WPCorp). Hence, the `wp` in `wpdomain.dc`. Some naming conventions were originally preserved for backward compatibility.

### **gwdom.dc file**

The `gwdom.dc` file is the distribution copy of the data dictionary for creating and rebuilding GroupWise 7, 6.x, and GroupWise 5.x domain databases (`wpdomain.db` files) in secondary domains.

If the `gwdom.dc` file is missing from the primary domain, you cannot create or rebuild GroupWise 7/6.x/5.x secondary domains. The original `gwdom.dc` file is located in the `domain` subdirectory of the GroupWise distribution media.

Historical Note: WP Office, the predecessor of GroupWise, was originally designed by WordPerfect Corporation (WPCorp). Hence, the `wp` in `wpdomain.db`. Some naming conventions were originally preserved for backward compatibility.

### **wphost.dc file**

The `wphost.dc` file is the distribution copy of the data dictionary for rebuilding GroupWise 4.x post office databases (`wphost.db` files).

If the `wphost.dc` file is missing from a domain, you cannot rebuild GroupWise 4.x post offices in that domain. The original `wphost.dc` file is located in the `domain` subdirectory of the GroupWise distribution media. There is also a copy in the `po` subdirectory.

Historical Note: WP Office, the predecessor of GroupWise, was originally designed by WordPerfect Corporation (WPCorp). Post offices were originally called hosts. Hence, the name `wphost.dc`. Some naming conventions were originally preserved for backward compatibility.

### **gwpo.dc file**

The `gwpo.dc` file is the distribution copy of the data dictionary for creating and rebuilding GroupWise 7, 6.x, and GroupWise 5.x post office databases (`wphost.db` files).

If the `gwpo.dc` file is missing from a domain, you cannot create or rebuild GroupWise 7/6.x/5.x post offices in that domain. The original `gwpo.dc` file is located in the `domain` directory of the GroupWise CD. There is also a copy in the `po` directory.

Historical Note: WP Office, the predecessor of GroupWise, was originally designed by WordPerfect Corporation (WPCorp). Post offices were originally called hosts. Hence, the name `wphost.db`. Some naming conventions were originally preserved for backward compatibility.

## **9.1.4 po directory**

The `po` subdirectory contains the files from which post offices are created.

## ngwguard.dc file

The `ngwguard.dc` file is the distribution copy of the data dictionary for building the following databases in the post office:

- `ngwguard.db` (guardian database)
- `dmxxxxn01-FF` (document management databases)
- `msgnnn.db` (message databases)
- `userxxx.db` (user databases)
- `puxxxxxx.db` (databases for replicated items like shared folders)

If the `ngwguard.dc` file is missing from a post office, new databases cannot be created in the post office, so the post office cannot grow. The original `ngwguard.dc` file is located in the `po` directory of the GroupWise CD.

In Remote mode, the GroupWise client also uses the `ngwguard.dc` file as the data dictionary for its local databases.

## 9.1.5 client directory

The `client` subdirectory contains all files associated with GroupWise Windows client. See “[Client](#)” in the *GroupWise 7 Administration Guide*.

### win32 directory

The `win32` subdirectory contains all GroupWise client files installed for use with Windows. See [Section 10.1, “Windows Client,” on page 171](#).

### setup.exe file

The `setup.exe` file is the program GroupWise client users run to install and set up the GroupWise client on their Windows workstations. See “[Client](#)” in the *GroupWise 7 Administration Guide*.

### setup.cfg file

The `setup.cfg` file enables you to automate installation of the GroupWise Windows client so that your users do not need to respond to the Setup program’s prompts. For more information, see “[Installing with the Configuration File \(setup.cfg\)](#)” in “[Client](#)” in the *GroupWise 7 Administration Guide*.

### addons directory

The `addons` directory contains subdirectories for programs that can be used along with the GroupWise client to enhance aspects of its functionality.

### gwmalto directory

The `gwmalto` directory contains a program that makes the GroupWise Windows client the default e-mail application in your Web browser. For more information, see “[\[GWMALTO\]](#)” in “[Modifying the Configuration File](#)” in “[Client](#)” in the *GroupWise 7 Administration Guide*.

## gwtip directory

The `gwtip` directory contains a program that displays a helpful tip about GroupWise each time the client starts. For more information, see “[GWTIP]” in “[Modifying the Configuration File](#)” in “[Client](#)” in the *GroupWise 7 Administration Guide*.

## pdaconnect directory

The `pdaconnect` directory contains a program to synchronize data between GroupWise and a PDA device. For more information, see the [PDA Connect Readme \(http://www.novell.com/documentation/gw7/readmeen\\_pda\\_connect/readmeen\\_pda\\_connect.html\)](http://www.novell.com/documentation/gw7/readmeen_pda_connect/readmeen_pda_connect.html).

## 9.1.6 gwcheck directory

The `gwcheck` subdirectory contains the GroupWise Check utility that can be made available in the GroupWise client by clicking *Tools > Repair Mailbox*. For more information, see “[Repairing Your Mailbox](#)” in “[Managing Your Mailbox](#)” in the *GroupWise 7 Windows Client User Guide*.

## 9.1.7 ofviews directory

The `ofviews` subdirectory contains platform-specific subdirectories of view files for use by the GroupWise client. In addition, the `gwviewxx.ini` and `ofviewxx.ini` files configure custom views on the menus where users select views. The `gwviewxx.ini` file configures GroupWise 7, 6.x, and GroupWise 5.5 views. The `ofviewxx.ini` file configures views from earlier versions of GroupWise.

## 9.1.8 ppforms directory

The `ppforms` subdirectory contains day planner forms for printing GroupWise calendars and tasks.

## 9.1.9 admin directory

The `admin` subdirectory contains subdirectories for administrative tools that can be used with GroupWise.

### c1admin directory

The `admin\c1admin` subdirectory contains the GroupWise snap-ins to ConsoleOne.

### monitor directory

The `admin\monitor` subdirectory contains the GroupWise 7/6.x Monitor program, an SNMP monitoring program for use with the GroupWise agents. See “[Monitor](#)” in the *GroupWise 7 Administration Guide*.

### utility directory

The `admin\utility` subdirectory contains helpful GroupWise utilities.

## gwcheck directory

The `admin\utility\gwcheck` subdirectory contains the GroupWise Check utility. See “[GroupWise Check](#)” in “[Standalone Database Maintenance Programs](#)” in the *GroupWise 7 Administration Guide*.

## gwcsrgen directory

The `admin\utility\gwcsrgen` subdirectory contains the GroupWise Generate CSR utility. See “[Server Certificates and SSL Encryption](#)” in “[Security](#)” in the *GroupWise 7 Administration Guide*.

## setupip directory

The `admin\utility\setupip` subdirectory contains supporting programs for the client AutoUpdate feature. See “[Enabling AutoUpdate](#)” in “[Client](#)” in the *GroupWise 7 Administration Guide*.

## 9.1.10 internet directory

The `internet` subdirectory contains subdirectories for GroupWise components that provide Internet connectivity.

### gwia directory

The `internet\gwia` subdirectory contains the GroupWise Internet Agent software, used to connect GroupWise systems across the Internet and to allow GroupWise users to exchange e-mail with users of various Internet e-mail programs. For information about Internet Agent files and directories, see [Section 7.4, “Internet Agent Queue Directory,” on page 87](#) and [Section 8.2, “Internet Agent Installation,” on page 119](#).

For information about the Internet Agent, see “[Internet Agent](#)” in the *GroupWise 7 Administration Guide*.

### webaccess directory

The `internet\webaccess` subdirectory contains the GroupWise WebAccess software, which allows users to access their GroupWise mailboxes from a Web browser. For information about WebAccess files and directories, see [Section 7.5, “WebAccess Agent Queue Directory,” on page 93](#), [Section 8.3, “WebAccess Agent Installation,” on page 126](#), and [Section 8.5, “Apache/Tomcat Installation,” on page 143](#)

For information about WebAccess, see “[WebAccess](#)” in the *GroupWise 7 Administration Guide*.

## 9.1.11 license directory

The `license` subdirectory contains the GroupWise Software License Agreement in multiple languages. Run `license.exe`, then select a language.

## 9.1.12 common directory






















The `common` subdirectory contains Java files used by various components of GroupWise.

## 9.1.13 docs directory

The docs subdirectory contains language-specific subdirectories for the *Installation Guide* in PDF format. You can find the most up-to-date version of the *GroupWise 7 Installation Guide* on the [GroupWise 7 Documentation Web site \(http://www.novell.com/documentation/gw7\)](http://www.novell.com/documentation/gw7).

## 9.2 Linux Software Distribution Directory












---

 /opt/novell/groupwise/software	Master copy of GroupWise software
 install	GroupWise Installation script
 agents	GroupWise agent software
 linux	Subdirectory for Linux software
 novell-groupwise-agents- ver.date.i386.rpm	GroupWise agent package
 novell-groupwise-gwha- ver.date.i386.rpm	GroupWise High Availability service package
 novell-sms-ver.i586.rpm	Novell® Storage Management Services™ package
 startups	Subdirectory for startup files
 language	Language-specific files
 strtupxx.poa	POA startup file
 strtupxx.mta	MTA startup file
 grpwise	GroupWise agent startup script (POA and MTA)
 domain	Domain data dictionary files
 wpdomain.dc	Data dictionary for GW 4.x domain databases
 gwdom.dc	Data dictionary for GW 7, 6.x, and 5.x domain databases
 wphost.dc	Data dictionary for GW 4.x post office databases
 gwpo.dc	Data dictionary for GW 7, 6.x, and 5.x post office databases
 po	Post office data dictionary files
 ngwguard.dc	Data dictionary for message store databases
 wphost.dc	Data dictionary for GW 4.x post office databases
 gwpo.dc	Data dictionary for GW 7, 6.x, and 5.x post office databases

---



---

 <code>client</code>	GroupWise client software
 <code>linux</code>	Subdirectory for Linux software
 <code>install</code>	Cross-Platform client installation script
 <code>novell-groupwise-gwclient- ver.date.i386.rpm</code>	Cross-Platform client package
 <code>novell-groupwise-gwcheck- ver.date.i386.rpm</code>	GroupWise Check Utility package
 <code>ofviews</code>	GroupWise client view files
 <code>admin</code>	GroupWise administrator software
 <code>novell-groupwise-admin- ver.date.i386.rpm</code>	GroupWise snap-ins to ConsoleOne package
 <code>novell-groupwise-dbcopy- ver.date.i386.rpm</code>	GroupWise Database Copy Utility package
 <code>novell-groupwise-gwcheck- ver.date.i386.rpm</code>	GroupWise Check Utility package
 <code>NOVLc1Linuxjre-ver.i386.rpm</code>	ConsoleOne JRE update package
 <code>monitor</code>	GroupWise Monitor software
 <code>linux</code>	Subdirectory for Linux software
 <code>novell-groupwise-gwmon- ver.date.i386.rpm</code>	Monitor Agent package
 <code>novell-groupwise-monitor- ver.date.i386.rpm</code>	Monitor Application package
 <code>startup</code>	Subdirectory for startup files
 <code>grpwise-ma</code>	Monitor startup script
 <code>S99grpwise-ma</code>	Monitor startup script for automatic start on reboot
 <code>internet</code>	Internet connectivity software

---



## 9.2.1 /opt/novell/groupwise/software directory

The GroupWise software distribution directory resides initially on the GroupWise distribution CD. GroupWise Administration is installed directly from the CD. In addition, during installation, you can create a software distribution directory on your network from which you subsequently install the GroupWise agents and GroupWise client software.

The default software distribution directory is `/opt/novell/groupwise/software`.

### install file

The `install` file is the script you use to install all components of GroupWise on Linux. See “[Linux: Setting Up a Basic GroupWise System](#)” in the *GroupWise 7 Installation Guide*.

## 9.2.2 agents directory

The `agents` subdirectory contains all files associated with GroupWise agents:

- Post Office Agent (POA)
- Message Transfer Agent (MTA)

### **novell-groupwise-agents.version.date.i386.rpm**

The `novell-groupwise-agents.version.date.i386.rpm` file is the GroupWise agent package that is installed by the Installation script. It installs the POA and the MTA. You can install the agent package manually if necessary. To see what files are installed by the package, see [Section 8.1.2, “Linux Installation Directory,” on page 110](#).

### **novell-groupwise-gwha.version.date.i386.rpm**

The `novell-groupwise-gwha.version.date.i386.rpm` file is the GroupWise High Availability service package that is installed by the Installation script. It is automatically installed along with the POA and the MTA. You can install the High Availability package manually if necessary. To see what files are installed by the package, see [Section 8.1.2, “Linux Installation Directory,” on page 110](#).

### **novell-sms-version.i586.rpm**

The `novell-sms-version.i586.rpm` file is the Novell Storage Management Services package that is used in conjunction with the Service Agent for File Systems (TSAFS) and TSAFS for GroupWise (TSAFSGW) for the purpose of backing up GroupWise databases in a live GroupWise system. It is not installed by the Installation script but must be installed manually, as described in “[Linux: Running TSAFS and TSAFSGW](#)” in “[Databases](#)” in the *GroupWise 7 Administration Guide*.

### startups directory

The `startups` subdirectory contains the default startup files for the GroupWise agents. During installation, a customized startup file is created for each agent that includes the location of the domain or post office serviced by that agent. The customized startup files are named after the domain or post office for which they are created. See [Section 8.1.2, “Linux Installation Directory,” on page 110](#).

## grpwise file

The `grpwise` file is the GroupWise agent startup script. It is installed in `/etc/init.d`. If you choose to have the agents start automatically when the server reboots, the Installation script places symbolic links to it named `S99grpwise` in the `rc3.d` and `rc5.d` subdirectories of `/etc/init.d`. For more information, see “[Linux: Installing and Starting the GroupWise Agents](#)” in “[Installing a Basic GroupWise System](#)” in the *GroupWise 7 Installation Guide*.

## 9.2.3 domain directory

The `domain` subdirectory contains the files from which domains are created.

### wpdomain.dc file

The `wpdomain.dc` file is the distribution copy of the data dictionary for rebuilding GroupWise 4.x domain databases (`wpdomain.db` files) in secondary domains.

If the `wpdomain.dc` file is missing from the primary domain, you cannot rebuild GroupWise 4.x secondary domains. The original `wpdomain.dc` file is located in the `domain` directory of the GroupWise distribution media.

Historical Note: WordPerfect Office (WP Office), the predecessor of GroupWise, was originally designed by WordPerfect Corporation (WPCorp). Hence, the `wp` in `wpdomain.dc`. Some naming conventions were originally preserved for backward compatibility.

### gwdom.dc file

The `gwdom.dc` file is the distribution copy of the data dictionary for creating and rebuilding GroupWise 7, 6.x, and 5.x domain databases (`wpdomain.db` files) in secondary domains.

If the `gwdom.dc` file is missing from the primary domain, you cannot create or rebuild GroupWise 7/6.x/5.x secondary domains. The original `gwdom.dc` file is located in the `domain` subdirectory of the GroupWise distribution media.

Historical Note: WP Office, the predecessor of GroupWise, was originally designed by WordPerfect Corporation (WPCorp). Hence, the `wp` in `wpdomain.db`. Some naming conventions were originally preserved for backward compatibility.

### wphost.dc file

The `wphost.dc` file is the distribution copy of the data dictionary for rebuilding GroupWise 4.x post office databases (`wphost.db` files).

If the `wphost.dc` file is missing from a domain, you cannot rebuild GroupWise 4.x post offices in that domain. The original `wphost.dc` file is located in the `domain` subdirectory of the GroupWise distribution media. There is also a copy in the `po` subdirectory.

Historical Note: WP Office, the predecessor of GroupWise, was originally designed by WordPerfect Corporation (WPCorp). Post offices were originally called hosts. Hence, the name `wphost.dc`. Some naming conventions were originally preserved for backward compatibility.

## gwpo.dc file

The `gwpo.dc` file is the distribution copy of the data dictionary for creating and rebuilding GroupWise 7, 6.x, and 5.x post office databases (`wphost.db` files).

If the `gwpo.dc` file is missing from a domain, you cannot create or rebuild GroupWise 7/6.x/5.x post offices in that domain. The original `gwpo.dc` file is located in the `domain` directory of the GroupWise CD. There is also a copy in the `po` directory.

Historical Note: WP Office, the predecessor of GroupWise, was originally designed by WordPerfect Corporation (WPCorp). Post offices were originally called hosts. Hence, the name `wphost.db`. Some naming conventions were originally preserved for backward compatibility.

## 9.2.4 po directory

The `po` subdirectory contains the files from which post offices are created.

### ngwguard.dc file

The `ngwguard.dc` file is the distribution copy of the data dictionary for building the following databases in the post office:

- `ngwguard.db` (guardian database)
- `dmxxxnn01-FF` (document management databases)
- `msgnnn.db` (message databases)
- `userxxx.db` (user databases)
- `puxxxxx.db` (databases for replicated items like shared folders)

If the `ngwguard.dc` file is missing from a post office, new databases cannot be created in the post office, so the post office cannot grow. The original `ngwguard.dc` file is located in the `po` directory of the GroupWise CD.

In Remote mode, the GroupWise client also uses the `ngwguard.dc` file as the data dictionary for its local databases.

## 9.2.5 client directory

The `client` subdirectory contains all files associated with GroupWise Windows client. See “[Client](#)” in the *GroupWise 7 Administration Guide*.

### install file

The `install` file is the script that GroupWise Cross-Platform client users run to install and set up the GroupWise client on their Linux or Macintosh\* workstations. See “[Setting Up the GroupWise Cross-Platform Client on Linux](#)” in the *GroupWise 7 Installation Guide*.

### novell-groupwise-gwclient-version.date.i386.rpm

The `novell-groupwise-client.version.date.i386.rpm` file is the GroupWise client package that is installed by the Installation script. You can install the client package manually if necessary. To see what files are installed by the package, see [Section 10.2, “Cross-Platform Client on Linux,” on page 175](#).

### **novell-groupwise-gwcheck-version.date.i386.rpm file**

The `novell-groupwise-gwcheck.version.date.i386.rpm` file is the GroupWise Check utility package. It is not installed by the Installation script but must be installed manually, as described in “Starting GWCheck on a Linux Workstation” in “Databases” in the *GroupWise 7 Administration Guide*.

## **9.2.6 ofviews directory**

The `client\ofviews` subdirectory contains platform-specific subdirectories of view files for use by the GroupWise client. On Linux, the `win` subdirectory contains the view files for the Windows client, so that users on a Linux post office can use the Windows client if desired. The Cross-Platform client does not use view files like the Windows client does.

In addition, the `gwviewxx.ini` and `ofviewxx.ini` files configure custom views on the menus where users select views in the Windows client. The `gwviewxx.ini` file configures GroupWise 7, 6.x, and 5.5 views. The `ofviewxx.ini` file configures views from earlier versions of GroupWise.

## **9.2.7 admin directory**

The `admin` subdirectory contains subdirectories for administrative tools that can be used with GroupWise.

### **novell-groupwise-admin-version.date.i386.rpm file**

The `novell-groupwise-admin.version.date.i386.rpm` file is the GroupWise administrator package that is installed by the Installation script. It contains the GroupWise Administrator snap-ins to ConsoleOne. You can install the admin package manually if necessary.

### **novell-groupwise-dbcopy-version.date.i386.rpm file**

The `novell-groupwise-dbcopy.version.date.i386.rpm` file is the GroupWise Database Copy utility package. It is not installed by the Installation script but must be installed manually, as described in “Using DBCopy on Linux Servers” in “Databases” in the *GroupWise 7 Administration Guide*.

### **novell-groupwise-gwcheck-version.date.i386.rpm file**

The `novell-groupwise-gwcheck.version.date.i386.rpm` file is the GroupWise Check utility package. It is not installed by the Installation script but must be installed manually, as described in “Starting GWCheck on a Linux Workstation” in “Databases” in the *GroupWise 7 Administration Guide*.

### **NOVLc1Linuxjre-version.i386.rpm file**

The `NOVLc1Linuxjre-version.i386.rpm` file is the package that updates ConsoleOne so that it is compatible with the GroupWise Administrator snap-ins. It is installed for you automatically when you install GroupWise administration.

## monitor directory

The `monitor` subdirectory contains the GroupWise Monitor software. See “[Monitor](#)” in the *GroupWise 7 Administration Guide*.

### novell-groupwise-gwmon-version.date.i386.rpm file

The `novell-groupwise-gwmon.version.date.i386.rpm` file is the GroupWise Monitor Agent package that is installed by the Installation script. You can install the package manually if necessary. To see what files are installed by the package, see [Section 8.4, “Monitor Agent Installation,”](#) on page 138 and [Section 8.5, “Apache/Tomcat Installation,”](#) on page 143.

### novell-groupwise-monitor-version.date.i386.rpm file

The `novell-groupwise-monitor.version.date.i386.rpm` file is the GroupWise Monitor Application package that is installed by the Installation script. You can install the package manually if necessary. To see what files are installed by the package, see [Section 8.4, “Monitor Agent Installation,”](#) on page 138 and [Section 8.5, “Apache/Tomcat Installation,”](#) on page 143.

### grpwise-ma file

The `grpwise-ma` file is the Monitor Agent startup script. During installation, it is placed in `/etc/init.d`. For more information, see “[Starting the Linux Monitor Agent for the First Time](#)” in “[Installing GroupWise Monitor](#)” in the *GroupWise 7 Installation Guide*.

### S99grpwise-ma file

The `S99grpwise-ma` file is the Monitor Agent startup script that is placed in the `rc3.d` and `rc5.d` subdirectories of `/etc/init.d` if you choose to have the Monitor Agent start automatically when the server reboots. For more information, see “[Starting the Linux Monitor Agent on System Startup](#)” in “[Installing GroupWise Monitor](#)” in the *GroupWise 7 Installation Guide*.

## 9.2.8 internet directory

The `internet` subdirectory contains subdirectories for GroupWise components that provide and support Internet connectivity.

### gwia directory

The `gwia` subdirectory contains the Internet Agent software, used to connect GroupWise systems across the Internet and to allow GroupWise users to exchange e-mail with users of various Internet e-mail programs. See “[Internet Agent](#)” in the *GroupWise 7 Administration Guide*.

### novell-groupwise-gwia-version.date.i386.rpm file

The `novell-groupwise-gwia.version.date.i386.rpm` file is the Internet Agent package that is installed by the Installation script. You can install the package manually if necessary. To see what files are installed by the package, see [Section 8.2, “Internet Agent Installation,”](#) on page 119.

## novell-groupwise-gwha.version.date.i386.rpm

The `novell-groupwise-gwha.version.date.i386.rpm` file is the GroupWise High Availability service package that is installed by the Installation script. It is automatically installed along with the Internet Agent. You can install the High Availability package manually if necessary. To see what files are installed by the package, see [Section 8.2.2, “Linux Installation Directory,” on page 120](#).

## root directory

The `root` directory contains boilerplate versions of the configuration files that are installed to the Internet Agent root directory under the `domain` directory. For more information, see [Section 7.4, “Internet Agent Queue Directory,” on page 87](#).

## grpwise file

The `grpwise` file is the Internet Agent startup script. During installation, it is placed in `/etc/init.d`. If you choose to have the Internet Agent start automatically when the server reboots, the Installation script places symbolic links to it named `S99grpwise-ia` in the `rc3.d` and `rc5.d` subdirectories of `/etc/init.d`. For more information, see [“Linux: Starting the Internet Agent” in “Installing the GroupWise Internet Agent” in the \*GroupWise 7 Installation Guide\*](#).

## webaccess directory

The `internet\webaccess` subdirectory contains the GroupWise WebAccess software, which allows users to access their GroupWise mailboxes from a Web browser. See [“WebAccess” in the \*GroupWise 7 Administration Guide\*](#).

## novell-groupwise-gwinter.version.date.i386.rpm file

The `novell-groupwise-gwinter.version.date.i386.rpm` file is the WebAccess Agent package that is installed by the Installation script. You can install the package manually if necessary. To see what files are installed by the package, see [Section 8.3, “WebAccess Agent Installation,” on page 126](#).

## novell-groupwise-webaccess.version.date.i386.rpm file

The `novell-groupwise-webaccess.version.date.i386.rpm` file is the WebAccess Application package that is installed by the Installation script. You can install the package manually if necessary. To see what files are installed by the package, see [Section 8.3, “WebAccess Agent Installation,” on page 126](#) and [Section 8.5, “Apache/Tomcat Installation,” on page 143](#).

## root directory

The `root` directory contains boilerplate versions of the configuration files that are installed to the WebAccess Agent root directory under the `domain` directory. For more information, see [Section 7.5, “WebAccess Agent Queue Directory,” on page 93](#).

## grpwise-wa file

The `grpwise-wa` file is the WebAccess Agent startup script. During installation, it is placed in `/etc/init.d`. For more information, see [“Starting the Linux WebAccess Agent for the First Time” in “Installing GroupWise WebAccess” in the \*GroupWise 7 Installation Guide\*](#).



## S99grpwise-wa file

The `S99grpwise-wa` file is the WebAccess Agent startup script that is placed in the `rc3.d` and `rc5.d` subdirectories of `/etc/init.d` if you choose to have the WebAccess Agent start automatically when the server reboots. During installation, it is named `grpwise-ma` and placed in `/etc/init.d`. For more information, see “Starting the Linux WebAccess Agent on System Startup” in “Installing GroupWise WebAccess” in the *GroupWise 7 Installation Guide*.

## webservice directory

On Linux, you can install Apache and Tomcat along with WebAccess and Monitor. This automatically integrates WebAccess and Monitor into Apache and Tomcat for you. If you are already running Apache and Tomcat, you can choose to integrate WebAccess and Monitor into that installation, or you can have two Apache/Tomcat installations on your server. WebAccess and Monitor cannot be used without a supporting Web server. For more information, see “Determining the WebAccess and WebPublisher Applications' Configuration” in “Installing GroupWise WebAccess” and “Determining the Monitor Application's Configuration” in “Installing GroupWise Monitor” *GroupWise 7 Installation Guide*.

## 9.2.9 license directory

The `license` subdirectory contains the GroupWise Software License Agreement in multiple languages. Use the `more` command to view the License Agreement.

## 9.2.10 docs directory

The `docs` subdirectory contains language-specific subdirectories for the *GroupWise 7 Installation Guide* and *Quick Start* in PDF format, along with the Readme in HTML format. You can find the most up-to-date version of the GroupWise documentation on the [GroupWise 7 Documentation Web site \(http://www.novell.com/documentation/gw7\)](http://www.novell.com/documentation/gw7).

## 9.2.11 gwinst directory

The `gwinst` subdirectory contains supporting files and subdirectories used by the Installation script.

























# GroupWise Client Installation Directories

# 10

- Section 10.1, “Windows Client,” on page 171
- Section 10.2, “Cross-Platform Client on Linux,” on page 175
- Section 10.3, “Cross-Platform Client on Macintosh,” on page 176




## 10.1 Windows Client

---

	Installation directory for GroupWise® 7 Windows client software
c:\novell\groupwise	
	grpwise.exe GroupWise client program
	gwtip.exe GroupWise Tip of the Day program
	notify.exe GroupWise Notify program
	addrbook.exe GroupWise Address Book program
	htrsetup.exe Hit the Road setup program
	gwimpe.exe GroupWise E-Mail Importer Utility
	gwwmailto.exe Web browser support program
	gwwreload.exe Mailbox mode switching program
	gwwsync.exe Mailbox synchronization program
	pdacconnect.exe PDA Connect Installation program
	ngwguard.dc Data dictionary for databases
	wprof.dc Data dictionary for Remote Address Book
	*.dll DLL programs to support GroupWise Windows client
	*.ocx OLE custom controls
	*.flt Graphics filters for Inso viewers
	*.chm Help files to support the GroupWise client
	gwcheck GroupWise Check utility
	ofviews GroupWise view files
	win GroupWise view files for Windows
	*.vew View files
	*.ini View initialization files

---

---

 ppforms	Day planner forms
 *.bfp	Form description files
 *.prs	Print resource files

---

## 10.1.1 c:\novell\groupwise

The GroupWise Windows client installation directory contains all files necessary to run the GroupWise client. The default location is `c:\novell\groupwise`.

- For a standard installation, the GroupWise client directory resides on the user's workstation.
- For a workstation installation, the GroupWise client directory resides on the network and is run by users on many workstations.
- For a remote GroupWise installation, the GroupWise directory contains the same files as would be installed on a workstation connected to the network. Whenever GroupWise cannot make a network connection, it checks for a Remote mailbox to access. See [Section 7.7, "Remote Mailbox Directory,"](#) on page 100.

## 10.1.2 grpwise.exe file

The `grpwise.exe` file is the GroupWise 7 client program for use with Windows.

## 10.1.3 gwtip.exe file

The `gwtip.exe` file is the GroupWise Tip of the Day program, which displays helpful information about a GroupWise feature each time you start the GroupWise client.

## 10.1.4 notify.exe file

The `notify.exe` file is the program that alerts you whenever you have incoming items, when your outgoing items are opened, or when you have an upcoming appointment. Notify can alert you in four ways: a sound, a dialog box, a small icon, or by launching an application.

## 10.1.5 addrbook.exe file

The `addrbook.exe` file is the program that accesses the GroupWise Address Book. The Address Book contains information for all Novell® eDirectory™ users, GroupWise external users, GroupWise external entities, GroupWise e-mail distribution lists, and so on.

## 10.1.6 htrsetup.exe file

The `htrsetup.exe` file is the setup program for Hit the Road, which creates your Remote mailbox. See ["Remote Mode"](#) in ["Client"](#) in the *GroupWise 7 Administration Guide*.

## 10.1.7 gwimpe.exe file

The `gwimpe.exe` file is the GroupWise E-Mail Importer Utility, which enables you to import supported POP3/IMAP4 accounts into GroupWise. See “[Importing POP3 and IMAP4 Accounts](#)” in “[Working with Items in Your Mailbox](#)” in the *GroupWise 7 Windows Client User Guide*.

## 10.1.8 gwmailto.exe file

The `gwmailto.exe` file is the program that integrates the GroupWise client with your Web browser. If you select *Internet Browser Mail Integration* during installation, the GroupWise client becomes the default e-mail program on your workstation. See “[Setting Up the GroupWise Client](#)” in “[Installing the GroupWise Windows and Cross-Platform Clients](#)” in the *GroupWise 7 Installation Guide*.

## 10.1.9 gwreload.exe file

The `gwreload.exe` file is the program that restarts the GroupWise client when you switch between Online, Caching, and Remote modes. See “[Using Caching Mode](#)” and “[Using Remote Mode](#)” in the *GroupWise 7 Windows Client User Guide*.

## 10.1.10 gwsync.exe file

The `gwsync.exe` file is the program that synchronizes your Online and Caching mailboxes. See “[Using Caching Mode](#)” in the *GroupWise 7 Windows Client User Guide*.

## 10.1.11 pdaconnect.exe file

The `pdaconnect.exe` file is the PDA Connect Installation program for synchronizing data between GroupWise and a PDA device. For more information, see the [PDA Connect Readme \(http://www.novell.com/documentation/gw7/readmeen\\_pda\\_connect/readmeen\\_pda\\_connect.html\)](http://www.novell.com/documentation/gw7/readmeen_pda_connect/readmeen_pda_connect.html).

## 10.1.12 ngwguard.dc file

The `ngwguard.dc` file is the data dictionary for building databases in the post office. In Remote mode, the GroupWise client also uses the `ngwguard.dc` file as the data dictionary for its local databases.

## 10.1.13 wprof.dc file

The `wprof.dc` file is the data dictionary for the remote GroupWise Address Book (`wprof.db`).

Historical Note: An earlier version of the GroupWise client Remote mode, designed by WordPerfect Corporation (WPCorp), was named WP Office Remote. Hence, the `wprof` in `wprof.dc`. Some naming conventions were originally preserved for backward compatibility.

## 10.1.14 \*.dll files

\*.dll files are dynamically linked libraries of program code used by executable programs. Language-independent \*.dll files are typically located in the same directory with the executable programs they support. Language-specific \*.dll files are grouped into subdirectories by language.

### 10.1.15 \*.ocx files

\*.ocx files are OLE custom controls. For example, \*.ocx files control the Address Book and name completion.

### 10.1.16 \*.flt files

\*.flt files are graphics filters used by the Inso viewers incorporated into the GroupWise client. The viewers enable you to view a wide variety of file types from within GroupWise.

### 10.1.17 \*.chm files

\*.chm files contain the online documentation for all components of GroupWise. \*.chm files are typically located in the same directory with the executable programs they support.

### 10.1.18 gwcheck directory

The `gwcheck` directory contains the GroupWise Check utility that can be made available in the GroupWise client by clicking *Tools > Repair Mailbox*. For more information, see “[Repairing Your Mailbox](#)” in “[Managing Your Mailbox](#)” in the *GroupWise 7 Windows Client User Guide*.

### 10.1.19 ofviews directory

The `ofviews` directory contains platform-specific subdirectories of view files for use by the GroupWise client.

Historical Note: An earlier version of GroupWise, designed by WordPerfect Corporation (WPCorp), was named WP Office. Hence, the `of` in `ofviews`. Some naming conventions were originally preserved for backward compatibility.

#### win directory

The `win` subdirectory contains view (\*.view) files for use by the GroupWise client. It also contains initialization (\*.ini) files to control display of views.

### 10.1.20 ppforms directory

The `ppforms` directory contains day planner forms for printing GroupWise calendars and tasks.

#### \*.bfp files














\*.bfp files are form description files that contain binder, filler, and page attributes for forms.

#### \*.prs files

\*.prs files are print resource files that indicate which forms are available for which languages. For example, day planners used by English-speaking people in the United States have different forms from day planners used for various languages in Europe.

## 10.2 Cross-Platform Client on Linux

---

 <code>/opt/novell/ groupwise/client</code>	GroupWise Cross-Platform client installation directory
 <code>gwclient.desktop</code>	Desktop shortcut for the Cross-Platform client
 <code>gwclient.png</code>	Desktop icon for the Cross-Platform client shortcut
 <code>bin</code>	Subdirectory for the Cross-Platform client executable
 <code>groupwise</code>	Cross-Platform client executable
 <code>lib</code>	Subdirectory for Cross-Platform client library files
 <code>gwenlxxx.fil</code>	Cross-Platform client language resource files
 <code>ngwguard.dc</code>	Data dictionary for local databases on the user's workstation
 <code>wprof.dc</code>	Data dictionary for the local copy of the Address Book
 <code>*.jar</code>	Java archive (.jar) files used by the Cross-Platform client
 <code>*.so</code>	Shared library files used by the Cross-Platform client
 <code>jre</code>	Java Runtime Environment (JRE) used by the Cross-Platform client
 <code>logs</code>	Log files generated by the Cross-Platform client

---

### 10.2.1 /opt/novell/groupwise/client directory

The `/opt/novell/groupwise/client` directory is the default location for the GroupWise Cross-Platform software. The Installation program does not provide the opportunity to specify a different location and typically there is no need to move the software.

#### gwclient.desktop file

The `gwclient.desktop` file create the GroupWise Cross-Platform client shortcut on your Linux desktop.

#### gwclient.png file

The `gwclient.png` file is the GroupWise icon used for Cross-Platform client shortcut.

### 10.2.2 bin directory

The `bin` directory is the standard Linux location for executable files.

#### groupwise file

The `groupwise` file is the GroupWise Cross-Platform client executable. See “[Installing the GroupWise Cross-Platform Client](#)” in the *GroupWise 7 Cross-Platform Client User Guide*.

## 10.2.3 lib directory

The `lib` directory is the standard Linux location for library files.

### **gwenlxxx.fil file**

The `gwenlxxx.file` provides the language-specific strings for the localized versions of the Cross-Platform client. The `xx` is a two-letter language code.

### **ngwguard.dc file**

The `ngwguard.dc` file is the data dictionary for building the databases used by the Cross-Platform client. It is parallel in function to the `ngwguard.dc` file in the post office.

### **wprof.dc file**

The `wprof.dc` file is the data dictionary used to create the local copy of the Address Book that resides on the user's workstation (`wprof.db`).

### **\*.jar files**

The `*.jar` files efficiently store information referenced by the Cross-Platform client. The `gwclient.jar` file contains the Cross-Platform online help information.

### **\*.so files**

The `*.so` files are Linux shared library files that provide information to the Cross-Platform client executable.

## 10.2.4 jre directory






The `jre` directory holds the version of the Java Runtime Environment (JRE) that is required by the Cross-Platform client.

## 10.2.5 logs directory

The `logs` directory stores log files generated by the Cross-Platform client when an error occurs.

# 10.3 Cross-Platform Client on Macintosh










---

 <code>/Applications/ GroupWise.app</code>	GroupWise Cross-Platform client installation directory
 <code>Contents</code>	Standard Macintosh directory for application files
 <code>PkgInfo</code>	Standard Macintosh package info file
 <code>Info.plist</code>	Standard Macintosh package list file
 <code>MacOS</code>	Standard Macintosh directory for operating system files

---



---

 <b>Resources</b>	Standard Macintosh directory for resource files
 <b>GroupWise.icns</b>	Icons used by the Cross-Platform client
 <b>lib</b>	Subdirectory for Cross-Platform client library files
 <b>gwenlxxx.fil</b>	Data dictionary for local databases on the user's workstation
 <b>ngwguard.dc</b>	Data dictionary for the local copy of the Address Book
 <b>wprof.dc</b>	Cross-Platform client language information files
 <b>Java</b>	JRE used by the Cross-Platform client
 <b>*.jar</b>	Java archive (.jar) files used by the Cross-Platform client
 <b>*.dylib</b>	Dynamic libraries used by the Cross-Platform client

---

### 10.3.1 /Applications/GroupWise.app directory

The `/Applications/GroupWise.app` directory contains the GroupWise Cross-Platform client on Macintosh.

### 10.3.2 Contents directory

The `Contents` directory is the standard location on Macintosh for all files that make up an application.

### 10.3.3 MacOS directory

The `MacOS` directory contains the `JavaApplicationStub` file that enables the Cross-Platform client to invoke the Java Virtual Machine (JVM) on Macintosh.

### 10.3.4 Resources directory

The `Resources` directory is the standard location on Macintosh for files that support an application.

#### GroupWise.icns file

The `GroupWise.icns` file contains all the images that display in the Cross-Platform client.

### 10.3.5 lib directory

The `lib` directory holds library files that provide information required by the Cross-Platform client.

#### gwenlxxx.fil file

The `gwenlxxx.fil` provides the language-specific strings for the localized versions of the Cross-Platform client. The `xx` is a two-letter language code.

### **ngwguard.dc file**

The `ngwguard.dc` file is the data dictionary for building the databases used by the Cross-Platform client. It is parallel in function to the `ngwguard.dc` file in the post office.

### **wprof.dc file**

The `wprof.dc` file is the data dictionary used to create the local copy of the Address Book that resides on the user's workstation (`wprof.db`).

## **10.3.6 Java directory**

The `Java` directory holds the version of the Java Runtime Environment (JRE) that is required by the Cross-Platform client.

### **\*.jar files**

The `*.jar` files efficiently store information referenced by the Cross-Platform client. The `gwclient.jar` file contains the Cross-Platform online help information.

### **\*.dylib files**

The `*.dylib` files are dynamic library files that provide information to the Cross-Platform client program.